

Motivations	Contributions	<pre>(***) --algorithm TwoPhaseCommit { /* unordered channels channels agt[Agent], coord; fair process (a \in Agent) variable aState = "unknown"; { /* sub-process a1: if (aState = "unknown") { with(st \in {"accept", "refuse"}) aState := st; send(coord, [type -> st, agent -> self]);};}; a2: await(aState \in {"commit", "abort"}) } { /* sub-process a3:await (aState # "unknown"); receive(agt[self], aState); } fair process (c = Coord) variables cState = "unknown", commits = {}, msg = {}; { /* sub-process c1: await(cState \in {"commit", "abort"}); broadcast(agt, [ag \in Agent -> cState]); } { /* sub-process c2:while (cState \notin {"abort", "commit"}) { receive(coord, msg); if (msg.type = "refuse") { cState := "abort"; } else if (msg.type = "accept") { commits := commits \cup {msg.agent}; if (commits = Agent) { cState := "commit";} } } } } } }***)</pre>
<p>➤ Formal Methods for Distributed Algorithms</p> <ul style="list-style-type: none">Distributed Algorithms are prone to deadlocks and race conditions.Formal verification methods have been employed successfully to model the system and its properties and then verify its correctness. <p>➤ Modeling Distributed Algorithms</p> <ul style="list-style-type: none">TLA+¹ is a formal language used to describe algorithms, it is used to specify and verify complicated algorithms concisely.TLA+ relies on mathematical logic, PlusCal²-was designed as an algorithm language with a more familiar syntax that can be translated into TLA+ specifications.PlusCal² lacks primitives for communication between processes which makes modeling distributed algorithms difficult.	<p>➤ We propose Distributed PlusCal, an extension of PlusCal that introduces constructs that can overcome some of the limitation of PlusCal.</p> <p>➤ Distributed PlusCal offers primitives that aid in modeling distributed algorithms.</p> <p>➤ We provide a backward compatible translator that translates from Distributed PlusCal and PlusCal to TLA+.</p>	
	Distributed PlusCal	
<h3>References</h3> <p>[1]Lamport, Leslie. (2000). Specifying Concurrent Systems with TLA+.</p> <p>[2] Lamport, Leslie. (2009). The PlusCal Algorithm Language. 5684. 36-60. 10.1007/978-3-642-03466-4_2.</p>	<p>➤ Distributed PlusCal is a PlusCal extension that offers primitives that aid in modeling distributed algorithms such as</p> <ul style="list-style-type: none">Sub-processesCommunication channels :<ul style="list-style-type: none">Unordered channels with the syntax <p><i>channel</i> (identifier)[(dimension1,...dimensionN)]</p> <ul style="list-style-type: none">FIFO channels with the syntax <p><i>fifo</i> (identifier)[(dimension1,...dimensionN)]</p> <ul style="list-style-type: none">Channels support the following operations <ol style="list-style-type: none">sendbroadcastmulticastreceiveclear	