

DRAFT - CUPS Software Security Report

CUPS-SSR-1.0

Easy Software Products Copyright 1997-1999, All Rights Reserved

Table of Contents

1
1
1
1
3
3
3
5
5
7
•••••••
7
7

DRAFT - CUPS Software Security Report

1 Scope

1.1 Identification

This software security report provides an analysis of possible security concerns for the Common UNIX Printing System ("CUPS") Version 1.0.

1.2 System Overview

The Common UNIX Printing System provides a portable printing layer for UNIX® operating systems. It has been developed by Easy Software Products to promote a standard printing solution for all UNIX vendors and users. CUPS provides the System V and Berkeley command-line interfaces.

CUPS uses the Internet Printing Protocol (IETF-IPP) as the basis for managing print jobs and queues. The Line Printer Daemon (LPD, RFC1179), Server Message Block (SMB), and AppSocket protocols are also supported with reduced functionality.

CUPS adds network printer browsing and PostScript Printer Description ("PPD")-based printing options to support real world applications under UNIX.

CUPS also includes a customized version of GNU GhostScript (currently based off GNU GhostScript 4.03) and an image file RIP that can be used to support non-PostScript printers.

1.3 Document Overview

This software security report is organized into the following sections:

- 1 Scope
- 2 References
- 3 Local Access Risks
- 4 Remote Access Risks
- A Glossary

1 Scope 1

2 1 Scope

2 References

2.1 CUPS Documentation

The following CUPS documentation is referenced by this document:

- CUPS-CMP-1.0: CUPS Configuration Management Plan
- CUPS-IDD-1.0: CUPS System Interface Design Description
- CUPS-SAM-1.0.x: CUPS Software Administrators Manual
- CUPS-SDD-1.0: CUPS Software Design Description
- CUPS-SPM-1.0: CUPS Software Programming Manual
- CUPS-SSR-1.0: CUPS Software Security Report
- CUPS-STP-1.0: CUPS Software Test Plan
- CUPS-SUM-1.0.x: CUPS Software Users Manual
- CUPS-SVD-1.0.x: CUPS Software Version Description

2.2 Other Documents

The following non-CUPS documents are referenced by this document:

- IEEE 1387.4, System Administration: Printing (draft)
- IPP/1.0: Additional Optional Operations Set 1
- IPP/1.0: Encoding and Transport
- IPP/1.0: Implementers Guide
- IPP/1.0: Model and Semantics
- RFC 1179, Line Printer Daemon Protocol

2 References 3

4 2 References

3 Local Access Risks

Local access risks are those that can be exploited only with a local user account. This section does not address issues related to dissemination of the root password or other security issues associated with the UNIX operating system.

3.1 Security Breaches

Since the default installation creates a world-readable request directory, it is possible for local users to read the contents of print files before they are printed.

This problem can be alleviated by making the request directory readable only by the user specified in the CUPS configuration file.

3 Local Access Risks 5

6 3 Local Access Risks

4 Remote Access Risks

Remote access risks are those that can be exploited without a local user account and/or from a remote system. This section does not address issues related to network or firewall security.

4.1 Denial of Service Attacks

Like all internet services, the CUPS server is vulnerable to denial of service attacks, including:

1. Establishing multiple connections to the server until the server will accept no more.

This cannot be protected against by the current software. It is possible that future versions of the CUPS software could be configured to limit the number of connections allowed from a single host, however that still would not prevent a determined attack.

2. Repeatedly opening and closing connections to the server as fast as possible.

There is no easy way of protecting against this in the CUPS software. If the attack is coming from outside the local network it might be possible to filter such an attack, however once the connection request has been received by the server it must at least accept the connection to find out who is connecting.

3. Flooding the network with broadcast packets on port 631.

It might be possible to disable browsing if this condition is detected by the CUPS software, however if there are large numbers of printers available on the network such an algorithm might think that an attack was occurring when instead a valid update was being received.

4. Sending partial IPP requests; specifically, sending part of an attribute value and then stopping transmission.

The current code is structured to read and write the IPP request data on-the-fly, so there is no easy way to protect against this for large attribute values.

5. Sending large/long print jobs to printers, preventing other users from printing.

There are limited facilities for protecting against large print jobs (the MaxRequestSize attribute), however this will not protect printers from malicious users and print files that generate hundreds or thousands of pages. In general, we recommend restricting printer access to known hosts or networks, and adding user-level access control as needed for expensive printers.

4.2 Security Breaches

The current CUPS server only supports Basic authentication with usernames and passwords. This essentially places the clear text of the username and password on the network. Since CUPS uses the UNIX username and password account information, the authentication information could be used to gain access to accounts (possibly priviledged accounts) on the server.

The default CUPS configuration disables remote administration. We do not recommend that remote

4 Remote Access Risks 7

DRAFT - CUPS Software Security Report

administration be enabled for all hosts, however if you have a trusted network or subnet access can be restricted accordingly.

The next minor release of CUPS will support Digest authentication of the entire message body using separate MD5-based username and password files. This will protect password information and prevent unauthorized access due to compromised account passwords.

A Glossary

A.1 Terms

```
\boldsymbol{C}
```

A computer language.

parallel

Sending or receiving data more than 1 bit at a time.

pipe

A one-way communications channel between two programs.

serial

Sending or receiving data 1 bit at a time.

socket

A two-way network communications channel.

A.2 Acronyms

```
ASCII
```

American Standard Code for Information Interchange

CUPS

Common UNIX Printing System

ESC/P

EPSON Standard Code for Printers

FTP

File Transfer Protocol

HP-GL

Hewlett-Packard Graphics Language

A Glossary 9

```
HP-PCL
       Hewlett-Packard Printer Control Language
HP-PJL
       Hewlett-Packard Printer Job Language
IETF
       Internet Engineering Task Force
IPP
       Internet Printing Protocol
ISO
       International Standards Organization
LPD
       Line Printer Daemon
MIME
       Multimedia Internet Mail Exchange
PCL
       Page Control Language
PPD
       PostScript Printer Description
SMB
       Server Message Block
TFTP
```

Trivial File Transfer Protocol

10 A.2 Acronyms