

DTD documentation

Table of contents

1 Top-level element(s).....	3
2 List of elements.....	3
3 Element declarations.....	4
3.1	4
3.2	4
3.3	5
3.4	5
3.5	5
3.6	6
3.7	6
3.8	6
3.9	7
3.10	7
3.11	8
3.12	8
3.13	8
3.14	9
3.15	9
3.16	10
3.17	10
3.18	10
3.19	11
3.20	11
3.21	11
3.22	12
3.23	12
3.24	12
3.25	13
3.26	13
3.27	14
3.28	14

3.29	14
3.30	15
3.31	15
3.32	15
3.33	16
3.34	16
3.35	16
3.36	17
3.37	17
3.38	17
3.39	18
3.40	18
3.41	18
3.42	19
3.43	19
3.44	19
3.45	19
3.46	20
3.47	20
3.48	20
3.49	21
3.50	21
3.51	21

1. Top-level element(s)

- [document](#)
- [faqs](#)

2. List of elements

- [a](#)
- [abstract](#)
- [acronym](#)
- [anchor](#)
- [answer](#)
- [area](#)
- [authors](#)
- [body](#)
- [br](#)
- [caption](#)
- [code](#)
- [dd](#)
- [dl](#)
- [document](#)
- [dt](#)
- [elaboration](#)
- [em](#)
- [faq](#)
- [faqs](#)
- [faqsection](#)
- [figure](#)
- [fixme](#)
- [footer](#)
- [header](#)
- [icon](#)
- [img](#)
- [legal](#)
- [li](#)
- [map](#)
- [meta](#)
- [note](#)
- [notice](#)
- [ol](#)
- [p](#)
- [person](#)
- [question](#)
- [section](#)
- [source](#)
- [strong](#)
- [sub](#)
- [subtitle](#)
- [sup](#)

- [table](#)
- [td](#)
- [th](#)
- [title](#)
- [tr](#)
- [type](#)
- [ul](#)
- [version](#)
- [warning](#)

3. Element declarations

3.1.

person		
Content model	EMPTY	
Attributes	id	type:
	class	type:
	xml:lang	type:
	name	type: requir
	email	type: requir
Used inside	authors	

3.2.

strong			
Content model		(#PCDATA strong em code sub sup br img icon acronym map a) *	
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	strong em a p source note warning fixme caption th td li dt dd title subtitle notice abstract legal question elaboration answer		

3.3.

em			
Content model		(#PCDATA strong em code sub sup br img icon acronym map a) *	
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	strong em a p source note warning fixme caption th td li dt dd title subtitle notice abstract legal question elaboration answer		

3.4.

code			
Content model		(#PCDATA)	
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	strong em a p source note warning fixme caption th td li dt dd title subtitle notice abstract legal question elaboration answer		

3.5.

sup			
Content model		(#PCDATA)	
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	strong em a p source note warning fixme caption th td li dt dd title subtitle		

	notice abstract legal question elaboration answer

3.6.

sub			
Content model		(#PCDATA)	
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	strong em a p source note warning fixme caption th td li dt dd title subtitle notice abstract legal question elaboration answer		

3.7.

a			
Content model		(#PCDATA strong em code sub sup br img icon acronym map) *	
Attributes	id		type:
	class		type:
	xml:lang		type:
	href		type: required
	title		type:
Used inside		strong em p source note warning fixme caption th td li dt dd title notice abstract legal question elaboration answer	

3.8.

br			
Content model		EMPTY	
Attributes		id	type:

	class		type:
	xml:lang		type:
Used inside	strong em a p source note warning fixme caption th td li dt dd title notice abstract legal question elaboration answer		

3.9.

img			
Content model		EMPTY	
Attributes	src		type: required
	alt		type: required
	height		type:
	width		type:
	usemap		type:
	ismap		possible
	id		type:
	class		type:
	xml:lang		type:
Used inside	strong em a p source note warning fixme caption th td li dt dd title notice abstract legal question elaboration answer		

3.10.

map			
Content model		(area +)	
Attributes		<div>name</div>	type:
Used inside		strong em a p source note warning fixme caption th td li dt dd title notice abstract legal question elaboration answer	

3.11.

area			
Content model		EMPTY	
Attributes	shape		default: possible default
	coords		type:
	href		type: required
	title		type:
	nohref		possible
	alt		type: required
Used inside		map	

3.12.

icon			
Content model		EMPTY	
Attributes	src		type: required
	alt		type: required
	height		type:
	width		type:
	id		type:
	class		type:
	xml:lang		type:
Used inside	strong em a p source note warning fixme caption th td li dt dd title notice abstract legal question elaboration answer		

3.13.

acronym			
Content model		(#PCDATA) *	
Attributes	title		type: required
	id		type: optional
	class		type: optional
	xml:lang		type: optional
Used inside	strong em a p source note warning fixme caption th td li dt dd title notice abstract legal question elaboration answer		

3.14.

p			
Content model		(#PCDATA strong em code sub sup br img icon acronym map a) *	
Attributes	id		type: optional
	class		type: optional
	xml:lang		type: optional
	xml:space		possible preserved
Used inside		th td li dd body section answer	

3.15.

source		
Content model	(#PCDATA strong em code sub sup br img icon acronym map a) *	
Attributes	id	type:
	class	type:
	xml:lang	type:
	xml:space	default fixed v possib prese

Used inside	th td li dd body section answer

3.16.

note		
Content model	(#PCDATA strong em code sub sup br img icon acronym map a) *	
Attributes	label	type:
	id	type:
	class	type:
	xml:lang	type:
Used inside	th td li dd body section answer	

3.17.

warning			
Content model		(#PCDATA strong em code sub sup br img icon acronym map a) *	
Attributes	label		type:
	id		type:
	class		type:
	xml:lang		type:
Used inside		th td li dd body section answer	

3.18.

fixme			
Content model	(#PCDATA strong em code sub sup br img icon acronym map a) *		
Attributes	author		type: require
	id		type:
	class		type:

	xml:lang		type:
Used inside	th td li dd body section answer		

3.19.

table			
Content model	(caption ? , tr +)		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	th td li dd body section answer		

3.20.

caption			
Content model	(#PCDATA strong em code sub sup br img icon acronym map a) *		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	table		

3.21.

tr			
Content model	(th td) +		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	table		

3.22.

th			
Content model	(#PCDATA strong em code sub sup br img icon acronym map a p source note warning fixme table ol ul dl figure anchor) *		
Attributes	id		type:
	class		type:
	xml:lang		type:
	colspan		type: default
	rowspan		type: default
Used inside	tr		

3.23.

td			
Content model	(#PCDATA strong em code sub sup br img icon acronym map a p source note warning fixme table ol ul dl figure anchor) *		
Attributes	id		type:
	class		type:
	xml:lang		type:
	colspan		type: default
	rowspan		type: default
Used inside	tr		

3.24.

li

Content model	(#PCDATA strong em code sub sup br img icon acronym map a p source note warning fixme table ol ul dl figure anchor) *		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	ul ol		

3.25.

ul			
Content model		(li) +	
Attributes	id		type:
	class		type:
	xml:lang		type:
	spacing		possible comp
Used inside		th td li dd body section answer	

3.26.

ol			
Content model		(li) +	
Attributes	id		type:
	class		type:
	xml:lang		type:
	spacing		possible comp
Used inside		th td li dd body section answer	

3.27.

dl			
Content model		(dt , dd) +	
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside		th td li dd body section answer	

3.28.

dt			
Content model		(#PCDATA strong em code sub sup br img icon acronym map a) *	
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	dl		

3.29.

dd			
Content model	(#PCDATA strong em code sub sup br img icon acronym map a p source note warning fixme table ol ul dl figure anchor) *		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	dl		

3.30.

figure			
Content model		EMPTY	
Attributes	src		type: require
	alt		type: require
	height		type:
	width		type:
	usemap		type:
	ismap		possib
	align		type:
	id		type:
	class		type:
	xml:lang		type:
Used inside	th td li dd body section answer		

3.31.

anchor			
Content model		EMPTY	
Attributes	id		type: required
	class		type:
	xml:lang		type:
Used inside	th td li dd body section answer		

3.32.

document	
Content model	(header , body , footer ?)

Attributes	id		type:
	class		type:
	xml:lang		type:

3.33.

header			
Content model	(title , subtitle ? , version ? , type ? , authors ? , notice * , abstract ? , meta *)		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	document		

3.34.

title			
Content model	(#PCDATA strong em code sub sup a br img icon acronym map) *		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	header section faqs faqsection		

3.35.

subtitle			
Content model	(#PCDATA strong em code sub sup) *		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	header		

3.36.

version			
Content model		(#PCDATA)	
Attributes	id		type:
	class		type:
	xml:lang		type:
	major		type:
	minor		type:
	fix		type:
	tag		type:
Used inside		header	

3.37.

type			
Content model		(#PCDATA)	
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside		header	

3.38.

authors			
Content model		(person +)	
Attributes	id		type:
	class		type:
	xml:lang		type:

Used inside	header faqs

3.39.

notice			
Content model	(#PCDATA strong em code sub sup br img icon acronym map a) *		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	header		

3.40.

abstract			
Content model		(#PCDATA strong em code sub sup br img icon acronym map a) *	
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside		header	

3.41.

meta			
Content model		(#PCDATA)	
Attributes	name		type: required
	id		type:
	class		type:
	xml:lang		type:

Used inside	header

3.42.

body		
Content model	(section p source note warning fixme table ol ul dl figure anchor) +	
Attributes	id	type:
	class	type:
	xml:lang	type:
Used inside	document	

3.43.

section			
Content model		(title , (section p source note warning fixme table ol ul dl figure anchor) *)	
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside		body section	

3.44.

footer	
Content model	(legal)
Used inside	document

3.45.

legal	
Content model	(#PCDATA strong em code sub sup br img icon acronym map a) *

Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	footer		

3.46.

faqs			
Content model	(title ? , authors ? , (faq faqsection) +)		
Attributes	id		type:
	class		type:
	xml:lang		type:

3.47.

faqsection			
Content model	(title , (faq faqsection) +)		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	faqs faqsection		

3.48.

faq			
Content model	(question , answer)		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	faqs faqsection		

3.49.

question			
Content model		(#PCDATA strong em code sub sup br img icon acronym map a elaboration) *	
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	faq		

3.50.

elaboration			
Content model		(#PCDATA strong em code sub sup br img icon acronym map a) *	
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside		question	

3.51.

answer			
Content model	(#PCDATA strong em code sub sup br img icon acronym map a p source note warning fixme table ol ul dl figure anchor) *		
Attributes	author		type:
Used inside	faq		