

DTD documentation

Table of contents

1 Top-level element(s).....	3
2 List of elements.....	3
3 Element declarations.....	4
3.1	4
3.2	4
3.3	5
3.4	5
3.5	5
3.6	6
3.7	6
3.8	7
3.9	7
3.10	7
3.11	8
3.12	8
3.13	9
3.14	9
3.15	9
3.16	10
3.17	10
3.18	11
3.19	11
3.20	11
3.21	12
3.22	12
3.23	12
3.24	13
3.25	13
3.26	13
3.27	14
3.28	14

3.29	15
3.30	15
3.31	15
3.32	16
3.33	16
3.34	16
3.35	17
3.36	17
3.37	17
3.38	18
3.39	18
3.40	18
3.41	19
3.42	19
3.43	19
3.44	20
3.45	20
3.46	20
3.47	20
3.48	21
3.49	21
3.50	21
3.51	22
3.52	22
3.53	22
3.54	22
3.55	23
3.56	23
3.57	23
3.58	24
3.59	24
3.60	24
3.61	25
3.62	25

1. Top-level element(s)

- [document](#)
- [howto](#)
- [overview](#)

2. List of elements

- [a](#)
- [abstract](#)
- [acronym](#)
- [anchor](#)
- [answer](#)
- [area](#)
- [audience](#)
- [authors](#)
- [body](#)
- [br](#)
- [caption](#)
- [code](#)
- [dd](#)
- [dl](#)
- [document](#)
- [dt](#)
- [elaboration](#)
- [em](#)
- [extension](#)
- [faq](#)
- [faqs](#)
- [faqsection](#)
- [feedback](#)
- [figure](#)
- [fixme](#)
- [footer](#)
- [header](#)
- [howto](#)
- [icon](#)
- [img](#)
- [last-modified-content-date](#)
- [legal](#)
- [li](#)
- [map](#)
- [meta](#)
- [note](#)
- [notice](#)
- [ol](#)
- [overview](#)
- [p](#)
- [person](#)
- [prerequisites](#)
- [purpose](#)

- [question](#)
- [references](#)
- [section](#)
- [source](#)
- [steps](#)
- [strong](#)
- [sub](#)
- [subtitle](#)
- [sup](#)
- [table](#)
- [td](#)
- [th](#)
- [tips](#)
- [title](#)
- [tr](#)
- [type](#)
- [ul](#)
- [version](#)
- [warning](#)

3. Element declarations

3.1.

person											
Content model	EMPTY										
Attributes	<table> <tr> <td>id</td><td></td></tr> <tr> <td>class</td><td></td></tr> <tr> <td>xml:lang</td><td></td></tr> <tr> <td>name</td><td></td></tr> <tr> <td>email</td><td></td></tr> </table>	id		class		xml:lang		name		email	
id											
class											
xml:lang											
name											
email											
Used inside	authors										

3.2.

strong					
Content model	(#PCDATA strong em code sub sup br img icon acronym map a) *				
Attributes	<table> <tr> <td>id</td><td></td></tr> <tr> <td>class</td><td></td></tr> </table>	id		class	
id					
class					

	xml:lang		
Used inside	strong em a p source note warning fixme caption th td li dt dd title subtitle notice abstract legal question elaboration answer		

3.3.

em			
Content model	(#PCDATA strong em code sub sup br img icon acronym map a) *		
Attributes	id		
	class		
	xml:lang		
Used inside	strong em a p source note warning fixme caption th td li dt dd title subtitle notice abstract legal question elaboration answer		

3.4.

code			
Content model	(#PCDATA)		
Attributes	id		
	class		
	xml:lang		
Used inside	strong em a p source note warning fixme caption th td li dt dd title subtitle notice abstract legal question elaboration answer		

3.5.

sup			
Content model	(#PCDATA)		

Attributes	id			ty
	class			ty
	xml:lang			ty
Used inside	strong em a p source note warning fixme caption th td li dt dd title subtitle notice abstract legal question elaboration answer			

3.6.

sub			
Content model		(#PCDATA)	
Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside	strong em a p source note warning fixme caption th td li dt dd title subtitle notice abstract legal question elaboration answer		

3.7.

a			
Content model	(#PCDATA strong em code sub sup br img icon acronym map) *		
Attributes	id		ty
	class		ty
	xml:lang		ty
	href		ty r
	title		ty
Used inside	strong em p source note warning fixme caption th td li dt dd title notice abstract legal question elaboration answer		

3.8.

br	
Content model	EMPTY
Attributes	
	id
	class
	xml:lang
Used inside	
	strong em a p source note warning fixme caption th td li dt dd title notice abstract legal question elaboration answer

3.9.

img	
Content model	EMPTY
Attributes	
	src
	alt
	height
	width
	usemap
	ismap
	id
	class
	xml:lang
Used inside	
	strong em a p source note warning fixme caption th td li dt dd title notice abstract legal question elaboration answer

3.10.

map	
Content model	(area +)

Attributes	<div>name</div>	
Used inside	<div>strong em a p source note warning fixme caption th td li dt dd title notice abstract legal question elaboration answer</div>	

3.11.

area	
Content model	EMPTY
Attributes	shape
	coords
	href
	title
	nohref
	alt
Used inside	map

3.12.

icon				
Content model	EMPTY			
Attributes	src			ty r
	alt			ty r
	height			ty
	width			ty
	id			ty
	class			ty
	xml:lang			ty

Used inside	strong em a p source note warning fixme caption th td li dt dd title notice abstract legal question elaboration answer

3.13.

acronym		
Content model	(#PCDATA) *	
Attributes	title	
	id	
	class	
	xml:lang	
Used inside	strong em a p source note warning fixme caption th td li dt dd title notice abstract legal question elaboration answer	

3.14.

p		
Content model	(#PCDATA strong em code sub sup br img icon acronym map a) *	
Attributes	id	
	class	
	xml:lang	
	xml:space	
Used inside	th td li dd body section answer overview purpose prerequisites audience steps extension tips references feedback	

3.15.

source	
Content model	(#PCDATA strong em code sub sup br img icon acronym map a) *

Attributes	id			ty
	class			ty
	xml:lang			ty
	xml:space			d fi p p
Used inside	th td li dd body section answer overview purpose prerequisites audience steps extension tips references feedback			

3.16.

note			
Content model		(#PCDATA strong em code sub sup br img icon acronym map a) *	
Attributes	label		ty
	id		ty
	class		ty
	xml:lang		ty
Used inside		th td li dd body section answer overview purpose prerequisites audience steps extension tips references feedback	

3.17.

warning			
Content model	(#PCDATA strong em code sub sup br img icon acronym map a) *		
Attributes	label		ty
	id		ty
	class		ty
	xml:lang		ty
Used inside	th td li dd body section answer overview purpose prerequisites audience steps extension tips references feedback		

3.18.	
fixme	
Content model	(#PCDATA strong em code sub sup br img icon acronym map a) *
Attributes	author
	id
	class
	xml:lang
Used inside	th td li dd body section answer overview purpose prerequisites audience steps extension tips references feedback

3.19.

table	
Content model	(caption ? , tr +)
Attributes	id
	class
	xml:lang
Used inside	th td li dd body section answer overview purpose prerequisites audience steps extension tips references feedback

3.20.

caption	
Content model	(#PCDATA strong em code sub sup br img icon acronym map a) *
Attributes	id
	class
	xml:lang

Used inside	table

3.21.

tr		
Content model	(th td) +	
Attributes	id	
	class	
	xml:lang	
Used inside	table	

3.22.

th	
Content model	(#PCDATA strong em code sub sup br img icon acronym map a p source note warning fixme table ol ul dl figure anchor) *
Attributes	id
	class
	xml:lang
	colspan
	rowspan
Used inside	tr

3.23.

td			
Content model	(#PCDATA strong em code sub sup br img icon acronym map a p source note warning fixme table ol ul dl figure anchor) *		
Attributes	<table><tr><td>id</td><td></td></tr></table>	id	
id			

	class			ty
	xml:lang			ty
	colspan			ty d
	rowspan			ty d
Used inside	tr			

3.24.

li				
Content model		(#PCDATA strong em code sub sup br img icon acronym map a p source note warning fixme table ol ul dl figure anchor) *		
Attributes	id			ty
	class			ty
	xml:lang			ty
Used inside		ul ol		

3.25.

ul			
Content model		(li) +	
Attributes	id		ty
	class		ty
	xml:lang		ty
	spacing		p c
Used inside	th td li dd body section answer overview purpose prerequisites audience steps extension tips references feedback		

3.26.

ol	
Content model	(li) +
Attributes	id
	class
	xml:lang
	spacing
Used inside	th td li dd body section answer overview purpose prerequisites audience steps extension tips references feedback

3.27.

dl	
Content model	(dt , dd) +
Attributes	id
	class
	xml:lang
Used inside	th td li dd body section answer overview purpose prerequisites audience steps extension tips references feedback

3.28.

dt	
Content model	(#PCDATA strong em code sub sup br img icon acronym map a) *
Attributes	id
	class
	xml:lang
Used inside	dl

3.29.

dd	
Content model	(#PCDATA strong em code sub sup br img icon acronym map a p source note warning fixme table ol ul dl figure anchor) *
Attributes	id
	class
	xml:lang
Used inside	dl

3.30.

figure	
Content model	EMPTY
Attributes	src
	alt
	height
	width
	usemap
	ismap
	align
	id
	class
	xml:lang
Used inside	th td li dd body section answer overview purpose prerequisites audience steps extension tips references feedback

3.31.

anchor

Content model	EMPTY		
Attributes	id		
	class		
	xml:lang		
Used inside	th td li dd body section answer overview purpose prerequisites audience steps extension tips references feedback		

3.32.

document			
Content model	(header , body , footer ?)		
Attributes	id		
	class		
	xml:lang		

3.33.

header			
Content model	(title , subtitle ? , version ? , type ? , authors ? , notice * , abstract ? , meta * , last-modified-content-date)		
Attributes	id		
	class		
	xml:lang		
Used inside	document howto		

3.34.

title			
Content model	(#PCDATA strong em code sub sup a br img icon acronym map) *		
Attributes	id		
	class		

	xml:lang		ty
Used inside	header section faqs faqsection		

3.35.

subtitle			
Content model	(#PCDATA strong em code sub sup) *		
Attributes	id		type
	class		type
	xml:lang		type
Used inside	header		

3.36.

version				
Content model		(#PCDATA)		
Attributes	id			ty
	class			ty
	xml:lang			ty
	major			ty
	minor			ty
	fix			ty
	tag			ty
Used inside		header		

3.37.

type				
Content model	(#PCDATA)			
Attributes	id			ty
	class			ty

	xml:lang			ty
Used inside	header			

3.38.

authors	
Content model	(person +)
Attributes	id
	class
	xml:lang
Used inside	header faqs

3.39.

notice							
Content model	(#PCDATA strong em code sub sup br img icon acronym map a) *						
Attributes	<table><tr><td>id</td><td></td></tr><tr><td>class</td><td></td></tr><tr><td>xml:lang</td><td></td></tr></table>	id		class		xml:lang	
id							
class							
xml:lang							
Used inside	header						

3.40.

abstract							
Content model	(#PCDATA strong em code sub sup br img icon acronym map a) *						
Attributes	<table><tr><td>id</td><td></td></tr><tr><td>class</td><td></td></tr><tr><td>xml:lang</td><td></td></tr></table>	id		class		xml:lang	
	id						
	class						
	xml:lang						
Used inside	header						

--

3.41.

meta	
Content model	(#PCDATA)
Attributes	
	name
	id
	class
	xml:lang
Used inside	header

3.42.

body	
Content model	(section p source note warning fixme table ol ul dl figure anchor) +
Attributes	
	id
	class
	xml:lang
Used inside	document

3.43.

section	
Content model	(title , (section p source note warning fixme table ol ul dl figure anchor) *)
Attributes	
	id
	class
	xml:lang
Used inside	body section prerequisites steps tips references

3.44.

footer	
Content model	(legal)
Used inside	document

3.45.

legal	
Content model	(#PCDATA strong em code sub sup br img icon acronym map a) *
Attributes	id
	class
	xml:lang
Used inside	footer

3.46.

faqs		
Content model	(title ? , authors ? , (faq faqsection) +)	
Attributes	id	
	class	
	xml:lang	
Used inside	howto	

3.47.

faqsection		
Content model	(title , (faq faqsection) +)	
Attributes	id	
	class	
	xml:lang	

Used inside	faqs faqsection

3.48.

faq		
Content model	(question , answer)	
Attributes	id	
	class	
	xml:lang	
Used inside	faqs faqsection	

3.49.

question	
Content model	(#PCDATA strong em code sub sup br img icon acronym map a elaboration) *
Attributes	id
	class
	xml:lang
Used inside	faq

3.50.

elaboration							
Content model	(#PCDATA strong em code sub sup br img icon acronym map a) *						
Attributes	<table><tr><td>id</td><td></td></tr><tr><td>class</td><td></td></tr><tr><td>xml:lang</td><td></td></tr></table>	id		class		xml:lang	
	id						
	class						
xml:lang							
Used inside	question						

3.51.

answer	
Content model	(#PCDATA strong em code sub sup br img icon acronym map a p source note warning fixme table ol ul dl figure anchor) *
Attributes	author
Used inside	faq

3.52.

howto	
Content model	(header , audience ? , purpose ? , prerequisites ? , steps , extension ? , faqs ? , tips ? , references ? , feedback ?)
Attributes	id class xml:lang

3.53.

overview	
Content model	(p source note warning fixme table ol ul dl figure anchor) *
Attributes	title id class xml:lang

3.54.

purpose	
Content model	(p source note warning fixme table ol ul dl figure anchor) *
Attributes	title

	id			ty
	class			ty
	xml:lang			ty
Used inside	howto			

3.55.

prerequisites				
Content model	(section p source note warning fixme table ol ul dl figure anchor) *			
Attributes	title			ty r
	id			ty
	class			ty
	xml:lang			ty
Used inside	howto			

3.56.

audience				
Content model	(p source note warning fixme table ol ul dl figure anchor) *			
Attributes	title			ty r
	id			ty
	class			ty
	xml:lang			ty
Used inside	howto			

3.57.

steps	
Content model	(section p source note warning fixme table ol ul dl figure anchor) *

Attributes	title			ty
	id			ty
	class			ty
	xml:lang			ty
Used inside	howto			

3.58.

extension			
Content model	(p source note warning fixme table ol ul dl figure anchor) *		
Attributes	title		
	id		
	class		
	xml:lang		
Used inside	howto		

3.59.

tips				
Content model		(section p source note warning fixme table ol ul dl figure anchor) *		
Attributes	title			ty
	id			ty
	class			ty
	xml:lang			ty
Used inside		howto		

3.60.

references

Content model	(section p source note warning fixme table ol ul dl figure anchor) *		
Attributes	title		
	id		
	class		
	xml:lang		
Used inside	howto		

3.61.

feedback			
Content model	(p source note warning fixme table ol ul dl figure anchor) *		
Attributes	title		
	id		
	class		
	xml:lang		
Used inside	howto		

3.62.

last-modified-content-date			
Content model	EMPTY		
Attributes	date		
Used inside	header		