

How to create a PDF document for each tab

This How-To describes the generation of a PDF document for each group of documents that is defined by a tab.

Table of contents

1 Intended Audience.....	2
2 Purpose.....	2
3 Prerequisites.....	2
4 Steps.....	2
4.1 Create your project's main sitemap.xmap.....	2
4.2 Create the aggregator sitemap pdf-tab.xmap.....	2
4.3 Edit project sitemap.xmap.....	2
4.4 Edit project sitemap.xmap to mount pdf-tab.xmap.....	3
4.5 Edit the file pdf-tab.xmap.....	3
4.6 Edit your site.xml.....	3
4.7 Explanation of the operation.....	4
5 Feedback and further development of this How-To.....	5

1. Overview

This How-To describes the generation of a PDF document for each group of documents that is defined by a tab.

1. Intended Audience

Users who need to generate one printable document aggregated from a group of documents.

2. Purpose

By default Forrest generates a pdf file for each separate document of your project. As well you can create a pdf of the whole site. But sometimes it may be necessary to generate a pdf file out of selected tab, i.e. only for certain parts of the site.

3. Prerequisites

- Understand how to create project-specific sitemaps by following the [Using Forrest](#) document.

4. Steps

The procedure outlined below will define a project `sitemap.xmap` and create a new `pdf-tab.xmap` based on the `aggregate.xmap`

4.1. Create your project's main sitemap.xmap

Simply copy the `sitemap.xmap` from the Forrest sitemaps at `${FORREST_HOME}/context/sitemap.xmap` into your `src/documentation` directory (or wherever `${project.sitemap-dir}` points to).

4.2. Create the aggregator sitemap pdf-tab.xmap

Copy the `aggregate.xmap` from Forrest sitemaps into your `${project.sitemap-dir}` and rename it to `pdf-tab.xmap`

4.3. Edit project sitemap.xmap

Note:

This is a workaround for Issue FOR-202

How to create a PDF document for each tab

Edit the project `sitemap.xmap` to comment-out the match for the sitemap like this:

```
<!--  
<map:pipeline internal-only="false">  
<map:select type="exists">  
  <map:when test="{project:sitemap}">  
    <map:mount uri-prefix="" src="{project:sitemap}" check-reload="yes" />  
  </map:when>  
</map:select>  
</map:pipeline  
-->
```

4.4. Edit project `sitemap.xmap` to mount `pdf-tab.xmap`

Insert the following lines after the `<map:match pattern="site.xml">` pipeline in the section called "SOURCE FORMATS".

```
...  
<map:match pattern="pdf-tab.xml">  
  <map:mount uri-prefix="" src="pdf-tab.xmap" check-reload="yes" />  
</map:match>  
...
```

4.5. Edit the file `pdf-tab.xmap`

The `<map:match pattern="*.xml">` element should look like the following:

```
<map:match pattern="*.xml">  
  <map:generate src="cocoon://abs-linkmap"/>  
  <map:transform type="xpath">  
    <map:parameter name="include" value="//*[@wholesite='true']"/>  
    <map:parameter name="exclude" value="//*[@wholesite='false']"/>  
  </map:transform>  
  <map:transform src="resources/stylesheets/site2book.xsl" />  
  <map:transform src="resources/stylesheets/aggregates/book2cinclude.xsl">  
    <map:parameter name="title"  
      value="{conf:project-name}: Still My Foo Site"/>  
  </map:transform>  
  <map:transform type="cinclude"/>  
  <map:transform  
src="resources/stylesheets/aggregates/doc2doc-uniqueids.xsl"/>  
  <map:transform src="resources/stylesheets/aggregates/docs2document.xsl"/>  
  <map:serialize type="xml"/>  
</map:match>
```

4.6. Edit your `site.xml`

Add the following entry to your site.xml in the <about> element

```
...  
<whole_foosite href="pdf-tab.html" label="sub site" />
```

Your site.xml should look like this ...

```
...  
<about label="About">  
  <index label="Index" href="index.html" description="Welcome to MyProj"/>  
  <changes label="Changes" href="changes.html"  
    description="History of Changes" />  
  <todo label="Todo" href="todo.html" description="Todo List" />  
  <whole_foosite href="pdf-tab.html" label="pdf-tab" />  
</about>  
...
```

This allows you to link to it via a <link href="site:whole_foosite"> reference.

Add to every element that should be included in the pdf-tab.pdf the attribute wholesite="true"

```
<sample-wiki label="Wiki page" href="wiki-sample.html "  
  description="wiki-sample" wholesite="true"/>
```

Note:

This attribute will be inherited by all children of the element. Do not use it in the parent element that contains the <whole_foosite href="pdf-tab.html" label="pdf-tab" /> as the child (will cause a stack overflow if you do)!!!

4.7. Explanation of the operation

Line 4 of our example

```
<map:parameter name="include" value="//*[@wholesite='true']"/>
```

looks at your site.xml and will match every element containing the wholesite="true" attribute. For example, to use the "samples" tab ...

```
...  
<samples label="Samples" href="samples/" tab="samples" wholesite="true">  
...  
</samples>  
...
```

It matches **all** of the elements that contain wholesite="true" (in our example <samples> and its "children") for the content of the pdf file to be generated.

How to create a PDF document for each tab

```
<samples label="Samples" href="samples/" tab="samples" wholesite="true">
  <sample2 label="Static content" href="sample2.html"
    description="More Samples" wholesite='false' />
  <sample-wiki label="Wiki page" href="wiki-sample.html"
    description="wiki-sample" />
  <sample-ihtml label="ihtml page" href="ihtml-sample.html"
    description="Test iHTML page" />
</samples>
```

This example shows that you can as well exclude site(s) from the aggregation by using the `wholesite="false"` attribute. This attribute will be as well inherited by all children of the element.

Line 8 defines the title of the pdf file by taking the content of the project-name variable in `skinconf.xml` and adding some funny text:

```
<map:parameter name="title" value="{conf:project-name}: Still
My Foo Site"/>
```

Note:

In the original `aggregate.xmap` there is the line
`<map:parameter name="ignore" value="{1}" />`
just before the title definition (`<map:parameter name="title" value="... />`). Be sure to delete it or comment it out if you like to generate a pdf-file for specific sites. You only need it for the generation of one pdf-file for the whole project (this is what `aggregate.xmap` usually does).

5. Feedback and further development of this How-To

Please provide feedback about this document via the [mailing lists](#).

In the future, this ability will probably be incorporated into the main Forrest process.

FIXME (open):

This document will need to be modified when Issue FOR-202 is solved.