

# DTD documentation

## Table of contents

1 Top-level element(s).....	3
2 List of elements.....	3
3 Element declarations.....	4
3.1 .....	4
3.2 .....	4
3.3 .....	4
3.4 .....	5
3.5 .....	5
3.6 .....	5
3.7 .....	6
3.8 .....	6
3.9 .....	7
3.10 .....	7
3.11 .....	7
3.12 .....	8
3.13 .....	8
3.14 .....	9
3.15 .....	9
3.16 .....	10
3.17 .....	10
3.18 .....	10
3.19 .....	11
3.20 .....	11
3.21 .....	11
3.22 .....	11
3.23 .....	12
3.24 .....	12
3.25 .....	13
3.26 .....	13
3.27 .....	13
3.28 .....	14

3.29 .....	14
3.30 .....	14
3.31 .....	15
3.32 .....	15
3.33 .....	15
3.34 .....	16
3.35 .....	16
3.36 .....	16
3.37 .....	17
3.38 .....	17
3.39 .....	17
3.40 .....	18
3.41 .....	18
3.42 .....	18
3.43 .....	19
3.44 .....	19
3.45 .....	19
3.46 .....	19
3.47 .....	20
3.48 .....	20
3.49 .....	20

## 1. Top-level element(s)

- [document](#)
- [faqs](#)

## 2. List of elements

- [abstract](#)
- [acronym](#)
- [anchor](#)
- [answer](#)
- [authors](#)
- [body](#)
- [br](#)
- [caption](#)
- [code](#)
- [dd](#)
- [dl](#)
- [document](#)
- [dt](#)
- [em](#)
- [faq](#)
- [faqs](#)
- [figure](#)
- [fixme](#)
- [footer](#)
- [fork](#)
- [header](#)
- [icon](#)
- [img](#)
- [jump](#)
- [legal](#)
- [li](#)
- [link](#)
- [note](#)
- [notice](#)
- [ol](#)
- [p](#)
- [part](#)
- [person](#)
- [question](#)
- [section](#)
- [source](#)
- [strong](#)
- [sub](#)
- [subtitle](#)
- [sup](#)
- [table](#)
- [td](#)
- [th](#)
- [title](#)

- [tr](#)
- [type](#)
- [ul](#)
- [version](#)
- [warning](#)

### 3. Element declarations

#### 3.1.

person	
Content model	EMPTY
Attributes	
	id
	class
	xml:lang
	name
	email
Used inside	<a href="#">authors</a>

#### 3.2.

strong	
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *
Attributes	
	id
	class
	xml:lang
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">subtitle</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>

#### 3.3.

em	
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *

Attributes	id			ty
	class			ty
	xml:lang			ty
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">subtitle</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>			

### 3.4.

code				
Content model		( #PCDATA )		
Attributes	id			ty
	class			ty
	xml:lang			ty
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">subtitle</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>			

### 3.5.

sup				
Content model		( #PCDATA )		
Attributes	id			ty
	class			ty
	xml:lang			ty
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">subtitle</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>			

### 3.6.

sub				
Content model		( #PCDATA )		
Attributes		id		ty

	class			ty
	xml:lang			ty
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">subtitle</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>			

**3.7.**

link				
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a> ) *			
Attributes	id			ty
	class			ty
	xml:lang			ty
	href			ty r
	role			ty
	title			ty
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>			

**3.8.**

jump				
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a> ) *			
Attributes	id			ty
	class			ty
	xml:lang			ty
	href			ty r
	role			ty
	title			ty

Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>

### 3.9.

fork													
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a> ) *												
Attributes	<table><tr><td>id</td><td></td></tr><tr><td>class</td><td></td></tr><tr><td>xml:lang</td><td></td></tr><tr><td>href</td><td></td></tr><tr><td>role</td><td></td></tr><tr><td>title</td><td></td></tr></table>	id		class		xml:lang		href		role		title	
	id												
	class												
	xml:lang												
	href												
	role												
title													
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>												

### 3.10.

br		
Content model	EMPTY	
Attributes		
	id	
	class	
	xml:lang	
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>	

### 3.11.

img	
Content model	EMPTY

Attributes	src			ty r
	alt			ty r
	height			ty
	width			ty
	usemap			ty
	ismap			p
	id			ty
	class			ty
	xml:lang			ty
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>			

**3.12.**

icon			
Content model		EMPTY	
Attributes	src		ty r
	alt		ty r
	height		ty
	width		ty
	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>		

**3.13.**

acronym	
Content model	( #PCDATA ) *



Attributes	title			ty
	id			ty
	class			ty
	xml:lang			ty
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>			

### 3.14.

p				
Content model		( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *		
Attributes	id			ty
	class			ty
	xml:lang			ty
	xml:space			p p
Used inside		<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>		

### 3.15.

source				
Content model		( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *		
Attributes	id			ty
	class			ty
	xml:lang			ty
	xml:space			d fi p p
Used inside		<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>		

**3.16.**

note	
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *
Attributes	label
	id
	class
	xml:lang
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>

**3.17.**

warning	
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *
Attributes	label
	id
	class
	xml:lang
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>

**3.18.**

fixme	
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *
Attributes	author
	id
	class
	xml:lang
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>

--

### 3.19.

table	
Content model	( <a href="#">caption</a> ? , <a href="#">tr</a> + )
Attributes	id
	class
	xml:lang
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>

### 3.20.

caption	
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *
Attributes	id
	class
	xml:lang
Used inside	<a href="#">table</a>

### 3.21.

tr	
Content model	( <a href="#">th</a>   <a href="#">td</a> ) +
Attributes	id
	class
	xml:lang
Used inside	<a href="#">table</a>

### 3.22.

th
----

Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *		
Attributes	id		ty
	class		ty
	xml:lang		ty
	colspan		ty d
	rowspan		ty d
Used inside	<a href="#">tr</a>		

**3.23.**

td			
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *		
Attributes	id		ty
	class		ty
	xml:lang		ty
	colspan		ty d
	rowspan		ty d
Used inside	<a href="#">tr</a>		

**3.24.**

li			
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *		
Attributes	id		ty

	class		ty
	xml:lang		ty
Used inside	<a href="#">ul</a>   <a href="#">ol</a>		

### 3.25.

ul			
Content model		( <a href="#">li</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a> ) +	
Attributes	id		ty
	class		ty
	xml:lang		ty
	spacing		p o
Used inside		<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">ul</a>   <a href="#">ol</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>	

### 3.26.

ol			
Content model		( <a href="#">li</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a> ) +	
Attributes	id		ty
	class		ty
	xml:lang		ty
	spacing		p c
Used inside		<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">ul</a>   <a href="#">ol</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>	

### 3.27.

dl				
Content model	( <a href="#">dt</a> , <a href="#">dd</a> ) +			
Attributes	id			ty
	class			ty

	xml:lang			ty
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">ul</a>   <a href="#">ol</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>			

**3.28.**

dt				
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *			
Attributes	id			ty
	class			ty
	xml:lang			ty
Used inside	<a href="#">dl</a>			

**3.29.**

dd				
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *			
Attributes	id			ty
	class			ty
	xml:lang			ty
Used inside	<a href="#">dl</a>			

**3.30.**

figure				
Content model	EMPTY			
Attributes	src			ty r
	alt			ty r
	height			ty

	width			ty
	usemap			ty
	ismap			p
	align			ty
	id			ty
	class			ty
	xml:lang			ty
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>			

### 3.31.

anchor				
Content model		EMPTY		
Attributes	id			ty r
	class			ty
	xml:lang			ty
Used inside		<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>		

### 3.32.

document				
Content model		( <a href="#">header</a> , <a href="#">body</a> , <a href="#">footer</a> ? )		
Attributes	id			ty
	class			ty
	xml:lang			ty

### 3.33.

header			
Content model		( <a href="#">title</a> , <a href="#">subtitle</a> ? , <a href="#">version</a> ? , <a href="#">type</a> ? , <a href="#">authors</a> ? , <a href="#">notice</a> * , <a href="#">abstract</a> ? )	
Attributes		id	

	class			ty
	xml:lang			ty
Used inside	<a href="#">document</a>			

**3.34.**

title				
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a> ) *			
Attributes	id			ty
	class			ty
	xml:lang			ty
Used inside	<a href="#">header</a>   <a href="#">section</a>   <a href="#">part</a>			

**3.35.**

subtitle				
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a> ) *			
Attributes	id			ty
	class			ty
	xml:lang			ty
Used inside	<a href="#">header</a>			

**3.36.**

version				
Content model	( #PCDATA )			
Attributes	id			ty
	class			ty
	xml:lang			ty
	major			ty



	minor			ty
	fix			ty
	tag			ty
Used inside	<a href="#">header</a>			

### 3.37.

type			
Content model		( #PCDATA )	
Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside		<a href="#">header</a>	

### 3.38.

authors			
Content model		( <a href="#">person</a> + )	
Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside		<a href="#">header</a>   <a href="#">faqs</a>	

### 3.39.

notice				
Content model		( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *		
Attributes	id			ty
	class			ty
	xml:lang			ty

Used inside	<a href="#">header</a>

**3.40.**

abstract	
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *
Attributes	id
	class
	xml:lang
Used inside	<a href="#">header</a>

**3.41.**

body							
Content model	( <a href="#">section</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) +						
Attributes	<table><tr><td>id</td><td></td></tr><tr><td>class</td><td></td></tr><tr><td>xml:lang</td><td></td></tr></table>	id		class		xml:lang	
id							
class							
xml:lang							
Used inside	<a href="#">document</a>						

**3.42.**

section	
Content model	( <a href="#">title</a> , ( <a href="#">section</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) * )
Attributes	id
	class
	xml:lang
Used inside	<a href="#">body</a>   <a href="#">section</a>

**3.43.**

footer	
Content model	( <a href="#">legal</a> )
Used inside	<a href="#">document</a>

**3.44.**

legal							
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *						
Attributes	<table> <tr> <td>id</td><td></td></tr> <tr> <td>class</td><td></td></tr> <tr> <td>xml:lang</td><td></td></tr> </table>	id		class		xml:lang	
id							
class							
xml:lang							
Used inside	<a href="#">footer</a>						

**3.45.**

faqs									
Content model	( <a href="#">authors</a> ? , ( <a href="#">faq</a>   <a href="#">part</a> ) + )								
Attributes	<table> <tr> <td>id</td><td></td></tr> <tr> <td>class</td><td></td></tr> <tr> <td>xml:lang</td><td></td></tr> <tr> <td>title</td><td></td></tr> </table>	id		class		xml:lang		title	
id									
class									
xml:lang									
title									

**3.46.**

part							
Content model	( <a href="#">title</a> , ( <a href="#">faq</a>   <a href="#">part</a> ) + )						
Attributes	<table> <tr> <td>id</td><td></td></tr> <tr> <td>class</td><td></td></tr> <tr> <td>xml:lang</td><td></td></tr> </table>	id		class		xml:lang	
id							
class							
xml:lang							

Used inside	<a href="#">faqs</a>   <a href="#">part</a>

**3.47.**

faq		
Content model	( <a href="#">question</a> , <a href="#">answer</a> )	
Attributes	id	
	class	
	xml:lang	
Used inside	<a href="#">faqs</a>   <a href="#">part</a>	

**3.48.**

question	
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *
Attributes	id
	class
	xml:lang
Used inside	<a href="#">faq</a>

**3.49.**

answer			
Content model	( <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *		
Attributes	<table><tr><td>author</td><td></td></tr></table>	author	
author			
Used inside	<a href="#">faq</a>		