

# Upgrading to Forrest 0.6

## Table of contents

1 Introduction.....	2
2 New Features.....	2
3 Run a clean target after upgrade.....	2
4 General upgrade tips.....	2
5 New location of \$FORREST_HOME.....	2
6 Copyless.....	2
7 Sitemap.....	3
8 Private skins might need changes to document2html.xsl.....	3
9 Various additions to skin configuration and new external DTD.....	3
10 forrest.antproxy.xml is obsolete in favor of Ant's <import> task.....	3
11 Deprecation of .html.....	4
12 New forrestbot.....	4
13 New DTDs.....	4
14 SystemIdentifiers for DTDs changed to forrest.apache.org.....	5
15 Projects can use a local CatalogManager.properties.....	5
16 Skins renamed and deleted.....	5
17 Wholesite.html/pdf.....	6
18 To be continued.....	6

## 1. Introduction

This page describes changes to Forrest that affect people who are upgrading to the 0.6 version. Please post your upgrade experiences to either the [dev](#) (../mail-lists.html#forrest-dev) or [user](#) (../mail-lists.html#forrest-user) mailing lists. As more experience is gained, this document will be updated.

(If you are upgrading from a version prior to 0.5 then you may want to see the notes for the [previous](#) (../docs/upgrading\_05.html) upgrade. However you should be fine with the notes from this 0.6 document.)

## 2. New Features

The following list shows some of the key new features for Forrest 0.6 (for the full list of changes, see the [change log](#) (../changes.html) ).

- Copyless
- Now using Subversion (SVN) for source control.
- New skinconf capabilities and new external DTD
- Forrestbot

## 3. Run a clean target after upgrade

To avoid any issue with old classes being loaded, run a 'forrest clean' in your project directory, after you upgraded to this version.

## 4. General upgrade tips

Take advantage of the separation of concerns. Create a fresh 'forrest seed' site, then tweak its forrest.properties and skinconf.xml until it reflects your old site. When it is ready, replace your project's skinconf.xml forrest.properties files. Any remaining issues would concern other aspects of your configuration, such as site.xml and your actual content.

## 5. New location of \$FORREST\_HOME

To use the new Forrest, run 'build.sh' or 'build.bat' as normal, then change the FORREST\_HOME environment variable to point to forrest/src/core instead of ../build/dist/shbat. Also make sure PATH gets updated to use the new \$FORREST\_HOME/bin

## 6. Copyless

## Upgrading to Forrest 0.6

In essence, Forrest does not create a dist anymore, and uses itself in place. No more useless copying to a separate build space, no more backcopying of your changes, all is used live.

It improves the build process a lot. Development turnaround time is excellent. You can even tweak the main forrest core stylesheets and see changes immediately.

### 7. Sitemap

If your old project did not use its own sitemap, then your upgrade process will be easy. If you did use your own sitemap, then you will need to be prepared to make some changes. Hopefully with the new functionality of Forrest, you can do away with it and just use the Forrest default sitemaps.

If you have your own matchers for handling special circumstances (for example special doctypes that you were handling), then you will need to make some changes to your sitemaps. However, you will be pleased to know that the mechanism for extending Forrest is greatly improved in version 0.6 and this will be the last time you will need to make changes to the sitemap when upgrading. See [Using project sitemaps](http://docs/project-sitemap.html) (../docs/project-sitemap.html) for details.

### 8. Private skins might need changes to document2html.xsl

Moved all references to `//skinconfig` out of the `document2html.xsl` into the `site2xhtml.xsl` file. If you have your own skins that were referencing `"$config"` or `"//skinconfig"` in the `document2html.xsl` then you need to make similar changes. For further information, see Issue [FOR-146](http://issues.cocoondev.org/secure/ViewIssue.jspa?key=FOR-146) (<http://issues.cocoondev.org/secure/ViewIssue.jspa?key=FOR-146>) .

### 9. Various additions to skin configuration and new external DTD

Various capabilities have been added to the skinconfig. See the new descriptions in the 'forrest seed' site `src/documentation/skinconf.xml` and synchronise yours.

For example, to use different colors (e.g. the light blue of the old krysalis skin), CSS colors can be specified in `skinconf.xml`

There is now an external DTD which makes it much easier to keep your `skinconf.xml` synchronised.

### 10. `forrest.antproxy.xml` is obsolete in favor of Ant's `<import>` task

Projects that use `forrest.antproxy.xml` via and Ant build task to invoke Forrest, will receive an error message directing them to this document. Please see the [Invoking Forrest](#)

[from Ant](#) (../docs/your-project.html#invoking\_from\_ant) documentation for instructions on how to use the <import> task.

## 11. Deprecation of .html

The .html input file format has been deprecated and will likely be removed in the next release. Please convert all .html files to .ihtml. If you do 'forrest seed' there is a sample ihtml file.

## 12. New forrestbot

The forrestbot and the forrestbot web interface have been completely rewritten. There is no direct way to convert old configurations to new configurations. Please see the [forrestbot documentation](#) (../docs/forrestbot.html) for instructions to create buildfiles that work with the new forrestbot.

## 13. New DTDs

Updated all v1.2 DTDs to become v1.3 DTDs (forward compatibility: v1.2 docs will work fine as V1.3). The main change is the addition of a @class attribute to every element, which enables the "extra-css" section in the skinconf to be put to good use.

Updated the v2.0a DTDs to become v2.0 DTDs (forward incompatibility: v1.2/1.3 docs are not forward-compatible as V2.0).

### Changes from V1.2 to V1.3

=====

document	- Addition of class attribute all elements
faq	- Addition of class attribute all elements
changes	- Addition of class attribute all elements
howto	- Addition of class attribute all elements
todo	- Addition of class attribute all elements

### Changes from V2.0a to V2.0

=====

document	- Addition of class attribute, all elements
	- Addition of label attribute to note and warning elements (consistent with v1.2/1.3)
faq	- Class attribute, all elements
changes	- New DTD
howto	- New DTD
todo	- New DTD

### Changes from V1.3 to V2.0

=====

document	- Renamed <link> to <a>
----------	-------------------------

## Upgrading to Forrest 0.6

faq	<ul style="list-style-type: none"><li>- Removed &lt;fork&gt; and &lt;jump&gt;.</li><li>- Renamed &lt;part&gt; to &lt;faqsection&gt;</li><li>- @title attribute on &lt;faqs&gt; is now a nested &lt;title&gt; element</li></ul>
changes	<ul style="list-style-type: none"><li>- Same changes as in document between 1.3 and 2.0</li></ul>
howto	<ul style="list-style-type: none"><li>- Same changes as in document between 1.3 and 2.0</li></ul>
todo	<ul style="list-style-type: none"><li>- Same changes as in document between 1.3 and 2.0</li></ul>

### 14. SystemIdentifiers for DTDs changed to forrest.apache.org

Everyone should still continue to use the [Catalog Entity Resolver](#) (../docs/catalog.html) and that certainly still operates at the core of Forrest using the well-defined PublicIdentifiers. However, some impoverished XML tools do not, so they need to be able to get the DTDs from the website. Some other tools rely on the System Identifier rather than the Public Identifier. See Forrest Issue [FOR-107](#) (<http://issues.cocoondev.org/secure/ViewIssue.jspa?key=FOR-107>) .

In previous versions of Forrest, and maybe in your application if you copied the fresh-site xdocs, there were inconsistent SystemIdentifiers. Some used local filenames, others used apache.org/forrest/dtd/ URIs. In v0.6 we changed to use System Identifiers at forrest.apache.org/dtd/ as resource URLs. You do not need to change them because you are using the entity resolver, but to remain consistent, it probably is best.

Beware if you have a catalog where the mapping is not declared properly. The Catalog Entity Resolver will miss the local mapping and happily go to the network to get the DTDs. That would cause Forrest to appear to be slow for you, yet it will still operate properly. While we are on that topic, if you use the XSLT document() function - there is a [Xalan bug 28341](#) ([http://issues.apache.org/bugzilla/show\\_bug.cgi?id=28341](http://issues.apache.org/bugzilla/show_bug.cgi?id=28341)) for DTD resolution via document() - please help to fix it. Also see the [Cocoon FAQ](#) (<http://cocoon.apache.org/2.1/faq/faq-xslt.html>) .

### 15. Projects can use a local CatalogManager.properties

You can add a local CatalogManager.properties to your project.classes-dir to define your additional catalogs for DTDs and other entities.

If you do not add such a configuration file then there will be a harmless message on startup "CatalogManager.properties not found".

### 16. Skins renamed and deleted

Skins now have a naming convention. The default skins are [described](#) (skins.html) .

The old skin names are automatically mapped to the new names. You should change your `forrest.properties` to use the new names.

The following skins were renamed (the old names still work, but may not in future releases).

0.5 Name	0.6 Name
krysalis-site	crust
tigris-style	tigris

The following skins were deleted (the old names still work, but may not in future releases).

0.5 Name	0.6 Alias
forrest-css	crust
avalon-tigris	tigris

The old "forrest-site" skin is retained for a little while longer, but is deprecated, so please move to one of the other skins.

## **17. Wholesite.html/pdf**

Instead of using names "site.html/pdf" to create an aggregate page of your entire site, use "wholesite.html/pdf". The old names are still supported for backwards compatibility but they may not be in the future.

## **18. To be continued...**

...as more issues are discovered/remembered :) Please send feedback to the [mailing list](#) (`./mail-lists.html#forrest-dev`) .