

# DTD documentation

## Table of contents

1 Top-level element(s).....	3
2 List of elements.....	3
3 Element declarations.....	4
3.1 .....	4
3.2 .....	4
3.3 .....	4
3.4 .....	5
3.5 .....	5
3.6 .....	6
3.7 .....	6
3.8 .....	6
3.9 .....	7
3.10 .....	7
3.11 .....	8
3.12 .....	8
3.13 .....	9
3.14 .....	9
3.15 .....	9
3.16 .....	10
3.17 .....	10
3.18 .....	10
3.19 .....	11
3.20 .....	11
3.21 .....	11
3.22 .....	12
3.23 .....	12
3.24 .....	13
3.25 .....	13
3.26 .....	13
3.27 .....	14
3.28 .....	14

---

3.29 .....	14
3.30 .....	15
3.31 .....	15
3.32 .....	16
3.33 .....	16
3.34 .....	16
3.35 .....	16
3.36 .....	17
3.37 .....	17
3.38 .....	17
3.39 .....	18
3.40 .....	18
3.41 .....	18
3.42 .....	19
3.43 .....	19
3.44 .....	19
3.45 .....	20
3.46 .....	20
3.47 .....	20
3.48 .....	20
3.49 .....	21

## 1. Top-level element(s)

- [document](#)
- [faqs](#)

## 2. List of elements

- [abstract](#)
- [acronym](#)
- [anchor](#)
- [answer](#)
- [authors](#)
- [body](#)
- [br](#)
- [caption](#)
- [code](#)
- [dd](#)
- [dl](#)
- [document](#)
- [dt](#)
- [em](#)
- [faq](#)
- [faqs](#)
- [figure](#)
- [fixme](#)
- [footer](#)
- [fork](#)
- [header](#)
- [icon](#)
- [img](#)
- [jump](#)
- [legal](#)
- [li](#)
- [link](#)
- [note](#)
- [notice](#)
- [ol](#)
- [p](#)
- [part](#)
- [person](#)
- [question](#)
- [section](#)
- [source](#)
- [strong](#)
- [sub](#)
- [subtitle](#)
- [sup](#)
- [table](#)
- [td](#)

- [th](#)
- [title](#)
- [tr](#)
- [type](#)
- [ul](#)
- [version](#)
- [warning](#)

### 3. Element declarations

#### 3.1.

person			
Content model		EMPTY	
Attributes	id		type:
	class		type:
	xml:lang		type:
	name		type: requir
	email		type: requir
Used inside		<a href="#">authors</a>	

#### 3.2.

strong			
Content model		( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *	
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside		<a href="#">strong</a>   <a href="#">em</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">subtitle</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>	

#### 3.3.

em			
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">subtitle</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>		

### 3.4.

code			
Content model	( #PCDATA )		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">subtitle</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>		

### 3.5.

sup			
Content model	( #PCDATA )		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">subtitle</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>		

## 3.6.

sub			
Content model		( #PCDATA )	
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">subtitle</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>		

## 3.7.

link			
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a> ) *		
Attributes	id		type:
	class		type:
	xml:lang		type:
	href		type: required
	role		type:
	title		type:
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>		

## 3.8.

jump			
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a> ) *		
Attributes	id		type:
	class		type:

	xml:lang		type:
	href		type: requir
	role		type:
	title		type:
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>		

### 3.9.

fork		
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a> ) *	
Attributes	id	type:
	class	type:
	xml:lang	type:
	href	type: requir
	role	type:
	title	type:
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>	

### 3.10.

br			
Content model		EMPTY	
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>		

	<a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>

**3.11.**

img			
Content model		EMPTY	
Attributes	src		type: requir
	alt		type: requir
	height		type:
	width		type:
	usemap		type:
	ismap		possib
	id		type:
	class		type:
	xml:lang		type:
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>		

**3.12.**

icon			
Content model		EMPTY	
Attributes	src		type: require
	alt		type: require
	height		type:
	width		type:
	id		type:
	class		type:
	xml:lang		type:



Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>

**3.13.**

acronym			
Content model		( #PCDATA ) *	
Attributes	title		type: required
	id		type: required
	class		type: required
	xml:lang		type: required
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>		

**3.14.**

p			
Content model		( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *	
Attributes	id		type: required
	class		type: required
	xml:lang		type: required
	xml:space		possible preserved
Used inside		<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>	

**3.15.**

source		
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *	
Attributes	id	type:

	class		type:
	xml:lang		type:
	xml:space		default fixed v possib prese
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>		

**3.16.**

note			
Content model		( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *	
Attributes	label		type:
	id		type:
	class		type:
	xml:lang		type:
Used inside		<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>	

**3.17.**

warning			
Content model		( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *	
Attributes	label		type:
	id		type:
	class		type:
	xml:lang		type:
Used inside		<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>	

**3.18.**

fixme
-------

Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *		
Attributes	author		type: required
	id		type: required
	class		type: required
	xml:lang		type: required
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>		

**3.19.**

table			
Content model	( <a href="#">caption</a> ? , <a href="#">tr</a> + )		
Attributes	id		type: required
	class		type: required
	xml:lang		type: required
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>		

**3.20.**

caption			
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *		
Attributes	id		type: required
	class		type: required
	xml:lang		type: required
Used inside	<a href="#">table</a>		

**3.21.**

tr			
----	--	--	--

Content model	( <a href="#">th</a>   <a href="#">td</a> ) +		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	<a href="#">table</a>		

**3.22.**

th			
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *		
Attributes	id		type:
	class		type:
	xml:lang		type:
	colspan		type: default
	rowspan		type: default
Used inside	<a href="#">tr</a>		

**3.23.**

td			
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *		
Attributes	id		type:
	class		type:
	xml:lang		type:
	colspan		type: default
	rowspan		type:

			default
Used inside	<a href="#">tr</a>		

**3.24.**

li			
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	<a href="#">ul</a>   <a href="#">ol</a>		

**3.25.**

ul			
Content model	( <a href="#">li</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a> ) +		
Attributes	id		type:
	class		type:
	xml:lang		type:
	spacing		possible comp
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">ul</a>   <a href="#">ol</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>		

**3.26.**

ol			
Content model	( <a href="#">li</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a> ) +		
Attributes	id		type:
	class		type:

	xml:lang		type:
	spacing		possib comp
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">ul</a>   <a href="#">ol</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>		

**3.27.**

dl			
Content model		( <a href="#">dt</a> , <a href="#">dd</a> ) +	
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside		<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">ul</a>   <a href="#">ol</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>	

**3.28.**

dt			
Content model		( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *	
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	<a href="#">dl</a>		

**3.29.**

dd			
Content model		( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *	
Attributes		id	type:

	class		type:
	xml:lang		type:
Used inside	<a href="#">dl</a>		

**3.30.**

figure			
Content model		EMPTY	
Attributes	src		type: require
	alt		type: require
	height		type:
	width		type:
	usemap		type:
	ismap		possib
	align		type:
	id		type:
	class		type:
	xml:lang		type:
Used inside		<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>	

**3.31.**

anchor			
Content model		EMPTY	
Attributes	id		type: required
	class		type: required
	xml:lang		type: required
Used inside		<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>	

**3.32.**

document			
Content model	( <a href="#">header</a> , <a href="#">body</a> , <a href="#">footer</a> ? )		
Attributes	id		type:
	class		type:
	xml:lang		type:

**3.33.**

header			
Content model	( <a href="#">title</a> , <a href="#">subtitle</a> ? , <a href="#">version</a> ? , <a href="#">type</a> ? , <a href="#">authors</a> ? , <a href="#">notice</a> * , <a href="#">abstract</a> ? )		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	<a href="#">document</a>		

**3.34.**

title			
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a> ) *		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	<a href="#">header</a>   <a href="#">section</a>   <a href="#">part</a>		

**3.35.**

subtitle	
Content model	( #PCDATA   <strong>   em   code   sub   sup ) *</strong>



Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	<a href="#">header</a>		

### 3.36.

version		
Content model	( #PCDATA )	
Attributes	id	type:
	class	type:
	xml:lang	type:
	major	type:
	minor	type:
	fix	type:
	tag	type:
Used inside	<a href="#">header</a>	

### 3.37.

type			
Content model		( #PCDATA )	
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside		<a href="#">header</a>	

### 3.38.

authors	
Content model	( <a href="#">person</a> + )

Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	<a href="#">header</a>   <a href="#">faqs</a>		

**3.39.**

notice			
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	<a href="#">header</a>		

**3.40.**

abstract			
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	<a href="#">header</a>		

**3.41.**

body			
Content model	( <a href="#">section</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) +		
Attributes	id		type:

	class		type:
	xml:lang		type:
Used inside	<a href="#">document</a>		

**3.42.**

section			
Content model	( <a href="#">title</a> , ( <a href="#">section</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) * )		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	<a href="#">body</a>   <a href="#">section</a>		

**3.43.**

footer	
Content model	( <a href="#">legal</a> )
Used inside	<a href="#">document</a>

**3.44.**

legal			
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	<a href="#">footer</a>		

**3.45.**

faqs			
Content model	( <a href="#">authors</a> ? , ( <a href="#">faq</a>   <a href="#">part</a> ) + )		
Attributes	id		type:
	class		type:
	xml:lang		type:
	title		type: required

**3.46.**

part			
Content model	( <a href="#">title</a> , ( <a href="#">faq</a>   <a href="#">part</a> ) + )		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	<a href="#">faqs</a>   <a href="#">part</a>		

**3.47.**

faq			
Content model	( <a href="#">question</a> , <a href="#">answer</a> )		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	<a href="#">faqs</a>   <a href="#">part</a>		

**3.48.**

question	
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *

Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	<a href="#">faq</a>		

### 3.49.

answer			
Content model	( <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *		
Attributes	author		type:
Used inside	<a href="#">faq</a>		