

DTD documentation

Table of contents

1 Top-level element(s).....	3
2 List of elements.....	3
3 Element declarations.....	4
3.1	4
3.2	4
3.3	5
3.4	5
3.5	5
3.6	6
3.7	6
3.8	7
3.9	7
3.10	7
3.11	8
3.12	8
3.13	9
3.14	9
3.15	10
3.16	10
3.17	10
3.18	11
3.19	11
3.20	12
3.21	12
3.22	12
3.23	13
3.24	13
3.25	13
3.26	14
3.27	14
3.28	14

3.29	15
3.30	15
3.31	16
3.32	16
3.33	16
3.34	17
3.35	17
3.36	17
3.37	18
3.38	18
3.39	18
3.40	19
3.41	19
3.42	19
3.43	20
3.44	20
3.45	20
3.46	20
3.47	21
3.48	21
3.49	21
3.50	22
3.51	22
3.52	22
3.53	23
3.54	23
3.55	23
3.56	24
3.57	24
3.58	24
3.59	25
3.60	25

1. Top-level element(s)

- [document](#)
- [howto](#)
- [overview](#)

2. List of elements

- [abstract](#)
- [acronym](#)
- [anchor](#)
- [answer](#)
- [audience](#)
- [authors](#)
- [body](#)
- [br](#)
- [caption](#)
- [code](#)
- [dd](#)
- [dl](#)
- [document](#)
- [dt](#)
- [em](#)
- [extension](#)
- [faq](#)
- [faqs](#)
- [feedback](#)
- [figure](#)
- [fixme](#)
- [footer](#)
- [fork](#)
- [header](#)
- [howto](#)
- [icon](#)
- [img](#)
- [jump](#)
- [last-modified-content-date](#)
- [legal](#)
- [li](#)
- [link](#)
- [note](#)
- [notice](#)
- [ol](#)
- [overview](#)
- [p](#)
- [part](#)
- [person](#)
- [prerequisites](#)
- [purpose](#)

- [question](#)
- [references](#)
- [section](#)
- [source](#)
- [steps](#)
- [strong](#)
- [sub](#)
- [subtitle](#)
- [sup](#)
- [table](#)
- [td](#)
- [th](#)
- [tips](#)
- [title](#)
- [tr](#)
- [type](#)
- [ul](#)
- [version](#)
- [warning](#)

3. Element declarations

3.1.

person			
Content model		EMPTY	
Attributes	id		type:
	class		type:
	xml:lang		type:
	name		type: requir
	email		type: requir
Used inside		authors	

3.2.

strong			
Content model		(#PCDATA strong em code sub sup br img icon acronym link jump fork) *	
Attributes	id		type:

	class		type:
	xml:lang		type:
Used inside	strong em link jump fork p source note warning fixme caption th td li dt dd title subtitle notice abstract legal question		

3.3.

em			
Content model	(#PCDATA strong em code sub sup br img icon acronym link jump fork) *		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	strong em link jump fork p source note warning fixme caption th td li dt dd title subtitle notice abstract legal question		

3.4.

code			
Content model	(#PCDATA)		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	strong em link jump fork p source note warning fixme caption th td li dt dd title subtitle notice abstract legal question		

3.5.

sup	
Content model	(#PCDATA)

Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	strong em link jump fork p source note warning fixme caption th td li dt dd title subtitle notice abstract legal question		

3.6.

sub			
Content model	(#PCDATA)		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	strong em link jump fork p source note warning fixme caption th td li dt dd title subtitle notice abstract legal question		

3.7.

link			
Content model	(#PCDATA strong em code sub sup br img icon acronym) *		
Attributes	id		type:
	class		type:
	xml:lang		type:
	href		type: required
	role		type:
	title		type:
Used inside	strong em p source note warning fixme caption th td li dt dd title notice abstract legal question		

3.8.

jump			
Content model	(#PCDATA strong em code sub sup br img icon acronym) *		
Attributes	id		type:
	class		type:
	xml:lang		type:
	href		type: required
	role		type:
	title		type:
Used inside	strong em p source note warning fixme caption th td li dt dd title notice abstract legal question		

3.9.

fork			
Content model	(#PCDATA strong em code sub sup br img icon acronym) *		
Attributes	id		type:
	class		type:
	xml:lang		type:
	href		type: required
	role		type:
	title		type:
Used inside	strong em p source note warning fixme caption th td li dt dd title notice abstract legal question		

3.10.

br

Content model	EMPTY		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	strong em link jump fork p source note warning fixme caption th td li dt dd title notice abstract legal question		

3.11.

img			
Content model		EMPTY	
Attributes	src		type: required
	alt		type: required
	height		type:
	width		type:
	usemap		type:
	ismap		possible
	id		type:
	class		type:
	xml:lang		type:
Used inside	strong em link jump fork p source note warning fixme caption th td li dt dd title notice abstract legal question		

3.12.

icon			
Content model		EMPTY	
Attributes	src		type: required
	alt		type:

			required
	height		type: integer
	width		type: integer
	id		type: ID
	class		type: CDATA
	xml:lang		type: language
Used inside	strong em link jump fork p source note warning fixme caption th td li dt dd title notice abstract legal question		

3.13.

acronym			
Content model	(#PCDATA) *		
Attributes	title		type: CDATA
	id		type: ID
	class		type: CDATA
	xml:lang		type: language
Used inside	strong em link jump fork p source note warning fixme caption th td li dt dd title notice abstract legal question		

3.14.

p			
Content model	(#PCDATA strong em code sub sup br img icon acronym link jump fork) *		
Attributes	id		type: ID
	class		type: CDATA
	xml:lang		type: language
	xml:space		possible values: preserve, default

Used inside	th td li dd body section answer overview purpose prerequisites audience steps extension tips references feedback

3.15.

source		
Content model	(#PCDATA strong em code sub sup br img icon acronym link jump fork) *	
Attributes	id	type:
	class	type:
	xml:lang	type:
	xml:space	default: fixed: possible: preserve:
Used inside	th td li dd body section answer overview purpose prerequisites audience steps extension tips references feedback	

3.16.

note		
Content model	(#PCDATA strong em code sub sup br img icon acronym link jump fork) *	
Attributes	label	type:
	id	type:
	class	type:
	xml:lang	type:
Used inside	th td li dd body section answer overview purpose prerequisites audience steps extension tips references feedback	

3.17.

warning

Content model	(#PCDATA strong em code sub sup br img icon acronym link jump fork) *		
Attributes	label		type:
	id		type:
	class		type:
	xml:lang		type:
Used inside	th td li dd body section answer overview purpose prerequisites audience steps extension tips references feedback		

3.18.

fixme			
Content model	(#PCDATA strong em code sub sup br img icon acronym link jump fork) *		
Attributes	author		type: required
	id		type:
	class		type:
	xml:lang		type:
Used inside	th td li dd body section answer overview purpose prerequisites audience steps extension tips references feedback		

3.19.

table			
Content model	(caption ? , tr +)		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	th td li dd body section answer overview purpose prerequisites audience steps extension tips references feedback		

3.20.

caption			
Content model	(#PCDATA strong em code sub sup br img icon acronym link jump fork) *		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	table		

3.21.

tr			
Content model	(th td) +		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	table		

3.22.

th			
Content model	(#PCDATA strong em code sub sup br img icon acronym link jump fork p source note warning fixme table ol ul dl figure anchor) *		
Attributes	id		type:
	class		type:
	xml:lang		type:
	colspan		type: default
	rowspan		type: default

Used inside	tr

3.23.

td			
Content model	(#PCDATA strong em code sub sup br img icon acronym link jump fork p source note warning fixme table ol ul dl figure anchor) *		
Attributes	id		type:
	class		type:
	xml:lang		type:
	colspan		type: default
	rowspan		type: default
Used inside	tr		

3.24.

li			
Content model		(#PCDATA strong em code sub sup br img icon acronym link jump fork p source note warning fixme table ol ul dl figure anchor) *	
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	ul ol		

3.25.

ul			
Content model	(li ol ul dl) +		
Attributes	id		type:

	class		type:
	xml:lang		type:
	spacing		possibl comp
Used inside	th td li ul ol dd body section answer overview purpose prerequisites audience steps extension tips references feedback		

3.26.

ol			
Content model	(li ol ul dl) +		
Attributes	id		type:
	class		type:
	xml:lang		type:
	spacing		possibl comp
Used inside	th td li ul ol dd body section answer overview purpose prerequisites audience steps extension tips references feedback		

3.27.

dl			
Content model	(dt , dd) +		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	th td li ul ol dd body section answer overview purpose prerequisites audience steps extension tips references feedback		

3.28.

dt			
Content model		(#PCDATA strong em code sub sup br img icon acronym link jump fork) *	
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside		dl	

3.29.

dd			
Content model	(#PCDATA strong em code sub sup br img icon acronym link jump fork p source note warning fixme table ol ul dl figure anchor) *		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	dl		

3.30.

figure			
Content model	EMPTY		
Attributes	src		type: required
	alt		type: required
	height		type:
	width		type:
	usemap		type:
	ismap		possible
	align		type:

	id		type:
	class		type:
	xml:lang		type:
Used inside	th td li dd body section answer overview purpose prerequisites audience steps extension tips references feedback		

3.31.

anchor			
Content model	EMPTY		
Attributes	id		type: required
	class		type:
	xml:lang		type:
Used inside	th td li dd body section answer overview purpose prerequisites audience steps extension tips references feedback		

3.32.

document			
Content model	(header , body , footer ?)		
Attributes	id		type:
	class		type:
	xml:lang		type:

3.33.

header			
Content model	(title , subtitle ? , version ? , type ? , authors ? , notice * , abstract ? , last-modified-content-date)		
Attributes	id		type:
	class		type:

	xml:lang		type:
Used inside	document howto		

3.34.

title			
Content model		(#PCDATA strong em code sub sup link jump fork br img icon acronym) *	
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside		header section part	

3.35.

subtitle		
Content model	(#PCDATA strong em code sub sup) *	
Attributes	id	type:
	class	type:
	xml:lang	type:
Used inside	header	

3.36.

version			
Content model	(#PCDATA)		
Attributes	id		type:
	class		type:
	xml:lang		type:
	major		type:
	minor		type:

	fix		type:
	tag		type:
Used inside	header		

3.37.

type			
Content model	(#PCDATA)		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	header		

3.38.

authors			
Content model	(person +)		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	header faqs		

3.39.

notice			
Content model	(#PCDATA strong em code sub sup br img icon acronym link jump fork) *		
Attributes	id		type:
	class		type:
	xml:lang		type:

Used inside	header

3.40.

abstract			
Content model	(#PCDATA strong em code sub sup br img icon acronym link jump fork) *		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	header		

3.41.

body			
Content model		(section p source note warning fixme table ol ul dl figure anchor) +	
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside		document	

3.42.

section			
Content model	(title , (section p source note warning fixme table ol ul dl figure anchor) *)		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	body section prerequisites steps tips references		

3.43.

footer	
Content model	(legal)
Used inside	document

3.44.

legal			
Content model	(#PCDATA strong em code sub sup br img icon acronym link jump fork) *		
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	footer		

3.45.

faqs			
Content model	(authors ? , (faq part) +)		
Attributes	id		type:
	class		type:
	xml:lang		type:
	title		type: requir
Used inside	howto		

3.46.

part	
Content model	(title , (faq part) +)

Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside	faqs part		

3.47.

faq			
Content model		(question , answer)	
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside		faqs part	

3.48.

question			
Content model		(#PCDATA strong em code sub sup br img icon acronym link jump fork) *	
Attributes	id		type:
	class		type:
	xml:lang		type:
Used inside		faq	

3.49.

answer			
Content model	(p source note warning fixme table ol ul dl figure anchor) *		
Attributes	author		type:

Used inside	faq

3.50.

howto		
Content model	(header , audience ? , purpose ? , prerequisites ? , steps , extension ? , faqs ? , tips ? , references ? , feedback ?)	
Attributes	id	type:
	class	type:
	xml:lang	type:

3.51.

overview			
Content model		(p source note warning fixme table ol ul dl figure anchor) *	
Attributes	title		type: required
	id		type: id
	class		type: class
	xml:lang		type: language

3.52.

purpose			
Content model		(p source note warning fixme table ol ul dl figure anchor) *	
Attributes	title		type: required
	id		type: id
	class		type: class
	xml:lang		type: language
Used inside	howto		

3.53.

prerequisites			
Content model	(section p source note warning fixme table ol ul dl figure anchor) *		
Attributes	title		type: required
	id		type: required
	class		type: required
	xml:lang		type: required
Used inside	howto		

3.54.

audience			
Content model	(p source note warning fixme table ol ul dl figure anchor) *		
Attributes	title		type: required
	id		type: required
	class		type: required
	xml:lang		type: required
Used inside	howto		

3.55.

steps			
Content model	(section p source note warning fixme table ol ul dl figure anchor) *		
Attributes	title		type: required
	id		type: required
	class		type: required
	xml:lang		type: required

Used inside	howto

3.56.

extension		
Content model	(p source note warning fixme table ol ul dl figure anchor) *	
Attributes	title	type: required
	id	type: required
	class	type: required
	xml:lang	type: required
Used inside	howto	

3.57.

tips			
Content model		(section p source note warning fixme table ol ul dl figure anchor) *	
Attributes	title		type: required
	id		type: required
	class		type: required
	xml:lang		type: required
Used inside	howto		

3.58.

references			
Content model	(section p source note warning fixme table ol ul dl figure anchor) *		
Attributes	title		type: required
	id		type: required

	class		type:
	xml:lang		type:
Used inside	howto		

3.59.

feedback			
Content model		(p source note warning fixme table ol ul dl figure anchor) *	
Attributes	title		type: required
	id		type:
	class		type:
	xml:lang		type:
Used inside	howto		

3.60.

last-modified-content-date			
Content model		EMPTY	
Attributes		date	type: required
Used inside		header	