# How to create a PDF document for each tab

This How-To describes the generation of a PDF document for each group of documents that is defined by a tab.

## **Table of contents**

1 Intended Audience	2
2 Purpose	2
3 Prerequisites	
4 Steps	
4.1 Create your project's main sitemap.xmap	
4.2 Create the aggregator sitemap pdf-tab.xmap	
4.3 Edit project sitemap.xmap	
4.4 Edit project sitemap.xmap to mount pdf-tab.xmap	
4.5 Edit the file pdf-tab.xmap	
4.6 Edit your site.xml	
4.7 Explanation of the operation	
5 Feedback and further development of this How-To	

#### 1. Intended Audience

Users who need to generate one printable document aggregated from a group of documents.

#### 2. Purpose

By default Forrest generates a pdf file for each separate document of your project. As well you can create a pdf of the whole site. But sometimes it may be necessary to generate a pdf file out of selected tab, i.e. only for certain parts of the site.

#### 3. Prerequisites

• Understand how to create project-specific sitemaps by following the <u>Using Forrest</u> document.

#### 4. Steps

The procedure outlined below will define a project sitemap.xmap and create a new pdf-tab.xmap based on the aggregate.xmap

#### 4.1. Create your project's main sitemap.xmap

Simply copy the sitemap.xmap from the Forrest sitemaps at \${FORREST\_HOME}/context/sitemap.xmap into your src/documentation directory (or wherever \${project.sitemap-dir} points to).

## 4.2. Create the aggregator sitemap pdf-tab.xmap

Copy the aggregate.xmap from Forrest sitemaps into your \${project.sitemap-dir} and rename it to pdf-tab.xmap

# 4.3. Edit project sitemap.xmap

Note:

This is a workaround for Issue FOR-202

Edit the project sitemap.xmap to comment-out the match for the sitemap like this:

#### 4.4. Edit project sitemap.xmap to mount pdf-tab.xmap

Insert the following lines after the <map:match pattern="site.xml"> pipeline in the section called "SOURCE FORMATS".

```
...
<map:match pattern="pdf-tab.xml">
          <map:mount uri-prefix="" src="pdf-tab.xmap" check-reload="yes" />
</map:match>
...
```

## 4.5. Edit the file pdf-tab.xmap

The <map:match pattern="\*.xml"> element should look like the following:

```
<map:match pattern="*.xml">
  <map:generate src="cocoon://abs-linkmap"/>
  <map:transform type="xpath">
        <map:parameter name="include" value="//*[@wholesite='true']"/>
        <map:parameter name="exclude" value="//*[@wholesite='false']"/>
  </map:transform>
  <map:transform src="resources/stylesheets/site2book.xsl" />
  <map:transform src="resources/stylesheets/aggregates/book2cinclude.xsl">
     <map:parameter name="title"</pre>
       value="{conf:project-name}: Still My Foo Site"/>
  </map:transform>
  <map:transform type="cinclude"/>
 <map:transform
src="resources/stylesheets/aggregates/doc2doc-uniqueids.xsl"/>
 <map:transform src="resources/stylesheets/aggregates/docs2document.xsl"/>
 <map:serialize type="xml"/>
</map:match>
```

## 4.6. Edit your site.xml

Add the following entry to your site.xml in the <about> element

```
... <whole_foosite href="pdf-tab.html" label="sub site" />
```

Your site.xml should look like this ...

This allows you to link to it via a link href="site:whole\_foosite"> reference.

Add to every element that should be included in the pdf-tab.pdf the attribute wholesite="true"

```
<sample-wiki label="Wiki page" href="wiki-sample.html"
  description="wiki-sample" wholesite="true"/>
```

#### Note:

This attribute will be inherited by all children of the element. Do not use it in the parent element that contains the <whole\_foosite href="pdf-tab.html" label="pdf-tab" /> as the child (will cause a stack overflow if you do)!!!

#### 4.7. Explanation of the operation

Line 4 of our example

<map:parameter name="include" value="//\*[@wholesite='true']"/>
looks at your site.xml and will match every element containing the wholesite="true"
attribute. For example, to use the "samples" tab ...

```
...
<samples label="Samples" href="samples/" tab="samples" wholesite="true">
...
</samples>
...
```

It matches **all** of the elements that contain wholesite="true" (in our example <samples> and its "children") for the content of the pdf file to be generated.

```
<samples label="Samples" href="samples/" tab="samples" wholesite="true">
    <sample2 label="Static content" href="sample2.html"
        description="More Samples" wholesite='false'/>
        <sample-wiki label="Wiki page" href="wiki-sample.html"
        description="wiki-sample" />
        <sample-ihtml label="ihtml page" href="ihtml-sample.html"
        description="Test iHTML page" />
        </samples>
```

This example shows that you can as well exclude site(s) from the aggregation by using the wholesite="false" attribute. This attribute will be as well inherited by all children of the element.

Line 8 defines the title of the pdf file by taking the content of the project-name variable in skinconf.xml and adding some funny text:

```
<map:parameter name="title" value="{conf:project-name}: Still
My Foo Site"/>
```

#### Note:

```
In the original aggregate.xmap there is the line <map:parameter name="ignore" value="{1}"/> just before the title definition (<map:parameter name="title" value=".../>). Be sure to delete it or comment it out if you like to generate a pdf-file for specific sites. You only need it for the generation of one pdf-file for the whole project (this is what aggregate.xmap usually does).
```

# 5. Feedback and further development of this How-To

Please provide feedback about this document via the mailing lists.

In the future, this ability will probably be incorporated into the main Forrest process.

#### FIXME (open):

This document will need to be modified when Issue FOR-202 is solved.