

# DTD documentation

## Table of contents

1 Top-level element(s).....	3
2 List of elements.....	3
3 Element declarations.....	4
3.1 .....	4
3.2 .....	4
3.3 .....	4
3.4 .....	5
3.5 .....	5
3.6 .....	6
3.7 .....	6
3.8 .....	6
3.9 .....	7
3.10 .....	7
3.11 .....	7
3.12 .....	8
3.13 .....	8
3.14 .....	9
3.15 .....	9
3.16 .....	9
3.17 .....	10
3.18 .....	10
3.19 .....	11
3.20 .....	11
3.21 .....	11
3.22 .....	11
3.23 .....	12
3.24 .....	12
3.25 .....	13
3.26 .....	13
3.27 .....	13
3.28 .....	14

3.29 .....	14
3.30 .....	14
3.31 .....	15
3.32 .....	15
3.33 .....	15
3.34 .....	16
3.35 .....	16
3.36 .....	16
3.37 .....	17
3.38 .....	17
3.39 .....	17
3.40 .....	18
3.41 .....	18
3.42 .....	18
3.43 .....	19
3.44 .....	19
3.45 .....	19
3.46 .....	19
3.47 .....	20
3.48 .....	20
3.49 .....	20
3.50 .....	20
3.51 .....	21

## 1. Top-level element(s)

- [document](#)
- [faqs](#)

## 2. List of elements

- [a](#)
- [abstract](#)
- [acronym](#)
- [anchor](#)
- [answer](#)
- [area](#)
- [authors](#)
- [body](#)
- [br](#)
- [caption](#)
- [code](#)
- [dd](#)
- [dl](#)
- [document](#)
- [dt](#)
- [elaboration](#)
- [em](#)
- [faq](#)
- [faqs](#)
- [faqsection](#)
- [figure](#)
- [fixme](#)
- [footer](#)
- [header](#)
- [icon](#)
- [img](#)
- [legal](#)
- [li](#)
- [map](#)
- [meta](#)
- [note](#)
- [notice](#)
- [ol](#)
- [p](#)
- [person](#)
- [question](#)
- [section](#)
- [source](#)
- [strong](#)
- [sub](#)
- [subtitle](#)
- [sup](#)
- [table](#)
- [td](#)

- [th](#)
- [title](#)
- [tr](#)
- [type](#)
- [ul](#)
- [version](#)
- [warning](#)

### 3. Element declarations

#### 3.1.

person	
Content model	EMPTY
Attributes	
	id
	class
	xml:lang
	name
	email
Used inside	<a href="#">authors</a>

#### 3.2.

strong	
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *
Attributes	
	id
	class
	xml:lang
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">subtitle</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>   <a href="#">elaboration</a>   <a href="#">answer</a>

#### 3.3.

em
----

Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *		
Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">subtitle</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>   <a href="#">elaboration</a>   <a href="#">answer</a>		

**3.4.**

code			
Content model	( #PCDATA )		
Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">subtitle</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>   <a href="#">elaboration</a>   <a href="#">answer</a>		

**3.5.**

sup			
Content model	( #PCDATA )		
Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">subtitle</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>   <a href="#">elaboration</a>   <a href="#">answer</a>		

**3.6.**

sub	
Content model	( #PCDATA )
Attributes	
	id
	class
	xml:lang
Used inside	
	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">subtitle</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>   <a href="#">elaboration</a>   <a href="#">answer</a>

**3.7.**

a	
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a> ) *
Attributes	
	id
	class
	xml:lang
	href
	title
Used inside	
	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>   <a href="#">elaboration</a>   <a href="#">answer</a>

**3.8.**

br	
Content model	EMPTY
Attributes	
	id
	class
	xml:lang

Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>   <a href="#">elaboration</a>   <a href="#">answer</a>

### 3.9.

img																			
Content model	EMPTY																		
Attributes	<table> <tr><td>src</td><td></td></tr> <tr><td>alt</td><td></td></tr> <tr><td>height</td><td></td></tr> <tr><td>width</td><td></td></tr> <tr><td>usemap</td><td></td></tr> <tr><td>ismap</td><td></td></tr> <tr><td>id</td><td></td></tr> <tr><td>class</td><td></td></tr> <tr><td>xml:lang</td><td></td></tr> </table>	src		alt		height		width		usemap		ismap		id		class		xml:lang	
src																			
alt																			
height																			
width																			
usemap																			
ismap																			
id																			
class																			
xml:lang																			
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>   <a href="#">elaboration</a>   <a href="#">answer</a>																		

### 3.10.

map			
Content model	( <a href="#">area</a> + )		
Attributes	<table> <tr><td>name</td><td></td></tr> </table>	name	
name			
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>   <a href="#">elaboration</a>   <a href="#">answer</a>		

### 3.11.

area	
Content model	EMPTY

Attributes	shape			d p d
	coords			ty r
	href			ty r
	title			ty
	nohref			p
	alt			ty r
Used inside	<a href="#">map</a>			

**3.12.**

icon				
Content model		EMPTY		
Attributes	src			ty r
	alt			ty r
	height			ty
	width			ty
	id			ty
	class			ty
	xml:lang			ty
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>   <a href="#">elaboration</a>   <a href="#">answer</a>			

**3.13.**

acronym				
Content model		( #PCDATA ) *		
Attributes	title			ty r
	id			ty



	class			ty
	xml:lang			ty
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>   <a href="#">elaboration</a>   <a href="#">answer</a>			

### 3.14.

p				
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *			
Attributes	id			ty
	class			ty
	xml:lang			ty
	xml:space			p p
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>			

### 3.15.

source				
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *			
Attributes	id			ty
	class			ty
	xml:lang			ty
	xml:space			d fi p p
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>			

### 3.16.

note				
------	--	--	--	--

Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *		
Attributes	label		
	id		
	class		
	xml:lang		
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>		

**3.17.**

warning			
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *		
Attributes	label		
	id		
	class		
	xml:lang		
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>		

**3.18.**

fixme			
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *		
Attributes	author		
	id		
	class		
	xml:lang		
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>		

**3.19.**

table							
Content model	( <a href="#">caption</a> ? , <a href="#">tr</a> + )						
Attributes	<table> <tr> <td>id</td><td></td></tr> <tr> <td>class</td><td></td></tr> <tr> <td>xml:lang</td><td></td></tr> </table>	id		class		xml:lang	
id							
class							
xml:lang							
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>						

**3.20.**

caption							
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *						
Attributes	<table> <tr> <td>id</td><td></td></tr> <tr> <td>class</td><td></td></tr> <tr> <td>xml:lang</td><td></td></tr> </table>	id		class		xml:lang	
id							
class							
xml:lang							
Used inside	<a href="#">table</a>						

**3.21.**

tr							
Content model	( <a href="#">th</a>   <a href="#">td</a> ) +						
Attributes	<table> <tr> <td>id</td><td></td></tr> <tr> <td>class</td><td></td></tr> <tr> <td>xml:lang</td><td></td></tr> </table>	id		class		xml:lang	
id							
class							
xml:lang							
Used inside	<a href="#">table</a>						

**3.22.**

th	
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>

	<a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *		
Attributes	id		
	class		
	xml:lang		
	colspan		
	rowspan		
Used inside	<a href="#">tr</a>		

**3.23.**

td			
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *		
Attributes	id		
	class		
	xml:lang		
	colspan		
	rowspan		
Used inside	<a href="#">tr</a>		

**3.24.**

li			
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *		
Attributes	id		
	class		

	xml:lang	
Used inside	<a href="#">ul</a>   <a href="#">ol</a>	

### 3.25.

ul										
Content model	( <a href="#">li</a> ) +									
Attributes	<table><tr><td>id</td><td></td></tr><tr><td>class</td><td></td></tr><tr><td>xml:lang</td><td></td></tr><tr><td>spacing</td><td></td></tr></table>		id		class		xml:lang		spacing	
	id									
	class									
	xml:lang									
	spacing									
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>									

### 3.26.

ol		
Content model	( <a href="#">li</a> ) +	
Attributes		
	id	
	class	
	xml:lang	
	spacing	
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>	

### 3.27.

dl		
Content model	( <a href="#">dt</a> , <a href="#">dd</a> ) +	
Attributes	id	
	class	
	xml:lang	

Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>

**3.28.**

dt									
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *								
Attributes	<table><tr><td>id</td><td></td></tr><tr><td>class</td><td></td></tr><tr><td>xml:lang</td><td></td></tr><tr><td></td><td></td></tr></table>	id		class		xml:lang			
	id								
	class								
	xml:lang								
Used inside	<a href="#">dl</a>								

**3.29.**

dd		
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *	
Attributes	id	
	class	
	xml:lang	
Used inside	<a href="#">dl</a>	

**3.30.**

figure		
Content model	EMPTY	
Attributes	src	
	alt	
	height	
	width	

	usemap			ty
	ismap			p
	align			ty
	id			ty
	class			ty
	xml:lang			ty
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>			

**3.31.**

anchor			
Content model		EMPTY	
Attributes	id		ty re
	class		ty
	xml:lang		ty
Used inside		<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>	

**3.32.**

document				
Content model		( <a href="#">header</a> , <a href="#">body</a> , <a href="#">footer</a> ? )		
Attributes	id			ty
	class			ty
	xml:lang			ty

**3.33.**

header				
Content model		( <a href="#">title</a> , <a href="#">subtitle</a> ? , <a href="#">version</a> ? , <a href="#">type</a> ? , <a href="#">authors</a> ? , <a href="#">notice</a> * , <a href="#">abstract</a> ? , <a href="#">meta</a> * )		
Attributes		id		ty
		class		ty

	xml:lang			ty
Used inside	<a href="#">document</a>			

**3.34.**

title				
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">a</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a> ) *			
Attributes	id			ty
	class			ty
	xml:lang			ty
Used inside	<a href="#">header</a>   <a href="#">section</a>   <a href="#">faqs</a>   <a href="#">faqsection</a>			

**3.35.**

subtitle				
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a> ) *			
Attributes	id			ty
	class			ty
	xml:lang			ty
Used inside	<a href="#">header</a>			

**3.36.**

version				
Content model	( #PCDATA )			
Attributes	id			ty
	class			ty
	xml:lang			ty
	major			ty
	minor			ty



	fix			ty
	tag			ty
Used inside	<a href="#">header</a>			

**3.37.**

type			
Content model		( #PCDATA )	
Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside		<a href="#">header</a>	

**3.38.**

authors			
Content model	( <a href="#">person</a> + )		
Attributes			
	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">header</a>   <a href="#">faqs</a>		

**3.39.**

notice				
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *			
Attributes	id			ty
	class			ty
	xml:lang			ty

Used inside	<a href="#">header</a>

**3.40.**

abstract		
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *	
Attributes	id	
	class	
	xml:lang	
Used inside	<a href="#">header</a>	

**3.41.**

meta		
Content model	( #PCDATA )	
Attributes	name	
	id	
	class	
	xml:lang	
Used inside	<a href="#">header</a>	

**3.42.**

body									
Content model	( <a href="#">section</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) +								
Attributes	<table><tr><td>id</td><td></td></tr><tr><td>class</td><td></td></tr><tr><td>xml:lang</td><td></td></tr><tr><td></td><td></td></tr></table>	id		class		xml:lang			
	id								
	class								
	xml:lang								
Used inside	<a href="#">document</a>								

--

**3.43.**

section	
Content model	( <a href="#">title</a> , ( <a href="#">section</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) * )
Attributes	
	id
	class
	xml:lang
Used inside	
<a href="#">body</a>   <a href="#">section</a>	

**3.44.**

footer	
Content model	( <a href="#">legal</a> )
Used inside	
<a href="#">document</a>	

**3.45.**

legal	
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *
Attributes	
	id
	class
	xml:lang
Used inside	
<a href="#">footer</a>	

**3.46.**

faqs	
Content model	( <a href="#">title</a> ? , <a href="#">authors</a> ? , ( <a href="#">faq</a>   <a href="#">faqsection</a> ) + )
Attributes	
	id
	class

	xml:lang			ty
--	----------	--	--	----

**3.47.**

faqsection				
Content model		( <a href="#">title</a> , ( <a href="#">faq</a>   <a href="#">faqsection</a> ) + )		
Attributes	id			ty
	class			ty
	xml:lang			ty
Used inside		<a href="#">faqs</a>   <a href="#">faqsection</a>		

**3.48.**

faq				
Content model		( <a href="#">question</a> , <a href="#">answer</a> )		
Attributes	id			ty
	class			ty
	xml:lang			ty
Used inside		<a href="#">faqs</a>   <a href="#">faqsection</a>		

**3.49.**

question				
Content model		( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a>   <a href="#">elaboration</a> ) *		
Attributes	id			ty
	class			ty
	xml:lang			ty
Used inside		<a href="#">faq</a>		

**3.50.**

elaboration	
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *
Attributes	id
	class
	xml:lang
Used inside	<a href="#">question</a>

### 3.51.

answer	
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *
Attributes	author
Used inside	<a href="#">faq</a>