

# DTD documentation

## Table of contents

1 Top-level element(s).....	3
2 List of elements.....	3
3 Element declarations.....	4
3.1 .....	4
3.2 .....	4
3.3 .....	5
3.4 .....	5
3.5 .....	5
3.6 .....	6
3.7 .....	6
3.8 .....	6
3.9 .....	7
3.10 .....	7
3.11 .....	8
3.12 .....	8
3.13 .....	8
3.14 .....	9
3.15 .....	9
3.16 .....	10
3.17 .....	10
3.18 .....	10
3.19 .....	11
3.20 .....	11
3.21 .....	11
3.22 .....	12
3.23 .....	12
3.24 .....	12
3.25 .....	13
3.26 .....	13
3.27 .....	14
3.28 .....	14

3.29 .....	14
3.30 .....	15
3.31 .....	15
3.32 .....	15
3.33 .....	16
3.34 .....	16
3.35 .....	16
3.36 .....	17
3.37 .....	17
3.38 .....	17
3.39 .....	18
3.40 .....	18
3.41 .....	18
3.42 .....	19
3.43 .....	19
3.44 .....	19
3.45 .....	19
3.46 .....	20
3.47 .....	20
3.48 .....	20
3.49 .....	21
3.50 .....	21
3.51 .....	21

## 1. Top-level element(s)

- [document](#)
- [faqs](#)

## 2. List of elements

- [a](#)
- [abstract](#)
- [acronym](#)
- [anchor](#)
- [answer](#)
- [area](#)
- [authors](#)
- [body](#)
- [br](#)
- [caption](#)
- [code](#)
- [dd](#)
- [dl](#)
- [document](#)
- [dt](#)
- [elaboration](#)
- [em](#)
- [faq](#)
- [faqs](#)
- [faqsection](#)
- [figure](#)
- [fixme](#)
- [footer](#)
- [header](#)
- [icon](#)
- [img](#)
- [legal](#)
- [li](#)
- [map](#)
- [meta](#)
- [note](#)
- [notice](#)
- [ol](#)
- [p](#)
- [person](#)
- [question](#)
- [section](#)
- [source](#)
- [strong](#)
- [sub](#)
- [subtitle](#)
- [sup](#)

- [table](#)
- [td](#)
- [th](#)
- [title](#)
- [tr](#)
- [type](#)
- [ul](#)
- [version](#)
- [warning](#)

### 3. Element declarations

#### 3.1.

person		
Content model	EMPTY	
Attributes	id	
	class	
	xml:lang	
	name	
	email	
Used inside	<a href="#">authors</a>	

#### 3.2.

strong		
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *	
Attributes	id	t
	class	t
	xml:lang	t
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">subtitle</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>   <a href="#">elaboration</a>   <a href="#">answer</a>	

## 3.3.

em			
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *		
Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">subtitle</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>   <a href="#">elaboration</a>   <a href="#">answer</a>		

## 3.4.

code			
Content model	( #PCDATA )		
Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">subtitle</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>   <a href="#">elaboration</a>   <a href="#">answer</a>		

## 3.5.

sup			
Content model	( #PCDATA )		
Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">subtitle</a>		

	<a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>   <a href="#">elaboration</a>   <a href="#">answer</a>

**3.6.**

sub		
Content model	( #PCDATA )	
Attributes	id	
	class	
	xml:lang	
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">subtitle</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>   <a href="#">elaboration</a>   <a href="#">answer</a>	

**3.7.**

a		
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a> ) *	
Attributes	id	
	class	
	xml:lang	
	href	
	title	
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>   <a href="#">elaboration</a>   <a href="#">answer</a>	

**3.8.**

br		
Content model	EMPTY	
Attributes	id	

	class		ty
	xml:lang		ty
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>   <a href="#">elaboration</a>   <a href="#">answer</a>		

**3.9.**

img			
Content model	EMPTY		
Attributes	src		ty r
	alt		ty r
	height		ty
	width		ty
	usemap		ty
	ismap		p
	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>   <a href="#">elaboration</a>   <a href="#">answer</a>		

**3.10.**

map			
Content model	( <a href="#">area</a> + )		
Attributes	name		ty
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>   <a href="#">elaboration</a>   <a href="#">answer</a>		

**3.11.**

area		
Content model	EMPTY	
Attributes	shape	
	coords	
	href	
	title	
	nohref	
	alt	
Used inside	<a href="#">map</a>	

**3.12.**

icon		
Content model	EMPTY	
Attributes	src	
	alt	
	height	
	width	
	id	
	class	
	xml:lang	
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>   <a href="#">elaboration</a>   <a href="#">answer</a>	

**3.13.**



acronym		
Content model	( #PCDATA ) *	
Attributes	title	type
	id	type
	class	type
	xml:lang	type
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>   <a href="#">elaboration</a>   <a href="#">answer</a>	

**3.14.**

p		
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *	
Attributes	id	type
	class	type
	xml:lang	type
	xml:space	type
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>	

**3.15.**

source		
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *	
Attributes	id	type
	class	type
	xml:lang	type
	xml:space	type

Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>

**3.16.**

note		
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *	
Attributes		
	label	
	id	
	class	
	xml:lang	
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>	

**3.17.**

warning		
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *	
Attributes	label	
	id	
	class	
	xml:lang	
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>	

**3.18.**

fixme		
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *	
Attributes	author	
	id	
	class	

	xml:lang		ty
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>		

**3.19.**

table			
Content model	( <a href="#">caption</a> ? , <a href="#">tr</a> + )		
Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>		

**3.20.**

caption			
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *		
Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">table</a>		

**3.21.**

tr			
Content model	( <a href="#">th</a>   <a href="#">td</a> ) +		
Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">table</a>		

**3.22.**

th		
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *	
Attributes	id	type
	class	type
	xml:lang	type
	colspan	type default
	rowspan	type default
Used inside	<a href="#">tr</a>	

**3.23.**

td		
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *	
Attributes	id	type
	class	type
	xml:lang	type
	colspan	type default
	rowspan	type default
Used inside	<a href="#">tr</a>	

**3.24.**

li
----

Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *	
Attributes	id	ty
	class	ty
	xml:lang	ty
Used inside	<a href="#">ul</a>   <a href="#">ol</a>	

**3.25.**

ul		
Content model	( <a href="#">li</a> ) +	
Attributes	id	ty
	class	ty
	xml:lang	ty
	spacing	p c
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>	

**3.26.**

ol		
Content model	( <a href="#">li</a> ) +	
Attributes	id	ty
	class	ty
	xml:lang	ty
	spacing	p c
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>	

**3.27.**

dl			
Content model		( <a href="#">dt</a> , <a href="#">dd</a> ) +	
Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside		<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>	

**3.28.**

dt			
Content model		( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *	
Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">dl</a>		

**3.29.**

dd			
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *		
Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">dl</a>		

**3.30.**

figure		
Content model	EMPTY	
Attributes	src	type="text" required="true" ref="figure-image">
	alt	type="text" required="true" ref="figure-image">
	height	type="text" required="true" ref="figure-image">
	width	type="text" required="true" ref="figure-image">
	usemap	type="text" required="true" ref="figure-image">
	ismap	type="boolean" required="true" ref="figure-image">
	align	type="text" required="true" ref="figure-image">
	id	type="text" required="true" ref="figure-image">
	class	type="text" required="true" ref="figure-image">
	xml:lang	type="text" required="true" ref="figure-image">
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>	

**3.31.**

anchor		
Content model	EMPTY	
Attributes	id	type="text" required="true" ref="anchor-id">
	class	type="text" required="true" ref="anchor-id">
	xml:lang	type="text" required="true" ref="anchor-id">
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>	

**3.32.**

document	
Content model	( <a href="#">header</a> , <a href="#">body</a> , <a href="#">footer</a> ? )

Attributes	id		ty
	class		ty
	xml:lang		ty

**3.33.**

header			
Content model	( <a href="#">title</a> , <a href="#">subtitle</a> ? , <a href="#">version</a> ? , <a href="#">type</a> ? , <a href="#">authors</a> ? , <a href="#">notice</a> * , <a href="#">abstract</a> ? , <a href="#">meta</a> * )		
Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">document</a>		

**3.34.**

title			
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">a</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a> ) *		
Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">header</a>   <a href="#">section</a>   <a href="#">faqs</a>   <a href="#">faqsection</a>		

**3.35.**

subtitle			
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a> ) *		
Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">header</a>		



**3.36.**

version		
Content model	( #PCDATA )	
Attributes	id	ty
	class	ty
	xml:lang	ty
	major	ty
	minor	ty
	fix	ty
	tag	ty
Used inside	<a href="#">header</a>	

**3.37.**

type		
Content model	( #PCDATA )	
Attributes	id	ty
	class	ty
	xml:lang	ty
Used inside	<a href="#">header</a>	

**3.38.**

authors		
Content model	( <a href="#">person</a> + )	
Attributes	id	ty
	class	ty
	xml:lang	ty

Used inside	<a href="#">header</a>   <a href="#">faqs</a>

**3.39.**

notice	
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *
Attributes	id
	class
	xml:lang
Used inside	<a href="#">header</a>

**3.40.**

abstract	
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *
Attributes	id
	class
	xml:lang
Used inside	<a href="#">header</a>

**3.41.**

meta	
Content model	( #PCDATA )
Attributes	name
	id
	class
	xml:lang

Used inside	<a href="#">header</a>

**3.42.**

body	
Content model	( <a href="#">section</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) +
Attributes	id
	class
	xml:lang
Used inside	<a href="#">document</a>

**3.43.**

section	
Content model	( <a href="#">title</a> , ( <a href="#">section</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) * )
Attributes	id
	class
	xml:lang
Used inside	<a href="#">body</a>   <a href="#">section</a>

**3.44.**

footer	
Content model	( <a href="#">legal</a> )
Used inside	<a href="#">document</a>

**3.45.**

legal	
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *

Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">footer</a>		

**3.46.**

faqs			
Content model	( <a href="#">title</a> ? , <a href="#">authors</a> ? , ( <a href="#">faq</a>   <a href="#">faqsection</a> ) + )		
Attributes	id		ty
	class		ty
	xml:lang		ty

**3.47.**

faqsection			
Content model	( <a href="#">title</a> , ( <a href="#">faq</a>   <a href="#">faqsection</a> ) + )		
Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">faqs</a>   <a href="#">faqsection</a>		

**3.48.**

faq			
Content model	( <a href="#">question</a> , <a href="#">answer</a> )		
Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">faqs</a>   <a href="#">faqsection</a>		

**3.49.**

question		
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a>   <a href="#">elaboration</a> ) *	
Attributes	id	ty
	class	ty
	xml:lang	ty
Used inside	<a href="#">faq</a>	

**3.50.**

elaboration		
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *	
Attributes	id	ty
	class	ty
	xml:lang	ty
Used inside	<a href="#">question</a>	

**3.51.**

answer		
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *	
Attributes	author	ty
Used inside	<a href="#">faq</a>	