

DTD documentation

Table of contents

1 Top-level element(s).....	3
2 List of elements.....	3
3 Element declarations.....	4
3.1	4
3.2	4
3.3	5
3.4	5
3.5	5
3.6	6
3.7	6
3.8	7
3.9	7
3.10	8
3.11	8
3.12	8
3.13	9
3.14	9
3.15	10
3.16	10
3.17	10
3.18	11
3.19	11
3.20	11
3.21	12
3.22	12
3.23	13
3.24	13
3.25	13
3.26	14
3.27	14
3.28	14

3.29	15
3.30	15
3.31	16
3.32	16
3.33	16
3.34	17
3.35	17
3.36	17
3.37	18
3.38	18
3.39	18
3.40	18
3.41	19
3.42	19
3.43	19
3.44	20
3.45	20
3.46	20
3.47	21
3.48	21
3.49	21
3.50	22
3.51	22
3.52	22
3.53	22
3.54	23
3.55	23
3.56	23
3.57	24
3.58	24
3.59	24
3.60	25
3.61	25
3.62	26

1. Top-level element(s)

- [document](#)
- [howto](#)
- [overview](#)

2. List of elements

- [a](#)
- [abstract](#)
- [acronym](#)
- [anchor](#)
- [answer](#)
- [area](#)
- [audience](#)
- [authors](#)
- [body](#)
- [br](#)
- [caption](#)
- [code](#)
- [dd](#)
- [dl](#)
- [document](#)
- [dt](#)
- [elaboration](#)
- [em](#)
- [extension](#)
- [faq](#)
- [faqs](#)
- [faqsection](#)
- [feedback](#)
- [figure](#)
- [fixme](#)
- [footer](#)
- [header](#)
- [howto](#)
- [icon](#)
- [img](#)
- [last-modified-content-date](#)
- [legal](#)
- [li](#)
- [map](#)
- [meta](#)
- [note](#)
- [notice](#)
- [ol](#)
- [overview](#)
- [p](#)
- [person](#)

- [prerequisites](#)
- [purpose](#)
- [question](#)
- [references](#)
- [section](#)
- [source](#)
- [steps](#)
- [strong](#)
- [sub](#)
- [subtitle](#)
- [sup](#)
- [table](#)
- [td](#)
- [th](#)
- [tips](#)
- [title](#)
- [tr](#)
- [type](#)
- [ul](#)
- [version](#)
- [warning](#)

3. Element declarations

3.1.

person		
Content model	EMPTY	
Attributes	id	type
	class	type
	xml:lang	type
	name	type re
	email	type re
Used inside	authors	

3.2.

strong	
Content model	(#PCDATA strong em code sub sup br img icon acronym map a) *

Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside	strong em a p source note warning fixme caption th td li dt dd title subtitle notice abstract legal question elaboration answer		

3.3.

em			
Content model		(#PCDATA strong em code sub sup br img icon acronym map a) *	
Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside	strong em a p source note warning fixme caption th td li dt dd title subtitle notice abstract legal question elaboration answer		

3.4.

code			
Content model		(#PCDATA)	
Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside	strong em a p source note warning fixme caption th td li dt dd title subtitle notice abstract legal question elaboration answer		

3.5.

sup		
Content model	(#PCDATA)	
Attributes	id	ty
	class	ty
	xml:lang	ty
Used inside	strong em a p source note warning fixme caption th td li dt dd title subtitle notice abstract legal question elaboration answer	

3.6.

sub		
Content model	(#PCDATA)	
Attributes	id	ty
	class	ty
	xml:lang	ty
Used inside	strong em a p source note warning fixme caption th td li dt dd title subtitle notice abstract legal question elaboration answer	

3.7.

a		
Content model	(#PCDATA strong em code sub sup br img icon acronym map) *	
Attributes	id	type
	class	type
	xml:lang	type
	href	type resource
	title	type

Used inside	strong em p source note warning fixme caption th td li dt dd title notice abstract legal question elaboration answer

3.8.

br		
Content model	EMPTY	
Attributes		
	id	
	class	
	xml:lang	
Used inside	strong em a p source note warning fixme caption th td li dt dd title notice abstract legal question elaboration answer	

3.9.

img		
Content model	EMPTY	
Attributes	src	
	alt	
	height	
	width	
	usemap	
	ismap	
	id	
	class	
	xml:lang	
Used inside	strong em a p source note warning fixme caption th td li dt dd title notice abstract legal question elaboration answer	

3.10.

map		
Content model	(area +)	
Attributes	name	ty
Used inside	strong em a p source note warning fixme caption th td li dt dd title notice abstract legal question elaboration answer	

3.11.

area		
Content model	EMPTY	
Attributes	shape coords href title nohref alt	d p d ty r ty p ty r
Used inside	map	

3.12.

icon		
Content model	EMPTY	
Attributes	src alt height width	ty r ty r ty ty

	id		ty
	class		ty
	xml:lang		ty
Used inside	strong em a p source note warning fixme caption th td li dt dd title notice abstract legal question elaboration answer		

3.13.

acronym		
Content model	(#PCDATA) *	
Attributes	title	
	id	
	class	
	xml:lang	
Used inside	strong em a p source note warning fixme caption th td li dt dd title notice abstract legal question elaboration answer	

3.14.

p			
Content model	(#PCDATA strong em code sub sup br img icon acronym map a) *		
Attributes	id		ty
	class		ty
	xml:lang		ty
	xml:space		p p
Used inside	th td li dd body section answer overview purpose prerequisites audience steps extension tips references feedback		

3.15.

source		
Content model	(#PCDATA strong em code sub sup br img icon acronym map a) *	
Attributes	id	ty
	class	ty
	xml:lang	ty
	xml:space	d fi p p
Used inside	th td li dd body section answer overview purpose prerequisites audience steps extension tips references feedback	

3.16.

note		
Content model	(#PCDATA strong em code sub sup br img icon acronym map a) *	
Attributes	label	ty
	id	ty
	class	ty
	xml:lang	ty
Used inside	th td li dd body section answer overview purpose prerequisites audience steps extension tips references feedback	

3.17.

warning		
Content model	(#PCDATA strong em code sub sup br img icon acronym map a) *	
Attributes	label	ty

	id		ty
	class		ty
	xml:lang		ty
Used inside	th td li dd body section answer overview purpose prerequisites audience steps extension tips references feedback		

3.18.

fixme			
Content model		(#PCDATA strong em code sub sup br img icon acronym map a) *	
Attributes	author		ty r
	id		ty
	class		ty
	xml:lang		ty
Used inside	th td li dd body section answer overview purpose prerequisites audience steps extension tips references feedback		

3.19.

table			
Content model		(caption ? , tr +)	
Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside	th td li dd body section answer overview purpose prerequisites audience steps extension tips references feedback		

3.20.

caption		
Content model	(#PCDATA strong em code sub sup br img icon acronym map a) *	
Attributes	id	ty
	class	ty
	xml:lang	ty
Used inside	table	

3.21.

tr		
Content model	(th td) +	
Attributes	id	ty
	class	ty
	xml:lang	ty
Used inside	table	

3.22.

th		
Content model	(#PCDATA strong em code sub sup br img icon acronym map a p source note warning fixme table ol ul dl figure anchor) *	
Attributes	id	ty
	class	ty
	xml:lang	ty
	colspan	ty d
	rowspan	ty d
Used inside	tr	

3.23.

td		
Content model	(#PCDATA strong em code sub sup br img icon acronym map a p source note warning fixme table ol ul dl figure anchor) *	
Attributes	id	type
	class	type
	xml:lang	type
	colspan	type d
	rowspan	type d
Used inside	tr	

3.24.

li		
Content model	(#PCDATA strong em code sub sup br img icon acronym map a p source note warning fixme table ol ul dl figure anchor) *	
Attributes	id	type
	class	type
	xml:lang	type
Used inside	ul ol	

3.25.

ul		
Content model	(li) +	
Attributes	id	type
	class	type
	xml:lang	type

	spacing		p c
Used inside	th td li dd body section answer overview purpose prerequisites audience steps extension tips references feedback		

3.26.

ol			
Content model	(li) +		
Attributes	id		ty
	class		ty
	xml:lang		ty
	spacing		p c
Used inside	th td li dd body section answer overview purpose prerequisites audience steps extension tips references feedback		

3.27.

dl			
Content model	(dt , dd) +		
Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside	th td li dd body section answer overview purpose prerequisites audience steps extension tips references feedback		

3.28.

dt	
Content model	(#PCDATA strong em code sub sup br img icon acronym map a) *

Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside	dl		

3.29.

dd			
Content model	(#PCDATA strong em code sub sup br img icon acronym map a p source note warning fixme table ol ul dl figure anchor) *		
Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside	dl		

3.30.

figure			
Content model	EMPTY		
Attributes	src		ty r
	alt		ty r
	height		ty
	width		ty
	usemap		ty
	ismap		p
	align		ty
	id		ty
	class		ty
	xml:lang		ty

Used inside	th td li dd body section answer overview purpose prerequisites audience steps extension tips references feedback

3.31.

anchor		
Content model	EMPTY	
Attributes	id	
	class	
	xml:lang	
Used inside	th td li dd body section answer overview purpose prerequisites audience steps extension tips references feedback	

3.32.

document		
Content model	(header , body , footer ?)	
Attributes	id	
	class	
	xml:lang	

3.33.

header		
Content model	(title , subtitle ? , version ? , type ? , authors ? , notice * , abstract ? , meta * , last-modified-content-date)	
Attributes	id	
	class	
	xml:lang	
Used inside	document howto	

3.34.

title		
Content model	(#PCDATA strong em code sub sup a br img icon acronym map) *	
Attributes	id	type
	class	type
	xml:lang	type
Used inside	header section faqs faqsection	

3.35.

subtitle		
Content model	(#PCDATA strong em code sub sup) *	
Attributes	id	type
	class	type
	xml:lang	type
Used inside	header	

3.36.

version		
Content model	(#PCDATA)	
Attributes	id	ty
	class	ty
	xml:lang	ty
	major	ty
	minor	ty
	fix	ty
	tag	ty
Used inside	header	

--

3.37.

type		
Content model	(#PCDATA)	
Attributes	id	t
	class	t
	xml:lang	t
Used inside	header	

3.38.

authors		
Content model	(person +)	
Attributes	id	t
	class	t
	xml:lang	t
Used inside	header faqs	

3.39.

notice		
Content model	(#PCDATA strong em code sub sup br img icon acronym map a) *	
Attributes	id	t
	class	t
	xml:lang	t
Used inside	header	

3.40.

abstract		
Content model	(#PCDATA strong em code sub sup br img icon acronym map a) *	
Attributes	id	ty
	class	ty
	xml:lang	ty
Used inside	header	

3.41.

meta		
Content model	(#PCDATA)	
Attributes	name	type: required
	id	type: required
	class	type: required
	xml:lang	type: required
Used inside	header	

3.42.

body		
Content model	(section p source note warning fixme table ol ul dl figure anchor) +	
Attributes	id	ty
	class	ty
	xml:lang	ty
Used inside	document	

3.43.

section		
Content model	(title , (section p source note warning fixme table ol ul dl figure anchor) *)	
Attributes	id	ty
	class	ty
	xml:lang	ty
Used inside	body section prerequisites steps tips references	

3.44.

footer		
Content model	(legal)	
Used inside	document	

3.45.

legal		
Content model	(#PCDATA strong em code sub sup br img icon acronym map a) *	
Attributes	id	ty
	class	ty
	xml:lang	ty
Used inside	footer	

3.46.

faqs		
Content model	(title ? , authors ? , (faq faqsection) +)	
Attributes	id	ty
	class	ty
	xml:lang	ty

Used inside	howto

3.47.

faqsection		
Content model	(title , (faq faqsection) +)	
Attributes	id	type
	class	type
	xml:lang	type
Used inside	faqs faqsection	

3.48.

faq			
Content model		(question , answer)	
Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside		faqs faqsection	

3.49.

question		
Content model	(#PCDATA strong em code sub sup br img icon acronym map a elaboration) *	
Attributes	id	type
	class	type
	xml:lang	type
Used inside	faq	

3.50.

elaboration		
Content model	(#PCDATA strong em code sub sup br img icon acronym map a) *	
Attributes	id	ty
	class	ty
	xml:lang	ty
Used inside	question	

3.51.

answer		
Content model	(#PCDATA strong em code sub sup br img icon acronym map a p source note warning fixme table ol ul dl figure anchor) *	
Attributes	author	ty
Used inside	faq	

3.52.

howto		
Content model	(header , audience ? , purpose ? , prerequisites ? , steps , extension ? , faqs ? , tips ? , references ? , feedback ?)	
Attributes	id	ty
	class	ty
	xml:lang	ty

3.53.

overview		
Content model	(p source note warning fixme table ol ul dl figure anchor) *	

Attributes	title		ty re
	id		ty
	class		ty
	xml:lang		ty

3.54.

purpose			
Content model	(p source note warning fixme table ol ul dl figure anchor) *		
Attributes	title		ty re
	id		ty
	class		ty
	xml:lang		ty
Used inside	howto		

3.55.

prerequisites			
Content model	(section p source note warning fixme table ol ul dl figure anchor) *		
Attributes	title		ty re
	id		ty
	class		ty
	xml:lang		ty
Used inside	howto		

3.56.

audience			
Content model	(p source note warning fixme table ol ul dl figure anchor) *		

Attributes	title		ty re
	id		ty
	class		ty
	xml:lang		ty
Used inside	howto		

3.57.

steps		
Content model	(section p source note warning fixme table ol ul dl figure anchor) *	
Attributes	title	
	id	
	class	
	xml:lang	
Used inside	howto	

3.58.

extension		
Content model	(p source note warning fixme table ol ul dl figure anchor) *	
Attributes	title	type: text, required
	id	type: text, required
	class	type: text, required
	xml:lang	type: text, required
Used inside	howto	

3.59.

tips			
Content model	(section p source note warning fixme table ol ul dl figure anchor) *		
Attributes	title		ty r
	id		ty
	class		ty
	xml:lang		ty
Used inside	howto		

3.60.

references			
Content model	(section p source note warning fixme table ol ul dl figure anchor) *		
Attributes	title		ty r
	id		ty
	class		ty
	xml:lang		ty
Used inside	howto		

3.61.

feedback			
Content model	(p source note warning fixme table ol ul dl figure anchor) *		
Attributes	title		ty r
	id		ty
	class		ty
	xml:lang		ty

Used inside	howto

3.62.

last-modified-content-date			
Content model	EMPTY		
Attributes	<table><tr><td>date</td><td></td></tr></table>	date	
date			
Used inside	header		