

EX 04. Ionospheric error map (09/04/19)

Compute 4 maps of ionospheric error corrections

- for elevation 90 degrees
- latitude = -80 to 80 degrees (step 0.5 degrees)
- longitude = -180 to 180 degrees (step 0.5 degrees);
- at 0:00, 6:00, 12:00, 18:00 (GMT)
- using the ionospheric parameters in "ionoparams.dat"

Compute 2 polar maps of ionospheric error corrections

- for an observer located in Milan
- elevation = 0 to 90 degrees (step 0.5 degrees)
- azimuth = -180 to 180 degrees (step 0.5 degrees);
- at 0:00, 12:00 (GMT)
- using the ionospheric parameters in "ionoparams.dat"

To compute the correction for one point you can use the function "iono_error_correction.m":
SYNTAX:

```
[corr] = iono_error_correction(lat, lon, az, el, time_rx, ionoparams, sbas);
```

INPUT:

```
lat = receiver latitude [degrees]
lon = receiver longitude [degrees]
az = satellite azimuth [degrees]
el = satellite elevation [degrees]
time_rx = receiver reception time
ionoparams = ionospheric correction parameters
sbas = SBAS corrections <optional if available>
```

OUTPUT:

```
corr = ionospheric error correction [m]
```

DESCRIPTION:

Computation of the pseudorange correction due to ionospheric delay.
Klobuchar model or SBAS ionosphere interpolation.

To create the ionoparams variable in the format required by the function
"iono_error_correction.m" copy the following lines:

```
line1 = 'GPSA    7.4506D-09  1.4901D-08 -5.9605D-08 -1.1921D-07      IONOSPHERIC
CORR';
line2 = 'GPSB    9.2160D+04  1.3107D+05 -6.5536D+04 -5.2429D+05      IONOSPHERIC
CORR';
ionoparams = [cell2mat(textscan(line1, '%*s %f %f %f %f %*s')) ...
              cell2mat(textscan(line2, '%*s %f %f %f %f %*s'))];
```

Workflow

Compute 4 maps of ionospheric error corrections

- 1) Set the elevation of the hypothetical satellite to 90 degrees (Note: At 90 degrees the azimuth is not relevant for the computation of the ionospheric map)
- 2) Set the time steps for the computation of the maps (in seconds)
- 3) Define the step of the grid
- 4) Preallocation of the ionospheric error correction maps
- 5) Cycle 'for' (3 cycles for) to estimate for each epoch and each point of the map the ionospheric error correction
- 6) Plot the computed maps (for example with 'geoshow' function)

Compute 2 polar maps of ionospheric error corrections

- 1) Set the time steps for the computation of the maps (in seconds)
- 2) Define the step of the grid
- 3) Set the geodetic coordinates of an observer located in Milan
- 4) Preallocation of the ionospheric error correction maps
- 5) Cycle 'for' (3 cycles for) to estimate for each epoch and each point of the map the ionospheric error correction
- 6) Plot the computed maps (for example with 'geoshow' function)