

Week 4 Module:

Date: 09/07/2026

EASY LEVEL:

Problem Statement:

Given a positive integer N , determine the total number of digits present in the number.

Your task is to write a program that counts and prints the total number of digits.

Input Format

A single integer N .

Output Format

Print a single integer representing the total number of digits in N .

Constraints

$$1 \leq N \leq 10^{18}$$

Example 1

Input

12345

Output

5

Explanation

The number 12345 contains 5 digits.

Example 2

Input

7

Output

1

Explanation

The number 7 consists of only one digit.

Easy Level

1) Total Number of Digits

- The objective is to determine the total numbers of digits present in a given positive integer N .
- The inputs is a single integer N , and the output should be a single integer representing the counts of its digits.
- We Can repeatedly divide the numbers by 10. Each division removes the last digit of the numbers. We keep a count of that increments with each division until the numbers becomes 0.

Code

```
#include <stdio.h>
int main() {
    unsigned long long n;
    int Count = 0;
    scanf ("%llu", &n);

    if (n == 0) {
        Count = 1;
    } else {
        while (n > 0) {
            Count++;
            n /= 10;
        }
    }

    printf ("%d\n", Count);
    return 0;
}
```

I/p:- 12345

O/p:- 5



```
2
3 int main() {
4     unsigned long long n;
5     int count = 0;
6
7     scanf("%llu", &n);
8
9     // Count digits
10    if (n == 0) {
11        count = 1;
12    } else {
13        while (n > 0) {
14            count++;
15            n /= 10;
16        }
17    }
18
19    printf("%d\n", count);
20
21    return 0;
22 }
```

Output

Clear

12345

5

=== Code Execution Successful ===

Problem Statement

Given a positive integer **N**, reverse its digits and print the reversed number.

Your task is to write a program that reverses the given number.

Input Format

A single integer **N**.

Output Format

Print the reversed number.

Constraints

$$1 \leq N \leq 10^{18}$$

Example 1**Input**

12345

Output

54321

Explanation

Reversing the digits of **12345** gives **54321**.

Example 2**Input**

90010

Output

1009

2) Reverse the Digits

- The program must reverse the digits of a given positive integer N and print the result.
- Any leading zeros that occur after reversing are removed automatically.
- Use the modulo operator ($\% 10$) to extract the last digit, multiply a tracking reverse variable by 10 and add the extracted digits. Then divide the original numbers by 10 to move to the next digit.

Code

```
#include <stdio.h>
int main() {
    unsigned long long n, reversed = 0;

    // Read the input
    scanf("%llu", &n);

    while (n > 0) {
        int remainder = n % 10;
        reversed = reversed * 10 + remainder;
        n /= 10;
    }

    // Print the output
    printf("%llu\n", reversed);
    return 0;
}
```

I/P:- 12345

O/P:- 54321



```
1  #include <stdio.h>
2
3  int main() {
4      unsigned long long n, reversed = 0;
5
6      // Read number
7      scanf("%llu", &n);
8
9      // Reverse the number
10     while (n > 0) {
11         int remainder = n % 10;
12         reversed = reversed * 10 + remainder;
13         n /= 10;
14     }
15
16     // Print result
17     printf("%llu\n", reversed);
18
19     return 0;
20 }
```

12345

54321

=== Code Execution Successful ===

Problem Statement

Given a positive integer N , calculate the sum of all its digits.

Your task is to write a program that computes and prints the sum of the digits.

Input Format

A single integer N .

Output Format

Print a single integer representing the sum of all digits.

Constraints

$$1 \leq N \leq 10^{18}$$

Example 1

Input

12345

Output

15

Explanation

The sum of the digits is:

$$1 + 2 + 3 + 4 + 5 = 15$$

Example 2

Input

9087

Output

24

Explanation

The sum of the digits is:

$$9 + 0 + 8 + 7 = 24$$

3) Sum of All Digits

- The task is to Compute and print the sum of all the digits in a positive integer N.
- Similar to extracting digits for reversing, we isolate the last digit using modulo 10 ($n \% 10$). We then add the extracted digit to an ongoing sum variable and reduce the number by dividing it by 10.

Code

```
#include <stdio.h>
int main(){
    unsigned long long n, sum = 0;
```

```
// Read the input
scanf ("%llu", &n);
```

```
while (n > 0){
    sum += (n % 10);
    n /= 10;
}
```

```
// Print the output
printf ("%llu\n", sum);
return 0;
}
```

I/P:- 12345

O/P:- 15



```
1  #include <stdio.h>
2
3  int main() {
4      unsigned long long n, sum = 0;
5
6      // Read number
7      scanf("%llu", &n);
8
9      // Add all digits
10     while (n > 0) {
11         |     sum += (n % 10);
12         |     n /= 10;
13     }
14
15     // Print sum
16     printf("%llu\n", sum);
17
18     return 0;
19 }
```

12345

15

=== Code Execution Successful ===

Problem Statement

Given a positive integer N , count how many **even** digits and how many **odd** digits are present in the number.

Your task is to write a program that prints the total count of even digits followed by the total count of odd digits.

Input Format

A single integer N .

Output Format

Print two integers separated by a space:

- Number of even digits
- Number of odd digits

Constraints

$$1 \leq N \leq 10^{18}$$

Example 1

Input

123456

Output

3 3

Explanation

Even digits are 2, 4, 6.

Odd digits are 1, 3, 5.

Therefore, the output is 3 3.

Example 2

Input

908172

Output

3 3

Explanation

Even digits are 0, 8, 2.

Odd digits are 9, 1, 7.

Therefore, the output is 3 3.

4) Count Even and add digits

- This problem requires counting the total numbers of even digits and odd digits in the numbers N .
- The required output format is two integers separated by a space: the number of even digits followed by the number of odd digits.
- Extract each digits using modulo 10. Use an if / else statement to check if the digits modulo 2 equals 0. If it does, increment the even counter. Otherwise, increment the odd counter.

Code

```
#include <stdio.h>
int main() {
    unsigned long long n;
    int even_count = 0, odd_count = 0;

    // Read the input
    scanf ("%llu", &n);
    if (n == 0) {
        even_count = 1;
    }
    while (n > 0) {
        int digit = n % 10;
        if (digit % 2 == 0) {
            even_count ++;
        } else {
            odd_count ++;
        }
        n /= 10;
    }

    // Print the output (Even count followed by odd count)
    printf ("%d %d\n", even_count, odd_count);
    return 0;
}
```

I/P:- 123456

O/P:- 3 3



```
1  #include <stdio.h>
2
3  int main() {
4      unsigned long long n;
5      int even_count = 0, odd_count = 0;
6
7      // Read number
8      scanf("%llu", &n);
9
10     if (n == 0) {
11         even_count = 1;
12     }
13
14     // Count even and odd digits
15     while (n > 0) {
16         int digit = n % 10;
17
18         if (digit % 2 == 0) {
19             even_count++;
20         } else {
21             odd_count++;
22         }
23     }
24 }
```

main.c



Share

Run

Output

Clear

```
11 |     even_count = 1;
12 | }
13 |
14 | // Count even and odd digits
15 | while (n > 0) {
16 | |     int digit = n % 10;
17 | |
18 | |     if (digit % 2 == 0) {
19 | | |         even_count++;
20 | | |     } else {
21 | | |         odd_count++;
22 | | |     }
23 | |
24 | |     n /= 10;
25 | | }
26 |
27 | // Print counts
28 | printf("%d %d\n", even_count, odd_count);
29 |
30 | return 0;
31 | }
```

123456

3 3

=== Code Execution Successful ===

Problem Statement

Given a positive integer N , find and print the largest digit present in the number.

Your task is to write a program that determines the maximum digit.

Input Format

A single integer N .

Output Format

Print the largest digit present in the given number.

Constraints

$$1 \leq N \leq 10^{18}$$

Example 1**Input**

472953

Output

9

Explanation

The digits are 4, 7, 2, 9, 5, 3.

The largest digit among them is 9.

Example 2**Input**

100248

Output

8

Explanation

The digits are 1, 0, 0, 2, 4, 8.

The largest digit is 8.

5) Largest Digit

- The task is to find and print the maximum digit present in the positive integer N.
- Initialize a max_digit variable to 0 (since digit range from 0 to 9). As you extract each digit using modulo while loop, compare it against max_digit. If the extracted digit is greater, update max_digit.

Code

```
#include <stdio.h>
int main(){
    unsigned long long n;
    int max_digit = 0;

    // Read the input
    scanf("%llu", &n);

    while (n > 0){
        int digit = n % 10;
        if (digit > max_digit)
            max_digit = digit;
        n /= 10;
    }

    // Print the output
    printf("%d\n", max_digit);
    return 0;
}
```

I/P:- 472952

O/P:- 9

I/P:- 472952

O/P:- 9



```
3 int main() {
4     unsigned long long n;
5     int max_digit = 0;
6
7     // Read number
8     scanf("%llu", &n);
9
10    // Find largest digit
11    while (n > 0) {
12        int digit = n % 10;
13
14        if (digit > max_digit) {
15            max_digit = digit;
16        }
17
18        n /= 10;
19    }
20
21    // Print answer
22    printf("%d\n", max_digit);
23 }
```

472953

9

=== Code Execution Successful ===

MEDIUM LEVEL:

Problem Statement

Given two positive integers **L** and **R**, count how many prime numbers are present in the inclusive range **[L, R]**.

A **prime number** is a natural number greater than **1** that has exactly two distinct positive divisors: **1** and itself.

Your task is to write a program that counts and prints the total number of prime numbers in the given range.

Input Format

Two integers **L** and **R** separated by a space.

Output Format

Print a single integer representing the total number of prime numbers in the given range.

Constraints

$$1 \leq L \leq R \leq 10^5$$

Example 1

Input

1 10

Output

4

Explanation

The prime numbers between **1** and **10** are: 2, 3, 5, 7

Hence, the total count is **4**.

Example 2

Input

11 20

Output

4

Explanation

The prime numbers between **11** and **20** are: 11, 13, 17, 19

Hence, the total count is **4**.

Code

```
#include <stdio.h>
```

```
// Helper function to check if a number is prime
```

```
int is_prime(int num) {
```

```
    if (num <= 1) return 0;
```

```
    if (num == 2 || num == 3) return 1;
```

```
    if (num % 2 == 0 || num % 3 == 0) return 0;
```

```
    for (int i = 5; i * i <= num; i += 6) {
```

```
        if (num % i == 0 || num % (i + 2) == 0)
```

```
            return 0;
```

```
    }
```

```
    return 1;
```

```
}
```

```
int main() {
```

```
    int L, R, prime_count = 0;
```

```
    // Read the input
```

```
    scanf("%d %d", &L, &R);
```

```
    for (int i = L; i <= R; i++) {
```

```
        if (is_prime(i)) {
```

```
            prime_count++;
```

```
        }
```

```
    }
```

```
    // Print the output
```

```
    printf("%d\n", prime_count);
```

```
    return 0;
```

```
}
```

I/P:- 10

O/P:- 4

7) Sum of proper divisors

- The objective is to calculate and print the Sum of all proper divisors of N .
- A proper divisor is a positive divisor of a number that excludes the number itself.
- N can be up to 10^6 .
- we can find all divisors efficiently by looping up to the square root of N . For each divisor i found, we add i and if N/i is distinct and not equal to N , we add N/i to our sum. Note that i is always a proper divisor for numbers greater than 1.

Code

```
#include <stdio.h>
int main() {
    int N;
    scanf("%d", &N);

    long long sum = 0;
    for (int i = 1; i * i <= N; i++) {
        if (N % i == 0) {
            sum += i;
            if (i != N / i)
                sum += N / i;
        }
    }
    printf("%lld\n", sum);
    return 0;
}
```



```
1  #include <stdio.h>
2
3  // Check if number is prime
4  int is_prime(int num) {
5      if (num <= 1)
6          return 0;
7
8      if (num == 2 || num == 3)
9          return 1;
10
11     if (num % 2 == 0 || num % 3 == 0)
12         return 0;
13
14     for (int i = 5; i * i <= num; i += 6) {
15         if (num % i == 0 || num % (i + 2) == 0) {
16             return 0;
17         }
18     }
19
20     return 1;
21 }
```



```
20     return 1;
21 }
22
23 int main() {
24     int L, R, prime_count = 0;
25
26     // Read range
27     scanf("%d %d", &L, &R);
28
29     // Count primes
30     for (int i = L; i <= R; i++) {
31         if (is_prime(i)) {
32             prime_count++;
33         }
34     }
35
36     // Print answer
37     printf("%d\n", prime_count);
38
39     return 0;
40 }
```

1 10

4

=== Code Execution Successful ===

Problem Statement

Given a positive integer N , find the sum of all its **proper divisors**.

A **proper divisor** of a number is a positive divisor of the number excluding the number itself.

Your task is to write a program that calculates and prints the sum of all proper divisors of N .

Input Format

A single integer N .

Output Format

Print a single integer representing the sum of all proper divisors of N .

Constraints

$$1 \leq N \leq 10^6$$

Example 1

Input

12

Output

16

Explanation

The proper divisors of **12** are:

1, 2, 3, 4, 6

Their sum is:

$$1 + 2 + 3 + 4 + 6 = 16$$

Example 2

Input

15

Output

9

Explanation

The proper divisors of **15** are:

1, 3, 5

Their sum is:

$$1 + 3 + 5 = 9$$

Code

```
#include <stdio.h>
int main () {
    int n;
    long long sum = 0;

    // Read the input
    scanf ("%d", &n);

    if (n > 1) {
        sum = 1; // 1 is always a proper divisor
        for (int i = 2; i*i <= n; i++) {
            if (n%i == 0) {
                sum += i;
                if (i != (n/i))
                    sum += (n/i);
            }
        }
    }

    // print the output
    printf ("%lld\n", sum);
    return 0;
}
```

I/p:- 12

O/p:- 16

8) Print all factors

- The goal is to print all factors of N in ascending order, separated by spaces.
- A factor is defined as an integer that divides the number completely without leaving a remainder.
- N goes up to 10^6 .
- Since we need them printed in perfect ascending order, the simplest and most robust way for $N \leq 10^6$ is to use a single for loop from 1 to N . We check if $N \% i == 0$ and print i immediately. This ensures strict ascending output.



```
1  #include <stdio.h>
2
3  int main() {
4      int n;
5      long long sum = 0;
6
7      // Read number
8      scanf("%d", &n);
9
10     // Find sum of proper divisors
11     if (n > 1) {
12         sum = 1;
13
14         for (int i = 2; i * i <= n; i++) {
15             if (n % i == 0) {
16                 sum += i;
17
18                 if (i != (n / i)) {
19                     sum += (n / i);
20                 }
21             }
22         }
23     }
```

main.c



Share

Run

Output

```
9
10 // Find sum of proper divisors
11 if (n > 1) {
12     sum = 1;
13
14     for (int i = 2; i * i <= n; i++) {
15         if (n % i == 0) {
16             sum += i;
17
18             if (i != (n / i)) {
19                 sum += (n / i);
20             }
21         }
22     }
23 }
24
25 // Print sum
26 printf("%lld\n", sum);
27
28 return 0;
29 }
```

12

16

=== Code Execution Successful ===

Problem Statement

Given a positive integer **N**, print all the factors of the number in **ascending order**.

A factor of a number is an integer that divides the number completely without leaving any remainder.

Your task is to write a program that prints all the factors of **N**.

Input Format

A single integer **N**.

Output Format

Print all the factors of **N** in ascending order, separated by spaces.

Constraints

$$1 \leq N \leq 10^6$$

Example 1

Input

12

Output

1 2 3 4 6 12

Explanation

The numbers **1, 2, 3, 4, 6, and 12** divide **12** exactly without leaving any remainder.

Example 2

Input

25

Output

1 5 25

Explanation

The numbers **1, 5, and 25** are the only factors of **25**.

Code

```
#include <stdio.h>
int main() {
    int n;

    // Read the input
    scanf("%d", &n);

    for (int i = 1; i <= n; i++) {
        if (n % i == 0) {
            printf("%d ", i); // print space separated
        }
    }

    // print final newline for clean output
    printf("\n");
    return 0;
}
```

I/p: - 12

O/p: - 1 2 3 4 6 12



```
3 int main() {  
4     int n;  
5  
6     // Read number  
7     scanf("%d", &n);  
8  
9     // Print divisors  
10    for (int i = 1; i <= n; i++) {  
11        if (n % i == 0) {  
12            printf("%d", i);  
13  
14            if (i != n) {  
15                printf(" ");  
16            }  
17        }  
18    }  
19  
20    printf("\n");  
21  
22    return 0;  
23 }
```

12

1 2 3 4 6 12

=== Code Execution Successful ===