

MCQ 1 `int a = 5;`

`int b = a++ + ++a;`

`System.out.println(a + " " + b);`

A. 6 11 B. 7 12 C. 7 13 D. Compilation Error

MCQ 2 `int x = 10;`

`System.out.println(x++ + x++ + ++x);`

A. 34 B. 35 C. 36 D. 37

MCQ 3 `int x = -8;`

`System.out.println(x >> 1);`

`System.out.println(x >>> 1);`

Output?

A.

-4 -4

B.

-4 2147483644

C.

2147483644 -4

D.

4 2147483644

MCQ 4

`System.out.println(5 << 2 + 1);`

A. 20 B. 40 C. 10 D. Compilation Error

MCQ 5

```
int x = 5;  
  
if (x > 2 || ++x > 5) System.out.println(x);
```

Output?

A. 5 B. 6 C. Compilation Error D. Runtime Error

MCQ 6 int x = 5;

```
if (x < 2 && ++x > 5) System.out.println(x);
```

```
System.out.println(x);
```

A. 5 B. 6 C. Compilation Error D. Runtime Error

MCQ 7 int a = 3;

```
int b = 4;
```

```
System.out.println(a & b); System.out.println(a | b); System.out.println(a ^ b);
```

A.

0 7 7

B.

1 7 6

C.

1 6 7

D.

0 6 7 MCQ 8

```
int x = Integer.MAX_VALUE;
```

```
System.out.println(x + 1);
```

A. Compilation Error

B.

2147483648

C.

-2147483648

D.

0 MCQ 9

```
int x = 5;
```

```
x += 3 * 2;
```

```
System.out.println(x);
```

A. 11

B. 16

C. 13

D. 10

MCQ 10

```
int x = 10;
```

```
System.out.println(x++ == 10 ? ++x : --x);
```

A. 10

B. 11

C. 12

D. 13

MCQ 11 int x = 5;

```
System.out.println(~x);
```

A. -5

B. -6

C. 6

D. 5

MCQ 12 `int x = 1;`

`System.out.println(x << 33);`

A. 2

B. 0

C. 1

D. Compilation Error

MCQ 13 `int x = 10;`

`System.out.println(x+++x);`

A. 20

B. 21

C. Compilation Error

D. Runtime Error

MCQ 14 `int a = 2;`

`a *= 3 + 2;`

`System.out.println(a);`

A. 10

B. 12

C. 8

D. 6

MCQ 15 (Very Tough) `int x = 1;`

`int y = x++ + ++x + x++ + ++x;`

`System.out.println(x);`

`System.out.println(y);`

A.

5 12

B.

5 13

C.

5 14

D.

4 13