

Forensic Data Analytics System

Goal: Build a fraud detection database to uncover anomalies in financial transactions.

Tables:

- accounts(account_id, customer_id, balance, opened_date)
- transactions(transaction_id, account_id, amount, transaction_type, timestamp)

Queries:

- Detects accounts with unusually high transaction frequency.
- Flag transactions above a certain threshold compared to the customer's average.

a. Create database

```
CREATE DATABASE forensic_analytics;  
USE forensic_analytics;
```

```
mysql> CREATE DATABASE forensic_analytics;  
Query OK, 1 row affected (0.03 sec)  
  
mysql> USE forensic_analytics;  
Database changed
```

b. Create tables

```
-- Customer accounts  
CREATE TABLE accounts (  
    account_id INT AUTO_INCREMENT PRIMARY KEY,  
    customer_id INT,  
    balance DECIMAL(12,2),  
    opened_date DATE  
);  
  
-- Transactions  
CREATE TABLE transactions (  
    transaction_id INT AUTO_INCREMENT PRIMARY KEY,  
    account_id INT,  
    amount DECIMAL(12,2),  
    transaction_type VARCHAR(50), -- e.g., 'Deposit', 'Withdrawal',  
    'Transfer'  
    timestamp DATETIME,  
    FOREIGN KEY (account_id) REFERENCES accounts(account_id)  
);
```

```

mysql> -- Customer accounts
mysql> CREATE TABLE accounts (
->     account_id INT AUTO_INCREMENT PRIMARY KEY,
->     customer_id INT,
->     balance DECIMAL(12,2),
->     opened_date DATE
-> );
Query OK, 0 rows affected (0.10 sec)

mysql>
mysql> -- Transactions
mysql> CREATE TABLE transactions (
->     transaction_id INT AUTO_INCREMENT PRIMARY KEY,
->     account_id INT,
->     amount DECIMAL(12,2),
->     transaction_type VARCHAR(50), -- e.g., 'Deposit', 'Withdrawal', 'Transfer'
->     timestamp DATETIME,
->     FOREIGN KEY (account_id) REFERENCES accounts(account_id)
-> );
Query OK, 0 rows affected (0.12 sec)

```

c. Insert sample data

```

INSERT INTO accounts (customer_id, balance, opened_date)
VALUES
(101, 5000.00, '2024-01-15'),
(102, 12000.00, '2024-03-10'),
(103, 800.00, '2024-05-20');

INSERT INTO transactions (account_id, amount, transaction_type,
timestamp)
VALUES
(1, 2000.00, 'Deposit', '2025-10-01 09:00:00'),
(1, 4500.00, 'Withdrawal', '2025-10-02 14:00:00'),
(2, 10000.00, 'Transfer', '2025-10-03 11:30:00'),
(3, 700.00, 'Withdrawal', '2025-10-04 16:00:00'),
(3, 50.00, 'Deposit', '2025-10-05 10:00:00');

```

```

mysql> INSERT INTO accounts (customer_id, balance, opened_date)
-> VALUES
-> (101, 5000.00, '2024-01-15'),
-> (102, 12000.00, '2024-03-10'),
-> (103, 800.00, '2024-05-20');
Query OK, 3 rows affected (0.04 sec)
Records: 3 Duplicates: 0 Warnings: 0

mysql>
mysql> INSERT INTO transactions (account_id, amount, transaction_type, timestamp)
-> VALUES
-> (1, 2000.00, 'Deposit', '2025-10-01 09:00:00'),
-> (1, 4500.00, 'Withdrawal', '2025-10-02 14:00:00'),
-> (2, 10000.00, 'Transfer', '2025-10-03 11:30:00'),
-> (3, 700.00, 'Withdrawal', '2025-10-04 16:00:00'),
-> (3, 50.00, 'Deposit', '2025-10-05 10:00:00');
Query OK, 5 rows affected (0.01 sec)
Records: 5 Duplicates: 0 Warnings: 0

```

d. Example queries

```

-- Detect accounts with unusually high transaction frequency
SELECT account_id, COUNT(*) AS transaction_count
FROM transactions
GROUP BY account_id
HAVING transaction_count > 3;

-- Flag transactions above a threshold compared to customer's

```

```

average
SELECT t.account_id, t.transaction_id, t.amount,
       AVG(t2.amount) AS avg_amount
FROM transactions t
JOIN transactions t2 ON t.account_id = t2.account_id
GROUP BY t.account_id, t.transaction_id
HAVING t.amount > 2 * avg_amount;

-- Find suspicious withdrawals (e.g., > 80% of account balance)
SELECT a.account_id, t.transaction_id, t.amount, a.balance
FROM accounts a
JOIN transactions t ON a.account_id = t.account_id
WHERE t.transaction_type = 'Withdrawal'
AND t.amount > (0.8 * a.balance);

```

```

mysql> -- Detect accounts with unusually high transaction frequency
mysql> SELECT account_id, COUNT(*) AS transaction_count
-> FROM transactions
-> GROUP BY account_id
-> HAVING transaction_count > 3;
Empty set (0.04 sec)

mysql>
mysql> -- Flag transactions above a threshold compared to customer's average
mysql> SELECT t.account_id, t.transaction_id, t.amount,
->         AVG(t2.amount) AS avg_amount
-> FROM transactions t
-> JOIN transactions t2 ON t.account_id = t2.account_id
-> GROUP BY t.account_id, t.transaction_id
-> HAVING t.amount > 2 * avg_amount;
Empty set (0.01 sec)

mysql>
mysql> -- Find suspicious withdrawals (e.g., > 80% of account balance)
mysql> SELECT a.account_id, t.transaction_id, t.amount, a.balance
-> FROM accounts a
-> JOIN transactions t ON a.account_id = t.account_id
-> WHERE t.transaction_type = 'Withdrawal'
-> AND t.amount > (0.8 * a.balance);
+-----+-----+-----+-----+
| account_id | transaction_id | amount | balance |
+-----+-----+-----+-----+
|          1 |              2 | 4500.00 | 5000.00 |
|          3 |              4 |  700.00 |  800.00 |
+-----+-----+-----+-----+
2 rows in set (0.01 sec)

```