

Spring Core - Incorporate Logging

Code:

SpringLearnApplication.java

```
package com.cognizant.spring_learn;

import java.text.SimpleDateFormat;
import java.util.Date;

import org.slf4j.Logger;
import org.slf4j.LoggerFactory;

import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;
import org.springframework.context.ApplicationContext;
import org.springframework.context.support.ClassPathXmlApplicationContext;

@SpringBootApplication
public class SpringLearnApplication {

    private static final Logger LOGGER =
        LoggerFactory.getLogger(SpringLearnApplication.class);

    public static void main(String[] args) {

        SpringApplication.run(SpringLearnApplication.class, args);

        displayDate();
    }

    public static void displayDate() {

        LOGGER.info("START");

        ApplicationContext context =
            new ClassPathXmlApplicationContext("date-format.xml");

        SimpleDateFormat format =
            context.getBean("dateFormat", SimpleDateFormat.class);

        try {

            Date date = format.parse("31/12/2018");

            LOGGER.debug("Date : {}", date);

        } catch (Exception e) {

            LOGGER.error("Exception occurred while parsing date", e);

        }
    }
}
```

```
        LOGGER.info("END");
    }
}
```

date-format.xml

```
<?xml version="1.0" encoding="UTF-8"?>

<beans xmlns="http://www.springframework.org/schema/beans"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="
    http://www.springframework.org/schema/beans
    https://www.springframework.org/schema/beans/spring-beans.xsd">

  <bean id="dateFormat" class="java.text.SimpleDateFormat">

    <constructor-arg value="dd/MM/yyyy"/>

  </bean>

</beans>
```

Output:

```
[32m :: Spring Boot :: [39m                [2m (v4.1.0) [0;39m
```

```
260721|17:25:22.431|restartedMain          |INFO|.s.SpringLearnApplication|
logStarting|Starting SpringLearnApplication using Java 17.0.18 with PID 15820
(D:\orm-learn\spring-learn\target\classes started by divit in D:\orm-learn\spring-learn)
260721|17:25:22.434|restartedMain          |DEBUG|.s.SpringLearnApplication|
logStarting|Running with Spring Boot v4.1.0, Spring v7.0.8
260721|17:25:22.435|restartedMain          |INFO|.s.SpringLearnApplication|
logStartupProfileInfo|No active profile set, falling back to 1 default profile:
"default"
260721|17:25:22.471|restartedMain          |INFO|ertyDefaultsPostProcessor|
log|Devtools property defaults active! Set 'spring.devtools.add-properties' to
'false' to disable
260721|17:25:22.471|restartedMain          |INFO|ertyDefaultsPostProcessor|
log|For additional web related logging consider setting the 'logging.level.web'
property to 'DEBUG'
260721|17:25:23.152|restartedMain          |INFO|o.s.b.t.TomcatWebServer  |
initialize|Tomcat initialized with port 8080 (http)
260721|17:25:23.163|restartedMain          |INFO|o.a.c.c.StandardService  |
log|Starting service [Tomcat]
260721|17:25:23.163|restartedMain          |INFO|o.a.c.core.StandardEngine|
log|Starting Servlet engine: [Apache Tomcat/11.0.22]
260721|17:25:23.196|restartedMain          |
INFO|icationContextInitializer|prepareWebApplicationContext|Root
WebApplicationContext: initialization completed in 723 ms
260721|17:25:23.498|restartedMain          |INFO|o.s.b.t.TomcatWebServer  |
start|Tomcat started on port 8080 (http) with context path '/'
260721|17:25:23.503|restartedMain          |INFO|.s.SpringLearnApplication|
logStarted|Started SpringLearnApplication in 1.415 seconds (process running for
1.945)
260721|17:25:23.506|restartedMain          |INFO|.s.SpringLearnApplication|
displayDate|START
260721|17:25:23.580|restartedMain          |DEBUG|.s.SpringLearnApplication|
displayDate|Date : Mon Dec 31 00:00:00 IST 2018
260721|17:25:23.581|restartedMain          |INFO|.s.SpringLearnApplication|
displayDate|END
```