

Spring Core – Load Country from Spring Configuration XML

Code:

SpringLearnApplication.java

```
package com.cognizant.spring_learn;

import java.text.SimpleDateFormat;
import java.util.Date;

import org.slf4j.Logger;
import org.slf4j.LoggerFactory;

import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;
import org.springframework.context.ApplicationContext;
import org.springframework.context.support.ClassPathXmlApplicationContext;

@SpringBootApplication
public class SpringLearnApplication {

    private static final Logger LOGGER =
        LoggerFactory.getLogger(SpringLearnApplication.class);

    public static void main(String[] args) {

        SpringApplication.run(SpringLearnApplication.class, args);

        displayDate();

        displayCountry();
    }

    // Hands-on 2 & 3 Method
    public static void displayDate() {

        LOGGER.info("START");

        ApplicationContext context =
            new ClassPathXmlApplicationContext("date-format.xml");

        SimpleDateFormat format =
            context.getBean("dateFormat", SimpleDateFormat.class);

        try {

            Date date = format.parse("31/12/2018");

            LOGGER.debug("Date : {}", date);

        } catch (Exception e) {

            LOGGER.error("Exception occurred while parsing date", e);
        }
    }
}
```

```

    }

    LOGGER.info("END");
}

// Hands-on 4 Method
public static void displayCountry() {

    LOGGER.info("START");

    ApplicationContext context =
        new ClassPathXmlApplicationContext("country.xml");

    Country country =
        context.getBean("country", Country.class);

    LOGGER.debug("Country : {}", country);

    LOGGER.info("END");
}
}

```

Country.java

```

package com.cognizant.spring_learn;

import org.slf4j.Logger;
import org.slf4j.LoggerFactory;

public class Country {

    private static final Logger LOGGER =
        LoggerFactory.getLogger(Country.class);

    private String code;
    private String name;

    // Constructor
    public Country() {

        LOGGER.debug("Inside Country Constructor.");

    }

    // Getter for code
    public String getCode() {

        LOGGER.debug("Inside getCode()");
        return code;

    }
}

```

```

// Setter for code
public void setCode(String code) {

    LOGGER.debug("Inside setCode()");
    this.code = code;

}

// Getter for name
public String getName() {

    LOGGER.debug("Inside getName()");
    return name;

}

// Setter for name
public void setName(String name) {

    LOGGER.debug("Inside setName()");
    this.name = name;

}

@Override
public String toString() {
    return "Country [code=" + code + ", name=" + name + "];"
}
}

```

Country.xml

```

<?xml version="1.0" encoding="UTF-8"?>

<beans xmlns="http://www.springframework.org/schema/beans "
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="
http://www.springframework.org/schema/beans
https://www.springframework.org/schema/beans/spring-beans.xsd">

    <bean id="country"
        class="com.cognizant.spring_learn.Country">

        <property name="code" value="IN"/>
        <property name="name" value="India"/>

    </bean>

```

```
</beans>
```

date-format.xml

```
<?xml version="1.0" encoding="UTF-8"?>

<beans xmlns="http://www.springframework.org/schema/beans"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="
    http://www.springframework.org/schema/beans
    https://www.springframework.org/schema/beans/spring-beans.xsd">

  <bean id="dateFormat" class="java.text.SimpleDateFormat">

    <constructor-arg value="dd/MM/yyyy"/>

  </bean>

</beans>
```

Output:

[illegible]

[illegible]