

Hibernate XML Config implementation walk through

Employee.java

```
package com.cognizant.hibernate;

public class Employee {

    private int id;

    private String name;

    private double salary;

    public int getId() {
        return id;
    }

    public void setId(int id) {
        this.id = id;
    }

    public String getName() {
        return name;
    }

    public void setName(String name) {
        this.name = name;
    }

    public double getSalary() {
        return salary;
    }

    public void setSalary(double salary) {
        this.salary = salary;
    }

    @Override
    public String toString() {
        return "Employee [id=" + id +
            ", name=" + name +
            ", salary=" + salary + "]\n";
    }
}
```

HibernateTest.java

```
package com.cognizant.hibernate;

import java.util.List;

import org.hibernate.Session;
import org.hibernate.SessionFactory;
import org.hibernate.Transaction;
import org.hibernate.cfg.Configuration;

public class HibernateTest {

    public static void main(String[] args) {

        Configuration configuration =
            new Configuration();

        configuration.configure("hibernate.cfg.xml");

        SessionFactory factory =
            configuration.buildSessionFactory();

        Session session =
            factory.openSession();

        try {

            // CREATE
            saveEmployee(session);

            // READ ONE
            getEmployee(session, 1);

            // READ ALL
            getAllEmployees(session);

        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
```

```
// UPDATE
updateEmployee(session,1);

// DELETE
deleteEmployee(session,1);

}

catch(Exception e){

    e.printStackTrace();

}

finally {

    session.close();

    factory.close();

}

}

// INSERT

private static void saveEmployee(Session session){

    Transaction tx =
        session.beginTransaction();

    Employee employee =
        new Employee();

    employee.setName("David");

    employee.setSalary(60000);
```

```
        session.save(employee);

        tx.commit();

        System.out.println(
            "Employee Saved"
        );
    }

    // READ ONE

    private static void getEmployee(
        Session session,
        int id){

        Employee employee =
            session.get(
                Employee.class,
                id
            );

        System.out.println(employee);
    }

    // READ ALL

    private static void getAllEmployees(
        Session session){

        List<Employee> employees =
            session.createQuery(
```

```

        "from Employee",
        Employee.class
    ).list();

    for(Employee employee:employees){

        System.out.println(employee);

    }
}

// UPDATE

private static void updateEmployee(
    Session session,
    int id){

    Transaction tx =
        session.beginTransaction();

    Employee employee =
        session.get(
            Employee.class,
            id
        );

    if(employee != null){

        employee.setSalary(75000);

        session.update(employee);

    }
}

```

```
        tx.commit();

        System.out.println(
            "Employee Updated"
        );
    }

    // DELETE

    private static void deleteEmployee(
        Session session,
        int id){

        Transaction tx =
            session.beginTransaction();

        Employee employee =
            session.get(
                Employee.class,
                id
            );

        if(employee != null){

            session.delete(employee);

        }

        tx.commit();

        System.out.println(
            "Employee Deleted"
```

```
);  
  
}  
  
}
```

Employee.hbm.xml

```
<?xml version="1.0"?>  
  
<!DOCTYPE hibernate-mapping PUBLIC  
    "-//Hibernate/Hibernate Mapping DTD 3.0//EN"  
    "http://hibernate.sourceforge.net/hibernate-mapping-3.0.dtd">  
  
<hibernate-mapping>  
  
    <class name="com.cognizant.hibernate.Employee"  
        table="employee">  
  
        <id name="id" column="id">  
            <generator class="native"/>  
        </id>  
  
        <property name="name" column="name"/>  
  
        <property name="salary" column="salary"/>  
  
    </class>  
  
</hibernate-mapping>
```

Hibernate.cfg.xml

```
<?xml version="1.0" encoding="UTF-8"?>  
  
<!DOCTYPE hibernate-configuration PUBLIC  
    "-//Hibernate/Hibernate Configuration DTD 3.0//EN"  
    "http://hibernate.sourceforge.net/hibernate-configuration-3.0.dtd">  
  
<hibernate-configuration>  
  
    <session-factory>
```

```
<!-- Database Driver -->
<property name="hibernate.connection.driver_class">
    com.mysql.cj.jdbc.Driver
</property>

<!-- Database URL -->
<property name="hibernate.connection.url">
    jdbc:mysql://localhost:3306/hibernate_demo
</property>

<!-- Username -->
<property name="hibernate.connection.username">
    root
</property>

<!-- Password -->
<property name="hibernate.connection.password">
    12345
</property>

<!-- Hibernate Dialect -->
<property name="hibernate.dialect">
    org.hibernate.dialect.MySQLDialect
</property>

<!-- Show SQL -->
<property name="hibernate.show_sql">
    true
</property>

<!-- Mapping File -->
<mapping resource="Employee.hbm.xml"/>

</session-factory>
</hibernate-configuration>
```

Output:

```
hibernate-xml-demo  Version Control  Current File  Start Free Trial  x
```

```
Project  hibernate-xml-demo  D:\JetBriansProject\hibernate-xml-demo
  > idea
  > mvn
  > src
    > main
      > java
        > com.cognizant.hibernate
          > Employee
          > HibernateTest
          > resources
            > Employee.hbm.xml
```

```
13  public class HibernateTest {
248      private static void deleteEmployee( 1 usage
282      }
283  }
284  }
285  }
286  }
287  }
288  }
289  }
```

```
Run  HibernateTest x
```

```
INFO: HH000489: No JTA platform available (set 'hibernate.transaction.jta.platform' to enable JTA platform integration)
Hibernate: insert into employee (name,salary) values (?,?)
Employee Saved
Hibernate: select e1_0.id,e1_0.name,e1_0.salary from employee e1_0 where e1_0.id=?
Employee [id=1, name=John, salary=50000.0]
Hibernate: select e1_0.id,e1_0.name,e1_0.salary from employee e1_0
Employee [id=1, name=John, salary=50000.0]
Employee [id=2, name=David, salary=60000.0]
Employee [id=3, name=David, salary=60000.0]
Hibernate: update employee set name=?,salary=? where id=?
Employee Updated
Hibernate: delete from employee where id=?
Employee Deleted
Process finished with exit code 0
```

```
hibernate-xml-demo > src > main > java > com > cognizant > hibernate > HibernateTest 288:1 CRLF UTF-8 4 spaces
```