

TARGET example.com	PROFILE Full Scan	AGGRESSION Attack	DATE 2026-03-15 16:13:24
-----------------------	----------------------	----------------------	-----------------------------

RISK SUMMARY

TOTAL FINDINGS 5	CRITICAL 0	HIGH 0	MEDIUM 2	LOW / INFO 3
---------------------	---------------	-----------	-------------	-----------------

PHASE ANALYSIS

PHASE 1: RECONNAISSANCE & FINGERPRINTING Target IP: 104.18.27.120 Subdomains Found: 1 SAMPLE SUBDOMAINS: www.example.com RESOLVED HOSTS: www.example.com (104.18.27.120) DETECTED TECHNOLOGIES: SERVER: CLOUDFLARE
PHASE 2: NETWORK AUDIT & EXPLOITATION Nmap Scan Status: UP OS Guess: N/A OPEN PORTS (13): 80/TCP (HTTP)443/TCP (SSL HTTPS)2052/TCP (HTTP)2053/TCP (SSL HTTP)2082/TCP (HTTP)2083/TCP (SSL HTTP)2086/TCP (HTTP)2087/TCP (SSL HTTP)2095/TCP (HTTP)2096/TCP (SSL HTTP)8080/TCP (HTTP)8443/TCP (SSL HTTPS-ALT)8880/TCP (HTTP)
PHASE 3: WEB APPLICATION AUDIT WAF Detected: Cloudflare (Method: Passive (Headers/Cookies)) Crawled URLs: 0 Forms Found: 0

API Endpoints: 0

PHASE 4: TRAFFIC ANALYSIS

Total Packets Captured: 0

No significant traffic anomalies detected.

NETSHIELD AGGREGATED FINDINGS

Medium Findings (2)

Clickjacking Risk

MEDIUM

SOURCE TOOL: NetShield AI

TIMESTAMP: 2026-03-15 16:16:48

PARAMETER / LOCATION

HTTP Headers

EVIDENCE / PROOF

Missing X-Frame-Options or CSP frame-ancestors

Content Security Policy (CSP) Header Not Set

MEDIUM

CWE-CWE-693

ML Score: N/A

SOURCE TOOL: NetShield AI

TIMESTAMP: N/A

DESCRIPTION

Content Security Policy (CSP) is an added layer of security that helps to detect and mitigate certain types of attacks, including Cross Site Scripting (XSS) and data injection attacks. These attacks are used for everything from data theft to site defacement or distribution of malware. CSP provides a set of standard HTTP headers that allow website owners to declare approved sources of content that browsers should be allowed to load on that page — covered types are JavaScript, CSS, HTML frames, fonts, images and embeddable objects such as Java applets, ActiveX, audio and video files.

REMEDIATION

Ensure that your web server, application server, load balancer, etc. is configured to set the Content-Security-Policy header.

Low Findings (2)

Missing CSP

LOW

SOURCE TOOL: NetShield AI

TIMESTAMP: 2026-03-15 16:16:48

PARAMETER / LOCATION

HTTP Headers

EVIDENCE / PROOF

Content-Security-Policy header is missing

X-Content-Type-Options Header Missing

LOW

CWE-CWE-693

ML Score: N/A

SOURCE TOOL: NetShield AI

TIMESTAMP: N/A

DESCRIPTION

The Anti-MIME-Sniffing header X-Content-Type-Options was not set to 'nosniff'. This allows older versions of Internet Explorer and Chrome to perform MIME-sniffing on the response body, potentially causing the response body to be interpreted and displayed as a content type other than the declared content type. Current (early 2014) and legacy versions of Firefox will use the declared content type (if one is set), rather than performing MIME-sniffing.

REMEDIATION

Ensure that the application/web server sets the Content-Type header appropriately, and that it sets the X-Content-Type-Options header to 'nosniff' for all web pages. If possible, ensure that the end user uses a standards-compliant and modern web browser that does not perform MIME-sniffing at all, or that can be directed by the web application/web server to not perform MIME-sniffing.

Info Findings (1)

Retrieved from Cache

INFO

CWE-UNKNOWN

ML Score: N/A

SOURCE TOOL: NetShield AI

TIMESTAMP: N/A

DESCRIPTION

The content was retrieved from a shared cache. If the response data is sensitive, personal or user-specific, this may result in sensitive information being leaked. In some cases, this may even result in a user gaining complete control of the session of another user, depending on the configuration of the caching components in use in their environment. This is primarily an issue where caching servers such as "proxy" caches are configured on the local network. This configuration is typically found in corporate or educational environments, for instance.

REMEDIATION

Validate that the response does not contain sensitive, personal or user-specific information. If it does, consider the use of the following HTTP response headers, to limit, or prevent the content being stored and retrieved from the cache by another user: Cache-Control: no-cache, no-store, must-revalidate, private Pragma: no-cache Expires: 0 This configuration directs both HTTP 1.0 and HTTP 1.1 compliant caching servers to not store the response, and to not retrieve the response (without validation) from the cache, in response to a similar request.