```
mysql> CREATE DATABASE School;
Query OK, 1 row affected (0.01 sec)
mysql> USE School;
Database changed
mysql> CREATE TABLE STUDENT (
           Roll_No INT PRIMARY KEY,
    ->
           Name VARCHAR(50),
          Marks INT,
    ->
           Grade CHAR(1)
-> );
Query OK, 0 rows affected (0.03 sec)
mysql> desc student;
                          Null | Key
Field
                                       Default
            Type
                                                Extra
 Roll_No
            int
                          NO
                                 PRI
                                       NULL
  Name
            varchar(50)
                          YES
                                       NULL
 Marks
                                       NULL
            int
                          YES
            char(1)
                          YES
                                       NULL
  Grade
4 rows in set (0.01 sec)
mysql> INSERT INTO STUDENT (Roll_No, Name, Marks, Grade) VALUES
    -> (1, 'Alice', 85, 'A'),
-> (2, 'Bob', 78, 'B'),
-> (3, 'Charlie', 92, 'A');
Query OK, 3 rows affected (0.01 sec)
Records: 3 Duplicates: 0 Warnings: 0
mysql> SELECT * FROM STUDENT;
 Roll_No
            Name
                       Marks Grade
        1
             Alice
                           85
                                Α
                           78
        2
             Bob
                                В
        3
             Charlie
                           92
                                Α
3 rows in set (0.00 sec)
mysql> ALTER TABLE STUDENT
    -> ADD Contact VARCHAR(15);
Query OK, 0 rows affected (0.02 sec)
Records: 0 Duplicates: 0 Warnings: 0
mysql> desc student;
                           | Null | Key | Default | Extra
 Field
           Type
  Roll_No
                                     PRI
             int
                             NO
                                            NULL
             varchar(50)
  Name
                             YES
                                            NULL
                             YES
  Marks
             int
                                            NULL
  Grade
             char(1)
                             YES
                                            NULL
             varchar(15)
  Contact
                             YES
                                            NULL
5 rows in set (0.00 sec)
```

```
mysql> ALTER TABLE STUDENT
-> DROP COLUMN Grade;
Query OK, 0 rows affected (0.02 sec)
Records: 0 Duplicates: 0 Warnings: 0
mysql> DESC STUDENT;
 | Field
               | Type
                                    Null | Key | Default | Extra
   Roll_No
                 int
                                    NO
                                              PRI
                                                      NULL
   Name
                 varchar(50)
                                    YES
                                                      NULL
   Marks
                 int
                                    YES
                                                      NULL
   Contact
                 varchar(15)
                                    YES
                                                      NULL
4 rows in set (0.00 sec)
mysql> RENAME TABLE STUDENT TO CLASSTEN;
Query OK, 0 rows affected (0.02 sec)
mysql> desc student;
ERROR 1146 (42S02): Table 'school.student' doesn't exist
mysql> SHOW TABLES;
 Tables_in_school |
 classten
1 row in set (0.01 sec)
mysql> TRUNCATE TABLE CLASSTEN;
Query OK, 0 rows affected (0.04 sec)
mysql> SELECT * FROM CLASSTEN;
Empty set (0.01 sec)
mysql> DROP TABLE CLASSTEN;
Query OK, 0 rows affected (0.02 sec)
mysql> SHOW TABLES;
Empty set (0.00 sec)
```