Command Prompt:

```
Ping 10.0.0.2

Pinging 10.0.0.2 with 32 bytes of data:
Request timed out.
Reply from 10.0.0.2: bytes = 32 time = 3ms TTL = 126
Reply from 10.0.0.2: bytes = 32 time = 3ms TTL = 126
Reply from 10.0.0.2: bytes = 32 time = 3ms TTL = 126

Ping statistics for 10.0.0.2:
    Packets: Sent = 4, Received = 3, Lost = 1
Approximate round trip times in milli-seconds
    Minimum = 3ms, Maximum = 3ms, Average = 3ms.
```

(6)

AIM:

To simulate and configure RIP (routing information Protocol) using Cisco Packet Tracer and verify, communication between different networks.

PROCEDURE:

1. Create the network
   * Place 3 routers (Router0, Router1, Router2) and 2PC's (PC0, PC1)
   * Connect the routers using serial links and PCs through Fast Ethernet.
   * Assign the given IP addresses to all PC's and router interfaces.
2. Configure Router Interfaces.
   * Open router → CLI and enter: enable, configure terminal, interface <interface-name>
   * For serial interfaces, configure clock rate 64000 and bandwidth 64 where required.
3. Configure RIP
   * Enable RIP on each router.
   * Advertise all directly connected networks.
   * Repeat the RIP configuration on Router1 and Router 2 with their respective connected networks.
4. Verify Connectivity.
   * Open PC → Desktop → Command prompt.
   * Test Communication
   * Verify that PC0 can successfully communicate with PC1 through the routers.
5. Verify Dynamic routing.
   * Use tracert to check the route taken by packets.
   * Disconnect one routing link and test again
   * RIP automatically selects an alternative available route if the current route fails.

RESULT:

Thus, RIP dynamic routing was successfully configured using Cisco packet tracer. Communication between different networks was verify using Ping and tracert, and RIP automatically selected an alternate route when a link failed.