

GE23131-Programming Using C-2024

Finish review

Status	Finished
Started	Monday, 23 December 2024, 5:33 PM
Completed	Monday, 9 December 2024, 1:11 PM
Duration	14 days 4 hours

Correct

Flag question

Input format:

The lines after that contain a different values for size of the chessboard

Output format:

REC-CIS

Print a chessboard of dimensions size * size. Print a Print W for white spaces and B for black spaces.

Input:

2

3

5

Output:

WBW

BWB

WBW

WBWBW

BWBWB

WBWBW

BWBWB

WBWBW

⚠ Not secure rajalakshmicolleges.org/moodle/mod/quiz/review.php?attempt=113147&cmid=122

REC-CIS

Answer: (penalty regime: 0 %)

```
1 #include <stdio.h>
2 int main()
3 {
4     int T,d,i=0,i1,i2,o;
5     char c;
6     scanf("%d",&T);
7     while(i<T)
8     {
9         scanf("%d",&d);
10        i1=0;
11        while(i1<d)
12        {
13            o=1;
14            i2=0;
15            if(i1%2==0)
16            {
17                o=0;
18            }
19            while(i2<d)
20            {
21                c='B';
22                if(i2%2==o)
23                {
24                    c='W';
25                }
26                printf("%c",c);
27                i2++;
```



REC-CIS

Question **2**

Correct

Marked out of
5.00 [Flag question](#)

Let's print a chessboard!

Write a program that takes input:

The first line contains T , the number of test cases

Each test case contains an integer N and also the starting character of the chessboard

Output Format

Print the chessboard as per the given examples

Sample Input / Output

Input:

2

2 W

REC-CIS

3 B

Output:

WB

BW

BWB

WBW

BWB

Answer: (penalty regime: 0 %)

```

1 #include<stdio.h>
2 int main()
3 {
4     int T,d,i,i1,i2,o,z;
5     char c,s;
6     scanf("%d",&T);
7     for(i=0;i<T;i++)
8     {
9         scanf("%d %c",&d,&s);
10        for(i1=0;i1<d;i1++)
11        {
12            z=(s=='W')?0:1;

```

REC-CIS

```

12     z=(s=='W')?0:1;
13     o=(i1%2==z)?0:1;
14     for(i2=0;i2<d;i2++)
15     {
16         c=(i2%2==o)?'W' : 'B';
17         printf("%c",c);
18     }
19     printf("\n");
20 }
21 }
22 return 0;
23 }
    
```

	Input	Expected	Got	
✓	2	WB	WB	✓
	2 W	BW	BW	
	3 B	BWB	BWB	
		WBW	WBW	
		BWB	BWB	

Passed all tests! ✓

REC-CIS

Question **3**

Correct

Marked out of
7.00[Flag question](#)

Decode the logic and print the Pattern that corresponds to given input.

If N= 3

then pattern will be :

10203010011012

**4050809

****607

If N= 4, then pattern will be:

1020304017018019020

**50607014015016

****809012013

*****10011

Constraints

REC-CIS

 $2 \leq N \leq 100$

Input Format

First line contains T, the number of test cases

Each test case contains a single integer N

Output

First line print Case #i where i is the test case number

In the subsequent line, print the pattern

Test Case 1

3

3

4

5

REC-CIS

Output

Case #1

10203010011012

****4050809**

****607

Case #2

1020304017018019020

****50607014015016**

****809012013

*****10011

Case #3

102030405026027028029030

****6070809022023024025**

***10011012019020021

*****13014017018

*****15016

△ Not secure rajalakshmicolleges.org/moodle/mod/quiz/review.php?attempt=113147&cmid=122

REC-CIS

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main(){
3     int n,v,p3,c,in,i,i1,i2,t,ti;
4     scanf("%d",&t);
5     for(ti=0;ti<t;ti++){
6         v=0;
7         scanf("%d",&n);
8         printf("Case #%d\n",ti+1);
9         for(i=0;i<n;i++){
10             c=0;
11             if(i>0){
12                 for(i1=0;i1<i;i1++){
13                     printf("**");
14                 }
15                 for(i1=i;i1<n;i1++){
16                     if(i>0)c++;
17                     printf("%d0",++v);
18                 }
19                 if(i==0){
20                     p3=v+(v*(v-1))+1;
21                     in=p3;
22                 }
23                 in=in-c;
24                 p3=in;
25                 for(i2=i;i2<n;i2++){
26                     printf("%d",p3++);
27                     if(i2!=n-1)
28                         printf("0");
29                 }
30                 printf("\n");
31             }
```

REC-CIS

```
27         if (i < n-1)
28             printf("0");
29         }printf("\n");
30     }
31 }
32 }
```

	Input	Expected	Got	
✓	3	Case #1	Case #1	✓
	3	10203010011012	10203010011012	
	4	**4050809	**4050809	
	5	****607	****607	
		Case #2	Case #2	
		1020304017018019020	1020304017018019020	
		**50607014015016	**50607014015016	
		****809012013	****809012013	
		*****10011	*****10011	
		Case #3	Case #3	
		102030405026027028029030	102030405026027028029030	
		**6070809022023024025	**6070809022023024025	
		****10011012019020021	****10011012019020021	
		*****13014017018	*****13014017018	
		*****15016	*****15016	

REC-CIS

	Input	Expected	Got	
✓	3	Case #1	Case #1	✓
	3	10203010011012	10203010011012	
	4	**4050809	**4050809	
	5	****607	****607	
		Case #2	Case #2	
		1020304017018019020	1020304017018019020	
		**50607014015016	**50607014015016	
		****809012013	****809012013	
		*****10011	*****10011	
		Case #3	Case #3	
		102030405026027028029030	102030405026027028029030	
		**6070809022023024025	**6070809022023024025	
		****10011012019020021	****10011012019020021	
		*****13014017018	*****13014017018	
		*****15016	*****15016	

Passed all tests! ✓

Finish review

GE23131-Programming Using C-2024

Finish review

Status	Finished
Started	Monday, 23 December 2024, 5:33 PM
Completed	Thursday, 5 December 2024, 9:01 AM
Duration	18 days 8 hours

Correct

Marked out of 3.00

Flag question

The k -digit number N is an Armstrong number if and only if the k -th power of each digit sums to N .

Given a positive integer N, return true if and only if it is an Armstrong number.

Example 1:

Input:

153

REC-CIS

Output:

true

Explanation:

153 is a 3-digit number, and $153 = 1^3 + 5^3 + 3^3$.

Example 2:

Input:

123

Output:

false

REC-CIS

Explanation:

123 is a 3-digit number, and $123 != 1^3 + 2^3 + 3^3 = 36$.

Example 3:

Input:

1634

Output:

true

Note:

$1 \leq N \leq 10^8$

⚠ Not secure rajalakshmicolleges.org/moodle/mod/quiz/review.php?attempt=108240&cmid=123

REC-CIS

Answer: (penalty regime: 0 %)

```
1 #include <stdio.h>
2 #include <math.h>
3 int main ()
4 {
5     int n;
6     scanf("%d", &n);
7     int x=0,n2=n;
8     while (n2!=0)
9     {
10         x++;
11         n2=n2/10;
12     }
13     int sum=0;
14     int n3=n,n4;
15     while (n3!=0)
16     {
17         n4=n3%10;
18         sum=sum+pow(n4,x);
19         n3=n3/10;
20     }
21     if (n==sum)
22     {
23         printf("true");
24     }else{
25         printf("false");
26     }
27     return 0;
28 }
```

REC-CIS

	Input	Expected	Got	
✓	153	true	true	✓
✓	123	false	false	✓

Passed all tests! ✓

Question **2**

Correct

Marked out of
5.00

🚩 Flag question

Take a number, reverse it and add it to the original number until the obtained number is a palindrome.
Constraints $1 \leq \text{num} \leq 99999999$ Sample Input 1 32 Sample Output 1 55 Sample Input 2 789 Sample Output 2 66066

Answer: (penalty regime: 0 %)

```

1  #include <stdio.h>
2  int main ()
3  {
4      int rn,n,nt=0,i=0;
5      scanf("%d",&n);
6      do{
7          nt=n;rn=0;
8          while (n!=0)
9          {
10             rn=rn*10+n%10;

```

⚠ Not secure rajalakshmicolleges.org/moodle/mod/quiz/review.php?attempt=108240&cmid=123

REC-CIS

```
11         n=n/10;
12     }
13     n=nt+rn;
14     i++;
15 }
16 while(rn!=nt || i==1);
17 printf ("%d",rn);
18 return 0;
19 }
```

	Input	Expected	Got	
✓	32	55	55	✓
✓	789	66066	66066	✓

Passed all tests! ✓

Question **3**

Correct

A number is considered lucky if it contains either 3 or 4 or 3 and 4 both in it. Write a program to print the nth lucky number. Example, 1st lucky number is 3, and 2nd lucky number is 4 and 3rd lucky number is 33 and 4th

REC-CIS

Question 3

Correct

Marked out of
7.00

🚩 Flag question

A number is considered lucky if it contains either 3 or 4 or 3 and 4 both in it. Write a program to print the nth lucky number. Example, 1st lucky number is 3, and 2nd lucky number is 4 and 3rd lucky number is 33 and 4th lucky number is 34 and so on. Note that 13, 40 etc., are not lucky as they have other numbers in it.

The program should accept a number 'n' as input and display the nth lucky number as output.

Sample Input 1:

3

Sample Output 1:

33

Explanation:

Here the lucky numbers are 3, 4, 33, 34, and the 3rd lucky number is 33.

Sample Input 2:

REC-CIS

34

Sample Output 2:

33344

Answer: (penalty regime: 0 %)

```
1 #include <stdio.h>
2 int main()
3 {
4     int n=1,i=0,nt,co=0,e;
5     scanf("%d",&e);
6     while(i<e)
7     {
8         nt=n;
9         while(nt!=0)
10        {
11            co=0;
12            if(nt %10!=3&&nt%10!=4)
```

REC-CIS

```

10
11     co=0;
12     if(nt %10!=3&&nt%10!=4)
13     {
14         co=1;
15         break;
16     }
17     nt=nt/10;
18 }
19 if(co==0)
20 {
21     i++;
22 }
23 n++;
24 }
25 printf("%d",--n);
26 return 0;
27 }
    
```

	Input	Expected	Got	
✓	34	33344	33344	✓

Passed all tests! ✓