Romanized Hindi Is Harder Than Hinglish: A Scoring-Aware Audit of Small LLMs

Anonymous ACL submission

Abstract

Prior work reports lower LLM accuracy on Romanized Hindi than on Romanized Hinglish versions of the same translated GSM8K questions, and shows that translation errors and answer extraction can skew multilingual math gaps. Building on this evidence, we audit small open LLMs on newly drafted, human-reviewed math triplets in English (E), Romanized Hindi (R) and Roman-script Hinglish (C), with code-computed gold and a frozen, scoring-aware protocol. On permanently excluded fixtures, a plausible answer-format instruction made 10/36 Qwen3-4B outputs fail strict scoring and pushed 8/12 R explanations into Devanagari; after one disclosed prompt revision both were zero, and format compliance across seven models was strongly model-specific. In two separately reviewed, pre-registered cohorts, never pooled, R is the lowest-scoring form for all three backbones. On the primary 70-family cohort, Qwen3-4B scores 94.3/85.7/94.3% on E/R/C, Qwen3-8B 98.6/91.4/98.6% and Llama-3.2-3B 94.3/57.1/70.0%; a 24-family cohort shows the same direction, with Qwen near ceiling. Both Qwen models have equal observed aggregate accuracy on E and C. R errors are not concentrated in items with Hindi operation words.

1 Introduction

A model that answers "How many marbles does Aman have?" may fail on *Aman ke paas kitne kanche hain?* although the mathematics is identical. We hold the mathematics fixed and vary only the form.

The ordering we observe is not new. CodeMixTax (Sthānika, 2026) aligns the same 955 GSM8K questions across five forms and already reports Romanized Hindi below Romanized Hinglish, which is direct prior evidence for our main result. Code-mixed and Romanized math gaps appear elsewhere too (Yang and Chai, 2025; Sarvam AI, 2025; Das et al., 2026), and Peter et al. (2026) show that translation errors and answer extraction can skew multilingual math gaps. Building on this evidence, we provide a reproducible, scoring-aware audit of small open LLMs on newly drafted, human-reviewed E/R/C math triplets, finding lower observed accuracy for R across the tested models and equal observed aggregate E–C accuracy for Qwen3-4B and Qwen3-8B in two separately reported cohorts. What we add: (1) **new triplets**, drafted rather than derived from GSM8K and written in natural Roman spelling rather than scheme transliteration, with human review; (2) **a scoring-aware frozen protocol**: on excluded fixtures a plausible final-answer instruction caused form-dependent scoring failures, and a seven-model compliance screen preceded model admission; (3) **two separately reviewed cohorts** whose direction is consistent.

2 Related Work

Hindi and multilingual math. MGSM translates GSM8K (Cobbe et al., 2021) into ten languages, but not Hindi (Shi et al., 2023). GSM8K-Hi is a human-verified machine translation of GSM8K into Devanagari (Kamath et al., 2025), and HAWP has 2,336 Hindi arithmetic problems (Sharma et al., 2022). Anand et al. (2025) tune on Hindi and English math, excluding Romanized Hindi; mCoT (Lai and Nissim, 2024), MathOctopus (Chen et al., 2024) and XCOT (Chai et al., 2025) study multilingual math training.

Code-mixed and Romanized evaluation. CodeMixBench's Hindi–English GSM8K mixes Devanagari and Latin script (Yang and Chai, 2025); Indi-RomCoM varies Romanized code-mixing intensity, without a separate monolingual-R condition (Das et al., 2026, preprint). Sarvam-M reports GSM8K accuracy falling from native-script to Romanized Indic

input (Sarvam AI, 2025), and Romanized input also hurts health triage (Khullar et al., 2026).

Operation cues and spelling. Math solvers exploit shallow cues (Patel et al., 2021), and LLMs turn irrelevant phrases into operations (Mirzadeh et al., 2025). Romanized Hindi has no standard orthography (Bali et al., 2014; Roark et al., 2020). Token counts differ across languages (Petrov et al., 2023); we treat them only as correlates.

3 Data

Families and forms. A family is one problem with three renderings. **E** is English; **R** is Hindi phrasing in Roman script, with a borrowing list for numbers, units and established loanwords; **C** is Roman-script Hindi with English lexical material beyond that list. Six topics (comparison, money, fractions/percentages, ratios, rates/units, algebra) are covered. The original pilot drafted 30 families (five per topic), of which 24 form its cohort; Pilot-B adds 70 (12/12/12/12/11/11).

AI drafting, code gold, blind verification. All families were LLM-drafted, with gold computed in code; Claude (claude-opus-5-5) drafted Pilot-B **[TODO:** drafting model of the original 30**]**. Claude and GPT each solved every Pilot-B rendering blind in a fresh context; no Qwen model ever drafted, solved or checked. Both solvers matched gold on 210/210 first-version and 15/15 revised renderings. This shows only that the text encodes the specified calculation; the solvers may share blind spots.

Human review: original cohort. Two humans (R01, R02) solved the mathematics independently before seeing gold; on the cohort's 72 renderings their answers agreed on 65, R02 matched gold on all 72, and the adjudicator (A01) confirmed gold for every cohort family. Language and equivalence review was by one human (R02) plus A01: R01's stage-2 judgments on 52 of the 72 cohort renderings were AI-prefilled and unverified, so they are excluded. Earlier review rounds were found non-independent and discarded. A01 decided 24 ACCEPT, 5 REVISE and 1 EXCLUDE (a near-duplicate); the cohort is the 24 families accepted without repair.

Human review: Pilot-B. One bilingual team member reviewed all of Pilot-B: 57 ACCEPT, 13 REVISE, 0 REJECT, with two equivalence failures. One bilingual team member **[TODO:** same reviewer as Pilot-B?**]** also reviewed a separate, not yet evaluated GPT-drafted test set **[TODO:** GPT model version**]**; its Romanized Hindi was systematically over-formal (68/100 families needed repair, against 13/70 for Claude-drafted Pilot-B). This is descriptive: drafter is confounded with split, prompt and review timing **[TODO:** share of REVISE decisions that targeted R**]**.

C as insertional Hinglish. Review showed natural Hinglish to be mostly *insertional*: Hindi grammar with English nouns, conjunct verbs and relation words (*23 add karta hai*). Pilot-B C therefore requires English material beyond R's borrowing list but no English clause; the original cohort keeps the earlier clause-based definition, so the cohorts are reported separately.

Operation-word lexicon and keep/switch balance. An AI research assistant proposed 25 Hindi operation-word families with spelling variants, flagged as lexically ambiguous (*bhinn* "fraction"/"different"; *bhaag* "divide"/"run") or context-dependent (*kam*). One bilingual team member reviewed all entries (13 AI- or dictionary-assisted, then endorsed); *anupat* (ratio) remains unconfirmed. On the original 30 drafts, a fixed matcher finds lexicon words in 27/30 R but only 10/30 C renderings, so a C advantage there could partly reflect easier vocabulary. Pilot-B counters this: C *keeps* R's Hindi operation word in 18 families, *switches* it to English in 17, and 35 are controls without one.

4 Protocol

Prompt and scoring. One English instruction (`test1-english-final-v2`) is used for every form. It asks for a short explanation in English and a final line beginning `FINAL:`, followed by an English unit only when the answer has one and by nothing after a pure number **[TODO:** quote exact prompt text in appendix**]**. It was revised once on excluded data (§5), then frozen. The primary endpoint is a frozen strict scorer (v1.0.0): exactly one terminal `FINAL:` line, an exact rational value, and a unit validated against pre-declared aliases and conversions; missing, refused, ambiguous and truncated answers count as wrong. The secondary endpoint, `numeric_literal_v1`, adopted before the pilot, checks whether the literal value on the sole FINAL line equals gold. It is reported beside,

Model	Inv.	E/R/C	Dominant failure
Qwen3-1.7B$^{\times}$	36	0/0/0	instruction echo
Qwen3-4B†	0	12/10/12	2 R op-word misreadings
Qwen3-8B	0	12/12/12	none (1 R in Devanagari)
Llama-3.2-3B	2	12/9/9	value errors in R, C
Phi-4-mini$^{\times}$	14	6/4/11	inline FINAL; R repetition
Granite-3.3-2B$^{\times}$	36	0/0/0	commentary after FINAL
Gemma-3-4B$^{\times}$	–	–	no outputs (CUDA, FP16)

Table 1: Format screening on the excluded fixtures (prompt v2; strict-invalid of 36; strict correct of 12 per form). †primary; $^{\times}$excluded from the pilot. Phi-4-mini and Granite were excluded before the $\leq$3/36 rule was formalized; both exceed it.

Backbone	E	R	C
Pilot-B (primary), 70 families			
Qwen3-4B	94.3 [86.2, 97.8]	85.7 [75.7, 92.1]	94.3 [86.2, 97.8]
invalid	3	2	1
Qwen3-8B	98.6 [92.3, 99.7]	91.4 [82.5, 96.0]	98.6 [92.3, 99.7]
invalid	1	1	0
Llama-3.2-3B	94.3 [86.2, 97.8]	57.1 [45.5, 68.1]	70.0 [58.5, 79.5]
invalid	1	6 (5)	4 (2)
Original cohort, 24 families (no invalid outputs)			
Qwen3-4B	100.0 [86.2, 100.0]	91.7 [74.2, 97.7]	100.0 [86.2, 100.0]
Qwen3-8B	100.0 [86.2, 100.0]	95.8 [79.8, 99.3]	100.0 [86.2, 100.0]
Llama-3.2-3B	87.5 [69.0, 95.7]	62.5 [42.7, 78.8]	91.7 [74.2, 97.7]

Table 2: Strict accuracy (%) by form and cohort, with 95% Wilson intervals; the cohorts are never pooled. *invalid*: strict-invalid outputs (truncated in parentheses). No refusals occurred. Qwen3-4B is primary.

never instead of, the strict endpoint. Disagreement does not prove a format-only error, and agreement does not rule out formatting failures that both endpoints reject (cf. Peter et al., 2026).

Models. The primary backbone is Qwen3-4B (Qwen Team, 2025) at revision `1cfa9a72...`, with NF4 4-bit quantization (Dettmers et al., 2023), FP16 compute, thinking disabled, greedy decoding, a 1,024-token cap and a fresh context per prompt, on a Colab T4. Qwen3-8B and Llama-3.2-3B-Instruct are secondary, descriptive backbones under the identical protocol, in both cohorts. Both passed a rule declared before screening: at most 3/36 strict-invalid fixture outputs under the unchanged prompt and scorer, with no per-model tuning.

5 Development Findings (Not Results)

All evidence here comes from 36 AI-authored, unreviewed fixture prompts (12 families $\times$ E/R/C), **permanently excluded** from both cohorts and all later data; every rate is only an indication.

Format confound and v1→v2. Under the original instruction (`FINAL: <number or fraction> <unit when applicable>`), 10/36 Qwen3-4B outputs were strict-invalid, all `invalid_unit`; strict-correct counts were 9/7/9 on E/R/C. In 8, roughly equally across forms, a unit word was appended to a dimensionless answer (`8 unitless`). With v2 there were 0/36 invalid outputs, strict and numeric endpoints agreed on all 36, and strict-correct counts were 12/10/12. The fixtures also changed between runs (one R rendering repaired, one alias added), so 10→0 is a development comparison, not an isolated prompt effect. **Devanagari drift:** under v1, 8/12 R explanations contained Devanagari despite the English instruction (0/12 for E and for C); under v2, 0/12. The detector is heuristic.

Cross-model format compliance. Six more models ran on the same prompts under frozen v2 (Table 1). Phi-4-mini's inline FINAL lines (rejected by both endpoints) and R repetition to the token cap (6/12) make its C > E ordering a formatting artifact. Within Qwen3, instruction following broke before mathematics did (36/36 invalid at 1.7B, 0/36 at 4B and 8B). Without a compliance check on excluded data, a multi-model comparison would mostly measure formatting.

Repeated *bhaag/bhinn* misreadings. Under v2, Qwen3-4B's only errors were two R items whose renderings an AI assistant, not an independent bilingual check, judged correct **[TODO:** confirm**]**. *Bhaag dekar bhinn likho* ("divide, write as a fraction") was answered as a difference, and *kitna bhinn istemaal hua* ("what fraction was used") received the remaining count (20) under both v1 and v2; Llama-3.2-3B gave the same 20. *Bhinn* means both "fraction" and "different" even in Devanagari. With $n = 2$ unreviewed items, these errors are *consistent with* operation-word misreading but do not establish it. They motivated the lexicon and keep/switch design, fixed before any pilot output.

6 Pilot Results

Each cohort was analysed under a pre-registration fixed before any of its outputs; Pilot-B is primary. The original cohort's plan was written with Pilot-B results known, so it is a descriptive replication, not an independent confirmation. Each backbone ran once per cohort and completed every rendering (210/210; 72/72); tables reproduce exactly from stored scores. The cohorts differ in items, review

Backbone	E−R	E−C	R−C
Pilot-B (primary), 70 families			
Qwen3-4B	+8.6 [−1.4, +18.6] (9/3)	0.0 [−7.1, +7.1] (3/3)	−8.6 [−15.7, −1.4] (1/7)
Qwen3-8B	+7.1 [0.0, +14.3] (6/1)	0.0 [−4.3, +4.3] (1/1)	−7.1 [−14.3, 0.0] (1/6)
Llama-3.2-3B	+37.1 [+24.3, +50.0] (28/2)	+24.3 [+11.4, +37.1] (21/4)	−12.9 [−27.1, +1.4] (10/19)
Original cohort, 24 families			
Qwen3-4B	+8.3 [0.0, +20.8] (2/0)	0.0 [0.0, 0.0] (0/0)	−8.3 [−20.8, 0.0] (0/2)
Qwen3-8B	+4.2 [0.0, +12.5] (1/0)	0.0 [0.0, 0.0] (0/0)	−4.2 [−12.5, 0.0] (0/1)
Llama-3.2-3B	+25.0 [+4.2, +45.8] (7/1)	−4.2 [−16.7, +8.3] (1/2)	−29.2 [−45.8, −12.5] (0/7)

Table 3: Paired family differences (percentage points) with 95% intervals from 10,000 family-bootstrap resamples (seed 101), computed within each cohort. In parentheses: discordant families correct only in the first / only in the second form. Zero-width intervals at ceiling are not evidence of equivalence.

and C definition and are never pooled.

Romanized Hindi is the hard case. R is the lowest-scoring form for every backbone in both cohorts (Tables 2 and 3). In Pilot-B the deficit is modest for Qwen (8.6 and 7.1 points; intervals touch zero) and large for Llama (37.1 points, [+24.3, +50.0]); Qwen3-8B improves all forms but keeps the R deficit. The direction replicates for every model in the original cohort, where Qwen is near ceiling (E = C = 100%) and Llama's E−R deficit is 25.0 points [+4.2, +45.8]. Zero-width intervals at ceiling are not evidence of equivalence.

Hinglish and English: equal aggregate accuracy for Qwen. Both Qwen models have equal observed aggregate accuracy on E and C in both cohorts (E−C = 0.0), which is not itemwise identity (Pilot-B discordances 3/3 and 1/1) and not an equivalence test. C exceeds R; for Qwen3-4B in Pilot-B the R−C interval excludes zero. For Llama, C lies well below E in Pilot-B (+24.3 points) but not in the original cohort, so C's position is model- and cohort-dependent.

The operation-word hypothesis is not supported. In a pre-registered descriptive Pilot-B split by whether C keeps or switches R's Hindi operation word (or R has none), R accuracy is similar across strata for every model (keep/switch/none): Qwen3-4B 89/82/86%, Qwen3-8B 94/94/89%, Llama 67/59/51%. The R deficit is therefore not concentrated in items with *bhaag*/*bhinn*-type vocabulary. Many Llama R errors are arithmetic slips on simple items (e.g., $1200 - 3 \times 265$ answered as 435). In the original cohort, one Qwen3-4B R error (PIL001-R, *Riya se 5 kam* "5 fewer than Riya" read as addition) is an isolated operation-word misreading; the other two Qwen errors there are wrong values.

Residual format effects. The numeric endpoint agrees with strict scoring on every Llama Pilot-B rendering and on all 72 original-cohort renderings for each model; this does not rule out formatting failures that both endpoints reject (Llama had 11 strict-invalid Pilot-B outputs, 7 of them truncated). For Qwen, the pre-registered secondary grammar does not accept a *trailing* rupee symbol (`FINAL: 1575 ₹`), which strict scoring accepts; this accounts for every strict-correct/numeric-fail case (30 for Qwen3-4B, 36 for Qwen3-8B). We report the secondary endpoint as specified; a post-hoc allowance for the trailing symbol restores agreement. Three of Qwen3-4B's four Pilot-B E failures are numerically correct answers with unlisted English unit phrases (`11 years old`, `4 bags of cement`), and one C failure is an unlisted spelling (`300 rupye`): the form-dependent alias penalty anticipated in §5.

Exploratory (not pre-registered). Despite the English-explanation instruction, Llama explained 60/70 R and 27/70 C Pilot-B outputs in Romanized-Hindi prose (heuristic detection). On C, Hindi-prose explanations were correct 13/27 against 36/43 for English explanations, an association confounded by item difficulty. For the Qwen3-4B Pilot-B outputs, two AI models pre-tagged error category and English compliance blind to each other (κ = 0.94 and 0.96); the human check is pending, so no audit result is reported **[TODO:** human audit check, then audit table].

7 Conclusion

With the mathematics fixed, small open models were least accurate on Romanized Hindi in two separately reviewed cohorts, by a model-specific amount; answer formats must first be checked on excluded data.

Limitations

- **Diagnostic scale.** With 70 and 24 families per cohort, intervals are wide and the vocabulary strata are sparse and descriptive. The original cohort is near ceiling for Qwen, and its analysis plan was written after Pilot-B results were known.
- **Thin development evidence.** §5 rests on 12 unreviewed fixture families, and the prompt was revised after seeing their outputs; no pilot item was used to design the prompt.
- **Limited language review.** Pilot-B, the test set and the lexicon each had one bilingual reviewer, who is a team member; the original cohort had one human language reviewer plus an adjudicator. Part of the lexicon was AI-assisted, and *anupat* is unconfirmed. Naturalness judgments reflect few speakers' register.
- **AI-authored data.** Items share LLM drafting styles. Claude both drafted and solved Pilot-B. The GPT/Claude repair contrast is confounded with split and prompt.
- **Different C definitions.** The original cohort and Pilot-B define C differently, which prevents a simple pooled C estimate.
- **Models.** All backbones are small, quantized, greedy and non-thinking. Admitting models by format compliance excludes families whose formatting the scorer does not accept.
- **No script control.** There is no Devanagari arm, so an E–R gap mixes script, language, register and spelling. C $\approx$ E with R $<$ E would suggest vocabulary but would not identify it. Each R rendering is one of many possible spellings.
- **Contamination.** The items are new, but the models' pretraining data cannot be audited.

Ethics Statement

Consent and credit. Reviewers received a consent note covering the task, data use and release **[TODO:** signed consent and exposure records for every reviewer; roles (team member or external); any compensation**]**. Reviewers will be credited in the camera-ready acknowledgments or as authors, as appropriate and according to their stated preference **[TODO:** confirm each reviewer's preference**]**. Real identities stay out of shared ledgers.

AI-assistance disclosure. (1) *AI-drafted items:* every rendering was drafted by an LLM (Claude for Pilot-B and the training split, GPT for test and development **[TODO:** drafting model of the original 30**]**). The families were then checked against code-computed gold and reviewed by humans; Pilot-B was also verified blind by two LLM solvers. (2) *AI-assisted human review:* humans made every acceptance decision, but some lexicon entries and some text edits were drafted by AI before reviewers confirmed them (§3). In the original cohort, one reviewer's AI-prefilled, unverified stage-2 judgments were excluded. (3) *Writing and coding:* AI assistants helped write the evaluation and analysis code, the research notes and this manuscript, and recorded protocol decisions under the authors' delegation. The authors reviewed all of this and take responsibility for it **[TODO:** name the assistant systems per venue policy**]**.

Data. The items are invented everyday word problems and are not expected to contain personal information **[TODO:** names/PII check before release**]**. Romanized Hindi varies by region and register, and our renderings reflect few speakers. Data are released under CC BY 4.0 and code under MIT. The test set stays unreleased until the confirmatory evaluation.

References

Avinash Anand, Kritarth Prasad, Chhavi Kirtani, Ashwin R. Nair, Manvendra Kumar Nema, Raj Jaiswal, and Rajiv Ratn Shah. 2025. Multilingual mathematical reasoning: Advancing open-source LLMs in Hindi and English. *Proceedings of the AAAI Conference on Artificial Intelligence*, 39(22):23415–23423.

Kalika Bali, Jatin Sharma, Monojit Choudhury, and Yogarshi Vyas. 2014. "I am borrowing ya mixing?" an analysis of English-Hindi code mixing in Facebook. In *Proceedings of the First Workshop on Computational Approaches to Code Switching*, pages 116–126, Doha, Qatar. Association for Computational Linguistics.

Linzheng Chai, Jian Yang, Tao Sun, Hongcheng Guo, Jiaheng Liu, Bing Wang, Xinnian Liang, Jiaqi Bai, Tongliang Li, Qiyao Peng, and Zhoujun Li. 2025. XCOT: Cross-lingual instruction tuning for cross-lingual chain-of-thought reasoning. *Proceedings of the AAAI Conference on Artificial Intelligence*, 39(22):23550–23558.

Nuo Chen, Zinan Zheng, Ning Wu, Ming Gong, Dongmei Zhang, and Jia Li. 2024. Breaking language barriers in multilingual mathematical reasoning: Insights and observations. In *Findings of the Association for Computational Linguistics: EMNLP 2024*,

pages 7001–7016, Miami, Florida, USA. Association for Computational Linguistics.

Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, Christopher Hesse, and John Schulman. 2021. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*.

Avisha Das, Mihir Parmar, Mohana Ramnath, and Pulkit Verma. 2026. Indi-RomCoM: Code-mixed benchmark for evaluating LLMs on romanized Indic-English instructions. *arXiv preprint arXiv:2606.30790*.

Tim Dettmers, Artidoro Pagnoni, Ari Holtzman, and Luke Zettlemoyer. 2023. QLoRA: Efficient finetuning of quantized LLMs. In *Advances in Neural Information Processing Systems*, volume 36.

Anusha Kamath, Kanishk Singla, Rakesh Paul, Raviraj Joshi, Utkarsh Vaidya, Sanjay Singh Chauhan, and Niranjan Wartikar. 2025. Benchmarking Hindi LLMs: A new suite of datasets and a comparative analysis. *arXiv preprint arXiv:2508.19831*.

Manurag Khullar, Utkarsh Desai, Poorva Malviya, Aman Dalmia, and Zheyuan Ryan Shi. 2026. Script gap: Evaluating LLM triage on Indian languages in native vs Romanized scripts in a real-world setting. In *Proceedings of the 2026 Conference on Empirical Methods in Natural Language Processing: Industry Track*, pages 2414–2429. Association for Computational Linguistics.

Huiyuan Lai and Malvina Nissim. 2024. mCoT: Multilingual instruction tuning for reasoning consistency in language models. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 12012–12026, Bangkok, Thailand. Association for Computational Linguistics.

Iman Mirzadeh, Keivan Alizadeh, Hooman Shahrokhi, Oncel Tuzel, Samy Bengio, and Mehrdad Farajtabar. 2025. GSM-Symbolic: Understanding the limitations of mathematical reasoning in large language models. In *The Thirteenth International Conference on Learning Representations (ICLR)*.

Arkil Patel, Satwik Bhattamishra, and Navin Goyal. 2021. Are NLP models really able to solve simple math word problems? In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 2080–2094. Association for Computational Linguistics.

Jan-Thorsten Peter, David Vilar, Tobias Domhan, Dan Malkin, and Markus Freitag. 2026. Mind the gap... or not? how translation errors and evaluation details skew multilingual results. In *Proceedings of the Fifth Workshop on Generation, Evaluation and Metrics (GEM)*, pages 191–204. Association for Computational Linguistics.

Aleksandar Petrov, Emanuele La Malfa, Philip H. S. Torr, and Adel Bibi. 2023. Language model tokenizers introduce unfairness between languages. In *Advances in Neural Information Processing Systems*, volume 36.

Qwen Team. 2025. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*.

Brian Roark, Lawrence Wolf-Sonkin, Christo Kirov, Sabrina J. Mielke, Cibu Johny, Isin Demirsahin, and Keith Hall. 2020. Processing South Asian languages written in the Latin script: the Dakshina dataset. In *Proceedings of the Twelfth Language Resources and Evaluation Conference*, pages 2413–2423, Marseille, France. European Language Resources Association.

Sarvam AI. 2025. Sarvam-M. Technical blog report, 23 May 2025. https://www.sarvam.ai/blogs/sarvam-m.

Harshita Sharma, Pruthwik Mishra, and Dipti Sharma. 2022. HAWP: a dataset for Hindi arithmetic word problem solving. In *Proceedings of the Thirteenth Language Resources and Evaluation Conference*, pages 3479–3490, Marseille, France. European Language Resources Association.

Freda Shi, Mirac Suzgun, Markus Freitag, Xuezhi Wang, Suraj Srivats, Soroush Vosoughi, Hyung Won Chung, Yi Tay, Sebastian Ruder, Denny Zhou, Dipanjan Das, and Jason Wei. 2023. Language models are multilingual chain-of-thought reasoners. In *The Eleventh International Conference on Learning Representations (ICLR)*.

Sthānika. 2026. The code-mixing tax on romanized Hindi, measured. Research report, 9 September 2026. https://sthanika.ai/research/codemix-tax-2026.

Yilun Yang and Yekun Chai. 2025. CodeMixBench: Evaluating code-mixing capabilities of LLMs across 18 languages. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 2139–2169, Suzhou, China. Association for Computational Linguistics.