🚀 Full-Stack MERN Habit Tracker (v1.0)

1. Project Overview

Version 1.0 represents the completed Minimum Viable Product (MVP) of a full-stack web application built from scratch using the **MERN** stack (MongoDB, Express.js, React, Node.js). The application allows users to track their daily habits with full **CRUD** (Create, Read, Update, Delete) functionality.

- **Database:** MongoDB Atlas (Cloud)
- **Backend:** Node.js with Express and Mongoose
- **Frontend:** React (scaffolded via Vite)
- **API Communication:** Axios
- **Version Control:** Git & GitHub



2. Phase 1: Backend Architecture & Database

What I Did:

- Set up a Node.js server using Express.
- Designed a strict Mongoose schema (`Habit.js`) to enforce data rules (requiring a `name` and `userId`, storing an array of `completedDates`, etc.).
- Provisioned a live cloud database using MongoDB Atlas and secured the connection credentials.

The Challenge: The `undefined` URI Error

- **The Problem:** When starting the server, Mongoose crashed with the error: `The uri parameter to openUri() must be a string, got "undefined"`.
- **The Solution:** Discovered that `process.env.MONGO_URI` was empty because the `.env` file hadn't been created yet. Created the `.env` file, generated the correct connection string from MongoDB Atlas, and successfully connected the server to the cloud database.

---

3. Phase 2: API Routing & Testing

What I Did:

- Built four core API routes:
  - `POST /api/habits` (Create a habit)
  - `GET /api/habits/:userId` (Read all habits for a user)
  - `PUT /api/habits/:id/toggle` (Update a habit by checking/unchecking a date)
  - `DELETE /api/habits/:id` (Delete a habit)
- Tested the backend pipeline manually using Thunder Client before touching the frontend.

The Challenge: The 500 Internal Server Error (Validation Failed)

- **The Problem:** Thunder Client returned a `500 Internal Server Error` stating `Path 'name' is required`, even though the JSON body contained the name.
- **The Solution (Part 1 - Middleware Order):** Added a `console.log(req.body)` and realized Express was receiving `{}` (an empty object). Fixed this by ensuring `app.use(express.json())` was placed *before* the route definitions in `server.js` so Express could translate the JSON data first.
- **The Solution (Part 2 - Data Mapping):** Updated the `POST` route to explicitly map the destructured variables into the `new Habit({...})` object so Mongoose could properly read and save the data.

---

4. Phase 3: Frontend React Integration

What I Did:

- Used **Vite** to quickly scaffold a modern React application.
- Installed **Axios** to handle HTTP requests.
- Used React Hooks (`useState` and `useEffect`) to fetch the habit data from the backend as soon as the page loaded.
- Built an interactive UI with a form to create habits, dynamic cards to display them, and interactive buttons to toggle completion and delete them in real-time.

The Challenge: Vite Setup & Invisible Text

- **The Problem (Vite CLI):** Running the Vite installation triggered several `npm warn` messages regarding the `--template` flag.
- **The Solution:** Learned to safely ignore harmless CLI warnings and successfully navigated the interactive menu to select React and JavaScript.
- **The Problem (Styling):** The habit cards rendered, but the text was completely invisible.
- **The Solution:** Realized Vite automatically injected dark-mode CSS into the global `index.css` file, which forced the text to be white against the white habit cards. Deleted the default Vite boilerplate CSS to restore standard black text and gain a clean styling slate.

---

5. Phase 4: Version Control

What I Did:

- Initialized a Git repository for the entire project.
- Created a `.gitignore` file in the backend to ensure the `.env` file (containing the database password) and the massive `node_modules` folder were never uploaded to the internet.
- Committed the code and pushed it to a remote GitHub repository.

The Challenge: Git Line-Break Warnings

- **The Problem:** Running `git add .` resulted in a massive wall of warnings stating `LF will be replaced by CRLF`.
- **The Solution:** Identified that this was not a code error, but rather a harmless background process where Git was standardizing invisible "Enter key" line breaks between Mac/Linux (`LF`) and Windows (`CRLF`) formats. Proceeded with the commit safely.

🚀 Full-Stack MERN Habit Tracker (v2.0)

1. Version 2.0 Overview (The Production Upgrade)

Version 2.0 takes the functional Minimum Viable Product (MVP) built in v1.0 and upgrades it to a production-ready application. This update focused on three major pillars: **UI/UX Modernization**, **Codebase Scalability**, and **Real-World Security**.

The app now features a sleek, responsive design, a modular component-based architecture, and a secure user authentication system using hashed passwords and JSON Web Tokens.

---

2. Phase 1: UI/UX Modernization (Tailwind CSS)

What I Did:

- Stripped out hardcoded inline styles and replaced them with **Tailwind CSS**.
- Designed a modern dashboard featuring custom shadows, hover transitions, dynamic conditional formatting (green for completed habits), and responsive layouts.

The Challenge: The Tailwind v4 Ecosystem Shift

- **The Problem:** Running the standard initialization command (`npx tailwindcss init -p`) failed and threw an npm error stating the executable could not be found.
- **The Solution:** Discovered that Tailwind CSS had just released Version 4.0, which entirely removed the need for the `tailwind.config.js` file. Pivoted to the cutting-edge Vite + Tailwind v4 setup by installing the `@tailwindcss/vite` plugin, updating `vite.config.js`, and using a single `@import "tailwindcss";` directive in the main CSS file.



3. Phase 2: React Architecture (Refactoring)

What I Did:

- Refactored a monolithic `App.jsx` file into the "React Way" using a Component-Based Architecture.
- Created a `components` folder and extracted the UI into specialized, reusable blocks:
  - `<HabitForm />`: Manages its own local typing state and passes packaged habit data *up* to the parent on submit.
  - `<HabitCard />`: A "dumb" presentation component that receives habit data and interaction functions passed *down* via **Props**.
- Simplified `App.jsx` to act strictly as the "Manager" that handles API calls and global state.

---

4. Phase 3: Real User Authentication (Security)

What I Did:

- Replaced the static, hardcoded `fakeUserId` with a dynamic, secure authentication flow.
- **Backend:** * Created a new `User.js` Mongoose schema enforcing unique emails.
  - Used **bcrypt.js** to salt and hash user passwords 10 times before saving them to the database.
  - Implemented **jsonwebtoken (JWT)** to generate secure, encrypted digital tokens ("VIP wristbands") upon successful login.
- **Frontend:** * Built an `<AuthForm />` component to handle both Account Creation and Logging In.
  - Utilized the browser's `localStorage` to save the JWT and user data, ensuring the user remains logged in even if the page refreshes.

The Challenge: Express Router Crashes (`TypeError`)

- **The Problem:** When wiring up the new `authRoutes.js`, the Express server immediately crashed on startup with: `TypeError: argument handler must be a function`.
- **The Solution:** Identified that Express was receiving an empty object instead of a valid route. The `module.exports = router;` line was missing at the bottom of the newly created route file. Adding it restored the server.

The Challenge: The 500 Internal Server Error (JWT Secret Missing)

- **The Problem:** User registration worked perfectly (`201 Created`), but attempting to log in threw a `500 Internal Server Error`. Adding a `console.log` revealed the specific error: `secretOrPrivateKey must have a value`.
- **The Solution:** The server was trying to generate a JWT but could not read the `JWT_SECRET` password from the `.env` file. Fixed this by ensuring `require('dotenv').config();` was placed at the absolute **very top** of `server.js`, allowing Express to load the secret keys into memory before the authentication routes were called.



The user can create a new account.



The user can log in with Email and Password.