AMRITA VISHWA VIDYAPEETHAM
DEEMED TO BE UNIVERSITY

DATASTRUCTURES AND ALGORITHMS

23CSE203

LAB MANUAL

SUBMITTED BY	
NAME	DIVYA SAHITHI MASINENI
ROLL NO	AV.SC.U4CSE25129
YEAR/SEM/SECTION	2ndYEAR/ SEM-3/CSE-B
CREDITS	05

SUBMITTED TO	DR. RAJ KUMAR BATCHU
DESIGNATION	ASST.PROFFESSOR(SL Grade)
DEPARTMENT	SCHOOL OF COMPUTING

INDEX

S.NO	TITLE	PAGE NO	REMARKS
1	WEEK 1: A. A rocket launch system displays a countdown before launch. Instead of using a loop implement the countdown using recursion. Write a recursion python program to display a countdown from n to 1 followed by “launch”. B. The banks calculate the growth of an investment using compound interest; the formula requires calculating powers. Which can be implemented recursively. Write a recursive program to calculate p^n(power), where p=principal growth factor, n= number of years. C. An HIR department stores employee IDs in a list. Develop a recursive program to search for a given employee ID. Write a recursive function to search for an employee ID in a list. D. In a logistics company the number of possible ways to arrange n different parcels are calculated using the factorial formula(n!). develop a recursive program to calculate the factorial of a given number. E. Write a recursive python program to print the first n terms of the Fibonacci series.		

INDEX

S.NO	TITLE	PAGE NO	REMARKS
2	WEEK 2: A. Write a program to perform linear search on a given input. B. (i) Write a python program to implement binary search with sorted array as an input. (ii) Write a python program to implement binary search without sorted array as an input		
3.	WEEK-3: A.Write a python program to implement bubble sort, where the input elements are taken from the user. B. Write a python program to implement insertion sort, where the input elements are taken from the user. C. Write a python program to implement selection sort, where the input elements are taken from the user.		
4	WEEK 4 : A.Write a python program to implement merge sort where the input elements are taken from the user B. Write a python program to implement quick sort where the input elements are taken from the user		

INDEX

S.NO	TITLE	PAGE NO	REMARKS
5.	WEEK 5 : a) Write a Python program to implement a singly linked list with the below operations: 1. Create linked list 2. Insert at beginning 3. Insert at end 4. Insert at a specific index 5. Delete by value 6. Delete first node 7. Delete last node 8. Count number of nodes 9. Display / Traverse 10. Exit b) Execute above programs for doubly linked list c) Execute above programs for Circular linked list		
6.	WEEK-6 Write a Python program to implement stack operations such as **Push, Pop, Peek, Display** using an **array and a linked list**.		
7.	WEEK-7 a) Write a Python program to implement a **queue** and its operations such as **Enqueue, Dequeue, Peek, Display** with a **menu-driven approach**. Implement using **array and linked-list data structures**.		

S.NO	TITLE	PAGE NO	REMARKS
	b) Circular Queue- its operations such as **Enqueue, Dequeue, Peek, Display** with a **menu-driven approach**. Implement using **array and linked-list data structures**.		

LAB-1

1.AIM: A rocket launch system displays a countdown before launch. Instead of using a loop implement the countdown using recursion. Write a recursion python program to display a countdown from n to 1 followed by “launch”.

PROGRAM:

```
def launch(n):
  for i in range(n,-1,-1):
   if i==0:
    print("launch")
  else:
    print(i)
n=int (input ("Enter  countdown number:"))
launch(n)
```

OUTPUT:

```
============ RESTART: C:\Users\Divya\OneDrive\Documents\DSA\lab1a.py ==========
Enter countdown number: 7
7
6
5
4
3
2
1
Launch
```

EXPLANATION:

This program displays a countdown from n to 1 and finally prints 'launch'. Although the aim mentions recursion, the given code uses a loop

ERROR TABLE:

S.no.	Errors	Rectification
1.	Indentation Error	Use 3 **spaces** for each level of indentation.
2.	Type Error	Convert the input to an integer using n = int (input ("Enter no. of seconds to launch: ")).

2.AIM: The banks calculate the growth of an investment using compound interest; the formula requires calculating powers. Which can be implemented recursively. Write a recursive program to calculate p^n(power), where p=principal growth factor, n= number of years.

PROGRAM:

```
def power (p, n):
  if n == 0:
   return 1
  else:
    return p * power (p, n - 1)
p = float (input ("Enter principal/base value: "))
n = int (input ("Enter number of years/powers: "))
result = power (p, n)
print("Power =", result)
```

OUTPUT:

```
============ RESTART: C:\Users\Divya\OneDrive\Documents\DSA\lab1b.py ==========
Enter principal/base value: 456
Enter number of years/power: 23
Result = 1432819163011061360894656451138504049716965586066841347398041 6
```

EXPLANATION:

- The function of power (p, n) calculates p^n using recursion by multiplying p with the result of power (p, n-1).
- The recursion stops when n becomes 0, returning 1, which is the base case.
- The final result is displayed after all recursive calls are completed.

ERROR TABLE:

S.no.	Errors	Rectification
1.	Type Error	Convert the input to float or int using float(input()) or int(input()).
2.	Incorrect output if the recursive call is written as power(p, n + 1) instead of power(p, n - 1).	Change the recursive call to power(p, n - 1) so that n decreases toward the base case.

3.AIM: An HR department stores employee IDs in a list. Develop a recursive program to search for a given employee ID. Write a recursive function to search for an employee ID in a list.

PROGRAM:

```
def search (list, key, index):
  if index >= len(list):
    return False
  if list[index] == key:
   return True
  return search (lst, key, index + 1)
employees = [101, 102, 103, 104, 105]
key = int (input ("Enter Employee ID to search: "))
```

```
if search (employees, key, 0):
print (f"Employee ID found at position {key}")
else:
print ("Employee ID Not Found")
```

OUTPUT:

```
============ RESTART: C:\Users\Divya\OneDrive\Documents\DSA\lab1c.py =========
Enter employee ID to search: 105
Employee ID found at position 5
```

```
============ RESTART: C:\Users\Divya\OneDrive\Documents\DSA\lab1c.py =======
Enter employee ID to search: 321
Employee ID not found
```

EXPLANATION:

- The recursive function checks each employee ID in the list one by one, starting from the first element.
- If the required ID is found, it returns True; otherwise, it continues searching recursively until the end of the list.
- If the entire list is searched without finding the ID, the function returns False.

ERROR TABLE:

S.no.	Errors	Rectification
1.	Name Error if the list name is misspelled (e.g., employee instead of employees).	Use the correct variable name consistently throughout the program.
2.	Syntax Error due to a missing colon (:) after an if statement or function definition.	Add the missing colon (:) after if, else, or def.

4.AIM: In a logistics company the number of possible ways to arrange n different parcels are calculated using the factorial formula(n!). develop a recursive program to calculate the factorial of a given number.

PROGRAM:

```
def factorial(n):
 if n == 0 or n == 1:
 return 1
 else:
 return n * factorial (n - 1)
num = int (input ("Enter a number: "))
if num < 0:
 print ("Factorial does not exist for negative numbers.")
else:
 print ("Factorial =", factorial(num))
```

OUTPUT:

```
============ RESTART: C:\Users\Divya\OneDrive\Documents\DSA\lab1d.py =======
Enter a number: 14
Factorial = 87178291200
```

EXPLANATION:

- The function factorial(n) computes the factorial by multiplying the current number with the factorial of the previous number.
- The recursion ends when n becomes 0 or 1, where the factorial value is 1.
- The program also checks for negative inputs since factorial is defined only for non-negative integers.

ERROR TABLE:

S.no.	Errors	Rectification
1.	IndentationError if the statements inside the function are not properly indented.	Maintain proper indentation (usually 4 spaces) inside the function.
2.	TypeError if a decimal number (e.g., 5.5) is entered for factorial calculation.	Enter only a whole number or convert the input using int().

5.AIM: Write a recursive python program to print the first n terms of the Fibonacci series.

PROGRAM:

```
def fibonacci(n):
 if n == 0:
 return 0
 elif n == 1:
 return 1
 else:
 return fibonacci(n - 1) + fibonacci(n - 2)
n = int (input ("Enter the number of terms: "))
print ("Fibonacci Series:")
for i in range(n):
 print (fibonacci(i), end=" ")
```

OUTPUT:

```
========== RESTART: C:\Users\Divya\OneDrive\Documents\DSA\lable.py ==========
Enter number of terms: 32
Fibonacci series:
0 1 1 2 3 5 8 13 21 34 55 89 144 233 377 610 987 1597 2584 4181 6765 10946 17711
 28657 46368 75025 121393 196418 317811 514229 832040 1346269
```

EXPLANATION:

- The function Fibonacci(n) returns the nth Fibonacci number by recursively adding the previous two Fibonacci numbers.
- The base cases return 0 for the first term and 1 for the second term.
- A for loop calls the recursive function repeatedly to print the first n terms of the Fibonacci series.

ERROR TABLE:

S.no.	Errors	Rectification
1.	Recursion Error if the base cases (n == 0 and n == 1) are not included.	Add both base conditions before the recursive call.
2.	Value Error if the user enters text instead of an integer.	Enter a valid integer for the number of terms.

LAB-2

1.AIM: Write a program to perform linear search on a given input.

PROGRAM:

```
def linear_search(arr,key):
 for i in range(len(arr)):
 if arr[i]==key:
 return i
 return -1
 n = int(input("Enter no. of elements:"))
arr=[]
print("Enter the elements:")
for i in range(n):
 arr.append(int(input()))
key=int(input("Enter element to search:"))
result=linear_search(arr,key)
if result!=-1:
 print("Element found at index",result)
else:
 print("Element not found.")
```

OUTPUT:

```
========== RESTART: C:\Users\Divya\OneDrive\Documents\DSA\lab2a.py ==========
Enter elements: 43 54 65 34 65 321 76 3
Enter element to search: 321
Element found at position 6
```

EXPLANATION:

The linear_search() function checks each element of the list one by one and compares it with the given key.

- If the key is found, its index is returned; otherwise, the function returns -1.
- The program takes the array and search element as input and displays whether the element is found.

ERROR TABLE:

S.no.	Errors	Rectification
1.	ValueError occurs if a non-integer value is entered when int(input()) is used.	Enter only integer values for the number of elements and array elements.
2.	TypeError may occur if len(arr) is used on a variable that is not a list.	Make sure arr is initialized as a list using arr = [] and elements are appended to it.

2.AIM: Write a Python program to perform binary search on the given input. Verify by taking sorted array and unsorted array as input.

PROGRAM:

```
def binary_search(arr,key):

 low=0

 high=len(arr)-1
```

```
while low<=high:
 mid=(low+high)//2
 if arr[mid]==key:
 return mid
 elif arr[mid]<key:
 low=mid+1
 else:
 high=mid-1
 return -1


n = int(input("Enter no. of elements:"))
arr=[]
print("Enter the elements:")
for i in range(n):
 arr.append(int(input()))


key=int(input("Enter element to search:"))
result=binary_search(arr,key)
if result!=-1:
 print("Element found at index",result)
else:
 print("Element not found.")
```

OUTPUT:

```
========== RESTART: C:\Users\Divya\OneDrive\Documents\DSA\lab2a.py ==========
Enter elements: 43 54 65 34 65 321 76 3
Enter element to search: 321
Element found at position 6
```

PROGRAM:

```
def binary_search(arr,key):
 low=0
 high=len(arr)-1
 while low<=high:
 mid=(low+high)//2
 if arr[mid]==key:
 return mid
 elif arr[mid]<key:
 low=mid+1
 else:
 high=mid-1
 return -1
 n = int(input("Enter no. of elements:"))
arr=[]
print("Enter the elements:")
for i in range(n):
 arr.append(int(input()))
 if arr==sorted(arr):
 print("\n The input list is already sorted.")
else:
```

```
 print("\n The input list is not sorted.")

 print("Sorting the list...")

 arr.sort()

print("Sorted list.",arr)

 key=int(input("Enter element to search:"))

result=binary_search(arr,key)

if result!=-1:

 print("Element found at index",result)

else:

 print("Element not found.")
```

OUTPUT:

```
========== RESTART: C:\Users\Divya\OneDrive\Documents\DSA\lab2b2.py =========
Enter elements: 542 43 53 756 423 67 342
Sorted array: [43, 53, 67, 342, 423, 542, 756]
Enter element to search: 43
Element found at position 1
```

EXPLANATION:

- The binary_search() function repeatedly divides the sorted list into two halves and compares the middle element with the search key.
- If the middle element is smaller than the key, the search continues in the right half; otherwise, it searches the left half.
- The second program verifies whether the input is sorted and sorts it using arr.sort() if necessary before performing binary search.

ERROR TABLE:

S.no.	Errors	Rectification
1.	IndexError can occur if mid is calculated or the low/high boundaries are modified incorrectly.	Initialize low = 0, high = len(arr) - 1 and update them as low = mid +1 or high = mid - 1.

Lab-3

1.AIM: write programs for the Bubble sort

PROGRAM:

```
#bubble sort
def bubble_sort(arr):
    n = len(arr)
    for i in range (n-1):
        for j in range(n-i-1):
            if arr[j]>arr[j+1]:
                arr[j],arr[j+1] = arr[j+1],arr[j]
    return arr
#taking input
n = int(input("Enter number of elements: "))
arr=[]
print("Enter elements: ")
for i in range(n):
    arr.append(int(input()))
bubble_sort(arr)
print("sorted array: ")
for element in arr:
    print(element, end=" ")
```

Output:

```
========== RESTART: C:\Users\Divya\OneDrive\Documents\DSA\lab3a.py ==========
Enter number of elements: 5
Enter elements:
45
3
77
56
54
sorted array:
3 45 54 56 77
```

Explanation:

Bubble sort compares two adjacent elements. If the left element is greater than the right element, they are swapped. After each pass, the largest remaining element moves to the end.

Error table:

S.no	Error	Correction
1.	Used wrong loop range	Use for j in range(n-i-1):
2.	Swap condition is wrong	Use if arr[j] > arr[j+1]:

2.AIM: write programs for the Insertion sort

PROGRAM:

```
# Insertion Sort

 def insertion_sort(arr):

    n = len(arr)

    for i in range(1, n):

        key = arr[i]

        j = i - 1

         while j >= 0 and arr[j] > key:

            arr[j + 1] = arr[j]

            j = j - 1
```

```
        arr[j + 1] = key
    return arr
# Taking input
n = int(input("Enter number of elements: "))
arr = []
print("Enter elements: ")
for i in range(n):
    arr.append(int(input()))
insertion_sort(arr)
print("Sorted array: ")
for element in arr:
    print(element, end=" ")   same for this
```

Output:

```
============ RESTART: C:\Users\Divya\OneDrive\Documents\DSA\lab3b.py =====
Enter number of elements: 7
Enter elements:
65
234
76
5
56
45
76
Sorted array:
5 45 56 65 76 76 234
```

Explanation:

Insertion sort builds the sorted array one element at a time.

It takes one element called the **key**, compares it with the elements before it, shifts larger elements to the right, and inserts the key in the correct position.

Error table:

S.no	Error	Correction
1.	key is not stored properly	Use key = arr[i]
2.	arr[j+1] = key placed inside while loop	Place it after the while loop

3.AIM: write programs for the Bubble sort

PROGRAM:

```
# Selection Sort
def selection_sort(arr):
    n = len(arr)
    for i in range(n - 1):
        min_index = i
        for j in range(i + 1, n):
            if arr[j] < arr[min_index]:
                min_index = j
        arr[i], arr[min_index] = arr[min_index], arr[i]
    return arr
# Taking input
n = int(input("Enter number of elements: "))
arr = []
print("Enter elements: ")
for i in range(n):
```

```
    arr.append(int(input()))

selection_sort(arr)

print("Sorted array: ")

for element in arr:

    print(element, end=" ")
```

Output

Explanation:

Selection sort repeatedly finds the **smallest element** from the unsorted part of the array and places it in its correct position.

Error table:

S.no	Error	Correction
1.	min_index is not initialized	Use min_index = i
2.	Swap is placed inside inner loop	Place swap after the inner loop

LAB-4

1.Aim: Write a python program to implement merge sort where the input elements are taken from the user

PROGRAM:

```
def merge_sort(arr):
    if len(arr) > 1:
        mid = len(arr) // 2
        left = arr[:mid]
        right = arr[mid:]
        merge_sort(left)
        merge_sort(right)
        i = j = k = 0
        while i < len(left) and j < len(right):
            if left[i] < right[j]:
                arr[k] = left[i]
                i += 1
            else:
                arr[k] = right[j]
                j += 1
            k += 1
        while i < len(left):
            arr[k] = left[i]
            i += 1
            k += 1
```

```
    while j < len(right):
        arr[k] = right[j]
        j += 1
        k += 1

# Input from user
arr = list(map(int, input("Enter elements separated by spaces: ").split()))
merge_sort(arr)
print("Sorted array:", arr)
```

Output:

```
>
============ RESTART: C:\Users\Divya\OneDrive\Documents\DSA\lab4a.py ===========
Enter elements separated by spaces: 43 45 35 9834 34 7  983 24 76
Sorted array: [7, 24, 34, 35, 43, 45, 76, 983, 9834]
>
============ RESTART: C:\Users\Divya\OneDrive\Documents\DSA\lab4a.py ===========
Enter elements separated by spaces: 46578908756432456
Sorted array: [46578908756432456]
>
```

Explanation:

Merge Sort is a **divide-and-conquer sorting algorithm**.It works in three main steps:

1. Divide – Divide the array into two halves.
2. Conquer – Recursively sort both halves.
3. Merge – Merge the two sorted halves into one sorted array.

Error table:

S.no	Error	Correction
1.	Wrong base condition	Use `if len(arr) > 1` for splitting
2.	Wrong midpoint	Use `mid = len(arr)//2`
3.	Forgetting remaining elements	Append remaining elements

2.Aim: Write a python program to implement quick sort where the input elements are taken from the user

Program:

```
def quick_sort(arr, low, high):
    if low < high:
        pivot = arr[high]
        i = low - 1
        for j in range(low, high):
            if arr[j] < pivot:
                i += 1
                arr[i], arr[j] = arr[j], arr[i]
        arr[i + 1], arr[high] = arr[high], arr[i + 1]
        p = i + 1
        quick_sort(arr, low, p - 1)
        quick_sort(arr, p + 1, high)
# Input from user
arr = list(map(int, input("Enter elements separated by spaces: ").split()))
quick_sort(arr, 0, len(arr) - 1)
print("Sorted array:", arr)
```

Output:

```
============ RESTART: C:\Users\Divya\OneDrive\Documents\DSA\lab4b.py ==========
Enter elements separated by spaces: 43 234 45 231 78  23 65
Sorted array: [23, 43, 45, 65, 78, 231, 234]

============ RESTART: C:\Users\Divya\OneDrive\Documents\DSA\lab4b.py ==========
Enter elements separated by spaces: 354679874
Sorted array: [354679874]
```

Explanation:

Quick Sort is also a **divide-and-conquer sorting algorithm**.

Its main idea is to select an element called a **pivot** and arrange the array so that:

Elements smaller than pivot | Pivot | Elements greater than pivot

Then Quick Sort is recursively applied to the left and right portions.

Error table:

S.No.	Error	Correction
1	Incorrect Python syntax, missing `:` or brackets	Check syntax, brackets and colons
2	Incorrect `low`/`high` boundaries are passed	Use `low, pivot-1` and `pivot+1, high`
3	Function keeps calling itself	Add `if low < high:`

LAB-5

1.Aim: Write a Python program to implement a singly linked list with the below operations:

1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at a specific index
5. Delete by value
6. Delete first node
7. Delete last node
8. Count number of nodes
9. Display / Traverse
10. Exit

Program:

```
class Node:
    def __init__(self, data):
        self.data = data
        self.next = None
class SinglyLinkedList:
    def __init__(self):
        self.head = None
    # 1. Create linked list
    def create(self):
        n = int(input("Enter number of nodes: "))
        for i in range(n):
            data = int(input(f"Enter data for node {i + 1}: "))
  new_node = Node(data)
            if self.head is None:
                self.head = new_node
```

```
        else:
            temp = self.head
            while temp.next:
                temp = temp.next
            temp.next = new_node
    print("Linked list created successfully.")
# 2. Insert at beginning
def insert_beginning(self):
    data = int(input("Enter data: "))
    new_node = Node(data)
    new_node.next = self.head
    self.head = new_node
    print("Node inserted at beginning.")
# 3. Insert at end
def insert_end(self):
    data = int(input("Enter data: "))
    new_node = Node(data)
    if self.head is None:
        self.head = new_node
    else:
        temp = self.head
```

```
while temp.next:
            temp = temp.next
        temp.next = new_node
    print("Node inserted at end.")
# 4. Insert at specific index
def insert_index(self):
    index = int(input("Enter index: "))
    data = int(input("Enter data: "))
    new_node = Node(data)
    if index == 0:
        new_node.next = self.head
        self.head = new_node
        print("Node inserted.")
        return
    temp = self.head
    for i in range(index - 1):
        if temp is None:
            print("Invalid index.")
            return
        temp = temp.next
    if temp is None:
        print("Invalid index.")
        return
```

```
 new_node.next = temp.next
    temp.next = new_node
    print("Node inserted.")
# 5. Delete by value
def delete_value(self):
    value = int(input("Enter value to delete: "))
    if self.head is None:
        print("List is empty.")
        return
    if self.head.data == value:
        self.head = self.head.next
        print("Node deleted.")
        return
    temp = self.head
    while temp.next and temp.next.data != value:
        temp = temp.next
    if temp.next is None:
        print("Value not found.")
    else:
        temp.next = temp.next.next
        print("Node deleted.")
# 6. Delete first node
def delete_first(self):
```

```
    if self.head is None:
        print("List is empty.")
else:
        self.head = self.head.next
        print("First node deleted.")
 # 7. Delete last node
 def delete_last(self):
    if self.head is None:
        print("List is empty.")
        return
    if self.head.next is None:
        self.head = None
        print("Last node deleted.")
        return
    temp = self.head
    while temp.next.next:
        temp = temp.next
    temp.next = None
    print("Last node deleted.")
 # 8. Count nodes
 def count(self):
    count = 0
    temp = self.head
    while temp:
```

```
        count += 1
            temp = temp.next
        print("Number of nodes:", count)
    # 9. Display / Traverse
    def display(self):
        if self.head is None:
            print("List is empty.")
            return
        temp = self.head
        while temp:
            print(temp.data, end=" -> ")
            temp = temp.next
        print("None")
# Main program
sll = SinglyLinkedList()
while True:
    print("\n--- SINGLY LINKED LIST ---")
    print("1. Create linked list")
    print("2. Insert at beginning")
    print("3. Insert at end")
    print("4. Insert at specific index")
    print("5. Delete by value")
    print("6. Delete first node")
    print("7. Delete last node")
```

```
print("8. Count number of nodes")
print("9. Display / Traverse")
print("10. Exit")
choice = int(input("Enter your choice: "))
if choice == 1:
    sll.create()
elif choice == 2:
    sll.insert_beginning()
elif choice == 3:
    sll.insert_end()
elif choice == 4:
    sll.insert_index()
elif choice == 5:
    sll.delete_value()
elif choice == 6:
    sll.delete_first()
elif choice == 7:
    sll.delete_last()
elif choice == 8:
    sll.count()
elif choice == 9:
    sll.display()
elif choice == 10:
    print("Program exited.")
```

```
        break
    else:
        print("Invalid choice.")
```

OUTPUT:

```
Python 3.14.0 (tags/v3.14.0:ebf955d, Oct  7 2025, 10:15:03) [MSC v.1944 64 bit (AMD
64)] on win32
Enter "help" below or click "Help" above for more information.
>
========== RESTART: C:/Users/Divya/OneDrive/Documents/DSA/lab5a.py ==========

--- SINGLY LINKED LIST ---
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete first node
7. Delete last node
8. Count number of nodes
9. Display / Traverse
10. Exit
Enter your choice: 1
Enter number of nodes: 5
Enter data for node 1: 54
Enter data for node 2: 54
Enter data for node 3: 32
Enter data for node 4: 2
Enter data for node 5: 6
Linked list created successfully.

--- SINGLY LINKED LIST ---
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete first node
7. Delete last node
8. Count number of nodes
9. Display / Traverse
10. Exit
Enter your choice: 2
Enter data: 43
Node inserted at beginning.
```

```
--- SINGLY LINKED LIST ---
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete first node
7. Delete last node
8. Count number of nodes
9. Display / Traverse
10. Exit
Enter your choice: 3
Enter data: 32
Node inserted at end.

--- SINGLY LINKED LIST ---
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete first node
7. Delete last node
8. Count number of nodes
9. Display / Traverse
10. Exit
Enter your choice: 4
Enter index: 2
Enter data: 323
Node inserted.

--- SINGLY LINKED LIST ---
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete first node
7. Delete last node
8. Count number of nodes
```

```
8. Count number of nodes
9. Display / Traverse
10. Exit
Enter your choice: 5
Enter value to delete: 776
Value not found.

--- SINGLY LINKED LIST ---
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete first node
7. Delete last node
8. Count number of nodes
9. Display / Traverse
10. Exit
Enter your choice: 5
Enter value to delete: 323
Node deleted.

--- SINGLY LINKED LIST ---
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete first node
7. Delete last node
8. Count number of nodes
9. Display / Traverse
10. Exit
Enter your choice: 6
First node deleted.

--- SINGLY LINKED LIST ---
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
```

```
5. Delete by value
6. Delete first node
7. Delete last node
8. Count number of nodes
9. Display / Traverse
10. Exit
Enter your choice: 7
Last node deleted.

--- SINGLY LINKED LIST ---
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete first node
7. Delete last node
8. Count number of nodes
9. Display / Traverse
10. Exit
Enter your choice: 8
Number of nodes: 5

--- SINGLY LINKED LIST ---
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete first node
7. Delete last node
8. Count number of nodes
9. Display / Traverse
10. Exit
Enter your choice: 9
54 -> 54 -> 32 -> 2 -> 6 -> None

--- SINGLY LINKED LIST ---
1. Create linked list
2. Insert at beginning
3. Insert at end
```

```
--- SINGLY LINKED LIST ---
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete first node
7. Delete last node
8. Count number of nodes
9. Display / Traverse
10. Exit
Enter your choice: 10
Program exited.
```

Explanation:

Singly Linked List – Explanation

A **singly linked list** is a linear data structure in which elements are stored in **nodes**. Each node contains two parts:

1. **Data** – stores the value.
2. **Next** – stores the address/reference of the next node.

- self.data stores the node value.
- self.next stores the reference to the next node.
- Initially, next = None because the node is not connected to another node.

Error table:

S.No	Mistake	Correction
1	`Node` class is not defined before using it	Define the `Node` class first
2	`temp` is not updated inside the loop	Add `temp = temp.next`
3	`head` is not updated	Use `self.head = new_node`
4	User enters an index outside the list range	Validate the index before insertion
5	The given value does not exist	Search the entire list and display "Value not found"
6	`head` is `None` and operation is performed directly	Check `if self.head is None`

2.Aim: Write a Python program to implement a Double linked list with the above operations

Program:

```
class Node:
 def __init__(self, data):
     self.data = data
      self.prev = None
       self.next = None
```

```
class DoublyLinkedList:
    def __init__(self):
        self.head = None
    # 1. Create linked list
    def create(self):
        n = int(input("Enter number of nodes: "))
        for i in range(n):
            data = int(input(f"Enter data for node {i + 1}: "))
            new_node = Node(data)
            if self.head is None:
                self.head = new_node
            else:
                temp = self.head
                while temp.next:
                    temp = temp.next
                temp.next = new_node
                new_node.prev = temp
        print("Doubly linked list created successfully.")
    # 2. Insert at beginning
    def insert_beginning(self):
        data = int(input("Enter data: "))
        new_node = Node(data)
```

```
    new_node = Node(data)
    if self.head is not None:
        new_node.next = self.head
        self.head.prev = new_node
    self.head = new_node
    print("Node inserted at beginning.")
# 3. Insert at end
def insert_end(self):
    data = int(input("Enter data: "))
    new_node = Node(data)
    if self.head is None:
        self.head = new_node
    else:
        temp = self.head
        while temp.next:
            temp = temp.next
        temp.next = new_node
        new_node.prev = temp
    print("Node inserted at end.")
# 4. Insert at specific index
def insert_index(self):
    index = int(input("Enter index: "))
    data = int(input("Enter data: "))
```

```
new_node = Node(data)
if index == 0:
    if self.head:
        new_node.next = self.head
        self.head.prev = new_node
    self.head = new_node
    print("Node inserted.")
    return
temp = self.head
for i in range(index - 1):
    if temp is None:
        print("Invalid index.")
        return
    temp = temp.next
if temp is None:
    print("Invalid index.")
    return
new_node.next = temp.next
new_node.prev = temp
if temp.next:
    temp.next.prev = new_node
temp.next = new_node
print("Node inserted.")
```

```
# 5. Delete by value
  def delete_value(self):
      value = int(input("Enter value to delete: "))
      temp = self.head
      while temp and temp.data != value:
          temp = temp.next
      if temp is None:
          print("Value not found.")
          return
      if temp.prev:
          temp.prev.next = temp.next
      else:
          self.head = temp.next
      if temp.next:
          temp.next.prev = temp.prev
      print("Node deleted.")
  # 6. Delete first node
  def delete_first(self):
      if self.head is None:
          print("List is empty.")
          return
      self.head = self.head.next
      if self.head:
          self.head.prev = None
```

```
print("First node deleted.")
 # 7. Delete last node
 def delete_last(self):
     if self.head is None:
         print("List is empty.")
         return
     temp = self.head
     while temp.next:
         temp = temp.next
     if temp.prev:
         temp.prev.next = None
     else:
         self.head = None
     print("Last node deleted.")
 # 8. Count nodes
 def count(self):
     count = 0
     temp = self.head
     while temp:
         count += 1
         temp = temp.next
     print("Number of nodes:", count)
 # 9. Display / Traverse
 def display(self):
```

```
        if self.head is None:
            print("List is empty.")
            return
        temp = self.head
        while temp:
            print(temp.data, end=" <-> ")
            temp = temp.next
        print("None")
# Main program
dll = DoublyLinkedList()
while True:
    print("\n--- DOUBLY LINKED LIST ---")
    print("1. Create linked list")
    print("2. Insert at beginning")
    print("3. Insert at end")
    print("4. Insert at specific index")
    print("5. Delete by value")
    print("6. Delete first node")
    print("7. Delete last node")
    print("8. Count number of nodes")
    print("9. Display / Traverse")
    print("10. Exit")

    choice = int(input("Enter your choice: "))
```

```
if choice == 1:
    dll.create()
elif choice == 2:
    dll.insert_beginning()
elif choice == 3:
    dll.insert_end()
elif choice == 4:
    dll.insert_index()
elif choice == 5:
    dll.delete_value()
elif choice == 6:
    dll.delete_first()
elif choice == 7:
    dll.delete_last()
elif choice == 8:
    dll.count()
elif choice == 9:
    dll.display()
elif choice == 10:
    print("Program exited.")
    break
else:
    print("Invalid choice.")
```

Output:

```
============ RESTART: C:/Users/Divya/OneDrive/Documents/DSA/lab5b.py ===========

--- DOUBLY LINKED LIST ---
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete first node
7. Delete last node
8. Count number of nodes
9. Display / Traverse
10. Exit
Enter your choice: 1
Enter number of nodes: 6
Enter data for node 1: 43
Enter data for node 2: 76
Enter data for node 3: 2
Enter data for node 4: 87
Enter data for node 5: 21
Enter data for node 6: 8
Doubly linked list created successfully.

--- DOUBLY LINKED LIST ---
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete first node
7. Delete last node
8. Count number of nodes
9. Display / Traverse
10. Exit
Enter your choice: 2
Enter data: 434

Node inserted at beginning.

--- DOUBLY LINKED LIST ---
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete first node
7. Delete last node
8. Count number of nodes
9. Display / Traverse
10. Exit
Enter your choice: 3
Enter data: 323
Node inserted at end.

--- DOUBLY LINKED LIST ---
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete first node
7. Delete last node
8. Count number of nodes
9. Display / Traverse
10. Exit
Enter your choice: 34
Invalid choice.

--- DOUBLY LINKED LIST ---
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete first node
7. Delete last node
8. Count number of nodes
```

```
9. Display / Traverse
10. Exit
Enter your choice: 4
Enter index: 4
Enter data: 33232
Node inserted.

--- DOUBLY LINKED LIST ---
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete first node
7. Delete last node
8. Count number of nodes
9. Display / Traverse
10. Exit
Enter your choice: 5
Enter value to delete: 34
Value not found.

--- DOUBLY LINKED LIST ---
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete first node
7. Delete last node
8. Count number of nodes
9. Display / Traverse
10. Exit
Enter your choice: 5
Enter value to delete: 87
Node deleted.

--- DOUBLY LINKED LIST ---
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete first node
7. Delete last node
8. Count number of nodes
9. Display / Traverse
10. Exit
Enter your choice: 6
First node deleted.

--- DOUBLY LINKED LIST ---
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete first node
7. Delete last node
8. Count number of nodes
9. Display / Traverse
10. Exit
Enter your choice: 7
Last node deleted.

--- DOUBLY LINKED LIST ---
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete first node
7. Delete last node
8. Count number of nodes
9. Display / Traverse
10. Exit
Enter your choice: 8
Number of nodes: 6

--- DOUBLY LINKED LIST ---
```

```
--- DOUBLY LINKED LIST ---
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete first node
7. Delete last node
8. Count number of nodes
9. Display / Traverse
10. Exit
Enter your choice: 9
43 <-> 76 <-> 2 <-> 33232 <-> 21 <-> 8 <-> None

--- DOUBLY LINKED LIST ---
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete first node
7. Delete last node
8. Count number of nodes
9. Display / Traverse
10. Exit
Enter your choice: 10
Program exited.
```

Explanation:

A **Doubly Linked List** is a linear data structure in which each node contains **three parts**:

1. prev – reference to the previous node
2. data – stores the value
3. next – reference to the next node

head points to the first node.

The first node's prev is None.

The last node's next is None.

Each node can be traversed **forward and backward**.

S.No	Error	Correction
1	Trying to access prev of a nonexistent node	Use an appropriate if condition
2	prev links are not updated	Correctly update prev references
3	head becomes None	Check whether the list becomes empty
4	Second-last node's next is not changed	Set temp.prev.next = None
5	Index is outside the list	Validate the index

2.Aim: Write a Python program to implement a Circular linked list with the above operations

Program:

```
class Node:
  def __init__(self, data):
     self.data = data
     self.next = None
class CircularLinkedList:
    def __init__(self):
         self.head = None
```

```
# 1. Create linked list
def create(self):
    n = int(input("Enter number of nodes: "))
    for i in range(n):
        data = int(input(f"Enter data for node {i + 1}: "))
        new_node = Node(data)
        if self.head is None:
            self.head = new_node
            new_node.next = self.head
        else:
            temp = self.head
            while temp.next != self.head:
                temp = temp.next
            temp.next = new_node
            new_node.next = self.head
    print("Circular linked list created successfully.")
# 2. Insert at beginning
def insert_beginning(self):
    data = int(input("Enter data: "))
    new_node = Node(data)
    if self.head is None:
        self.head = new_node
        new_node.next = self.head
```

```
    else:
        temp = self.head
        while temp.next != self.head:
            temp = temp.next
        new_node.next = self.head
        temp.next = new_node
        self.head = new_node
    print("Node inserted at beginning.")
# 3. Insert at end
def insert_end(self):
    data = int(input("Enter data: "))
    new_node = Node(data)
    if self.head is None:
        self.head = new_node
        new_node.next = self.head
    else:
        temp = self.head
        while temp.next != self.head:
            temp = temp.next
        temp.next = new_node
        new_node.next = self.head

    print("Node inserted at end.")
```

```
# 4. Insert at specific index
def insert_index(self):
    index = int(input("Enter index: "))
    data = int(input("Enter data: "))
    new_node = Node(data)
    if index == 0:
        if self.head is None:
            self.head = new_node
            new_node.next = self.head
        else:
            temp = self.head
            while temp.next != self.head:
                temp = temp.next
            new_node.next = self.head
            temp.next = new_node
            self.head = new_node
        print("Node inserted.")
        return
    if self.head is None:
        print("Invalid index.")
        return
    temp = self.head
    for i in range(index - 1):
        temp = temp.next
```

```
# 5. Delete by value
def delete_value(self):
    value = int(input("Enter value to delete: "))
    if self.head is None:
        print("List is empty.")
        return
    current = self.head
    previous = None
    while True:
        if current.data == value:
            break
        previous = current
        current = current.next
        if current == self.head:
            print("Value not found.")
            return
    # Only one node
    if current == self.head and current.next == self.head:
        self.head = None
    # Delete head
    elif current == self.head:
        last = self.head
        while last.next != self.head:
            last = last.next
```

```
            self.head = self.head.next
            last.next = self.head
        # Delete other node
        else:
            previous.next = current.next
        print("Node deleted.")
    # 6. Delete first node
    def delete_first(self):
        if self.head is None:
            print("List is empty.")
            return
        # Only one node
        if self.head.next == self.head:
            self.head = None
        else:
            last = self.head
            while last.next != self.head:
                last = last.next
            self.head = self.head.next
            last.next = self.head
        print("First node deleted.")
    # 7. Delete last node
    def delete_last(self):
        if self.head is None:
```

```
        print("List is empty.")
        return
    # Only one node
    if self.head.next == self.head:
        self.head = None
        print("Last node deleted.")
        return
    temp = self.head
    while temp.next.next != self.head:
        temp = temp.next
    temp.next = self.head
    print("Last node deleted.")
# 8. Count nodes
def count(self):
    if self.head is None:
        print("Number of nodes: 0")
        return
    count = 0
    temp = self.head
    while True:
        count += 1
        temp = temp.next
        if temp == self.head:
            break
    print("Number of nodes:", count)
```

```
    # 9. Display / Traverse
    def display(self):
        if self.head is None:
            print("List is empty.")
            return
        temp = self.head
        while True:
            print(temp.data, end=" -> ")
            temp = temp.next
            if temp == self.head:
                break
        print("(back to head)")
# Main program
cll = CircularLinkedList()
while True:
    print("\n--- CIRCULAR LINKED LIST ---")
    print("1. Create linked list")
    print("2. Insert at beginning")
    print("3. Insert at end")
    print("4. Insert at specific index")
    print("5. Delete by value")
    print("6. Delete first node")
    print("7. Delete last node")
    print("8. Count number of nodes")
```

```
print("9. Display / Traverse")
print("10. Exit")
choice = int(input("Enter your choice: "))
if choice == 1:
    cll.create()
elif choice == 2:
    cll.insert_beginning()
elif choice == 3:
    cll.insert_end()
elif choice == 4:
    cll.insert_index()
elif choice == 5:
    cll.delete_value()
elif choice == 6:
    cll.delete_first()
elif choice == 7:
    cll.delete_last()
elif choice == 8:
    cll.count()
elif choice == 9:
    cll.display()
elif choice == 10:
    print("Program exited.")
    break
else:
    print("Invalid choice.")
```

Output:

```
>
============ RESTART: C:/Users/Divya/OneDrive/Documents/DSA/lab5c.py ===========

--- CIRCULAR LINKED LIST ---
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete first node
7. Delete last node
8. Count number of nodes
9. Display / Traverse
10. Exit
Enter your choice: 1
Enter number of nodes: 7
Enter data for node 1: 657
Enter data for node 2: 543
Enter data for node 3: 45
Enter data for node 4: 3245
Enter data for node 5: 876
Enter data for node 6: 345
Enter data for node 7: 34456
Circular linked list created successfully.

--- CIRCULAR LINKED LIST ---
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete first node
7. Delete last node
8. Count number of nodes
9. Display / Traverse
10. Exit
Enter your choice: 2
Enter data: 32
Node inserted at beginning.

--- CIRCULAR LINKED LIST ---
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete first node
7. Delete last node
8. Count number of nodes
9. Display / Traverse
10. Exit
Enter your choice: 3
Enter data: 7654
Node inserted at end.

--- CIRCULAR LINKED LIST ---
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete first node
7. Delete last node
8. Count number of nodes
9. Display / Traverse
10. Exit
Enter your choice: 23
Invalid choice.

--- CIRCULAR LINKED LIST ---
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete first node
7. Delete last node
```

```
8. Count number of nodes
9. Display / Traverse
10. Exit
Enter your choice: 4
Enter index: 5
Enter data: 66665
Node inserted.

--- CIRCULAR LINKED LIST ---
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete first node
7. Delete last node
8. Count number of nodes
9. Display / Traverse
10. Exit
Enter your choice: 5
Enter value to delete: 754
Value not found.

--- CIRCULAR LINKED LIST ---
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete first node
7. Delete last node
8. Count number of nodes
9. Display / Traverse
10. Exit
Enter your choice: 45
Invalid choice.

--- CIRCULAR LINKED LIST ---
1. Create linked list
2. Insert at beginning
```

```
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete first node
7. Delete last node
8. Count number of nodes
9. Display / Traverse
10. Exit
Enter your choice: 5
Enter value to delete: 45
Node deleted.

--- CIRCULAR LINKED LIST ---
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete first node
7. Delete last node
8. Count number of nodes
9. Display / Traverse
10. Exit
Enter your choice: 6
First node deleted.

--- CIRCULAR LINKED LIST ---
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete first node
7. Delete last node
8. Count number of nodes
9. Display / Traverse
10. Exit
Enter your choice: 7
Last node deleted.
```

```
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete first node
7. Delete last node
8. Count number of nodes
9. Display / Traverse
10. Exit
Enter your choice: 8
Number of nodes: 7

--- CIRCULAR LINKED LIST ---
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete first node
7. Delete last node
8. Count number of nodes
9. Display / Traverse
10. Exit
Enter your choice: 9
657 -> 543 -> 3245 -> 66665 -> 876 -> 345 -> 34456 -> (back to head)

--- CIRCULAR LINKED LIST ---
1. Create linked list
2. Insert at beginning
3. Insert at end
4. Insert at specific index
5. Delete by value
6. Delete first node
7. Delete last node
8. Count number of nodes
9. Display / Traverse
10. Exit
Enter your choice: 10
Program exited.
```

Explanation:

A Circular Linked List is a linked list in which the **last node points back to the first node**

instead of pointing to None.

New node points to the old head.

Last node points to the new head.

Error table:

S.No	Error	Correction
1	Infinite loop during traversal	Stop when `temp == head`
2	Circular connection is lost	Set last node's `next` to `head`
3	Insert at beginning breaks the circle	Update `last.next = new_node`
4	Count is incorrect	Stop when pointer reaches `head`
5	Invalid index	Check index before insertion

LAB-6

1.Aim: Write a Python program to implement stack operations such as **Push, Pop, Peek, Display** using an **array**

Program:

```
# Stack implementation using Array

stack = [543,45,324,435,34,45,32]

MAX_SIZE = 5

def push():

if len(stack) == MAX_SIZE:

print("Stack Overflow")

else:

element = int(input("Enter element to push: "))

stack.append(element)

print(element, "pushed into stack")

def pop():

if len(stack) == 0:

print("Stack Underflow")

else:

element = stack.pop()

print(element, "popped from stack")

def peek():


if len(stack) == 0:


print("Stack is empty")
```

```
else:
print("Top element is:", stack[-1])
def display():
if len(stack) == 0:
print("Stack is empty")
else:
print("Stack elements are:")
for i in range(len(stack) - 1, -1, -1):
print(stack[i])
Menu-driven program
while True:
print("\n--- STACK USING ARRAY ---")
print("1. Push")
print("2. Pop")
print("3. Peek")
print("4. Display")
print("5. Exit")
choice = int(input("Enter your choice: "))
 if choice == 1:
     push()
 elif choice == 2:
   pop()
 elif choice == 3:
    peek()
```

```
elif choice == 4:
        display()
elif choice == 5:
    print("Program terminated")
     break
else:
    print("Invalid choice")
```

Output:





Explanation:

A **stack** is a linear data structure that follows the **LIFO (Last In, First Out)** principle. The element inserted last is removed first.

The main stack operations are:

1. **Push** – Adds an element to the top of the stack.
2. **Pop** – Removes the top element from the stack.
3. **Peek** – Displays the top element without removing it.
4. **Display** – Displays all elements in the stack.

Error table:

S.No	Error	Correction
1	`IndexError: pop from empty list`	Check `len(stack) == 0` before pop
2	Stack Overflow	Check `len(stack) == MAX_SIZE`
3	`IndexError: list index out of range`	Check whether stack is empty before Peek
4	`ValueError`	Enter a valid integer

2.Aim: Write a Python program to implement stack operations such as **Push, Pop, Peek, Display** using **a linked list**.

Program:

```
#Stack implementation using Linked List

class Node:

  def init(self, data):

    self.data = data

    self.next = None

class Stack:

 def init(self):

   self.top = None


 # Push operation
 def push(self):
    element = int(input("Enter element to push: "))

    new_node = Node(element)
    new_node.next = self.top
    self.top = new_node

    print(element, "pushed into stack")

 # Pop operation
 def pop(self):
    if self.top is None:
       print("Stack Underflow")
    else:
       element = self.top.data
       self.top = self.top.next
       print(element, "popped from stack")
```

```
# Peek operation
def peek(self):
    if self.top is None:
        print("Stack is empty")
    else:
        print("Top element is:", self.top.data)

# Display operation
def display(self):
    if self.top is None:
        print("Stack is empty")
    else:
        temp = self.top
        print("Stack elements are:")

        while temp is not None:
            print(temp.data)
            temp = temp.next

#Menu-driven program

stack = Stack()

while True:

print("\n--- STACK USING LINKED LIST ---")

print("1. Push")

print("2. Pop")

print("3. Peek")

print("4. Display")

print("5. Exit")
```

```
choice = int(input("Enter your choice: "))
if choice == 1:
    stack.push()
elif choice == 2:
    stack.pop()
elif choice == 3:
    stack.peek()
elif choice == 4:
    stack.display()
elif choice == 5:
    print("Program terminated")
    break
else:
    print("Invalid choice")
```

Output:


```
============ RESTART: C:/Users/Divya/OneDrive/Documents/DSA/lab6b.py =======

--- STACK USING LINKED LIST ---
1. Push
2. Pop
3. Peek
4. Display
5. Exit
Enter your choice: 1
Enter element to push: 32
32 pushed into stack

--- STACK USING LINKED LIST ---
1. Push
2. Pop
3. Peek
4. Display
5. Exit
Enter your choice: 1987
Invalid choice

--- STACK USING LINKED LIST ---
1. Push
2. Pop
3. Peek
4. Display
5. Exit
Enter your choice: 13
Invalid choice

--- STACK USING LINKED LIST ---
1. Push
2. Pop
3. Peek
4. Display
5. Exit
Enter your choice: 1
Enter element to push: 345
345 pushed into stack
```



Explanation:

A linked-list stack consists of **nodes**.

A temporary pointer travels through the linked list:

Error table:

S.No	Error	Correction
1	`AttributeError`	Check `self.top is None` before accessing data
2	Stack Underflow	Check whether `top` is `None`
4	`NameError`	Use the correct variable/reference

Lab-7

1.Aim:

Write a Python program to implement a **queue** and its operations such as **Enqueue, Dequeue, Peek, Display** with a **menu-driven approach**. Implement using **array**

Program:

```
#Queue Implementation using Linked List

#Operations: Enqueue, Dequeue, Peek, Display

class Node:

  def init(self, data):

    self.data = data

    self.next = None

class Queue:

  def init(self):

    self.front = None

    self.rear = None


  # Enqueue operation
  def enqueue(self, data):
    new_node = Node(data)
    if self.rear is None:
      self.front = self.rear = new_node
    else:
      self.rear.next = new_node
      self.rear = new_node
    print(data, "inserted into queue.")
```

```
# Dequeue operation
def dequeue(self):
    if self.front is None:
        print("Queue Underflow! Queue is empty.")
        return
    value = self.front.data
    self.front = self.front.next
    if self.front is None:
        self.rear = None
    print(value, "deleted from queue.")
# Peek operation
def peek(self):
    if self.front is None:
        print("Queue is empty.")
    else:
        print("Front element:", self.front.data)

# Display operation
def display(self):
    if self.front is None:
        print("Queue is empty.")
        return
    current = self.front
    print("Queue elements:", end=" ")
    while current is not None:
        print(current.data, end=" ")
        current = current.next
    print()

queue = Queue()

while True:

print("\n----- QUEUE USING LINKED LIST -----")

print("1. Enqueue")

print("2. Dequeue")

print("3. Peek")

print("4. Display")

print("5. Exit")
```

```
choice = int(input("Enter your choice: "))
if choice == 1:
    value = int(input("Enter element to enqueue: "))
   queue.enqueue(value)
elif choice == 2:
    queue.dequeue()

elif choice == 3:
    queue.peek()
elif choice == 4:
    queue.display()

elif choice == 5:
    print("Program terminated.")
    break
else:
    print("Invalid choice! Please try again.")
```

Output:

```
============ RESTART: C:/Users/Divya/OneDrive/Documents/DSA/lab7a.py ===========

----- QUEUE USING ARRAY -----
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Exit
Enter your choice: 1
Enter element to enqueue: 765
765 inserted into queue.

----- QUEUE USING ARRAY -----
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Exit
Enter your choice: 1
Enter element to enqueue: 87867
87867 inserted into queue.

----- QUEUE USING ARRAY -----
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Exit
Enter your choice: 187
Invalid choice! Please try again.

----- QUEUE USING ARRAY -----
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Exit
Enter your choice: 1
Enter element to enqueue: 543
543 inserted into queue.
```

```
5. Exit
Enter your choice: 2
765 deleted from queue.

----- QUEUE USING ARRAY -----
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Exit
Enter your choice: 87867
Invalid choice! Please try again.

----- QUEUE USING ARRAY -----
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Exit
Enter your choice: 3
Front element: 87867

----- QUEUE USING ARRAY -----
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Exit
Enter your choice: 4
Queue elements: [87867, 543]

----- QUEUE USING ARRAY -----
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Exit
Enter your choice: 5
Program terminated.
```

Explanation:

A **queue** is a linear data structure that follows the **FIFO (First In, First Out)** principle.

In this program, Python's **list** is used as an array to store queue elements.

Error table:

S.No	Error	Rectification
1	Using `queue.pop()` instead of `queue.pop(0)` removes the last element instead of the front element.	Use `queue.pop(0)` for dequeue operation.
2	Not checking the queue size before insertion can cause the queue to exceed its maximum size.	Check `if len(queue) == MAX_SIZE` before enqueue.
3	Accessing `queue[0]` when the queue is empty causes an `IndexError`.	Check `if len(queue) == 0` before performing Peek.

2.Aim:

Write a Python program to implement a **queue** and its operations such as **Enqueue, Dequeue, Peek, Display** with a **menu-driven approach**. Implement using **linked-list data structures**.

Program:

```
#Queue Implementation using Linked List

#Operations: Enqueue, Dequeue, Peek, Display

class Node:

  def init(self, data):

      self.data = data

      self.next = None

class Queue:

  def init(self):

       self.front = None

       self.rear = None
```

```
# Enqueue operation
def enqueue(self, data):
    new_node = Node(data)
    if self.rear is None:
        self.front = self.rear = new_node
    else:
        self.rear.next = new_node
        self.rear = new_node
    print(data, "inserted into queue.")
# Dequeue operation
def dequeue(self):
    if self.front is None:
        print("Queue Underflow! Queue is empty.")
        return

    value = self.front.data
    self.front = self.front.next

    if self.front is None:
        self.rear = None
    print(value, "deleted from queue.")
```

```
# Peek operation
def peek(self):
    if self.front is None:
        print("Queue is empty.")
    else:
        print("Front element:", self.front.data)
# Display operation
def display(self):
    if self.front is None:
        print("Queue is empty.")
        return
    current = self.front
    print("Queue elements:", end=" ")
    while current is not None:
        print(current.data, end=" ")
       current = current.next
    print()

queue = Queue()

while True:

print("\n----- QUEUE USING LINKED LIST -----")

print("1. Enqueue")

print("2. Dequeue")

print("3. Peek")

print("4. Display")

print("5. Exit")

choice = int(input("Enter your choice: "))

if choice == 1:
    value = int(input("Enter element to enqueue: "))
    queue.enqueue(value)
```

```
elif choice == 2:
    queue.dequeue()

elif choice == 3:
    queue.peek()

elif choice == 4:
    queue.display()

elif choice == 5:
    print("Program terminated.")
    break

else:
    print("Invalid choice! Please try again.")
```

Output:

```
============ RESTART: C:/Users/Divya/OneDrive/Documents/DSA/lab7b.py =======

----- QUEUE USING LINKED LIST -----
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Exit
Enter your choice: 1
Enter element to enqueue: 65
65 inserted into queue.

----- QUEUE USING LINKED LIST -----
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Exit
Enter your choice: 1
Enter element to enqueue: 787
787 inserted into queue.

----- QUEUE USING LINKED LIST -----
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Exit
Enter your choice: 1
Enter element to enqueue: 987
987 inserted into queue.

----- QUEUE USING LINKED LIST -----
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Exit
Enter your choice: 1857
```

```
Edit  Shell  Debug  Options  Window  Help
5. Exit
Enter your choice: 1857
Invalid choice! Please try again.

----- QUEUE USING LINKED LIST -----
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Exit
Enter your choice: 2
65 deleted from queue.

----- QUEUE USING LINKED LIST -----
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Exit
Enter your choice: 3
Front element: 787

----- QUEUE USING LINKED LIST -----
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Exit
Enter your choice: 4
Queue elements: 787 987

----- QUEUE USING LINKED LIST -----
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Exit
Enter your choice: 5
Program terminated.
```

Explanation:

A **linked-list queue** consists of dynamically created nodes. Each node contains two parts:

Two pointers are maintained:

- **Front:** Points to the first node.
- **Rear:** Points to the last node.

Error table:

S.No	Error	Rectification
1	After deleting the last node, `rear` may still point to the deleted node.	If `front` becomes `None`, set `self.rear = None`.
2	Displaying the linked list without moving to the next node can create an infinite loop.	Use `current = current.next` inside the display loop.

3.Aim: Write a Python program to implement a **queue** and its operations such as **Enqueue, Dequeue, Peek, Display** with a **menu-driven approach**. Implement using **Circular Queue Arrays structures**.

Program:

```
#Circular Queue Implementation using Array

#Operations: Enqueue, Dequeue, Peek, Display

MAX_SIZE = 5

queue = [None] * MAX_SIZE

front = -1

rear = -1

while True:

print("\n----- CIRCULAR QUEUE -----")

print("1. Enqueue")

print("2. Dequeue")

print("3. Peek")

print("4. Display")

print("5. Exit")

  choice = int(input("Enter your choice: "))

  # Enqueue
  if choice == 1:

     # Check whether queue is full
     if (rear + 1) % MAX_SIZE == front:
        print("Queue Overflow! Circular Queue is full.")

     else:
        value = int(input("Enter element to enqueue: "))
```

```
 # First element
        if front == -1:
            front = 0
            rear = 0
        else:
            rear = (rear + 1) % MAX_SIZE
        queue[rear] = value
        print(value, "inserted into circular queue.")

# Dequeue
elif choice == 2:

    if front == -1:
        print("Queue Underflow! Circular Queue is empty.")
    else:
        value = queue[front]
        print(value, "deleted from circular queue.")
        # Only one element was present
        if front == rear:
            front = -1
            rear = -1
        else:
            front = (front + 1) % MAX_SIZE
# Peek
elif choice == 3:

    if front == -1:
        print("Queue is empty.")
    else:
        print("Front element:", queue[front])
# Display
elif choice == 4:
    if front == -1:
        print("Queue is empty.")
    else:
        print("Circular Queue elements:", end=" ")
        i = front
```

```
while True:
        print(queue[i], end=" ")
        if i == rear:
            break

        i = (i + 1) % MAX_SIZE
    print()
# Exit
elif choice == 5:
    print("Program terminated.")
    break

else:
    print("Invalid choice! Please try again.")
```

Output:

```
========== RESTART: C:/Users/Divya/OneDrive/Documents/DSA/lab7c.py =====

----- CIRCULAR QUEUE -----
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Exit
Enter your choice: 1
Enter element to enqueue: 46
46 inserted into circular queue.

----- CIRCULAR QUEUE -----
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Exit
Enter your choice: 1
Enter element to enqueue: 87
87 inserted into circular queue.

----- CIRCULAR QUEUE -----
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Exit
Enter your choice: 1
Enter element to enqueue: 8756
8756 inserted into circular queue.

----- CIRCULAR QUEUE -----
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Exit
Enter your choice: 1786
Invalid choice! Please try again.
```

```
5. Exit
Enter your choice: 1786
Invalid choice! Please try again.

----- CIRCULAR QUEUE -----
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Exit
Enter your choice: 2
46 deleted from circular queue.

----- CIRCULAR QUEUE -----
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Exit
Enter your choice: 3
Front element: 87

----- CIRCULAR QUEUE -----
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Exit
Enter your choice: 4
Circular Queue elements: 87 8756

----- CIRCULAR QUEUE -----
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Exit
Enter your choice: 5
Program terminated.
```

Explanation:

A **circular queue** is a queue in which the last position is connected back to the first position.

Unlike a normal linear queue, a circular queue can **reuse empty positions** created after dequeue operations.

Error table:

S.No	Error	Rectification
1	Using `rear + 1` without `% MAX_SIZE` can make the rear go outside the array.	Use `rear = (rear + 1) % MAX_SIZE`.
2	Not resetting both pointers after deleting the last element can leave the queue in an incorrect state.	When `front == rear`, set both `front = -1` and `rear = -1`.

4.Aim: Write a Python program to implement a **queue** and its operations such as **Enqueue, Dequeue, Peek, Display** with a **menu-driven approach**. Implement using **Circular Queue linked-list data structures**.

Program:

```
#Circular Queue using Singly Linked List

#Operations: Enqueue, Dequeue, Peek, Display

class Node:

  def init(self, data):

     self.data = data

      self.next = None

class CircularQueue:

  def init(self):

     self.rear = None



  # Enqueue operation
  def enqueue(self, data):
     new_node = Node(data)
     # Queue is empty
     if self.rear is None:
        self.rear = new_node
        self.rear.next = self.rear
     else:
        # New node is inserted after rear
        new_node.next = self.rear.next
        self.rear.next = new_node
        self.rear = new_node

     print(data, "inserted into circular queue.")
```

```
# Dequeue operation
def dequeue(self):
    if self.rear is None:
        print("Queue Underflow! Queue is empty.")
        return

    # Front node
    front = self.rear.next

    # Only one node
    if self.rear == front:
        self.rear = None

    else:
        self.rear.next = front.next

    print(front.data, "deleted from circular queue.")
# Peek operation
def peek(self):
    if self.rear is None:
        print("Queue is empty.")
    else:
        print("Front element:", self.rear.next.data)
# Display operation
def display(self):
    if self.rear is None:
        print("Queue is empty.")
        return

    front = self.rear.next
    current = front
    print("Circular Queue elements:", end=" ")
    while True:
        print(current.data, end=" ")
        current = current.next
        if current == front:
            break
    print()
```

```
#Create circular queue

queue = CircularQueue()

Menu-driven program

while True:

print("\n----- CIRCULAR QUEUE USING SINGLY LINKED LIST -----")

print("1. Enqueue")

print("2. Dequeue")

print("3. Peek")

print("4. Display")

print("5. Exit")
```

```
choice = int(input("Enter your choice: "))

if choice == 1:
    value = int(input("Enter element to enqueue: "))
    queue.enqueue(value)
elif choice == 2:
    queue.dequeue()
elif choice == 3:
    queue.peek()
elif choice == 4:
    queue.display()
elif choice == 5:
    print("Program terminated.")
    break
else:
    print("Invalid choice! Please try again.")
```

Output:

```
============ RESTART: C:/Users/Divya/OneDrive/Documents/DSA/lab7d.py =====

----- CIRCULAR QUEUE USING SINGLY LINKED LIST -----
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Exit
Enter your choice: 1
Enter element to enqueue: 67
67 inserted into circular queue.

----- CIRCULAR QUEUE USING SINGLY LINKED LIST -----
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Exit
Enter your choice: 1
Enter element to enqueue: 897
897 inserted into circular queue.

----- CIRCULAR QUEUE USING SINGLY LINKED LIST -----
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Exit
Enter your choice: 1768
Invalid choice! Please try again.

----- CIRCULAR QUEUE USING SINGLY LINKED LIST -----
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Exit
Enter your choice: 187
Invalid choice! Please try again.
```

```
Edit  Shell  Debug  Options  Window  Help
5. Exit
Enter your choice: 187
Invalid choice! Please try again.

----- CIRCULAR QUEUE USING SINGLY LINKED LIST -----
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Exit
Enter your choice: 2
67 deleted from circular queue.

----- CIRCULAR QUEUE USING SINGLY LINKED LIST -----
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Exit
Enter your choice: 3
Front element: 897

----- CIRCULAR QUEUE USING SINGLY LINKED LIST -----
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Exit
Enter your choice: 4
Circular Queue elements: 897

----- CIRCULAR QUEUE USING SINGLY LINKED LIST -----
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Exit
Enter your choice: 5
Program terminated.
```

Explanation:

data → stores the element.

next → stores the address/reference of the next node.

This inserts the new node at the **rear** while maintaining the circular connection.

Error table:

S.No	Error	Rectification
1	Setting `rear.next = None` breaks the circular connection.	Set `rear.next = front` so the last node points to the first node.
2	Not setting `rear = None` when the only node is deleted leaves an invalid queue.	If `rear == front`, set `rear = None`.