

GE23131-Programming Using C-2024

Quiz navigation

1

2

3

Show one page at a time


Finish review

Status	Finished
Started	Monday, 23 December 2024, 5:33 PM
Completed	Friday, 13 December 2024, 6:17 PM
Duration	9 days 23 hours

Question **1**

Correct

Marked out of 3.00

 [Flag question](#)

A set of N numbers (separated by one space) is passed as input to the program. The program must identify the count of numbers where the number is odd number.

Input Format:

The first line will contain the N numbers separated by one space.

Boundary Conditions:

$3 \leq N \leq 50$

The value of the numbers can be from -99999999 to 99999999

Output Format:

The count of numbers where the numbers are odd numbers.

Input:

5 10 15 20 25 30 35 40 45 50

Output:

5

Explanation:

The numbers meeting the criteria are 5, 15, 25, 35, 45.

Answer: (penalty regime: 0 %)

```
1 #include <stdio.h>
2 int main()
3 {
4     int n,x=0;
5     while(scanf("%d",&n)==1){
6         if(n%2!=0){
7             x++;}}
8     printf("%d",x);
9     return 0;
10
11 }
```

	Input	Expected	Got	
✓	5 10 15 20 25 30 35 40 45 50	5	5	✓

Passed all tests! ✓

Question **2**

Correct

Marked out of
5.00

🚩 [Flag question](#)

Given a number N, return true if and only if it is a *confusing number*, which satisfies the following condition: //

We can rotate digits by 180 degrees to form new digits. When 0, 1, 6, 8, 9 are rotated 180 degrees, they become 0, 1, 9, 8, 6 respectively. When 2, 3, 4, 5 and 7 are rotated 180 degrees, they become invalid. A *confusing number* is a number that when rotated 180 degrees becomes a **different** number with each digit valid.

Example 1:

6 -> 9

Input: 6

Output: true

Explanation:

We get 9 after rotating 6, 9 is a valid number and 9!=6.

Input: 89

Output: true

Explanation:

We get 68 after rotating 89, 86 is a valid number and $86 \neq 89$.

Example 3:

11 -> 11

Input: 11

Output: false

Explanation:

We get 11 after rotating 11, 11 is a valid number but the value remains the same, thus 11 is not a confusing number.

Note:

1. $0 \leq N \leq 10^9$
2. After the rotation we can ignore leading zeros, for example if after rotation we have 0008 then this number is considered as just 8.

Answer: (penalty regime: 0 %)

```

1  #include <stdio.h>
2  int main()
3  {
4      int n,x,y=1;
5      scanf("%d",&n);
6      while(n!=0&&y==1){
7          x=n%10;n=n/10;
8          if(x==2 || x==3 || x==4 || x==7){

```

```
12     }
13     else
14     {
15         printf("false");
16     }
17 }
```


	Input	Expected	Got	
✓	6	true	true	✓
✓	89	true	true	✓
✓	25	false	false	✓

Passed all tests! ✓

Question **3**

Correct

Marked out of 7.00

 [Flag question](#)

A nutritionist is labeling all the best power foods in the market. Every food item arranged in a single line, will have a value beginning from 1 and increasing by 1 for each, until all items have a value associated with them. An item's value is the same as the number of macronutrients it has. For example, food item with value 1 has 1 macronutrient, food item with value 2 has 2 macronutrients, and incrementing in this fashion.

The nutritionist has to recommend the best combination to patients, i.e. maximum total of macronutrients. However, the nutritionist must avoid prescribing a particular

macronutrients that can be prescribed to a patient, without the sum matching the given 'unhealthy' number.

Here's an illustration:

Given 4 food items (hence value: 1,2,3 and 4), and the unhealthy sum being 6 macronutrients, on choosing items 1, 2, 3 -> the sum is 6, which matches the 'unhealthy' sum. Hence, one of the three needs to be skipped. Thus, the best combination is from among:

- $2 + 3 + 4 = 9$
- $1 + 3 + 4 = 8$
- $1 + 2 + 4 = 7$

Since $2 + 3 + 4 = 9$, allows for maximum number of macronutrients, 9 is the right answer.

Complete the code in the editor below. It must return an integer that represents the maximum total of macronutrients, modulo 1000000007 ($10^9 + 7$).

It has the following:

n : an integer that denotes the number of food items

k : an integer that denotes the unhealthy number

Constraints

- $1 \leq n \leq 2 \times 10^9$
- $1 \leq k \leq 4 \times 10^{15}$

The first line contains an integer, n , that denotes the number of food items.

The second line contains an integer, k , that denotes the unhealthy number.

Sample Input 0

2

2

Sample Output 0

3

Explanation 0

The following sequence of $n = 2$ food items:

1. Item 1 has 1 macronutrients.
2. $1 + 2 = 3$; observe that this is the max total, and having avoided having exactly $k = 2$ macronutrients.

Sample Input 1

2

Sample Output 1

2

Explanation 1

- 1. Cannot use item 1 because $k = 1$ and $sum \equiv k$ has to be avoided at any time.
- 2. Hence, max total is achieved by $sum = 0 + 2 = 2$.

Sample Case 2

Sample Input For Custom Testing

Sample Input 2

3

3

Sample Output 2

5

Explanation 2

Answer: (penalty regime: 0 %)

```
1 #include <stdio.h>
2 int main()
3 {
4     long long int n,t,i,nut=0;
5     scanf("%lld %lld",&n,&t);
6     for(i=1;i<=n;i++){
7         nut=nut+i;
8         if(nut==t){
9             nut = nut-1;
10        }
11    }
12    printf("%lld",nut%1000000007);
13    return 0;
14 }
```

	Input	Expected	Got	
✓	2 2	3	3	✓
✓	2 1	2	2	✓
✓	3 3	5	5	✓

Finish review