

Problem

Submissions

Leaderboard

Discussions

Editorial

hackerank.com/challenges/diagonal-difference/problem?isFullScreen=true

Ask Gemini

School

HackerRank

Prepare Algorithms Warmup Diagonal Difference

Exit Full Screen View

Given a square matrix, calculate the absolute difference between the sums of its diagonals.
For example, the square matrix `arr` is shown below:

```
1 2 3
4 5 6
9 8 9
```

- The left-to-right diagonal = $1 + 5 + 9 = 15$.
- The right-to-left diagonal = $3 + 5 + 9 = 17$.

Their absolute difference is $|15 - 17| = 2$.

Function description

Complete the `diagonalDifference` function with the following parameter:

- `int arr[n][m]`: a 2-D array of integers

Return

- `int`: the absolute difference in sums along the diagonals

Input Format

The first line contains a single integer, `n`, the number of rows and columns in the square matrix `arr`.
Each of the next `n` lines describes a row, `arr[i]`, and consists of `n` space-separated integers `arr[i][j]`.

Constraints

- $-100 \leq arr[i][j] \leq 100$

Sample Input

STDIN	Function
3	<code>arr</code> sizes <code>n = 3</code> , <code>m = 3</code>
11 2 4	<code>arr = [[11, 2, 4], [4, 5, 6], [10, 8, -12]]</code>

```
38 result = diagonalDifference(arr)
39
40 fptr.write(str(result) + '\n')
41
42 fptr.close()
43
```

Upload Code as File

Test against custom input

Run Code

Submit Code

Congratulations!

You have passed the sample test cases. Click the submit button to run your code against all the test cases.

Sample Test case 0

Input (stdin)

Download

```
1 3
2 11 2 4
3 4 5 6
4 10 8 -12
```

Your Output (stdout)

Download

```
1 15
```

Expected Output

Download

```
1 15
```

Type here to search

30°C Sunny

09:13 12-08-2026

You are signed in as VTU28432

(S) WhatsApp

Lapindromes Practice Coding F

Halves Are Alike Java

Ask Gemini

codechef.com/problems/LAPIN

Ask Google

School

Difficulty: 1159

Expand

Prev Problem

Next Problem

Statement

Hints

Submissions

Solution

Help

two halves **ga** and **ga** have the same characters with same frequency. Also, **abccab**, **rotor** and **xyzxy** are a few examples of lapindromes. Note that **abbaab** is NOT a lapindrome. The two halves contain the same characters but their frequencies do not match.

Your task is simple. Given a string, you need to tell if it is a lapindrome.

Input:

First line of input contains a single integer **T**, the number of test cases.

Each test is a single line containing a string **S** composed of only lowercase English alphabet.

Output:

For each test case, output on a separate line: "YES" if the string is a lapindrome and "NO" if it is not.

Constraints:

- $1 \leq T \leq 100$
- $2 \leq |S| \leq 1000$, where $|S|$ denotes the length of **S**

Sample 1:

Input	Output
6	YES
gaga	NO
abcde	YES
rotor	YES
xyzxy	NO
abbaab	NO
ababc	

Did you like the problem statement?
134 users found this helpful

Python3

Test against Custom Input

6
gaga
abcde
rotor

Status : Successfully executed

Time: 0.0100 secs
Memory: 9.184 Mb

Sample Input
6
gaga
abcde
rotor
xyzxy
abbaab
ababc

Your Output
YES
NO
YES
YES
NO
NO

Visualize Code

Run

Submit

Type here to search

32°C Partly sunny

ENG

11:46
11-08-2026

1704. Determine if String Halves Are Alike

Easy

Topics

Companies

Hint

You are given a string `s` of even length. Split this string into two halves of equal lengths, and let `a` be the first half and `b` be the second half.

Two strings are **alike** if they have the same number of vowels ('a', 'e', 'i', 'o', 'u', 'A', 'E', 'I', 'O', 'U'). Notice that `s` contains uppercase and lowercase letters.

Return `true` if `a` and `b` are **alike**. Otherwise, return `false`.

Example 1:

Input: `s = "book"`
Output: `true`
Explanation: `a = "bo"` and `b = "ok"`. `a` has 1 vowel and `b` has 1 vowel. Therefore, they are alike.

Example 2:

Input: `s = "textbook"`
Output: `false`
Explanation: `a = "text"` and `b = "book"`. `a` has 1 vowel whereas `b` has 2. Therefore, they are not alike.
Notice that the vowel `o` is counted twice.

Constraints:

- `2 <= s.length <= 1000`

2.3K

108

11 Online

Code

```
1 class Solution:
2     def halvesAreAlike(self, s):
3         vowels = "aeiouAEIOU"
4         mid = len(s) // 2
5
6         first_half = s[:mid]
7         second_half = s[mid:]
8
9
10        count_first = sum(1 for ch in first_half if ch in vowels)
11        count_second = sum(1 for ch in second_half if ch in vowels)
12
13        return count_first == count_second
```

Saved

Ln 1, Col 1

Testcase

Test Result

Accepted Runtime: 0 ms

Case 1

Case 2

Input

```
s =
"book"
```

Output

```
true
```

Expected

```
true
```

Problem

Submissions

Leaderboard

Discussions

Editorial

hackerank.com/challenges/time-conversion/problem?isFullScreen=true

HackerRank

PrepareAlgorithmsWarmupTime Conversion

Exit Full Screen View

Given a time in 12-hour AM/PM format, convert it to military (24-hour) time.

Notes: - 12:00:00AM on a 12-hour clock is 00:00:00 on a 24-hour clock.
- 12:00:00PM on a 12-hour clock is 12:00:00 on a 24-hour clock.

Example

• s = "12:01:00PM"

Return "12:01:00".

• s = "12:01:00AM"

Return "00:01:00".

Function Description

Complete the `timeConversion` function with the following parameter(s):

• `string s`: a time in 12 hour format

Returns

• `string`: the time in 24 hour format

Input Format

A single string `s` that represents a time in 12-hour clock format (i.e.: hh:mm:ssAM or hh:mm:ssPM).

Constraints

• All input times are valid

Sample Input 0

07:05:45PM

Sample Output 0

19:05:45

10

11

12

13

14

15

16

17

18

19

```
11 hour -= 12;
    hour += 12;

    return f"{hour:02d}:{rest}"

s = input().strip()
print(timeConversion(s))
```

Upload Code as File

☐ Test against custom input

Run Code

Submit Code

Congratulations!

You have passed the sample test cases. Click the submit button to run your code against all the test cases.

Sample Test case 0

Input (stdin)

07:05:45PM

Download

Type here to search

32°C Partly sunny

12:27
11-08-2026

You are signed in as VTU284

(5) WhatsApp

Compare the Triplets | HackerRank

Lapindromes Practice Coding

Halves Are Alike Java

Ask Gemini

hackerrank.com/challenges/compare-the-triplets/problem?isFullScreen=true

HackerRank

PrepareAlgorithmsWarmupCompare the Triplets

Exit Full Screen View

Problem

Submissions

Leader Board

Discussions

Editorial

Alice and Bob each created one problem for HackerRank. A reviewer rates the two challenges, awarding points on a scale from 1 to 100 for three categories: problem clarity, originality, and difficulty.

The rating for Alice's challenge is the triplet $a = [a[0], a[1], a[2]]$, and the rating for Bob's challenge is the triplet $b = [b[0], b[1], b[2]]$.

The task is to calculate their comparison points by comparing each category:

- If $a[i] > b[i]$, then Alice is awarded 1 point.
- If $a[i] < b[i]$, then Bob is awarded 1 point.
- If $a[i] = b[i]$, then neither person receives a point.

Example

$a = [1, 2, 3]$
 $b = [3, 2, 1]$

- For elements $a[0]$, Bob is awarded a point because $a[0] < b[0]$.
- For the equal elements $a[1]$ and $b[1]$, no points are earned.
- Finally, for elements $a[2]$, $a[2] > b[2]$ so Alice receives a point.

The return array is $[1, 1]$ with Alice's score first and Bob's second.

Function Description

Complete the function `compareTriplets` with the following parameter(s):

- `int a[3]`: Alice's challenge rating
- `int b[3]`: Bob's challenge rating

Returns

- `int[2]`: the first element is Alice's score and the second is Bob's score

Input Format

The first line contains 3 space-separated integers, $a[0]$, $a[1]$, and $a[2]$, the respective values in triplet a .

The second line contains 3 space-separated integers, $b[0]$, $b[1]$, and $b[2]$, the respective values in triplet b .

Constraints

- $1 \leq a[i] \leq 100$
- $1 \leq b[i] \leq 100$

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

```
for i in range(3):
    if a[i] > b[i]:
        alice += 1
    elif a[i] < b[i]:
        bob += 1

return [alice, bob]

a = list(map(int, input().split()))
b = list(map(int, input().split()))

result = compareTriplets(a, b)

print(result[0], result[1])
```

Line: 20 Col: 1

Upload Code as File

☐ Test against custom input

Run Code

Submit Code

Congratulations!

You have passed the sample test cases. Click the submit button to run your code against all the test cases.

Type here to search

ENG 11:55 11-08-2026

Matrix Block Sum

Transpose Matrix

Diagonal Difference

Move Zeroes - I

Move Zeroes - II

Move Zeroes In-Place

Ask Gemini

leetcode.com/problems/matrix-block-sum/

Problem List

Submit

Run

Ctrl

Editorial

Solutions

Submissions

Medium

Topics

Companies

Hint

Given a $m \times n$ matrix `mat` and an integer `k`, return a matrix `answer` where each `answer[i][j]` is the sum of all elements `mat[r][c]` for:

- $i - k \leq r \leq i + k$,
- $j - k \leq c \leq j + k$, and
- (r, c) is a valid position in the matrix.

Example 1:

Input: `mat = [[1,2,3],[4,5,6],[7,8,9]]`, `k = 1`
Output: `[[12,21,16],[27,45,33],[24,39,28]]`

Example 2:

Input: `mat = [[1,2,3],[4,5,6],[7,8,9]]`, `k = 2`
Output: `[[45,45,45],[45,45,45],[45,45,45]]`

Constraints:

- $m == \text{mat.length}$
- $n == \text{mat}[i].\text{length}$
- $1 \leq m, n, k \leq 100$

2.5K 51 8 Online

Code

Python

Auto

```
5  m = len(mat)
6
7  answer = [[0] * n for _ in range(m)]
8
9  for i in range(m):
10     for j in range(n):
11         for r in range(max(0, i - k), min(m, i + k + 1)):
12             for c in range(max(0, j - k), min(n, j + k + 1)):
13                 answer[i][j] += mat[r][c]
14
15 return answer
```

Saved

Ln 14, Col 22

Testcase

Test Result

Accepted

Runtime: 0 ms

Case 1

Case 2

Input

mat =

[[1,2,3],[4,5,6],[7,8,9]]

k =

1

Output

Type here to search

AIRTELPP -1.95%

ENG

09:19

12-08-2026

Problem

Submissions

Leaderboards

Discussions

Editorial

28 27 26 25
22 9 15 19
16 8 21 13
10 14 20 7
4 3 2 1

Explanation #2

The various states through 7 rotations:

1 2 3 4	2 3 4 10	3 4 10 16	4 10 16 22
7 8 9 10	1 9 15 16	2 15 21 22	3 21 28 28
13 14 15 16 ->	7 8 21 22 ->	1 9 20 28 ->	2 15 14 27 ->
19 20 21 22	13 14 20 28	7 8 14 27	1 9 8 26
25 26 27 28	19 25 26 27	13 19 25 26	7 13 19 25
10 16 22 28	16 22 28 27	22 28 27 26	28 27 26 25
4 20 14 27	10 14 8 26	16 8 9 25	22 9 15 19
3 21 8 26 ->	4 20 9 25 ->	10 14 15 19 ->	16 8 21 13
2 15 9 25	3 21 15 19	4 20 21 13	10 14 20 7
1 7 13 19	2 1 7 13	3 2 1 7	4 3 2 1

Sample Input #03

2 2 3
1 1
1 1

Sample Output #03

1 1
1 1

Explanation #03

All of the elements are the same, so any rotation will repeat the same matrix.

35
36
37
38
39

Bottom row: Right to left
for j in range(n - layer - 2, layer - 1, -1):
 elements.append(matrix[m - layer - 1][j])

Left column: bottom to top
for i in range(m - layer - 2, layer, -1):

Upload Code as File

Test against custom input

Run Code

Submit Code

Congratulations!

You have passed the sample test cases. Click the submit button to run your code against all the test cases.

Sample Test case 0

Sample Test case 1

Sample Test case 2

Sample Test case 3

Input (stdin)

1 4 4 1
2 1 2 3 4
3 5 6 7 8
4 9 10 11 12
5 13 14 15 16

Download

Your Output (stdout)

1 2 3 4 8
2 1 7 11 12
3 5 6 10 16
4 9 13 14 15

hackerank.com/challenges/matrix-rotation-algo/problem?isFullScreen=true

Ask Gemini

School

Type here to search

Humid

ENG

09:24
12-08-2026