

NAME: SIDDHANT

ROLL NO: 1906589

SUBJECT: CN LAB 24.08.21

CN LAB

QUES: WAP to implement an UDP Socket through which client will send few commands to the server.

SOL: #server.c

```
/*  
** A datagram sockets "server" demo  
*/  
#include <stdio.h>  
#include <stdlib.h>  
#include <unistd.h>  
#include <errno.h>  
#include <string.h>  
#include <sys/types.h>
```

```
#include <sys/socket.h>
#include <netinet/in.h>
#include <arpa/inet.h>
#include <dirent.h>
#define MYPORT 4952 // the port users will be connecting to
#define MAXBUFLLEN 200
int main()
{
    int sockfd;
    struct sockaddr_in my_addr; // my address information
    struct sockaddr_in their_addr; // connector's address information
    socklen_t addr_len;
    DIR *d;
    struct dirent *dir;
    int numbytes;
    char buf[MAXBUFLLEN], buf1[MAXBUFLLEN];
    if ((sockfd = socket(AF_INET, SOCK_DGRAM, 0)) == -1) {
        perror("socket");
        exit(1);
    }
```

```
}  
my_addr.sin_family = AF_INET; // host byte order  
my_addr.sin_port = htons(MYPORT); // short, network byte order  
my_addr.sin_addr.s_addr = INADDR_ANY; // automatically fill with my IP  
//memset(my_addr.sin_zero, '\0', sizeof my_addr.sin_zero);  
if (bind(sockfd, (struct sockaddr *)&my_addr, sizeof my_addr) == -1) {  
    perror("bind");  
    exit(1);  
}  
addr_len = sizeof their_addr;  
if ((numbytes = recvfrom(sockfd, buf, MAXBUFLen-1 , 0,  
    (struct sockaddr *)&their_addr, &addr_len)) == -1) {  
    perror("recvfrom");  
    exit(1);  
}  
char abc[10000];  
strcpy(abc, "/home/user/CN_LAB/");  
strcat(abc, buf);  
char mn[10];
```

```
strcpy(mn,"exit");
d= opendir(abc);
if(d)
{
while((dir=readdir(d))!=NULL)
printf("%s\n",dir->d_name);
closedir(d);
}
/*printf("got packet from %s\n",inet_ntoa(their_addr.sin_addr));
printf("packet is %d bytes long\n",numbytes);
buf[numbytes] = '\0';
printf("packet contains \"%s\"\n",buf);*/
recvfrom(sockfd, buf1, MAXBUFLen-1 , 0,
(struct sockaddr *)&their_addr, &addr_len);
FILE *fp;
char ch;
fp=fopen(buf1,"r");
while(1)
{
```

```
ch=fgetc(fp);
if(ch==EOF)
    break;
printf("%c",ch);
}
fclose(fp);
close(sockfd);
return 0;
}
```

#client.c

```
/*
** A datagram "client" demo
*/
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <errno.h>
#include <string.h>
```

```
#include <sys/types.h>
#include <sys/socket.h>
#include <netinet/in.h>
#include <arpa/inet.h>
#include <netdb.h>
#define SERVERPORT 4952 // the port users will be connecting to
int main()
{
    int sockfd;
    struct sockaddr_in their_addr; // connector's address information
    //struct hostent *he;
    int numbytes;
    char arg[30];
    if ((sockfd = socket(AF_INET, SOCK_DGRAM, 0)) == -1) {
        perror("socket");
        exit(1);
    }
    their_addr.sin_family = AF_INET; // host byte order
    their_addr.sin_port = htons(SERVERPORT); // short, network byte order
```


```
their_addr.sin_addr.s_addr = inet_addr("127.0.0.1");
//memset(their_addr.sin_zero, '\0', sizeof their_addr.sin_zero);
//addr_len = sizeof their_addr;
printf("Enter the folder name\n");
scanf("%s",arg);
if ((numbytes = sendto(sockfd, arg, strlen(arg), 0,
(struct sockaddr *)&their_addr, sizeof their_addr)) == -1) {
perror("sendto");
exit(1);
}
/*while(1)
{
recvfrom(sockfd, buf, MAXBUFLen-1 , 0,
(struct sockaddr *)&their_addr, &addr_len);
if(strcmp(buf,"exit")==0)
break;
else
printf("%s\n",buf);
}*/
```

```

//printf("sent %d bytes to %s\n", numbytes, inet_ntoa(their_addr.sin_addr));
printf("\nEnter the file name with extension\n");
scanf("%s",arg);
sendto(sockfd, arg, strlen(arg), 0,
(struct sockaddr *)&their_addr, sizeof their_addr);
close(sockfd);
return 0;
}

```

OUTPUT:



```

client
hi hello how are you?

server
VirtualBox:~/CN_LAB/LAB_7$ gcc 1s.c -o se
LAB_7
VirtualBox:~/CN_LAB/LAB_7$ ./server
Enter the folder name
LAB_7
Enter the file name with extension
file.txt
VirtualBox:~/CN_LAB/LAB_7$
a.out
..
1c.c
client
hi hello how are you?

```