

MATLAB SYNTAX TIPS

There are many ways to read data into files here are a few:

Contents

- File input as a matrix
- File input as a table (a mixed-type) matrix:
- Logical indexing

File input as a matrix

```
items = importdata('items.csv')
```

```
items =
```

```
      data: [22x2 double]  
    textdata: {23x3 cell}
```

```
items.data
```

```
ans =
```

```
     9    150  
    13     35  
   153    200  
    50    160  
    15     60  
    68     45  
    27     60  
    39     40  
    23     30  
    52     10  
    11     70  
    32     30  
    24     15  
    48     10  
    73     40  
    42     70  
    43     75  
    22     80  
     7     20  
    18     12
```

```

4      50
30     10

```

```
items.textdata
```

```
ans =
```

'item'	'weight'	'value'
'map'	''	''
'compass'	''	''
'water'	''	''
'sandwich'	''	''
'glucose'	''	''
'tin'	''	''
'banana'	''	''
'apple'	''	''
'cheese'	''	''
'beer'	''	''
'suntan cream'	''	''
'camera'	''	''
'T-shirt'	''	''
'trousers'	''	''
'umbrella'	''	''
'waterproof trousers'	''	''
'waterproof overcl...	''	''
'note-case'	''	''
'sunglasses'	''	''
'towel'	''	''
'socks'	''	''
'book'	''	''

```
weight = items.data(:,1)
```

```
weight =
```

```

9
13
153
50
15
68

```

27
39
23
52
11
32
24
48
73
42
43
22
7
18
4
30

File input as a table (a mixed-type) matrix:

```
items = readtable('items.csv')
```

```
items =
```

item	weight	value
-----	-----	-----
'map'	9	150
'compass'	13	35
'water'	153	200
'sandwich'	50	160
'glucose'	15	60
'tin'	68	45
'banana'	27	60
'apple'	39	40
'cheese'	23	30
'beer'	52	10
'suntan cream'	11	70
'camera'	32	30
'T-shirt'	24	15
'trousers'	48	10
'umbrella'	73	40
'waterproof trousers'	42	70
'waterproof overclothes'	43	75
'note-case'	22	80

'sunglasses'	7	20
'towel'	18	12
'socks'	4	50
'book'	30	10

Can be accessed like a normal matrix, but returns a table type

```
items([1 2 4],1)
```

```
ans =
```

item

'map'
'compass'
'sandwich'

```
items([1:5],3)
```

```
ans =
```

value

150
35
200
160
60

But called in this way they keep the table type so many functions this don't work, ie ('sum(items([1:5],3))')

Instead used the name of the column rather than the index

```
items.value([1:5])
```

```
ans =
```

```
150
35
200
160
60
```

```
sum(items.value([1:5]))
```

```
ans =
```

```
605
```

Logical indexing

Selecting items in a matrix can be done either with a positive integer index, or with a boolean string

Using the index

```
items.value([1:5])
```

```
ans =
```

```
150
35
200
160
60
```

Using a boolean string

```
selection = false(1,length(items.value)); % create a 1 X length vector of falses
selection(1:2:10) = true % make every other index true up to 10 true
```

```
selection =
```

```
Columns 1 through 13
```

```
1    0    1    0    1    0    1    0    1    0    0    0    0
```

Columns 14 through 22

0 0 0 0 0 0 0 0 0

```
items(selection,:)
```

```
ans =
```

item	weight	value
-----	-----	-----
'map'	9	150
'water'	153	200
'glucose'	15	60
'banana'	27	60
'cheese'	23	30

```
sum(items.value(selection))
```

```
ans =
```

500

NOTE: this has to be a 'logical' index – otherwise Matlab wouldn't know whether you meant 1 as in true or 1 as in the first index

So if you have something like this

```
selection = zeros(1,length(items.value)); % create a 1 X length vector of zeros  
selection(2:2:10) = 1 % make every other index true up to 10 1
```

```
selection =
```

Columns 1 through 13

0 1 0 1 0 1 0 1 0 1 0 0 0

Columns 14 through 22

0 0 0 0 0 0 0 0 0

Be sure to put cast it as a logical

```
sum( items.value( logical(selection) ) )
```

```
ans =
```

```
290
```