Odsek Visoka ICT škola, Akademija tehničko-umetničkih strukovnih studija Beograd

Dokumentacija Bookstore

Smer: Internet tehnologije Modul: Web programiranje

Predmet: Web programiranje PHP 2

Đorđe Solomun 16/19

Contents

1.	Uvod		5
	1.1 Korišo	ćene tehnologije	5
	1.2 Opis f	funkcionalnosti	5
	1.3 Te	emplate	6
2.	Organi	zacija	6
	6		
	2.2 Strukt	tura projekta	7
	2.3 SI	ike stranica i opis funkcionalnosti	9
	2.3.1	Home za korisnike i goste	9
	2.3.2	Shop	10
	2.3.3	Stranica za prikaz jedne knjige	13
	2.3.4	Contact	14
	2.3.5	Register	15
	2.3.6	Login	16
	2.3.7	Author	17
	2.3.8	Cart	17
	2.3.9	Admin home	19
	2.3.10	Admin products	19
	2.3.11	Add new book	20
	2.3.12	Edit book	20
	2.3.13	Admin genres	21
	2.3.14	Add new genre	21
	2.3.15	Edit genre	22
	2.3.16	Admin users	22
3.	Kodovi	i	23
	3.1 Kontr	3.1 Kontroleri	
3.1.1 AdminController			23
	3.1.2 A	24	
	3.1.3 B	25	
	3.1.4 B	26	
	3.1.5 C	artController	29
	3.1.6 C	ontactController	31
	3.1.7 C	ontroller (Laravelov kontroler nije menjan)	32
	3.1.8 GenreController		32
	3.1.9 H	IomeController	33

3.2. Middleware	34
3.2.1 IsAdmin	34
3.2.2 IsGuest	34
3.2.3 IsLoggedIn	35
3.3 Requests	35
3.3.1 BookStoreRequest	35
3.3.2 BookUpdateRequest	36
3.3.3 ContactRequest	37
3.3.4 GenreStoreRequest	38
3.3.5 GenreUpdateRequest	38
3.3.6 LoginRequest	39
3.3.7 RegisterRequest	40
3.4 Models	40
3.4.1 Activity	40
3.4.2 Author	41
3.4.3 Book	41
3.4.4 Contact	41
3.4.5 Genre	41
3.4.6 Role	42
3.4.7 User	42
3.5 Migrations	42
3.5.1 Roles table	42
3.5.2 Users table	43
3.5.3 Genres table	44
3.5.4 Authors table	44
3.5.5 Books table	45
3.5.6 Author_book table	45
3.5.7 Contacts table	46
3.5.8 Activities table	46
3.6. Seeders	47
3.6.1 BookSeeder	47
3.6.2 DatabaseSeeder	63
3.6.3 GenreSeeder	63
3.6.4 RoleSeeder	64
3.6.5 UserSeeder	64
3.7 Views	65

3.7.1 Fixed	65
3.7.2 Layouts	68
3.7.3 Pages	68
3.8 Routes	
3.8.1 web.php	88
3.9 CSS	89
3.9.1 style.css	89
3.10 JavaScript	93
3.10.1 main.js	93

1. Uvod

1.1 Korišćene tehnologije

- HTML 5
- CSS 3
- JavaScript
- jQuery
- Toastr
- Bootstrap v4.5
- Font Awesome
- Heroku za online bazu
- MySQL Workbench za rad sa bazom
- PHP
- Laravel 8 PHP Framework

Kucano u PhpStorm.

Baza postavljena online na Heroku sajt.

1.2 Opis funkcionalnosti

- Sajt je responsive i prilagođen prikazu na svim ekranima.
- Navigacioni meni je responsive, na manjim rezolucijama se prikazuje hamburger ikonica na koju se klikne da bi se meni proširio. Realizovano bootstrapom.
- Linkovi u navigacionom meniju se menjaju u zavisnosti od toga da li je neko ulogovan i ako je ulogovan da li je običan korisnik ili admin.
- Prodavnica sa proizvodima koji se dinamički ispisuju iz baze, dohvaćeni AJAX-om i ispisani JavaScript-om.
- Elementi za filtriranje po žanru ispisani dinamički podacima iz baze.
- U donjem desnu uglu sajta se pojavljuje dugme za skrol na vrh kada se skroluje 200 pixela na dole.
- Paginacija proizvoda, usklađena sa filtriranjem po žanru, sortiranjem i pretragom po imenu knjige ili imenu autora knjige.
- Slanje poruke na kontakt strani, validacija sa serverske i klijentske strane.
- Registracija korisnika, validacija forme i na klijentskoj i na serverskoj strani.
- Login korisnika, validacija forme i na klijentskoj i na serverskoj strani. Nakon login-a obični korisnici se šalju na početnu stranu sajta za korisnike, a admin se šalje na admin panel.
- Ulogovani korisnik može da dodaje proizvode u korpu. Admin ne može. Realizovano pomoću AJAX-a i Toastr ispisuje adekvatnu poruku o uspehu ili neuspehu.
- Korisnik može da pregleda svoju korpu koja se čuva u sesiji i odatle dinamički ispisuje. Može da menja količinu proizvoda u korpi, da ih briše iz korpe i da poruči. JavaScript i AJAX realizuju ove promene količine i dinamički osvežavaju prikaz ukupne cene i broja proizvoda u korpi. Samo ulogovani korisnici mogu pristupiti stranici za pregled korpe.
- Zapisivanje ključnih događaja kao što su registracija novog korisnika, login, logout, dodavanje u korpu, poručivanje, dodavanje novih proizvoda, menjanje proizvoda, dodavanje žanrova, menjanje žanrova, brisanje korisnika u tabelu u bazi.
- Admin panel sa prikazom svih ključnih aktivnosti od strane korisnika, mogućnost sortiranja po datumu. Prikaz svih proizvoda, žanrova i mogućnost dodavanja novih, menjanja ili brisanja postojećih. Prikaz svih korisnika i mogućnost brisanja korisnika. Prikaz svih poruka koje su poslate sa kontakt strane.
- Admin panelu može da pristupi samo admin, ako običan korisnik pokuša biće redirektovan. Admin može da pristupi korisničkim stranicama, ali ne može da dodaje u korpu i da pristupi stranici za pregled korpe.

Admin stranice i korisničke stranice koriste drugačije layout fajlove.


Sajt treba da realizuje online prodaju knjiga, uz admin panel da admin može da upravlja sadržajem i korisnicima sajta. Korisničke stranice i admin stranice koriste drugačiji layout. Korisnici ne mogu da pristupe stranicama za admina, a admin može da pristupi admin panelu i svim korisničkim stranicama samo nema pristup njihovim funkcionalnostima kao što je dodavanje u korpu i pregled korpe.

1.3 Template


Nije korišćen gotov template, kucan je html,css,js i php kod da bi se realizovao izgled.


2. Organizacija


2.1 Dizajn baze podataka



2.2 Struktura projekta







2.3 Slike stranica i opis funkcionalnosti

2.3.1 Home za korisnike i goste

Navigacioni meni se menja u zavisnosti od toga da li je ulogovan korisnik ili admin. Kad je neko ulogovan pojavljuje se logout dugme pored kojeg piše ime i prezime korisnika. Navigacioni link je obojen ako je ta stranica trenutno aktivna. Na stranici se nalazi statički sadržaj i blok u kome se prikazuju četiri najskorije dodata proizvoda. Ovo je prikaz kada niko nije ulogovan.



AT THE RESERVE OF THE PARTY OF

PC Center


PC Center

and we are always expanding our offer.

Take a look at our book collection: shop



Newest releases










Login Register

Newest releases





Navigacioni meni kada se uloguje korisnik.


Bookstore Home Shop Contact Cart

Navigacioni meni kada se uloguje admin. Ovo je korisničkoj home stranici na stranicama za admina navigacija je drugačija jer te stranice koriste drugi layout.


Bookstore Home Shop Contact Admin panel Marko Markovic Logout

2.3.2 Shop


Prikaz svih knjiga. Mogućnost sortiranja po ceni ili imenu knjige u rastućem i opadajućem poretku. Mogućnost filtriranja po žanru, pretraga po imenu knjige ili imenu autora. Knjige dohvaćene AJAX-om i ispisane kroz JavaScript, filteri i sortiranje se takođe šalju JavaScriptom. Napravljena paginacija kroz JavaScript i usklađena s filtriranjem i sortiranjem tako da se zadrže izabrane vrednosti prilikom promene stranice. Klikom na dugme Add to cart proizvod se dodaje u korpu ako je korisnik ulogovan i dobija Toastr poruku da je uspešno dodato. Ako je admin dobija poruku da ne sme da dodaje, ako je gost, odnosno niko nije ulogovan dobija poruku da mora prvo da se uloguje. Klikom na ime knjige otvara se strana za prikaz informacija o jednoj knjizi. Ukoliko nema proizvoda koji odgovaraju kriterijumima pretrage prikazuje se poruka o tome. Paginacija prikazuje 9 proizvoda po strani.



Primer pokušaja dodavanja u korpu bez logovanja.



Primer filtriranja i pretrage.




2.3.3 Stranica za prikaz jedne knjige

Nema posebnih funkcionalnosti, dodavanje u korpu isto kao na Shop stranici. Prikaz svih podataka o knjizi.





Ovako admin vidi stranicu za prikaz jedne knjige:



2.3.4 Contact


Osnovne kontakt informacije i forma za slanje poruke validirana i na klijentskoj i na serverskoj strani. Ako je neki podatak pogrešno unet ispod polja se ispisuje adekvatna poruka. Ako je sve ispravno uneto i poruka poslata ispisaće se poruka o uspehu.






2.3.5 Register


Forma za registraciju, validirana i sa klijentske i sa serverske strane. Ako je neki podatak pogrešno unet ispod polja se ispisuje adekvatna poruka. Ako je sve ispravno uneto ispisuje se poruka o uspešnoj registraciji i link koji vodi na login stranu. Ulogovani korisnici ne mogu opet doći na stranicu za registraciju.





2.3.6 Login

Forma za login. Validirana i sa klijentske i sa serverske strane. Ako je neki podatak pogrešno unet ispod polja se ispisuje adekvatna poruka. Ako su email ili lozinka pogrešni ispisaće se poruka o tome. Ako je login uspešan korisnici se vraćaju na home, a admin se šalje na admin panel.




2.3.7 Author

Nema posebnih funkcionalnosti. Osnovne informacije o autoru sajta.




2.3.8 Cart


Prikaz svih proizvoda u korisnikovoj korpi, njihova količina i ukupna cena svega u korpi. Ovo je inicijalni prikaz odnosno kada je korpa prazna.



Prikaz kada nešto postoji u korpi. Korpa i njen sadržaj se čuvaju u sesiji i odatle se ispisuju, a funkcionalnost brisanja iz korpe i menjanja količine se postiže AJAX zahtevima i JavaScript ažurira prikaz.




Kada se obriše poslednji proizvod prikaz će se osvežiti i ponovo će pisati poruka da je korpa prazna. Klikom na dugme Checkout korpa će da se isprazni iz sesije i korisnik će dobiti sledeći prikaz.




2.3.9 Admin home

Početna stranica za admina na njoj se nalazi prikaz svih ključnih aktivnosti od strane korisnika u vidu tabele. Urađena paginacija pomoću Laravela, mogućnost sortiranja po datumu u rastućem i opadajućem poretku.




2.3.10 Admin products

Prikaz svih proizvoda sa filtriranjem i sortiranjem. Prikaz, filtriranje i sortiranje su odrađeni kroz Laravel. Dugme za dodavanje novog proizvoda, dugme za edit i brisanje nekog od proizvoda.




2.3.11 Add new book

Forma za unos novog proizvoda. Validirana kroz laravel, sva polja su obavezna i ispod svakog će se ispisati opisna greška ako je nešto pogrešno uneto. Drugi autor nije obavezan. Ako se proizvod uspešno unese admin se šalje na stranicu za prikaz svih proizvoda i tamo dobija poruku o uspešnom unosu. Uneti autor će pokušati da se pronađe u bazi, ukoliko postoji knjiga će se spojiti sa njim, a ako ne postoji biće unet novi autor sa tim imenom i spojiće se sa knjigom.




2.3.12 Edit book

Forma za edit postojećeg proizvoda, već popunjena podacima o tom proizvodu, sva polja osim slike su obavezna. Ako se pošalje i slika stara će biti obrisana, nova upload-ovana i biće promenjen naziv slike u bazi.




2.3.13 Admin genres

Prikaz svih žanrova u vidu tabele. Dugme za dodavanje novog žanra, dugme za edit postojećeg i dugme za brisanje. Brisanje neće biti dozvoljeno ako neke knjige pripadaju tom žanru. Ako se žanr uspešno obriše na ovoj stranici će biti prikazana poruka o uspehu.




2.3.14 Add new genre

Forma za dodavanje novog žanra, ime žanra ne sme da bude ime već postojećeg žanra. Ako je unos uspešan povratak na stranicu sa svim žanrovima sa porukom o uspehu.




2.3.15 Edit genre

Forma za edit žanra popunjena podacima o žanru koji se edituje. Sme da se ostavi isto ime tada se neće validirati da bude jedinstveno u tabeli za žanrove, ali ukoliko se promeni tada se primenjuje validacija i ne sme se uneti ime nekog od postojećih žanrova. Ako je edit uspešan povratak na stranicu sa svim žanrovima sa porukom o uspehu.



2.3.16 Admin users

Prikaz svih korisnika u vidu tabele. Dugme za brisanje korisnika. Kad je brisanje uspešno na ovoj stranici se prikazuje poruka o uspehu.



3.1 Kontroleri

3.1.1 AdminController

```
namespace App\Http\Controllers;
use App\Models\Activity;
use App\Models\Book;
use App\Models\Contact;
use App\Models\Genre;
use App\Models\User;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\Log;
class AdminController extends BaseController
    public function index(Request $request){
        $qs=[];
        $activities = new Activity();
        if($request->has('sortBy')){
            $qs['sort'] = $request->get('sortBy');
            $sort=explode('-',$request->get('sortBy'));
            $activities = $activities->orderBy($sort[0],$sort[1]);
        $this->data['qs'] = $qs;
        $this->data['activities'] = $activities->paginate(9)->withQueryString();
        return view('pages.admin.index', $this->data);
    public function products(Request $request){
        $genres = Genre::with('books')->get();
        qs = [];
        if($request->has('chbGenres') && $request->get('chbGenres')){
            $qs['chbGenres'] = $request->chbGenres;
            $books = $books->whereIn("genre id", $request->get("chbGenres"));
        if($request->has('search') && $request->get('search')){
            $search = $request->search;
            $qs['search'] = $search;
            $books = $books->where(function($q) use ($search){
                $q->whereHas("authors", function($q) use($search){
                    $q->where('name','like',"%".$search."%");
                ->orWhere('book name','like',"%".$search."%");
            });
        if($request->has('sortBy') && $request->get('sortBy')){
            $qs['sortBy'] = $request->get('sortBy');
            $sort = explode("-", $request->get("sortBy"));
            $books = $books->orderBy($sort[0], $sort[1]);
        $this->data['qs'] = $qs;
        $this->data['genres'] = $genres;
        $this->data['books'] = $books->paginate(12)->withQueryString();
        return view('pages.admin.books.products', $this->data);
```

3.1.2 AuthController

```
namespace App\Http\Controllers;
use App\Http\Requests\LoginRequest;
use App\Http\Requests\RegisterRequest;
use App\Models\Activity;
use App\Models\User;
use Illuminate\Support\Facades\Log;
class AuthController extends BaseController
    public function loginForm(){
    public function registerForm() {
    public function login(LoginRequest $request){
        $email = trim($request->tbEmail);
        $pass = md5($request->tbPass);
        $user = User::where('email', $email)
            ->where('password',$pass)
            ->with("role")
            ->first();
        if(!$user){
        Activity::create([
```

```
'user name'=>$user->name
    session()->put("user", $user);
    if($user->role->role name == 'admin'){
        return redirect()->route('admin.home');
        return redirect()->route("home");
public function register(RegisterRequest $request){
    $name = $request->tbName;
    $email = $request->tbEmail;
    $password = md5($request->tbPass);
    $user = new User;
   $user->name = $name;
    $user->email = $email;
    $user->password = $password;
        if($res){
            Activity::create([
                'user name'=>$user->name
            ]);
            return redirect()->back()->with('success','Registered successfully.');
    }catch(\Exception $e){
        Log::error($e->getMessage());
        return redirect()->back()->with('error','There was an error processing your
public function logout(){
        'user name'=>session()->get('user')->name
    ]);
    session()->forget('user');
    return redirect()->route('home');
```

3.1.3 BaseController

```
<?php
namespace App\Http\Controllers;
use Illuminate\Http\Request;
class BaseController extends Controller
{
   public $data;
   public function __construct() {</pre>
```

ı

3.1.4 BookController

```
namespace App\Http\Controllers;
use App\Http\Requests\BookStoreRequest;
use App\Http\Requests\BookUpdateRequest;
use App\Models\Activity;
use App\Models\Author;
use App\Models\Book;
use App\Models\Genre;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\File;
use Illuminate\Support\Facades\Log;
class BookController extends BaseController
       parent:: construct();
        $this->middleware('isAdmin')
            ->only([
            1);
   public function get json(Request $request) {
        if($request->ajax()){
            $books = Book::with('genre')->with('authors');
            if($request->genres){
                $books = $books->whereIn('genre_id', $request->genres);
            if($request->search && !empty($request->search)){
                $search = $request->search;
                $books = $books->where(function($q) use ($search){
                    $q->whereHas("authors", function($q) use($search){
                        $q->where('name','like',"%".$search."%");
                        ->orWhere('book name','like',"%".$search."%");
                });
            if($request->sort){
                $column = explode('-',$request->sort)[0];
                $type = explode('-', $request->sort)[1];
                $books = $books->orderBy($column,$type);
            header('Content-type:application/json');
            echo json encode($books->paginate(12));
            return redirect()->back();
```

```
public function index()
       $genres = Genre::with('books')->get();
       $this->data['genres']=$genres;
      return view('pages.books.index', $this->data);
  public function create()
       $genres = Genre::all();
      $this->data['genres']=$genres;
  public function store(BookStoreRequest $request)
       $title = $request->get('title');
       $author_1 = $request->get('author1');
       if(isset($request->author2)){
           $author 2 = $request->get('author2');
       $price = $request->get('price');
       $publishYear = $request->get('publishYear');
       $description = $request->get('description');
       $genreId = $request->get('genreId');
       $extension = $request->image->extension();
       $imageName = strtolower(implode(' ',explode('
,str_replace(':','',$title)))).'.'.$extension;
       $request->image->move(public path('img/books'), $imageName);
           $book = Book::create([
               'price' => $price,
               'description'=>$description,
               'image'=>$imageName,
               'publish_year'=>$publishYear,
               'genre id'=>$genreId
           $author = Author::firstOrCreate(['name'=>$author 1]);
           array_push($authors,$author->id);
           if(isset($author 2)){
               array push($authors,$author2->id);
           $book->authors()->sync($authors);
           Activity::create([
               'user name'=>session()->get('user')->name
           ]);
           return redirect()->route('admin.products')->with('success','true');
       }catch(\Exception $e){
           Log::error($e->getMessage());
           return redirect()->back()->with("error", $e->getMessage());
  public function show($id)
```

```
$this->data['book'] = Book::with('authors')->with('genre')->find($id);
        return view('pages.books.show',$this->data);
   public function edit($id)
        $genres = Genre::all();
        $this->data['genres']=$genres;
        return view('pages.admin.books.edit',$this->data);
   public function update(BookUpdateRequest $request, $id)
        $title = $request->get('title');
        $author 1 = $request->get('author1');
        if(isset($request->author2)){
            $author 2 = $request->get('author2');
        $price = $request->get('price');
        $publishYear = $request->get('publishYear');
$description = $request->get('description');
        $genreId = $request->get('genreId');
            $book = Book::with('authors')->with('genre')->find($id);
            authors = [];
            $author = Author::firstOrCreate(['name'=>$author 1]);
            array push($authors,$author->id);
                array push($authors,$author2->id);
            $book->price = $price;
            $book->publish year = $publishYear;
            $book->genre id = $genreId;
            $book->description = $description;
            if(isset($request->image)){
                $oldImage = public_path("img/books/{$book->image}");
                if (File::exists($oldImage)) {
                    unlink($oldImage);
                $extension = $request->image->extension();
                $imageName = strtolower(implode(' ',explode('
,str replace(':','',$title)))).'.'.$extension;
                $request->image->move(public path('img/books'), $imageName);
                $book->image = $imageName;
            $book->save();
            $book->authors()->sync($authors);
            Activity::create([
                'user name'=>session()->get('user')->name
            1);
            return redirect()->route('admin.products')->with('success','Updated
book!');
        }catch(\Exception $e){
            Log::error($e->getMessage());
            return redirect()->back()->with("error", $e->getMessage());
```

3.1.5 CartController

```
namespace App\Http\Controllers;
use App\Models\Activity;
use App\Models\Book;
use Illuminate\Http\Request;
class CartController extends BaseController
    public function index(Request $request) {
                if(session()->has('user') && session()->get('user')->role->role name ==
                        $bookId = $request->get("bookId");
                        if(!$request->session()->has("cart")) {
                            $request->session()->put("cart", []);
                        $book = Book::find($bookId);
                        $cart = $request->session()->get("cart");
                        if(isset($cart[$bookId])) {
                            $alreadyInCart = $cart[$bookId];
                            $alreadyInCart->quantity++;
                            $cart[$bookId] = $alreadyInCart;
                            $item = new \stdClass();
                            $item->bookId = $bookId;
                            item->quantity = 1;
                            $item->price = $book->price;
```

```
$item->image = $book->image;
                        $item->name = $book->book name;
                        $cart[$bookId] = $item;
                    $request->session()->put("cart", $cart);
                    Activity::create([
                        'user name'=>session()->get('user')->name
                    ]);
                } catch(\Exception $e) {
            elseif(session()->has('user') && session()->get('user')->role-
public function adjustQuantity(Request $request) {
    if(session()->get('user')->role->role name == 'admin'){
        return redirect()->back();
    $bookId = $request->get("bookId");
    $quantity = $request->get("quantity");
    $cart = $request->session()->get("cart");
    if(isset($cart[$bookId])) {
        $alreadyInCart = $cart[$bookId];
        $alreadyInCart->quantity = $quantity;
        $cart[$bookId] = $alreadyInCart;
       $request->session()->put("cart", $cart);
public function get(Request $request) {
    if(session()->get('user')->role->role name == 'admin'){
       return redirect()->back();
    $cart = $request->session()->get("cart");
    if(!$cart) {
       $cart = [];
        "cartItems" => $cart ]);
public function remove($bookId, Request $request) {
    if(session()->get('user')->role->role name == 'admin'){
        return redirect()->back();
    $cart = $request->session()->get("cart");
```

3.1.6 ContactController

```
namespace App\Http\Controllers;
use App\Http\Requests\ContactRequest;
use App\Models\Activity;
use App\Models\Contact;
use Illuminate\Support\Facades\Log;
class ContactController extends BaseController
    public function index(){
        return view('pages.contact');
    public function send(ContactRequest $request) {
        $name = $request->tbName;
        $email = $request->tbEmail;
        $message = $request->userMessage;
            Contact::create([
            ]);
                 'type' => 'Sent a message',
'user_name' => $name
            return redirect()->back()->with('success', 'Message sent!');
        catch(\Exception $e){
            Log::error($e->getMessage());
            return redirect()->back()->with('error','There was an error sending your
message');
```

ļ

3.1.7 Controller (Laravelov kontroler nije menjan)

```
namespace App\Http\Controllers;

use Illuminate\Foundation\Auth\Access\AuthorizesRequests;
use Illuminate\Foundation\Bus\DispatchesJobs;
use Illuminate\Foundation\Validation\ValidatesRequests;
use Illuminate\Routing\Controller as BaseController;

class Controller extends BaseController
{
    use AuthorizesRequests, DispatchesJobs, ValidatesRequests;
}
```

3.1.8 GenreController

```
namespace App\Http\Controllers;
use App\Http\Requests\GenreStoreRequest;
use App\Http\Requests\GenreUpdateRequest;
use App\Models\Activity;
use App\Models\Genre;
use Illuminate\Support\Facades\Log;
class GenreController extends BaseController
       $genres = Genre::with('books')->get();
   public function create(){
   public function store(GenreStoreRequest $request) {
        $name = $request->genreName;
            Genre::create([
            ]);
            Activity::create([
                'user name'=>session()->get('user')->name
            return redirect()->route('admin.genres')->with('success',"New genre
added!");
        }catch(\Exception $e){
            Log::error($e->getMessage());
            return redirect()->back()->with('error',"There was an error processing the
request.");
```

```
public function edit($id){
       $this->data['genre'] = Genre::find($id);
       return view('pages.admin.genres.edit', $this->data);
   public function update(GenreUpdateRequest $request,$id) {
       $genre = Genre::find($id);
       $name = $request->genreName;
       if($genre->genre name != $name){
            $request->validate(['genreName' => 'unique:genres,genre name']);
           $genre->genre name = $name;
           $genre->save();
                'user name'=>session()->get('user')->name
            return redirect()->route('admin.genres')->with('success','Updated genre');
       }catch(\Exception $e){
           Log::error($e->getMessage());
            return redirect()->back()->with('error','There was an error processing your
request.');
   public function destroy($id) {
       $genre = Genre::with('books')->find($id);
       if(count($genre->books) > 0){
           return redirect()->back()->with('error', "Genre has books associated with
it, can't delete.");
           $genre->delete();
           Activity::create([
                'user name'=>session()->get('user')->name
           ]);
           return redirect()->back()->with('success', "Genre deleted!");
       }catch(\Exception $e){
           Log::error($e->getMessage());
```

3.1.9 HomeController

```
<!php

namespace App\Http\Controllers;

use App\Models\Book;

class HomeController extends BaseController
{
    public function index() {
        $books = Book::with('authors')->with('genre')->orderBy('created_at', 'desc')-
>take(4)->get();
        $this->data['books'] = $books;
        return view('pages.home',$this->data);
}
```

```
public function author() {
    return view('pages.author');
}
```

3.2. Middleware

3.2.1 IsAdmin

3.2.2 IsGuest

```
<?php

namespace App\Http\Middleware;

use Closure;
use Illuminate\Http\Request;

class IsGuest
{
    /**
    * Handle an incoming request.
    *
    * @param \Illuminate\Http\Request $request
    * @param \Closure(\Illuminate\Http\Request):
(\Illuminate\Http\Response|\Illuminate\Http\RedirectResponse) $next
    * @return \Illuminate\Http\Response|\Illuminate\Http\RedirectResponse
    */
    public function handle(Request $request, Closure $next)
    {
        if (session()->get('user')) {
            return redirect()->back();
        }
        return $next($request);
    }
}
```

3.2.3 IsLoggedIn

3.3 Requests

3.3.1 BookStoreRequest

```
'publishYear'=>'required|numeric'
];
}
public function messages()
{
    return [
        'title.required'=>'Title field is required',
        'author1.required'=>'Author field is required',
        'description.required'=>'Description field is required',
        'image.required'=>'Title field can contain only text',
        'author1.string'=>'Author field can contain only text',
        'author2.string'=>'Author field can contain only text',
        'author2.string'=>'Author must have at least 4 characters',
        'author2.min'=>'Author must have at least 4 characters',
        'image.image'=>'Uploaded file must be an image',
        'image.max'=>'The image must be under 2MB',
        'genreId.required'=>'Genre is required',
        'price.required'=>'Price is required',
        'price.numeric'=>'Price must be a number',
        'publishYear.numeric'=>'Publication year m
```

3.3.2 BookUpdateRequest

3.3.3 ContactRequest

```
namespace App\Http\Requests;
use Illuminate\Foundation\Http\FormRequest;
class ContactRequest extends FormRequest
    public function authorize()
        return true;
    public function rules()
    public function messages()
```

3.3.4 GenreStoreRequest

```
namespace App\Http\Requests;
use Illuminate\Foundation\Http\FormRequest;
class GenreStoreRequest extends FormRequest
    public function authorize()
    public function rules()
    public function messages()
```

3.3.5 GenreUpdateRequest

```
<?php
namespace App\Http\Requests;
use Illuminate\Foundation\Http\FormRequest;
class GenreUpdateRequest extends FormRequest
{
    /**
    * Determine if the user is authorized to make this request.
    *
    * @return bool</pre>
```

3.3.6 LoginRequest

3.3.7 RegisterRequest

```
namespace App\Http\Requests;
use Illuminate\Foundation\Http\FormRequest;
class RegisterRequest extends FormRequest
    public function authorize()
        return true;
    public function rules()
    public function messages()
yourname@gmail.com).',
```

3.4 Models

3.4.1 Activity

```
<?php
namespace App\Models;
use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class Activity extends Model
{
   use HasFactory;
   public $fillable=['type','user_name'];
}</pre>
```

3.4.2 Author

```
<?php
namespace App\Models;
use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class Author extends Model
{
    use HasFactory;
    public $guarded=['id,created_at,updated_at'];
    public function books() {
        return $this->belongsToMany(Book::class)->withTimeStamps();
    }
}
```

3.4.3 Book

```
<?php
namespace App\Models;
use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class Book extends Model
{
    use HasFactory;
    public $guarded=['id,created_at,updated_at'];
    public function authors() {
        return $this->belongsToMany(Author::class)->withTimestamps();
    }

    public function genre() {
        return $this->belongsTo(Genre::class);
    }
}
```

3.4.4 Contact

```
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class Contact extends Model
{
    use HasFactory;
    public $guarded=['id','created_at','updated_at'];
}</pre>
```

3.4.5 Genre

```
<?php
```

```
namespace App\Models;
use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class Genre extends Model
{
    use HasFactory;
    public $guarded = ['id','created_at','updated_at'];

    public function books() {
        return $this->hasMany(Book::class);
    }
}
```

3.4.6 Role

```
<?php
namespace App\Models;
use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;
class Role extends Model
{
   use HasFactory;
}</pre>
```

3.4.7 User

```
namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class User extends Model
{
    use HasFactory;
    public $guarded=['id','created_at','updated_at'];
    protected $hidden=['password'];

    public function role() {
        return $this->belongsTo(Role::class,"role_id","id");
    }
}
```

3.5 Migrations

3.5.1 Roles table

```
<?php
use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

class CreateRolesTable extends Migration
{</pre>
```

3.5.2 Users table

3.5.3 Genres table

3.5.4 Authors table

```
{
    Schema::dropIfExists('authors');
}
```

3.5.5 Books table

```
use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;
class CreateBooksTable extends Migration
   public function up()
        Schema::create('books', function (Blueprint $table) {
            $table->id();
            $table->string('book name');
           $table->integer('price');
           $table->string('image');
           $table->string('publish year');
            $table->foreignId('genre id')->references('id')->on('genres');
            $table->timestamps();
        });
     * @return void
        Schema::dropIfExists('books');
```

3.5.6 Author book table

```
$table->foreignId('author_id')->references('id')->on('authors');
    $table->foreignId('book_id')->references('id')->on('books');
    $table->timestamps();
});
}

/**
    * Reverse the migrations.
    *
    * @return void
    */
    public function down()
{
        Schema::dropIfExists('author_book');
}
```

3.5.7 Contacts table

3.5.8 Activities table

```
<?php
use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

class CreateActivitiesTable extends Migration
{</pre>
```

3.6. Seeders

3.6.1 BookSeeder

```
$book = Book::create([
$author = Author::firstOrCreate(['name'=>'Stephen King']);
$author2 = Author::firstOrCreate(['name'=>'Richard Chizmar']);
$book->authors()->sync([$author->id,$author2->id]);
]);
$book->authors()->sync($author->id);
$book = Book::create([
]);
$author = Author::firstOrCreate(['name'=>'Oscar Wilde']);
$book->authors()->sync($author->id);
$book = Book::create([
    'price'=>13,
```

```
'image'=>'the only good indians.jpg',
       ]);
        $author = Author::firstOrCreate(['name'=>'Stephen Graham Jones']);
       $book->authors()->sync($author->id);
       $book = Book::create([
perfect chance for a fresh start. As the off-season caretaker at the atmospheric old
       ]);
       $author = Author::firstOrCreate(['name'=>'Stephen King']);
        $book->authors()->sync($author->id);
       $book = Book::create([
        ]);
       $author = Author::firstOrCreate(['name'=>'Edgar Allan Poe']);
       $book->authors()->sync($author->id);
       $book = Book::create([
```

```
for readers young and old.',
        1);
        $author = Author::firstOrCreate(['name'=>'Dr. Seuss']);
        $book->authors()->sync($author->id);
        $book = Book::create([
            'image'=>'the lorax.jpg',
        $author = Author::firstOrCreate(['name'=>'Dr. Seuss']);
        $book->authors()->sync($author->id);
        $book = Book::create([
            'image'=>'barnyard dance!.jpg',
        ]);
        $book->authors()->sync($author->id);
        $book = Book::create([
to the root of it. So begins an adventure bigger than anything Zuli could've ever
an ancient dragon, the so-called Witch-Queen, and most surprisingly of all: her true
            'genre id'=>11
        1);
        $author = Author::firstOrCreate(['name'=>'Marjorie Liu']);
        $book->authors()->sync($author->id);
```

```
$book = Book::create([
                'image'=>'the tale of peter rabbit.jpg',
          ]);
           $author = Author::firstOrCreate(['name'=>'Beatrix Potter']);
          $book->authors()->sync($author->id);
hunt is going to be egg-stra special. Where are all the eggs hidden? Your little pup will enjoy lifting the flaps to find the eggs! Happy Easter, Biscuit! is a fun Easter basket and springtime gift. Biscuit and the little girl have been warmly embraced by
           ]);
          $author = Author::firstOrCreate(['name'=>'Alyssa Satin Capucilli']);
          $book->authors()->sync($author->id);
          $book = Book::create([
           1);
           $author = Author::firstOrCreate(['name'=>'Karin Slaughter']);
           $book->authors()->sync($author->id);
          $book = Book::create([
```

```
'price'=>8,
    'genre id'=>21
$author = Author::firstOrCreate(['name'=>'Kym Roberts']);
$book->authors()->sync($author->id);
     image'=>'and_then_there_were_none.jpg',
    'genre id'=>21
]);
$author = Author::firstOrCreate(['name'=>'Agatha Cristie']);
$book->authors()->sync($author->id);
$book = Book::create([
]);
$author = Author::firstOrCreate(['name'=>'Edward Powys Mathers']);
$book->authors()->sync($author->id);
$book = Book::create([
```

```
party. The clues are scarce—a few license plates, a phone shattered on the roadside—but
            'image'=>'city problems.jpg',
        $author = Author::firstOrCreate(['name'=>'Steve Goble']);
        $book->authors()->sync($author->id);
        $book = Book::create([
        $author = Author::firstOrCreate(['name'=>'Nita Prose']);
        $book->authors()->sync($author->id);
        $book = Book::create([
        ]);
        $author = Author::firstOrCreate(['name'=>'Homer']);
        $book->authors()->sync($author->id);
```

```
$book = Book::create([
                 'genre id'=>31
           ]);
           $author = Author::firstOrCreate(['name'=>'Tupac Shakur']);
           $book->authors()->sync($author->id);
           $book = Book::create([
into a lyric of hope and healing. In Call Us What We Carry, Gorman explores history, language, identity, and erasure through an imaginative and intimate collage. Harnessing the collective grief of a global pandemic, this beautifully designed volume features poems in many inventive styles and structures and shines a light on a moment of
           ]);
           $author = Author::firstOrCreate(['name'=>'Amanda Gorman']);
           $book->authors()->sync($author->id);
           $book = Book::create([
           1);
           $author = Author::firstOrCreate(['name'=>'Courtney Peppernell']);
           $book->authors()->sync($author->id);
           $book = Book::create([
serves a different purpose. Deals with a different pain. Heals a different heartache.
                 'image'=>'milk and honey.jpg',
```

```
]);
        $author = Author::firstOrCreate(['name'=>'Rupi Kaur']);
        $book->authors()->sync($author->id);
        $book = Book::create([
            'image'=>'home body.jpg',
        $author = Author::firstOrCreate(['name'=>'Rupi Kaur']);
        $book->authors()->sync($author->id);
        $book = Book::create([
             image'=>"what_if_it's_us.jpg",
        ]);
        $book->authors()->sync([$author->id,$author2->id]);
        $book = Book::create([
reigning lab tyrant agrees to keep her charade a secret and be her fake boyfriend. But
unyielding...six-pack abs. Suddenly their little experiment feels dangerously close to
```

```
'genre id'=>41
]);
$author = Author::firstOrCreate(['name'=>'Ali Hazelwood']);
$book->authors()->sync($author->id);
$book = Book::create([
    'image'=>'hook, line, and sinker.jpg',
]);
$author = Author::firstOrCreate(['name'=>'Tessa Bailey']);
$book->authors()->sync($author->id);
$book = Book::create([
    'image'=>'a_will_and_a_way.jpg',
$author = Author::firstOrCreate(['name'=>'Nora Roberts']);
$book->authors()->sync($author->id);
$book = Book::create([
```

```
for the God of the Dead grows-and it\'s forbidden.',
        1);
        $author = Author::firstOrCreate(['name'=>'Scarlett St. Clair']);
        $book->authors()->sync($author->id);
        $book = Book::create([
            'image'=>'a touch of ruin.jpg',
        $author = Author::firstOrCreate(['name'=>'Scarlett St. Clair']);
        $book->authors()->sync($author->id);
        $book = Book::create([
            'image'=>'a touch of malice.jpg',
        ]);
        $author = Author::firstOrCreate(['name'=>'Scarlett St. Clair']);
        $book->authors()->sync($author->id);
        $book = Book::create([
boy Paul Atreides, heir to a noble family tasked with ruling an inhospitable world
fruition humankind's most ancient and unattainable dream. A stunning blend of adventure
            'image'=>'dune.jpg',
            'genre id'=>51
        1);
```

```
$author = Author::firstOrCreate(['name'=>'Frank Herbert']);
             $book->authors()->sync($author->id);
             $book = Book::create([
Factory. But fortunately for Harry, he\'s about to be granted a scholarship to a unique boarding school called THE HOGWARTS SCHOOL OF WITCHCRAFT AND WIZARDRY, where he will
             $author = Author::firstOrCreate(['name'=>'J. K. Rowling']);
             $book->authors()->sync($author->id);
Harry Potter wanted was to get back to the Hogwarts School for Witchcraft and Wizardry. But just as he\'s packing his bags, Harry receives a warning from a strange, impish creature named Dobby who says that if Harry Potter returns to Hogwarts, disaster will strike. And strike it does. For in Harry\'s second year at Hogwarts, fresh torments and
             $author = Author::firstOrCreate(['name'=>'J. K. Rowling']);
             $book->authors()->sync($author->id);
             $book = Book::create([
             ]);
```

```
$author = Author::firstOrCreate(['name'=>'J. K. Rowling']);
$book->authors()->sync($author->id);
$book = Book::create([
    'image'=>'harry potter and the goblet_of_fire.jpg',
]);
$author = Author::firstOrCreate(['name'=>'J. K. Rowling']);
$book->authors()->sync($author->id);
$book = Book::create([
    'image'=>'harry_potter_and_the_order_of_the_phoenix.jpg',
]);
$author = Author::firstOrCreate(['name'=>'J. K. Rowling']);
$book->authors()->sync($author->id);
$book = Book::create([
    'image'=>'harry potter and the half-blood prince.jpg',
    'genre id'=>51
1);
$author = Author::firstOrCreate(['name'=>'J. K. Rowling']);
$book->authors()->sync($author->id);
$book = Book::create([
```

```
'image'=>'harry potter and the deathly hallows.jpg',
]);
$author = Author::firstOrCreate(['name'=>'J. K. Rowling']);
$book->authors()->sync($author->id);
$book = Book::create([
    'image'=>'the fellowship of the ring the lord of the rings part one.jpg',
]);
$author = Author::firstOrCreate(['name'=>'J. R. R. Tolkien']);
$book->authors()->sync($author->id);
$book = Book::create([
    'image'=>'the two towers the lord of the rings part two.jpg',
]);
$author = Author::firstOrCreate(['name'=>'J. R. R. Tolkien']);
$book->authors()->sync($author->id);
$book = Book::create([
```

```
1);
       $author = Author::firstOrCreate(['name'=>'J. R. R. Tolkien']);
       $book->authors()->sync($author->id);
       $book = Book::create([
       ]);
       $author = Author::firstOrCreate(['name'=>'Colleen Hoover']);
       $book->authors()->sync($author->id);
       $book = Book::create([
            'image'=>'the overnight_guest.jpg',
            'genre id'=>61
       ]);
        $author = Author::firstOrCreate(['name'=>'Heather Gudenkauf']);
       $book->authors()->sync($author->id);
        $book = Book::create([
            'description'=>'A DEAD WOLF. A DRUG DEAL GONE WRONG. A LETHAL FEMALE
policewoman in the remote northern town of Haparanda, Sweden, finds herself on the
```

```
no stone unturned. But time is scarce and they aren't the only ones looking. When the
                 'genre id'=>61
           ]);
           $author = Author::firstOrCreate(['name'=>'Hans Rosenfeldt']);
           $book->authors()->sync($author->id);
           $book = Book::create([
stop her from counseling those in crisis, though they have to adhere to her unorthodox methods. And the Bishops are desperate. When they glide through Avery's door and Marissa reveals her infidelity, all three are set on a collision course. Because the biggest secrets in the room are still hidden, and it's no longer simply a marriage
           ]);
           $author = Author::firstOrCreate(['name'=>'Greer Hendricks']);
           $book->authors()->sync([$author->id,$author2->id]);
           $book = Book::create([
           ]);
           $author = Author::firstOrCreate(['name'=>'Clare Mackintosh']);
           $book->authors()->sync($author->id);
           $book = Book::create([
                 'price'=>8,
```

```
Jessie Mercado in a baffling case. An army vet and former bodyguard for the rich and famous, Jessie has faced all kinds of danger but one thing the motorcycle-riding private investigator has never encountered before is an incarceration consultant. Preparing wealthy people to go to prison is big business. When Owen Blake of Mamertine Consulting hires Mercado to find his missing partner, their suspect list is filled with recently released white-collar criminals, a few drug kingpins, and a couple of murderers to keep things interesting. As witnesses turn up dead and car chases leave destruction in their wake, Jessie and Kendra learn just how far someone will go to keep the fate of one man hidden. But why? Together they must hunt down the lethal secrets of Blake's company, hell-bent on staying one step ahead of disaster.',

'image'=>'killer_view.jpg',

'publish_year'=>'2022',

'genre_id'=>61

]);

$author = Author::firstOrCreate(['name'=>'Roy Johansen']);

$book->authors()->sync($author->id);
}
```

3.6.2 DatabaseSeeder

3.6.3 GenreSeeder

```
<?php
namespace Database\Seeders;
use App\Models\Genre;
use Illuminate\Database\Seeder;
class GenreSeeder extends Seeder
{
    /**
    * Run the database seeds.
    *
    * @return void
    */
    public function run()
    {</pre>
```

```
Genre::create(['genre_name'=>'Horror']);
    Genre::create(['genre_name'=>'Kids']);
    Genre::create(['genre_name'=>'Mystery']);
    Genre::create(['genre_name'=>'Poetry']);
    Genre::create(['genre_name'=>'Romance']);
    Genre::create(['genre_name'=>'Sci-Fi & Fantasy']);
    Genre::create(['genre_name'=>'Thriller']);
}
```

3.6.4 RoleSeeder

```
<?php

namespace Database\Seeders;

use App\Models\Role;
use Illuminate\Database\Seeder;

class RoleSeeder extends Seeder
{
    /**
    * Run the database seeds.
    *
    * @return void
    */
    public function run()
    {
        Role::create(['role_name'=>'user']);
        Role::create(['role_name'=>'admin']);
    }
}
```

3.6.5 UserSeeder

3.7 Views

3.7.1 Fixed

3.7.1.1 footer.blade.php

```
<h4>Follow us</h4>
                       <a href="https://www.facebook.com" target="blank"><i
                       <a href="https://www.instagram.com" target="blank"><i</pre>
class="fab fa-instagram"></i> Instagram</a>
                       <a href="https://www.youtube.com" target="blank"><i</pre>
                   <h4>Working hours</h4>
                   <i class="fas fa-clock"></i> Workdays: 08-20h
                   <i class="fas fa-map-marker-alt"></i> Knez Mihailova 1,
Belgrade
                   <h4>Links</h4>
                       <a href="{{asset('dokumentacija.pdf')}}" target="blank"><i</pre>
                       <a href="{{route('author')}}"><i class="far fa-file-</a>
                       ©Djordje Solomun 16/19
```

3.7.1.2 head.blade.php

3.7.1.3 nav.blade.php

```
<a class="navbar-brand" href="{{route('home')}}">Bookstore</a>
   <button class="navbar-toggler" type="button" data-toggle="collapse" data-</pre>
target="#navbarTogglerDemo02" aria-controls="navbarTogglerDemo02" aria-expanded="false"
aria-label="Toggle navigation">
           class="nav-item @if(request()->routeIs('home')) active @endif">
           routeIs('books.index')) active @endif">
           routeIs('contact.index')) active
              <a class="nav-link" href="{{route('contact.index')}}">Contact</a>
           @if(session()->has('user'))
              @if(session()->get('user')->role->role name == 'user')
                  class="nav-item @if(request()->routeIs('cart')) active @endif">
                      <a class="nav-link" href="{{route('cart')}}">Cart<i class="fas</pre>
                  <a class="nav-link" href="{{route('admin.home')}}">Admin
panel</a>
                  <span class="text-white">{{session()->qet('user')->name}}</span>
                  <a class="auth-button" href="{{route('logout')}}">Logout</a>
                  <a class="auth-button" href="{{route('login')}}">Login</a>
                  <a class="auth-button" href="{{route('register')}}">Register</a>
```

3.7.1.4 nav admin.blade.php

```
chav class="navbar sticky-top navbar-expand-lg navbar-dark bg-dark">
   <button class="navbar-toggler" type="button" data-toggle="collapse" data-</pre>
target="#navbarTogglerDemo02" aria-controls="navbarTogglerDemo02" aria-expanded="false"
             routeIs('admin.home')) active
                 <a class="nav-link" href="{{route('admin.home')}}">Admin home</a>
             routeIs('admin.products')) active
                <a class="nav-link" href="{{route('admin.products')}}">Admin
products</a>
             routeIs('admin.genres')) active
                <a class="nav-link" href="{{route('admin.genres')}}">Admin
genres</a>
             routeIs('admin.users')) active
                 <a class="nav-link" href="{{route('admin.users')}}">Admin users</a>
          routeIs('admin.messages')) active
             <a class="nav-link" href="{{route('admin.messages')}}">Admin
messages</a>
                 <span class="text-white">{{session()->get('user')->name}}</span>
                 <a class="auth-button" href="{{route('logout')}}">Logout</a>
```

3.7.1.5 scripts.blade.php

```
<script src="https://code.jquery.com/jquery-3.5.1.min.js" integrity="sha256-
9/aliU8dGd2tb60SsuzixeV4y/faTqgFtohetphbbj0=" crossorigin="anonymous"></script>
<script
src="https://cdn.jsdelivr.net/npm/bootstrap@4.5.3/dist/js/bootstrap.bundle.min.js"
integrity="sha384-ho+j7jyWK8fNQe+A12Hb8AhRq26LrZ/JpcUGGOn+Y7RsweNrtN/tE3MoK7ZeZDyx"
crossorigin="anonymous"></script>
<script
src="https://cdnjs.cloudflare.com/ajax/libs/toastr.js/latest/toastr.min.js"></script>
<script
$.ajaxSetup({
    headers: {
        'X-CSRF-TOKEN': $('meta[name="csrf-token"]').attr('content')
    }
});
toastr.options = {
    "closeButton": true,
    "positionClass": "toast-bottom-right",
    "timeOut": "5000",
    "hideEasing": "linear",
    "showMethod": "fadeIn",
    "hideMethod": "fadeOut"</pre>
```

```
}
</script>
@stack('scripts')
<script src="{{asset('js/main.js')}}"></script>
```

3.7.2 Layouts

3.7.2.1 admin_layout.blade.php

```
<!DOCTYPE html>
<html>
@include('fixed.head')
@include('fixed.nav_admin')

@yield('content')

@include('fixed.scripts')
</html>
```

3.7.2.2 layout.blade.php

```
<!DOCTYPE html>
<html>
@include('fixed.head')
@include('fixed.nav')

@yield('content')

@include('fixed.footer')
@include('fixed.scripts')
</html>
```

3.7.3 Pages

3.7.3.1 Admin

3.7.3.1.1 index.blade.php

```
<option {{(isset($qs['sort']) && $qs['sort'] ==</pre>
<option {{(isset($qs['sort']) && $qs['sort'] ==</pre>
                  <input type="submit" value="Sort" class="btn btn-outline-</pre>
                  >User name
                  Date
              @forelse($activities as $a)
                     { { $a->type } } 
                     { { $a->user name } } 
                     {td>{{$a->created at}}
```

3.7.3.1.2 messages.blade.php

3.7.3.1.3 Books

3.7.3.1.3.1 create.blade.php

```
books, bookstore, admin, novels, add
            @if(session()->has('success'))
                <div class="alert alert-success rounded text-center">
                    Added new book!
            @if(session()->has('error'))
                    {{session()->get('error')}}
                <form action="{{route('books.store')}}" method="POST"</pre>
enctype="multipart/form-data">
                        <input type="text" class="form-control" name="title"</pre>
placeholder="Book title" value="{{old('title')}}">
danger">@error('title'){{$message}}@enderror</span>
                        <label for="genreId">Select genre</label>
```

```
<option value="0">Select</option>
                             @foreach($genres as $g)
                             @if(old('genreId') == $q->id)
                                 <option selected value="{{$q->id}}">{{$q-
>genre name}}</option>
                                 <option value="{{$g->id}}">{{$g->genre name}}</option>
                         <span class="text-</pre>
danger">@error('genreId'){{$message}}@enderror</span>
                         <input type="text" class="form-control mb-2" name="author1"</pre>
                         <input type="text" class="form-control mb-2" name="author2"</pre>
value="{{old('author2')}}" placeholder="Optional">
danger">@error('author1'){{$message}}@enderror</span>
                         <label for="price">Price</label>
                         <input type="text" class="form-control"</pre>
danger">@error('price') { {$message} } @enderror</span>
                         <label for="publishYear">Publication year
                         <input type="text" class="form-control"</pre>
value="{{old('publishYear')}}" name="publishYear" placeholder="Publication year"/>
danger">@error('publishYear'){{$message}}@enderror</span>
                         <label for="description">Description</label>
danger">@error('description'){{$message}}@enderror</span>
                         <label for="image">Image</label>
                         <input type="file" name="image" class="form-control-file"/>
                         <div><input type="submit" value="Add" class="btn btn-outline-</pre>
```

```
@extends('layouts.admin layout')
    books, bookstore, admin, novels, edit
    Bookstore - admin edit book.
    Edit book
        <div class="mx-auto">
            @if(session()->has('error'))
                <div class="alert alert-danger rounded text-center">
                     {p>{{session()->get('error')}}
            <h1 class="accent">Edit book</h1>
        <div class="row p-2">
                <form action="{{route('books.update',['book'=>$book->id])}}"
method="POST" enctype="multipart/form-data">
                         <input type="text" class="form-control" name="title"</pre>
placeholder="Book title" value="{{$book->book name}}">
danger">@error('title') { {$message}} @enderror</span>
                             <option value="0">Select</option>
                             @foreach($genres as $g)
                                 @if($book->genre->id == $g->id)
                                     <option selected value="{{$q->id}}">{{$q-
>genre name}}</option>
                                     <option value="{{$q->id}}">{{$q-
>genre name}}</option>
danger">@error('genreId'){{$message}}@enderror</span>
                     <div class="form-group">
                         @if(count($book->authors) == 1)
                             <input type="text" class="form-control mb-2" name="author1"</pre>
value="{{$book->authors[0]->name}}" placeholder="Author name">
danger">@error('author1'){{$message}}@enderror</span>
                             <input type="text" class="form-control mb-2" name="author1"</pre>
value="{{$book->authors[0]->name}}" placeholder="Author name">
                             <input type="text" class="form-control mb-2" name="author2"</pre>
value="{{$book->authors[1]->name}}" placeholder="Author name">
```

```
<span class="text-</pre>
danger">@error('author1') { {$message} } @enderror</span>
                              <span class="text-</pre>
danger">@error('author2') { {$message} } @enderror</span>
                     <div class="form-group">
                          <label for="price">Price</label>
                          <input type="text" class="form-control" value="{{$book-</pre>
danger">@error('price'){{$message}}@enderror</span>
                          <label for="publishYear">Publication year</label>
                          <input type="text" class="form-control" value="{{$book-</pre>
>publish year}}" name="publishYear" placeholder="Publication year"/>
danger">@error('publishYear'){{$message}}@enderror</span>
rows="3">{ {$book->description} }</textarea>
danger">@error('image') { {$message} } @enderror</span>
                          <div><input type="submit" value="Edit" class="btn btn-outline-</pre>
```

3.7.3.1.3.3 products.blade.php

```
@extends('layouts.admin_layout')

@section('keywords')
    books,bookstore,admin,novels,products
@endsection

@section('description')
    Bookstore - admin view all products.
@endsection

@section('title')
    Admin products
@endsection

@php

$sortBy=[['key'=>'Price','value'=>'ASC'],['key'=>'Price','value'=>'DESC'],['key'=>'book_name','value'=>'ASC']];
```

```
@if(session()->has('success'))
              <div class="alert alert-success rounded text-center">
                   {p>{{session()->get('success')}}
              @if(session()->has('error'))
                       { session() ->get('error')}}
                       <div class="col-12">
                                 Sort by:
                                          @if(isset($qs['sortBy']) && explode('-
                                               <option selected value="{{$s['key']}}-</pre>
{{$$['value']}}"> {{ucfirst(implode(' ',explode(' ',$$['key'])))}}
                                               <option value="{{$s['key']}}-{{$s['value']}}">
{{ucfirst(implode(' ',explode('_',$s['key'])))}} {{$s['value']}}</option>
                                 <input type="text" class="form-control"</pre>
name="search" value="{{ isset($qs["search"]) ? $qs["search"] : "" }}"/>
                                     <div class="col-12">
                                          Genres:
                                               @foreach($genres as $g)
                                                        <input type="checkbox" {{</pre>
(isset($qs["chbGenres"]) && in array($q->id, $qs["chbGenres"])) ? "checked" : "" }}
value="\{\{\$g->id\}\}" \ name="chbGenres[]"/> \{\{\$g->genre \ name\}\} \ (\{\{count(\$g->books)\}\}) \ name="chbGenres[]"/> \{\{\$g->genre \ name\}\} \ (\{\{count(\$g->books)\}\}) \ name="chbGenres[]"/> \{\{\{\$g->genre \ name\}\}\} \ (\{\{\{count(\$g->books)\}\}\}) \ name="chbGenres[]"/> \{\{\{\{\{g->genre \ name\}\}\}\}\}]
                                          <input type="submit" value="Search" class="btn btn-</pre>
```

3.7.3.1.4 Genres

3.7.3.1.4.1 create.blade.php

```
books, bookstore, admin, genre, new
    Bookstore - admin add a new genre.
    Admin add genre
            @if(session()->has('success'))
                    {p>{{session()->get('success')}}
            @if(session()->has('error'))
                    {p>{{session()->get('error')}}
                <form action="{{route('admin.genres.store')}}" method="POST">
                        <input type="text" class="form-control" name="genreName"</pre>
placeholder="Genre name" value="{{old('genreName')}}">
danger">@error('genreName'){{$message}}@enderror</span>
                        <div><input type="submit" value="Add" class="btn btn-outline-</pre>
```

3.7.3.1.4.2 edit.blade.php

```
books, bookstore, admin, genre, new
    Bookstore - admin add a new genre.
    Admin add genre
            @if(session()->has('success'))
                    {p>{{session()->get('success')}}
            @if(session()->has('error'))
                    {{session()->get('error')}}
            <h1 class="accent">Edit genre</h1>
                <form action="{{route('admin.genres.update',['genre'=>$genre->id])}}"
method="POST">
                        <label for="genreName">Genre name</label>
                        <input type="text" class="form-control" name="genreName"</pre>
placeholder="Genre name" value="{{$genre->genre name}}">
                        <div><input type="submit" value="Edit" name="btnAddGenre"</pre>
```

3.7.3.1.4.3 index.blade.php

```
@extends('layouts.admin layout')
    books, bookstore, admin, novels, genres
    Bookstore - admin genre page.
   Admin genres
       <div class="mx-auto my-3">
           @if(session()->has('success'))
                    {p>{{session()->qet('success')}}
            @if(session()->has('error'))
                    {p>{{session()->get('error')}}
            <h1 class="accent">Genres</h1>
            <a href="{{route('admin.genres.create')}}" class="btn btn-primary">Add new
genre</a>
                @foreach($genres as $g)
                        {\{\$q-}\neq name\}}
                        <a href="{{route('admin.genres.edit',['genre'=>$g->id])}}"
class="btn btn-outline-warning">Edit</a>
                            <form action="{{route('admin.genres.delete',['genre'=>$g-
>id])}}" method="POSt">
                                <input type="submit" class="btn btn-outline-danger"</pre>
value="Delete"/>
```

3.7.3.1.5.1 index.blade.php

```
@extends('layouts.admin layout')
   books, bookstore, admin, novels, users
   Bookstore - admin users page.
   Admin users
           @if(session()->has('success'))
                   {{session()->get('success')}}
           @if(session()->has('error'))
                  {p>{{session()->get('error')}}
           <h1 class="accent">Users</h1>
                   User ID
                  Name
                  Email
                  Delete
               @foreach($users as $u)
                  @if($u->role->role name != 'admin')
                          { {$u->id}} 
>id])}}" method="POST">
                                 <input type="submit" class="btn btn-outline-danger"</pre>
value="Delete"/>
```

```
</div>
</div>
@endsection
```

3.7.3.2 Auth

3.7.3.2.1 login.blade.php

```
books, bookstore, account, novels, login
   Bookstore - login to your account.
   Login
           <h1 class="text-center accent">Login</h1>
                  @if(session()->has('error'))
                      { { session() ->get('error') } } 
method="post">
                          <input type="text" name="tbEmail" id="tbEmail" class="form-</pre>
control" value="{{old('tbEmail')}}"/>
                          <label for="tbPass">Password</label>
                          <input type="password" name="tbPass" id="tbPass"</pre>
                         @error('tbPass') {{$message}}
                          <input type="submit" name="btnLogin" id="btnLogin"</pre>
class="auth-button" value="Login" />
```

3.7.3.2.2 register.blade.php

```
books, bookstore, account, novels, register
   Bookstore - register and create a new account.
   Register
       <div class="container py-5">
          <h1 class="text-center accent">Register</h1>
           <div class="row py-5">
              <div class="col-12 col-1q-5 mx-auto py-5">
                  @if(session()->has('error'))
                         {p>{{session()->get('error')}}
                      @if(session()->has('success'))
                             {p>{{session()->get('success')}}<span>Click <a
class='accent' href="{{route('login')}}">here</a> to login now</span>
method="post">
                         <label for="tbName">Full name<mark>*</mark></label>
                         <input type="text" name="tbName" id="tbName" class="form-</pre>
                         @error('tbName') {{$message}}
                         <label for="tbEmail">Email<mark>*</mark></label>
                         <input type="text" name="tbEmail" id="tbEmail" class="form-</pre>
control" value="{{old('tbEmail')}}"/
                         @error('tbEmail')
{{$message}} @enderror
                         <label for="tbPass">Password<mark>*</mark></label>
                         <input type="password" name="tbPass" id="tbPass"</pre>
class="form-control" />
                         @error('tbPass') {{$message}}
                      <div class="col-12"><mark>*</mark> Required fields</div>
                         <input type="submit" name="btnReg" id="btnReg" class="auth-</pre>
```

```
</div>
</div>
@endsection
```

3.7.3.3 Books

3.7.3.3.1 cart.blade.php

```
books, bookstore, cart, novels, order
    Bookstore - review the items in your cart.
   Cart
           @if(count($cartItems) == 0)
               @if(session()->has('msg'))
been placed. Go back to the <a href="{{route('books.index')}}">store</a></div>
                   <div class=" mt-5 mx-auto alert alert-danger">You have nothing in
your cart. Visit the <a href="{{route('books.index')}}">store</a></div>
                   <div class="container">
                       <h1 class="accent text-center"><b>Shopping Cart</b></h1>
id="count">{{count($cartItems)}} items</div>
                           @foreach($cartItems as $c)
                               <div class="border-top border-bottom p-2 mb-3 cart-item"</pre>
fluid" src="{{ asset("img/books/".$c->image) }}"></div>
href="{{route('books.show',['book'=>$c->bookId])}}">{{ $c->name }}</a></div>
quantity" min="1" data-price="{{$c->price}}" data-id="{{$c->bookId}}" type="number"
value="{{ $c->quantity }}"></div>
```

3.7.3.3.2 index.blade.php

```
<div class="row">
                    <div class="col-12">
                       Genres:
                       @foreach($genres as $g)
                               <input type="checkbox" value="{{$g->id}}"
class="genre" name="genres"/> {{$g->genre name}} ({{count($g->books)}})
```

3.7.3.3 show.blade.php

```
@section('content')
   @include('pages.partials.singleProduct')
@endsection
```

3.7.3.4 Partials

3.7.3.4.1 product.blade.php

```
foreach($b->authors as $a){
      array push($authorArr,$a->name);
   $author = implode(', ',$authorArr);
       <img src="{{asset('img/books/'.$b->image)}}" class="card-img-top" alt="{{$b-
>book name}}">
           Genre: {{$b->genre->genre name}}<hr><p</pre>
>price}}
           @if(session()->has('user') && session()->get('user')->role->role name ==
               <a href="{{route('books.edit',['book'=>$b->id])}}" class="btn btn-
outline-warning mt-2">Edit</a>
               <form action="{{route('books.destroy',['book'=>$b->id])}}"
method="POST">
                   <input type="submit" class="btn btn-outline-danger mt-2"</pre>
value="Delete"/>
               <a href="#!" class="btn btn-outline-warning mt-2 addToCart" data-
```

3.7.3.4.2 singleProduct.blade.php

3.7.3.5 author.blade.php

```
books, bookstore, contact, novels, information
   Bookstore - if you have a question, please contact us.
   Contact us
       <h1 class="text-center my-5 accent">Contact us</h1>
       <div class="container mx-auto row">
           <div class="col-12 col-md-6 mb-2 p-3">
               <h3 class="text-center accent">Send us a message</h3>
               <form method="post" action='{{route('contact.send')}}' id="con-form"</pre>
name="conForm">
                   <div class="row">
                           <label for="tbName">Full name<mark>*</mark></label>
                           <input type="text" class="form-control" name="tbName"</pre>
id="tbName"placeholder="ex. John Doe" value="{{old('tbName')}}"/>
                           @error('tbName') {{$message}}
                           <label for="tbEmail">Email<mark>*</mark></label>
                           <input class="form-control" type="text" name="tbEmail"</pre>
id="tbEmail" placeholder="ex. johndoe@gmail.com" value="{{old('tbEmail')}}"/>
                           <label for="tbMessage">Your message<mark>*</mark></label>
                           <textarea name="userMessage" id="userMessage" class="form-</pre>
control" placeholder="Your message.">{{old('tbMessage')}}</textarea>
{{$message}} @enderror
                       <div class="col-12"><mark>*</mark> Required fields</div>
                       <div class="form-group col">
                           <input type="submit" value="Send" name="submitContact"</pre>
                           @if(session()->has('success'))
                                {{ session()->get('success')}
                           @elseif(session()->has('error'))
                                {{ session()->get('error')}
```

3.7.3.7 home.blade.php

```
books, bookstore, bookshop, novels, home
    Bookstore - buy books of all genres and authors.
    <div class="container mt-3">
        <div id="carouselExampleFade" class="carousel slide carousel-fade" data-</pre>
ride="carousel">
                <div class="carousel-item active" data-interval="3000">
                    <img src="{{asset('img/store.jpg')}}" class="d-block w-100"</pre>
alt="Book store">
                        <h1 class="accent">Bookstore</h1>
                        Online book shop
                <div class="carousel-item" data-interval="3000">
                    <imq src="{{asset('img/books.jpg')}}" class="d-block w-100"</pre>
alt="Books">
                    <div class="carousel-caption rounded d-none d-md-block text-body">
                        <h2 class="accent">Everything you need</h2>
                        Find books from your favorite authors and genres. Check out
the <a href="{{route('books.index')}}" class="btn btn-outline-warning">shop</a>
        <h2 class="text-center accent">PC Center</h2>
                If you like to read this is the place for you. We have something for
everyone, and we are always expanding our offer.
href="{{route('books.index')}}" class="btn btn-outline-warning">shop</a>
            <div class="col-9 col-md-6 mx-auto">
```

```
<imq src="{{asset('img/bookshelf.jpq')}}" alt="Bookshelf" class="w-100</pre>
    <div class="container mt-5">
       <h2 class="text-center accent">Newest releases</h2>
       <div class="row w-100 mt-3 pb-3 d-flex justify-content-center align-items-</pre>
               autoriN = [];
                  array push($autoriN,$a->name);
               $autori = implode(', ',$autoriN);
                        <img src="{{asset('img/books/'.$b->image)}}" class="card-img-
                           Genre: {{$b->genre-
>genre name}}<hr>
${{$b->price}}
                           <a href="#!" class="btn btn-outline-warning mt-2 addToCart"</pre>
id="1">Add to cart</a>
```

3.8 Routes

3.8.1 web.php

```
wse Illuminate\Support\Facades\Route;
use App\Http\Controllers\AuthController;
use App\Http\Controllers\HomeController;
use App\Http\Controllers\ContactController;
use App\Http\Controllers\BookController;
use App\Http\Controllers\AdminController;
use App\Http\Controllers\AdminController;
use App\Http\Controllers\CartController;
use App\Http\Controllers\CartController;
use App\Http\Controllers\GenreController;
use App\Http\Controllers\GenreController;
Route::get('/home', [HomeController::class, 'index'])->name('home');
Route::get('/about', [HomeController::class, 'index'])->name('contact.index');
Route::get('/contact', [ContactController::class, 'send'])->name('contact.send');
Route::get('/author', [HomeController::class, 'author'])->name('author');
```

```
Route::middleware('isGuest')->group(function(){
    Route::get('/login',[AuthController::class,'loginForm'])->name('login');
    Route::post('/login',[AuthController::class, 'login']) ->name('doLogin');
    Route::get('/register',[AuthController::class, 'registerForm'])->name('register');
    Route::post('/register', [AuthController::class, 'register']) -> name('doRegister');
});
Route::middleware('isLoggedIn')->group(function(){
    Route::get('/logout', [AuthController::class, 'logout']) ->name('logout');
    Route::get('/cart',[CartController::class,'get']) ->name('cart');
    Route::post("/cart/adjustQuantity", [CartController::class, "adjustQuantity"]);
Route::delete("/cart/{bookId}", [CartController::class, "remove"]);
    Route::get('/cart/checkout',[CartController::class, 'checkout'])->name('checkout');
    Route::middleware('isAdmin')->group(function(){
        Route::get('/admin', [AdminController::class, 'index']) ->name('admin.home');
        Route::get('/admin/products', [AdminController::class, 'products']) -
        Route::get('/admin/users', [AdminController::class, 'users']) -
>name('admin.users');
        Route::delete('admin/users/{user}', [AdminController::class, 'destroy user'])-
>name('admin.users.delete');
        Route::get('/admin/genres',[GenreController::class,'index'])-
>name('admin.genres');
        Route::get('admin/genres/{genre}/edit',[GenreController::class, 'edit'])-
>name('admin.genres.edit');
        Route::get('admin/genres/create', [GenreController::class, 'create']) -
>name('admin.genres.create');
        Route::post('admin/genres',[GenreController::class, 'store'])-
        Route::put('admin/genres/{genre}',[GenreController::class, 'update'])-
        Route::delete('admin/genres/{genre}',[GenreController::class, 'destroy'])-
        Route::get('/admin/messages', [AdminController::class, 'messages']) -
>name('admin.messages');
Route::post('/cart',[CartController::class,'index']);
Route::get('/books/json',[BookController::class,'get json']);
Route::resource('books',BookController::class);
```

3.9 CSS

3.9.1 style.css

```
* {
    padding: 0;
    margin: 0;
}
.carousel-caption {
    background-color: rgba(255, 255, 0.9);
}
.card {
    border: 0px solid black !important;
```

```
background-color: transparent;
    width: inherit !important;
.card:hover {
   box-shadow: 0 0 0 0.2rem rgb(206, 120, 82, 25%);
    transition: 0.5s;
    list-style-type: none;
   margin-bottom: 0rem !important;
#kontakt {
#kontakt i {
    font-weight: bold;
#price{
   color: #ce7852!important;
    border-color: #ce7852!important;
.btn-outline-warning:hover{
   background-color: #ce7852!important;
    color:#fff!important;
#name{
   color: #212529;
#name:hover{
    text-decoration-color: #ce7852;
#loader{
    display:flex;
.page-link{
    color: #ce7852;
```

```
.page-item.active .page-link{
    color: #fff;
    background-color: #ce7852;
    border-color: #ce7852;
   color: #fff;
    border-color: #ce7852;
.page-link:focus{
    box-shadow: 0 0 0 0.2rem rgb(206, 120, 82, 25%);
    padding: .375rem .75rem;
a.auth-button{
    text-decoration: none;
.auth-button:hover{
   background-color: #fff;
    box-shadow: 0 0 0 0.2rem rgb(206, 120, 82, 25%);
input[type=checkbox]{
.bg-dark{
    background-color: #031546!important;
    color: #ce7852!important;
.navbar-dark .navbar-brand:hover,.navbar-dark .navbar-brand, .accent{
    color: #ce7852;
    color: #ce7852;
    border-color: #ce7852;
button:focus {
```

```
height: 40px;
   position: fixed;
    color: #ce7852;
    z-index: 5;
   display: none!important;
@keyframes ldio-zftvpl388ch {
    100% { transform: translate(-50%,-50%) rotate(360deg); }
   position: absolute;
    animation: ldio-zftvpl388ch 1s linear infinite;
.loadingio-spinner-rolling-5dqev8yz7mg {
   display: inline-block;
   width: 100%;
   height: 100%;
   position: relative;
   transform: translateZ(0) scale(1);
   backface-visibility: hidden;
 ldio-zftvpl388ch div { box-sizing: content-box; }
```

3.10 JavaScript

3.10.1 main.js

```
$ (document) .ready (function() {
    if($('#products').length){
       filterProizvoda();
   correctTotalPrice()
   $ (document) .on("click", ".addToCart", addToCart);
   $("#search").keyup(filterProizvoda);
   $("#sort").on("change", filterProizvoda);
   $ (document).on('change','.quantity',changeQuantity);
   $ (document) .on('click','.remove', removeFromCart);
    $ (document) .on('click','.page-link',getPage);
})
function fetchData(url,method,data){
    return new Promise((resolve, reject) => {
       $.ajax({
           url:url,
           method:method,
           dataType: "json",
           data:data,
           success:resolve,
           error:reject
    })
function ispisProizvoda(proizvodi){
    if (proizvodi.length>0) {
        for(proizvod of proizvodi){
             <img src="${imgPath}/${proizvod.image}" class="card-img-top"</pre>
alt="${proizvod.book name}">
              <div class="card-body">
              <a href="/books/${proizvod.id}" id="name">
               <h5 class="card-title" >${proizvod.book name}</h5><hr/>
                Genre: ${proizvod.genre.genre name}<hr/>`;
                let authors = proizvod.authors.map(item => {
                    return item.name
               html+=`Author: ${authors}<hr/>
$${proizvod.price}`;
                if($("#navigacija").data('admin') == 'true'){
                   html+=`<a href="/books/${proizvod.id}/ed" class="btn btn-outline-
data-id=${proizvod.id}>Add to cart</a>`;
```

```
products that match the criteria.</div>
   $('#products').html(html);
async function filterProizvoda() {
    let searchVal = $("#search").val().toLowerCase();
   let sortVal = $("#sort").val();
    let izabraniZanrovi=[];
       izabraniZanrovi.push(parseInt($(this).val()));
       search: searchVal,
       genres:izabraniZanrovi
       $("#pagination").hide();
       let books = await fetchData('/books/json', 'get', filterObj);
       $("#loader").hide();
       $('#count').html("Books ("+books.total+")")
       ispisProizvoda(books.data);
       printPagination(books.last page);
       console.error(ex);
function printPagination(page,activePage = 1) {
    for(i =1;i<=page;i++) {</pre>
       html += `<a</pre>
class="page-link" href="#!" data-page="${i}">${i}</a>`;
   $("#pagination").show();
async function getPage() {
    let page = $(this).data('page');
    let dataObj = filterObj;
   dataObj.page = page;
       $("html").animate({
           scrollTop: $("nav").offset().top
       }, 300);
       $("#products .product, #products .not-found").remove();
       $('#loader').show();
       let books = await fetchData('/books/json','get',dataObj);
```

```
$("#loader").hide();
        $('#count').html("Books ("+books.total+")")
        ispisProizvoda(books.data);
        printPagination(books.last page,books.current page);
    }catch(ex){
        console.error(ex);
function poruka(tekst){
            toastr.success('Added to cart!')
            toastr.warning('Admin can not add to cart.');
            toastr.warning('You have to login first.')
            toastr.warning('There has been an error processing your request.')
function ukloniGreske() {
    $('.greska').hide();
    $('.uspeh').hide();
function greskaForme(elementForme, poruka) {
    $ (elementForme) .next() .text(poruka) .fadeIn();
var izrazMejl = /^([a-z]{3,15})(([\.]?[-]?[_]?[a-z]{3,20})*([\d]{1,3})*)@([a-
$ (document.regForm) .on("submit", function(event) {
    event.preventDefault();
    ukloniGreske();
    let forma=document.regForm;
    let greska=false;
        greskaForme (forma.tbName, "First and last name must start with capital letter
        greska = true;
    if(!izrazMejl.test(forma.tbEmail.value)){
        greskaForme(forma.tbEmail, "Please enter a valid email(example:
        greska = true;
    if(forma.tbPass.value.length < 7) {</pre>
        greskaForme(forma.tbPass, "Password must have at least 7 characters.");
        greska = true;
```

```
if(!greska){
        $('#btnReg').attr('type','hidden');
        forma.submit();
})
$ (document.logForm) .on ("submit", function (event) {
    event.preventDefault();
    ukloniGreske();
    let forma = document.logForm;
    let greska = false;
    if(!izrazMejl.test(forma.tbEmail.value)){
        greskaForme(forma.tbEmail, "Please enter a valid email(example:
        greska = true;
    if(!forma.tbEmail.value){
        greskaForme(forma.tbEmail, "Email field can't be empty.");
        greska=true;
    if(!forma.tbPass.value){
        greskaForme(forma.tbPass,"Password field can't be empty.");
        greska=true
    if(!greska){
        $('#btnLogin').attr('type','hidden');
        forma.submit();
})
$ (document.conForm) .on ("submit", function (event) {
    event.preventDefault();
   ukloniGreske();
    let forma=document.conForm;
    let greska=false;
    if(!izrazImePrezime.test(forma.tbName.value)){
       greskaForme(forma.tbName,"First and last name must start with capital letter
       greska = true;
    if(!izrazMejl.test(forma.tbEmail.value)){
        greskaForme(forma.tbEmail, "Please enter a valid email(example:
yourname@gmail.com).")
        greska = true;
    if(!forma.tbEmail.value){
        greskaForme(forma.tbEmail, "Email field can't be empty.");
        greska=true;
    if(forma.userMessage.value.length == "" || forma.userMessage.value.length > 200) {
        greskaForme (forma.userMessage, "Please enter a message no longer than 200
characters.");
        greska = true;
    if(!greska){
        $('#btnSubmitContact').attr('type','hidden');
        forma.submit();
```

```
const showOnPx = 200;
const backToTopButton = document.querySelector(".back-to-top");
const scrollContainer = () => {
    return document.documentElement || document.body;
};
const goToTop = () => {
    document.body.scrollIntoView({
        behavior: "smooth"
    });
document.addEventListener("scroll", () => {
        backToTopButton.classList.remove("hidden");
        backToTopButton.classList.add("hidden");
});
backToTopButton.addEventListener("click", goToTop);
function addToCart() {
    let id=$(this).data('id');
    $.ajax({
        method: "POST",
        data: {
            bookId : id
            poruka(data)
            console.error(xhr);
    })
function changeQuantity() {
    let inputVal = $(this).val();
    let price = $(this).data('price');
    let bookId = $(this).data('id');
    console.log(inputVal)
    if(!inputVal || inputVal < 1) {</pre>
        toastr.warning('Only numbers equal to or higher than 1 are allowed in the
        $(this).val(1);
        $("#span price " + bookId).html($(this).val() * price);
        correctTotalPrice();
        $.ajax({
            method: "POST",
            data: {
                bookId : bookId,
                quantity : inputVal
```

```
success: function() {
                toastr.success("Adjustment successfull.")
               toastr.error("There was an error processing your request.")
function correctTotalPrice() {
   var allPrices = document.querySelectorAll(".product price")
   var totalPrice = 0;
   for(let priceSpan of allPrices) {
       totalPrice += Number(priceSpan.innerHTML)
function removeFromCart() {
    let bookId = $(this).data('id');
   $.ajax({
       method: "DELETE",
       url: "/cart/" + bookId,
       success: function() {
           toastr.success("Item successfully removed.")
           let cartItemDiv = $("#cart item " + bookId)
           cartItemDiv.remove()
           if($('.cart-item').length == 0){
                location.reload();
           $("#count").html($('.cart-item').length+" items");
           correctTotalPrice()
```