



Ifs and Lists

Cybersecurity

Bash Scripting and Programming Day 2



Class Objectives

By the end of today's class, you will be able to:



Read bash and interpret scripts.



Use variables in your bash scripts.



Use if statements in your bash scripts.



Use lists in your bash scripts.




Iterate through lists with a for loop.

If Statements

Bash Scripting

Bash scripting is a vital skill for any cybersecurity professional. Scripts can be used for the following:



Conditional Statements

Cyber professional roles often require advanced bash skills. Today, we'll continue to develop our scripting skills in order to incorporate the following into our script:

01

If statements.

02

For loops to
complete
repetitive tasks.

03

Automating
the set up of
a machine.

Criteria and Decision Making

First, we will need our scripts to make decisions based on specific criteria.

For example:

Our scripts can check for the existence of users, directories, files or permissions.

Based on the results, the script can then take specific action or even stop execution.



Criteria and Decision Making

To accomplish these tasks, we will need to learn a few useful scripting techniques:



Using if statements.



Using if/else statements.



Testing multiple conditions using if/else statements.

First, a comment...

This is a comment

Comments are non-executable text within the script.



Placing a # in front of a line tells bash to ignore it. This is known as “commented out”.



These comments can describe the script functionality in plain English, making it easier for developers to understand the code.



Commenting out is often preferable to simply deleting the code. It also allows developers to toggle certain code on and off.

If Syntax

```
if [ <test> ]  
then  
<run_this_command>  
fi
```

if	Initiates our if statement.
[]	Encapsulates the condition.
then	Then runs following commands if the condition is met.
fi	Ends the if statement.

If Syntax

```
if [ 5 -gt 8 ]  
then  
    echo "This doesn't make sense!"  
fi
```

<code>if [5 -gt 8]</code>	This will check if 5 is greater than 8.
<code>then</code>	Runs the following commands if the condition is met.
<code>echo "This doesn't make sense!"</code>	Will have the script print to the screen "That doesn't make sense".
<code>fi</code>	Ends the if statement.

If Else Syntax

```
if [ <test> ]  
then  
    <run_this_code>  
else  
    <run_this_code>  
fi
```

if [<condition>]	If this test is true...
then	Runs the following code.
else	Runs the following code if the condition is false.
fi	Ends the if statement.

If Else Syntax

```
if [ 5 -gt 4 ]  
then  
    echo "That is correct!"  
else  
    echo "That doesn't make sense!"  
fi
```

<code>if [5 -gt 4]</code>	This will check if 5 is greater than 4.
<code>then</code>	Runs following code if the condition is met.
<code>echo "That is correct!"</code>	Is printed to the screen.
<code>else</code>	Runs the following code if the condition is unmet: <code>echo "This doesn't make sense!"</code>
<code>fi</code>	Ends the if statement.

&& Syntax

```
if [ <condition_1> ] && [ <condition_2> ]  
then  
    <run_this_code>  
fi
```

if [<test1>]	Checks if one condition is true.
&& [<test2>]	Checks if a second condition is true.
then	Runs the following code if both conditions are met.
fi	Ends the if statement.

&& Syntax

```
if [ 5 -gt 4 ] && [ 4 -gt 3 ]  
then  
    echo "That makes sense".  
fi
```

If the following two conditions are met:

```
if [ 5 -gt 4 ]
```

```
&& [ 4 -gt 3 ]
```

Run `echo "That makes sense".`

|| Syntax

```
if [ <condition1> ] || [ <condition2> ]  
then  
<run_this_code>  
else  
<run_this_code>  
fi
```

<code>if [<condition1>]</code>	If condition 1 is true.
<code> [<condition 2>]</code>	Or if condition 2 is true.
<code>then</code>	Run the following code.
<code>else</code>	Runs code if both conditions are false.
<code>fi</code>	Ends the if statement.

|| Syntax

```
if [5 -gt 4] || [4 -gt 3 ]
then
    echo "That only partially makes sense"
else
    echo "None of this makes sense"
fi
```

<code>if [5 -gt 4]</code>	If this condition is true...
<code> [4 -gt 3]</code>	...or if this test is true...
<code>then</code>	Run the following code.
<code>else</code>	Otherwise (if both conditions are false), run the following command.
<code>fi</code>	Ends the if statement.

Summary

if	<pre>if [<condition>] then <run_this_command> fi</pre>	Runs code <i>if</i> the condition is met.
if / else	<pre>if [<condition>] then <run_this_command> else <run_this_command> fi</pre>	Runs code <i>if</i> the condition is met. If condition isn't met, it will run a different command.
&&	<pre>if [<condition1>] && [<condition2>] then <run_this_command> fi</pre>	Runs code if more than one condition is met.
	<pre>if [<condition1>] [<condition2>] then <run_this_command> else <run_this_command> fi</pre>	Runs code if only one of multiple conditions are met.

Creating Conditionals

Now, we'll compare variables using the following conditionals:

<code>=</code>	This strings is equal to another
<code>==</code>	If two strings are equal.
<code>!=</code>	If two strings are not equal
<code>-gt</code>	If one integer is greater than another.
<code>-lt</code>	If one integer is less than another.
<code>-d /path_to/directory</code>	Checks for existence of a directory.
<code>-f /path_to?files</code>	Checks for existence of a file.

Equals to

```
# If $x is equal to $y, run the echo command.  
if [ $x = $y ]  
then  
    echo "X is equal to Y!"  
fi
```

<code>if [\$x = \$y]</code>	If the value of the x variable is equal to the value of the y variable.
<code>then</code>	Then, run the following command.
<code>echo "X is equal to Y!"</code>	The echo command that will run if the initial condition is met.
<code>fi</code>	Ends the if statement.

Not equals to

```
# If $x is not equal to $y, run the echo command.  
if [ $x != $y ]  
then  
    echo "X does not equal Y!"  
fi
```

<code>if [\$x != \$y]</code>	If the value of the x variable is not equal to the value of the y variable.
<code>then</code>	Then, run the following command.
<code>echo "X does not equal Y!"</code>	The echo command that will run if the initial condition is met.
<code>fi</code>	Ends the if statement.

Conditionals and Strings

```
# If str1 is not equal to str2, run the echo command and exit the script.
if [ "$str1" != "$str2" ]
then
    echo "These strings do not match."
    echo "Exiting this script."
fi
```

<code>if ["\$str1" != "\$str2"]</code>	If string 1 is not equal to string 2...
<code>then</code>	Then, run the following command.
<code>echo "These strings do not match"</code>	
<code>echo "Exiting this script."</code>	
<code>fi</code>	Ends the if statement.

Greater Than and Less Than

```
# If x is greater than y, run the echo command
if [ $x -gt $y ]
then
    echo "$x is greater than $y".
fi
```

```
# Checks if x is less than y
if [ $x -lt $y ]
then
    echo "$x is less than $y!"
else
    echo "$x is not less than $y!"
fi
```

Checking Files and directories

```
# check for the /etc directory
if [ -d /etc ]
then
    echo The /etc directory exists!
fi
```

```
# check for my_cool_folder
if [ ! -d /my_cool_folder ]
then
    echo my_cool_folder is not there!
fi
```

```
# check for my_file.txt
if [ -f /my_file.txt ]
then
    echo my_file.txt is there
fi
```

```
if [ -d /etc ]...
```

If the /etc directory exists, run the following echo command.

```
if [ ! -d /my_cool_folder ]...
```

If /my_cool_folder does not exist, run the following echo command.

```
if [ -f /my_file.txt ]...
```

If the file /my_file.txt exists, then run the following echo command.



**We can use built-in variables and
command expansions inside our tests.**

Built In Variables and Command Expansions

In the following three examples, we will use these variables and command expansions to verify:



If certain users are sysadmin.



The UID of the users.



The current user running the script is a sysadmin.

Built In Variables and Command Expansions

```
# if the user that ran this script is not the sysadmin user, run the echo command
if [ $USER != 'sysadmin' ]
then
    echo "You are not the sysadmin!"
    exit
fi
```

```
if [ $USER != 'sysadmin' ]
```

If the user that ran this script is not “sysadmin,” then run the following echo command.

Built In Variables and Command Expansions

```
# if the uid of the user that ran this script does not equal 1000, run the echo command
```

```
if [ $UID != 1000 ]
```

```
then
```

```
    echo your UID is wrong
```

```
    exit
```

```
fi
```

```
if [ $UID != 1000 ]
```

If the UID of the user who is running this script does not equal 1000, then run the following echo command.

Built In Variables and Command Expansions

```
# if the sysadmin ran the script, run the echo command
```

```
if [ $(whoami) = 'sysadmin']
```

```
then
```

```
    echo 'you are the sysadmin!'
```

```
fi
```

```
if [ $(whoami) = 'sysadmin']
```

If the user “sysadmin” ran the script, then run the following echo command.



Activity: Variables and If Statements

In this activity, you will add variables and conditional if statements to your scripts.

Suggested Time:

20 Minutes




Time's Up! Let's Review.

Questions?



List and Loops

Optimizing our Scripts




The tools we
are learning simplify
and expedite the
day-to-day workloads
of sysadmins.

In this section,
we will continue
to streamline
our scripts by
incorporating loops.

Sysadmins will often
complete the same
common task over and
over and over again.





For loops allow us to run a block of code multiple times in a row, without having to repeatedly enter that code.

For Loops

The code is run against each item in a list of items. The for loop runs for as many times as there are items on the loop.

```
for package in ${packages[@]}  
do  
    if [ ! $(which $package) ]  
    then  
        apt install -y $package  
    fi  
done
```



Instructor Demonstration

For Loops

Demo Summary

Made lists

```
my_list=(a b c d e f)
```

Created for loops

```
# for <item> in <list>;  
# do  
#   <run_this_command>  
#   <run_this_command>  
# done
```

Accessed the list with commands

```
$ echo ${my_list[0]}  
a  
$ echo ${my_list[4]}  
e  
$ echo ${my_list[@]}  
a b c d e f
```

Created loops with conditionals

```
# run an operation on each number  
for num in {0..5};  
do  
    if [ $num = 1 ] || [ $num = 4 ]  
    then  
        echo $num  
    fi  
done
```



Activity: Lists and Loops

In this activity, you use for loops to automate repetitive tasks.

Suggested Time:

20 Minutes



Time's Up! Let's Review.

Questions?








Countdown timer

15:00

(with alarm)

For Loops for Sysadmins



Sometimes, creating a script might be excessive for the scale of the present task. Instead, we can use these for loops directly on the command line, outside of a script.

For Loops for SysAdmins

For example, suppose that a sysadmin needs to prep each employees computer with the following packages:



slack



DocuSign

Rather than just logging onto each of the computers and installing the packages, the sysadmin could turn these apps into a list.

```
packages = [Zoom, Slack, Excel, Docusign]
```

We can then employ a for loop to iterate through the packages list and install the apps on each machine.

Why For Loops

Loop through...



...a list of packages to check if they are installed.



...the results of a find command and take action on each item found.



...a group of files, check their permissions and change if needed.



...a group of files and create a cryptographic hash of each file.



...all the users on the system and take an action for each one.

For Loops for Sysadmins

In the next demo, you will see how loops can be used to:



Run through a list of packages and check if certain ones are installed.



Search users' home directories for scripts and print a confirmation statement.



Loop through scripts in your scripts folder and change the permissions to execute.



Create a **for** loop that moves through a group of files and creates a hash of each file.



We will also write for loops directly on the command line.



Instructor Demonstration

Scripts and Loops



Activity: For Loops for SysAdmins

In this activity, you will add loops to your `sys_info.sh` script, and run loops directly on the command line.

Suggested Time:

25 Minutes



Time's Up! Let's Review.

Questions?





Optional: Script Along Set Up

- So far, we have use if statements to control the execution flow in a script.
- We also used if statements with loops to perform administrative tasks.
- For our final activity, we apply these new skills by going through a completed user setup script.



Instructor Demonstration

Script Along

*The
End*