



# Access Controls and Managing Services

Cybersecurity

## 4.3 Managing Permissions and Services



# Class Objectives

---

By the end of class, you will be able to:



Inspect and set file permissions for sensitive files on the system.



Manage and monitor services on the system, and remove unused services.



Create and assign users for services.

# Access Controls



Like Google Docs, Linux has **access controls**, which grant permission to access documents and files on a host.

# Managing Access Controls in Linux

Managing files, programs, and files as items.

---




**Item**

# Managing Access Controls in Linux

Each process has a number of *permissions* associated with the item, the *group* associated with the item, and *others*.


---



# Managing Access Controls in Linux

Each file or directory has a *user* associated with it, the *group* associated with the item, and *others*.


---



# Managing Access Controls in Linux

Managing access policies, rules and permissions that we can allow or prevent:  
read, write, execute.

---






# Managing Access Controls in Linux

---

Assigning these permissions is called **Discretionary Access Control (DAC)**. It is *discretionary* because item permissions can pass from one subject to another.



# Permissions Demo

---

In the upcoming demo, we'll create a file and a directory, observing default permissions. Then, we will change the permissions to deny certain groups and users access.

To read and manipulate these file permissions, we'll use these commands:

<code>ls -l</code>	Show the permissions info.
<code>chmod</code>	Change the permissions info.
<code>chown</code>	Change the owner and group of a file.



# Instructor Demonstration

---

## Permissions

# Inspecting File Permissions

---

**-rw-r--r--**

Item type (- for file, d for directory)

# Inspecting File Permissions

---

- **rw-** r - - r - -



Owner permission (in this case, *read* and *write*)

Item type

# Inspecting File Permissions

---

- rw- r - - r - -




Group permission (*read*)

Owner permission (in this case, *read* and *write*)

Item type

# Inspecting File Permissions



# Changing File Permissions

---

File permissions can be set using two different notations: **symbolic** and octal.

Symbolic Notation	
r	read
w	write
x	execute

**rwX**      **rw-**      **r--**

⏟                      ⏟                      ⏟


User can read,  
write execute      Group can  
read and write      Others can read



# Changing File Permissions

File permissions can be set using two different notations: symbolic and **octal**.

Octal Notation				
	4	2	1	
0	-	-	-	No permission
1	-	-	x	Only execute
2	-	w	-	Only write
3	-	w	x	Write and execute
4	r	-	-	Only read
5	r	-	x	Read and execute
6	r	w	-	Read and write
7	r	w	x	Read, write, and execute





## Activity: Access Controls and Permissions

In this activity, you will inspect and set file permissions on a few of the most sensitive items on a Linux system.

Suggested Time:

25 Minutes



Time's Up! Let's Review.

# Questions?






# Recap: Permissions

---

How permissions apply to each specific file and folder with `r`, `w`, and `x`.

Symbolic Notation	
<code>r</code>	read
<code>w</code>	write
<code>x</code>	execute

<code>rwX</code>	<code>rw-</code>	<code>r--</code>
		
User can read, write execute	Group can read and write	Others can read

# Permissions

---

How to view and apply permissions to an item's user, group, and other.

## Users

Every file and program on a Linux system has permissions.

These permissions tell the system which users can access a file or run a program.

## Groups

Users can be placed in groups, which can have special permissions that apply to all members of the group.

## Root

File and program permissions apply to all users *except* the root.

The root user (or super user) has complete access to the system and can perform any task.

# Permissions

---

We can use `sudo` user to invoke the `root` user and bypass any permissions.

<code>ls -l</code>	To show the permissions info.
<code>chmod</code>	To change the permissions info.
<code>chown</code>	To change the owner and group of a file.

# Permissions

---

We can assign `sudo` for a specific command for a specific user.

<code>whoami</code>	To determine the current user.
<code>su</code>	To switch to another user, in this case the root user.
<code>sudo</code>	To invoke the root user for one command only.
<code>sudo -l</code>	To list the <code>sudo</code> privileges for a user.
<code>visudo</code>	To edit the <code>sudoers</code> file.



A close-up, high-angle shot of a computer keyboard. The central focus is a large, white, rectangular key with rounded corners. On this key, there is a dark blue icon of a coffee cup with three wavy lines above it representing steam. Below the icon, the word "Break" is printed in a dark blue, serif font. The key is set against a light-colored, textured keyboard surface. Surrounding the main key are other keys: to the left, a key with double quotation marks; above, a key with a right arrow; and to the right, a key with a left arrow. The lighting is soft and even, highlighting the texture of the keys and the surface.

Break

# Managing Services



**Servers** are computers that offer services to other computers.

# Managing Services

---

A service is a function or capability that a machine makes available to another.


For example, file sharing services allow computers to send and receive data.





# Managing Services

Some services, like Tripwire, are only run locally on the server and are not provided to other computers. These services are packages that can be installed and removed just like other programs.



# Services and Security

# Services and Security


---

Attackers can manipulate services into doing things that they are not designed to do.



# Services and Security

For example: Samba (SMB), the file sharing protocol, allows users to view, download, and store files remotely.



The screenshot shows the Samba.org website homepage. At the top right is a search bar with the text "search samba.org:" and a red checkmark icon. Below the search bar is a large banner with the Samba logo and the tagline "opening windows to a wider world". On the left side, there is a vertical navigation menu with red buttons labeled "Home", "think Samba", "get Samba", "learn Samba", "talk Samba", "hack Samba", and "contact Samba". The main content area features a section titled "About Samba" with the text: "Samba is the standard Windows interoperability suite of programs for Linux and Unix." followed by a paragraph about its licensing under the GNU General Public License and its membership in the Software Freedom Conservancy. To the right of the "About Samba" section, there are two boxes: "Donations" with the text "Nowadays, the Samba Team needs a dollar instead of pizza :-)" and "Latest News" with a calendar icon showing "21" and the text "03 September 2019 Samba 4.11.0rc3 Available for Download" and "This is the third release candidate of the upcoming Samba 4.11 release series."



# Finding and Stopping SMB Demo

---

If a malicious user is able to gain access to a shared folder, they can exfiltrate, alter, or delete sensitive files.

- In this example, the server has already been compromised.
- In the following demo, we will stop the SMB service, and then uninstall it from the system.



# Finding and Stopping SMB Demo

---

This will require the following steps:



Listing all running services.



Identifying the Samba service in the list to confirm it's running, then stopping it.



Ensuring Samba doesn't start when the machine is started up.



Ensuring Samba is no longer running.



Uninstalling the Samba service completely.



# Instructor Demonstration

---

## Finding and Stopping SMB Demo



## Activity: Managing Services

Your senior administrator wants you to audit the services being run by the server and shut down old and unused services.

Suggested Time:

25 Minutes



Time's Up! Let's Review.

# Questions?



# Service Users



Some services are not run by real users. They are run by specific **service users** that are dedicated to running their own specific service.



# Service Users

---

Typically, when you install a service with the package manager, a service user is automatically created and configured.

Running services under a dedicated user offers several security benefits.

It makes it easier to start, stop, and manage the service, and control which files the service needs to access.



# Service Users

---

A service user usually has a system UID less than 1000 and cannot log in to use a shell.



```
root:x:0:0:root:/root:/bin/bash
```

# Service Users

---

Since service users aren't humans who need to log into and interact with the machine, it's best practice to ensure that users cannot log into an interactive shell using a service username.



# Scenario: Setting Up and Adding Service Users Demo

---

Your senior administrator asked you to follow up on your uninstallation of unused services.

You must now ensure the services' corresponding users have also been removed from the system.

Previously, you disabled `vsftpd`, but its service user, `ftp`, still exists.



# Scenario: Setting Up and Adding Service Users Demo

Your senior administrator also plans to install a security service called Splunk to collect and analyze logs for suspicious activity. Like Tripwire, Splunk makes it easier for admins and security personnel to detect and stop malicious behavior.

The screenshot shows the Splunk website homepage. At the top is a navigation bar with the Splunk logo and links for Products, Solutions, Why Splunk?, and Resources. On the right side of the navigation bar are links for Support, a search icon, a globe icon, a user icon, and a 'Free Splunk' button. The main content area features a large headline: 'Turn Data Into Doing Powering Security, IT and DevOps'. Below this headline is a 'Free Trial' button. To the right of the headline is a preview of a Splunk dashboard with various charts and tables. At the bottom of the page, there is a banner for '.conf21 splunk>' with the text 'Missed .conf21 Virtual? On-demand content now available!' and a 'Learn More' button.

splunk> Products Solutions Why Splunk? Resources Support Search User Free Splunk

**Turn Data Into Doing**  
**Powering Security, IT**  
**and DevOps**

Free Trial

**.conf21**  
splunk>


Missed .conf21 Virtual? On-demand content now available!

Learn More

# Scenario: Setting Up and Adding Service Users Demo

---

Your senior administrator told you that they'll handle the installation and configuration themselves, but have requested that you create a service user that they can use later.



# Scenario: Setting Up and Adding Service Users Demo

---

Completing this task will require the following steps:

01

Delete

Deleting an old, unused service user with `deluser/`.

02

Create

Creating and validating a new service user with `adduser`.



# Instructor Demonstration

---

## Setting up and Adding Service Users





## Activity: Service Users

Your senior administrator would like you to remove any old service users from the system and create a new user dedicated to running Tripwire.

- Use `adduser` and `deluser` with the correct flags to clean up the system and create this new Tripwire user.
- Tripwire can only be run as `root`, so you must add a line to the `sudoers` file to allow this.

Suggested Time:

25 Minutes



Time's Up! Let's Review.

# Questions?



# Homework

In this week's homework, you will practice all the hardening steps we learned this week, this time on a new system.

You will also run a few new tools: **chkrootkit** and **lynis**.



# Questions?



*The  
End*