



**Weierstraß-Institut für
Angewandte Analysis und Stochastik**



Clustering using adaptive weights

Vladimir Spokoiny, WIAS and HU (Berlin)
joint with Kirill Efimov and Larisa Hax

- 1 Introduction**
- 2 AWC Procedure**
- 3 Properties of the AWC**
- 4 Evaluation**
- 5 Summary and outlook**

1 Introduction

2 AWC Procedure

3 Properties of the AWC

4 Evaluation


5 Summary and outlook

Data $X_1, \dots, X_n \in \mathbb{R}^d$.





Aim: split into homogeneous groups (clusters).





Number and structure/shape of clusters usually **unknown**.

Ideal picture:



What is a cluster in general?





- **Partitional** clustering (k-mean) [MacQueen et al., 1967]. Minimizing the objective function over partitions. **Require to fix the number of clusters, hard to implement; cannot deal with non-spherical clusters**
- **Hierarchical**: agglomerative (bottom-up) and divisive (top-down). **Irreversibility of the merge decision;**
- **Density based**: cluster = mode of the density, [Ester et al., 1996]. **Poor quality of density estimation if $d > 2$;**
- **Spectral**: dimensionality reduction by eigenvalue decomposition of the adjacency matrix; [Ng et al., 2002]. **Require a good separation between clusters – spectral gap;**
- **Affinity propagation**: dynamic graphical models by responsibility and availability for each two points; [Frey and Dueck, 2007]. **unstable, sensitive to parameter choice.**

Aim: an efficient procedure which adapts to **unknown cluster structure**.

Approach: Describe the cluster structure by an **adjacency matrix** $W = (w_{ij})$, each w_{ij} means the probability that X_i and X_j are in the same cluster. For the standard (partitioned) clustering, W is a block matrix:

$$w_{ij} = \begin{cases} 1 & i, j \text{ from the same cluster,} \\ 0, & \text{otherwise} \end{cases}$$

The matrix W is recovered from the data by an iterative procedure:

- Initialize with one cluster $\mathcal{C}_i^{(0)}$ per point X_i ;
- At each step, increase the locality parameter h_k and recompute the local weights $w_{ij}^{(k)}$ using a **statistical test** that there is **no gap** between two local clusters $\mathcal{C}_i^{(k-1)}$ and $\mathcal{C}_j^{(k-1)}$.
- Stop when the bandwidth h_k reaches the global value.

1 Introduction

2 **AWC Procedure**


3 Properties of the AWC

4 Evaluation

5 Summary and outlook


Let $\{X_1, \dots, X_n\} \subset \mathbb{R}^d$ with $d < n$ be the set of all samples X_i .

Example: 250 points, 3 normal clusters (100 + 100 + 50) and the corresponding matrix of weights W .





Relaxation: allow a general symmetric $n \times n$ matrix of weights $W = (w_{ij})_{i,j=1,\dots,n}$ with $w_{ij} \in [0, 1]$.

Homogeneous case:



“Gap” case:



After $k - 1$ steps, for each $i \leq n$, the cluster $\mathcal{C}_i^{(k-1)}$ is given via weights $w_{ij}^{(k-1)}$, $j \leq n$.

At step k , suppose the locality parameter h_k to be fixed and consider any pair (X_i, X_j) with $\|X_i - X_j\| \leq h_k$.

Problem: For two local clusters $\mathcal{C}_i^{(k-1)}$ and $\mathcal{C}_j^{(k-1)}$ with $\|X_i - X_j\| \leq h_k$, compute the value $w_{ij}^{(k)}$ reflecting the gap between $\mathcal{C}_i^{(k-1)}$ and $\mathcal{C}_j^{(k-1)}$.

Principal idea: check the data density in the overlap $\mathcal{C}_i^{(k-1)} \cap \mathcal{C}_j^{(k-1)}$.

Mass of the overlap $N_{i \wedge j}^{(k)}$:

$$N_{i \wedge j}^{(k)} \stackrel{\text{def}}{=} \sum_{l \neq i, j} w_{il}^{(k-1)} w_{jl}^{(k-1)} \approx \# \text{ points in } \mathcal{B}(X_i, h_k) \cap \mathcal{B}(X_j, h_k)$$

Mass of the union $N_{i \vee j}^{(k)}$:

$$N_{i \vee j}^{(k)} \stackrel{\text{def}}{=} N_{i \wedge j}^{(k)} + N_{i \triangle j}^{(k)} \approx \# \text{ points in } \mathcal{B}(X_i, h_k) \cup \mathcal{B}(X_j, h_k)$$

where $N_{i \triangle j}^{(k)}$ is the mass of the complementary parts:

$$N_{i \triangle j}^{(k)} \stackrel{\text{def}}{=} \sum_{l \neq i, j: \{\|X_i - X_l\| \leq h_{k-1}\} \triangle \{\|X_j - X_l\| \leq h_{k-1}\}} \left(w_{il}^{(k-1)} + w_{jl}^{(k-1)} \right) .$$

Estimated relative density in the overlap:

$$\tilde{\theta}_{i \wedge j}^{(k)} = \frac{N_{i \wedge j}^{(k)}}{N_{i \vee j}^{(k)}}$$


Local homogeneous case corresponds to the nearly uniform distribution:

$$\tilde{\theta}_{i \wedge j}^{(k)} \approx q_{ij}^{(k)} \stackrel{\text{def}}{=} \frac{\text{Vol}_{\cap}(d_{ij}, h_k)}{2 \text{Vol}(h_k) - \text{Vol}_{\cap}(d_{ij}, h_k)},$$

where $\text{Vol}(h)$ is the volume of a ball with radius h and $\text{Vol}_{\cap}(d, h)$ is the volume of the intersection of two balls with radii h and the distance d between centers, $d_{ij} = \|X_i - X_j\|$.


Null (no gap): $\theta_{i \wedge j}^{(k)} = q_{ij}^{(k)}$ vs alternative (a gap) $\theta_{i \wedge j}^{(k)} < q_{ij}^{(k)}$.

Homogeneous case:



Brown area: overlap of two clusters, green and pink - complements.

“Gap” case:



The value $q_{ij}^{(k)}$ depends only on the ratio $t_{ij}^{(k)} = d_{ij}/h_k$ and can be calculated explicitly: $q_{ij}^{(k)} = q(t_{ij}^{(k)})$ with

$$q(t) = 2 \frac{B(d + \frac{1}{2}, \frac{1}{2})}{B(1 - \frac{t}{2}, d + \frac{1}{2}, \frac{1}{2})} - 1,$$

where $B(a, b)$ is the beta-function, $B(x, a, b)$ is the incomplete beta-function, and d is the space dimension.

We need to test if $\tilde{\theta}_{i \wedge j}^{(k)} < q_{ij}^{(k)}$. Following to [Polzehl and Spokoiny, 2006], define the test statistic $T_{ij}^{(k)}$

$$T_{ij}^{(k)} = N_{i \vee j}^{(k)} \mathcal{K}(\tilde{\theta}_{i \wedge j}^{(k)}, q_{ij}^{(k)}) \{ \mathbb{I}(\tilde{\theta}_{i \wedge j}^{(k)} < q_{ij}^{(k)}) - \mathbb{I}(\tilde{\theta}_{i \wedge j}^{(k)} > q_{ij}^{(k)}) \},$$

where $\mathcal{K}(\theta, q)$ is the symmetrized Kullback-Leibler divergence:

$$\mathcal{K}(\theta, q) = (\theta - q) \log \frac{\theta(1 - q)}{q(1 - \theta)}.$$

Parameters:

- A sequence of radii h_k . Fixed from the data to ensure that each ball $\mathcal{B}(X_i, h_k)$ contains nearly $n_k \approx (2d+1)a^k$ points for $a = 2^{1/4}$ and $k = 1, \dots, K$.
- A parameter λ .
- Localizing kernel $K_{\text{loc}}(u)$; (Default choice – a uniform kernel $K_{\text{loc}}(u) = \mathbb{I}(u \leq 1)$);
- Statistical kernel $K_{\text{stat}}(u)$ (Default choice – a uniform kernel);

Initialization: $k = 0$, for each i and j

$$w_{ij}^{(0)} = K_{\text{loc}} \left(\frac{\|X_i - X_j\|}{h_0} \right).$$

Increase k , recompute

$$w_{ij}^{(k)} = K_{\text{loc}} \left(\frac{\|X_i - X_j\|}{h_k} \right) K_{\text{stat}} \left(\frac{T_{ij}^{(k)}}{\lambda} \right).$$

where

$$T_{ij}^{(k)} = N_{i \vee j}^{(k)} \mathcal{K}(\tilde{\theta}_{i \wedge j}^{(k)}, q_{ij}^{(k)}) \mathbb{I}(\tilde{\theta}_{i \wedge j}^{(k)} < q_{ij}^{(k)})$$

for

$$\tilde{\theta}_{i \wedge j}^{(k)} = \frac{N_{i \wedge j}^{(k)}}{N_{i \vee j}^{(k)}}.$$

The parameter λ is fixed as the minimal value to ensure that for an artificial sample with one cluster, the procedure ends up with homogeneous weights $w_{ij}^{(K)} = 1$.

Alternatively one can run the procedure with different λ and select one by checking an increase of the sum of weights $\sum_{i,j} w_{ij}^{(K)}$.

1 Introduction

2 AWC Procedure

3 Properties of the AWC

4 Evaluation

5 Summary and outlook


The final clustering decision is made from the weights $w_{ij}^{(K)}$ computed at the last step K .

Propagation: If X_i and X_j are within a homogeneous (spherical) region, then the construction ensures $w_{ij}^{(K)} = 1$.


Propagation continues to apply even for many homogeneous regions:
 $w_{ij}^{(K)} = 1$ for any pairs (X_i, X_j) from the same region.

If $X_i \in \mathcal{C}_i$ and \mathcal{C}_i is separated from all other clusters with a significant gap, then $w_{ij}^K = 0$ for any $X_j \notin \mathcal{C}_i$.


AWC provides the optimal separation rate (minimal margins between clusters) for two or more dense convex (Gaussian like) clusters. [see demo](#)



AWC detects automatically sharp edges with a slight gravitation effect: neighbor points are gravitated to (included into) dense clusters.



The propagation property works well along a low dimensional manifold.



The complexity is (almost) dimension free and can be upper bounded by $C n n_K^2$, where n_K is the number of screened neighbors of each point X_i at the last step.

For small datasets ($n \leq 2000$) we use $n_K = n$. Then complexity of order n^3 .

For larger n , the value n_K can be bounded to control the total complexity of the procedure.

1 Introduction

2 AWC Procedure

3 Properties of the AWC

4 **Evaluation**

5 Summary and outlook


Misweighting error via the final computed weights $w_{ij}^{(K)}$: e_s counts all connections (positive weights) between points from different clusters, while e_p indicates the number of disconnecting points in the same cluster:

$$e_s = \frac{\sum_{i \neq j} |\hat{w}_{ij}| \mathbb{I}(w_{ij}^* = 0)}{\sum_{i \neq j} \mathbb{I}(w_{ij}^* = 0)}, \quad e_p = \frac{\sum_{i \neq j} |1 - \hat{w}_{ij}| \mathbb{I}(w_{ij}^* = 1)}{\sum_{i \neq j} \mathbb{I}(w_{ij}^* = 1)},$$


where w_{ij}^* denote the true weights describing the underlying clustering structure.

Standard *rand index* R [Rand, 1971] and total error e :


$$R = 1 - \frac{\sum_{i \neq j} |\hat{w}_{ij}| \mathbb{I}(w_{ij}^* = 0) + \sum_{i \neq j} |1 - \hat{w}_{ij}| \mathbb{I}(w_{ij}^* = 1)}{\sum_{i \neq j} \mathbb{I}(w_{ij}^* = 0) + \sum_{i \neq j} \mathbb{I}(w_{ij}^* = 1)} = 1 - e.$$




Original
clustering




AWC,
 $\lambda = 5.5$




Spectral,
 $\sigma = 0.1$




K-means,
 $K=3$




Affinity prop.
 $D=0.5, P=-1464$




DBSCAN,
 $e=2.1, sp=10$




Original
clustering




AWC,
 $\lambda = 4$




Spectral,




K-means,




Affinity prop.




DBSCAN,




Original
clustering




AWC,
 $\lambda = 2.1$




Spectral,




K-means,







Affinity prop.




DBSCAN,



Original clustering

AWC, $\lambda = 3.3$ Spectral, $\sigma = 0.1$ K-means, $K = 6$ 

Affinity prop.




DBSCAN

The data sets are taken from UCI repository.

Data	n	d	<i>#clusters</i>
Iris	150	4	3
Wine	178	13	3
Seeds	210	7	3
Thyroid gland	215	5	3
Ecoli	336	7	8
Olive	572	8	9
Wisconsin	699	9	2
Banknote	1372	4	2

Tabelle: Real world data sets description



Data	Error	Algorithm						
		AWC_best	AWC	k-means	GMM	Affinity	DBSCAN	Spectral
Iris	e_U	0.037	0.037	0.038	0.026	0.038	0.015	0.059
	e_N	0.076	0.076	0.076	0.051	0.076	0.325	0.453
	e	0.05	0.05	0.050	0.034	0.05	0.117	0.188
Wine	e_U	0.058	0.092	0.071	0.053	0.071	0.286	0.02
	e_N	0.181	0.191	0.145	0.189	0.145	0.233	0.519
	e	0.099	0.125	0.096	0.099	0.096	0.268	0.189
Seeds	e_U	0.093	0.11	0.164	0.237	0.135	0.199	0.037
	e_N	0.248	0.249	0.301	0.394	0.264	0.479	0.373
	e	0.144	0.156	0.21	0.289	0.178	0.292	0.148
Thy	e_U	0.08	0.081	0.074	0.127	0.101	0.174	0.151
	e_N	0.077	0.097	0.085	0.071	0.188	0.1	0.331
	e	0.082	0.09	0.08	0.097	0.147	0.135	0.247
Ecoli	e_U	0.125	0.114	0.08	0.121	0.072	0.137	0.061
	e_N	0.113	0.228	0.201	0.294	0.198	0.259	0.331
	e	0.121	0.145	0.122	0.167	0.106	0.17	0.134
Olive	e_U	0.076	0.076	0.097	0.152	0.063	0.052	0.062
	e_N	0.117	0.136	0.114	0.155	0.133	0.462	0.075
	e	0.083	0.087	0.1	0.153	0.076	0.127	0.065

Data	Error	Algorithm						
		AWC_best	AWC	k-means	GMM	Affinity	DBSCAN	Spectral
Wisconsin	e_U	0.059	0.06	0.103	0.030	0.129	0.073	0.066
	e_{\cap}	0.081	0.137	0.07	0.18	0.071	0.075	0.188
	e	0.071	0.102	0.077	0.112	0.098	0.074	0.133
Banknote	e_U	0.001	0.001	0.107	0.437	0.094	0.01	0.082
	e_{\cap}	0.367	0.367	0.676	0.409	0.624	0.413	0.389
	e	0.186	0.186	0.395	0.423	0.362	0.214	0.237



Abbildung: $DS3$, $n = 8000$, AWC result for $\lambda = 15$




Abbildung: $n = 8000$, AWC result for $\lambda = 15$




Abbildung: $DS4$, $n = 10000$ points, AWC result for $\lambda = 15$




Abbildung: *DS5*, $n = 8000$, AWC result for $\lambda = 15$

1 Introduction

2 AWC Procedure




3 Properties of the AWC

4 Evaluation

5 Summary and outlook

- New approach to **understand clustering** using the notions “propagation” and “separation”;
- **Structural adaptation** using adaptive weights;
- Procedure **numerically feasible** and applicable even for large data sets
- **Optimal separability** of convex clusters;
- Procedure is **fully adaptive** to unknown clustering structure including the number and shape of clusters and the separation distance;
- **State-of-the-art performance** of a wide range of artificial and real life examples;

- **Theoretical study** is difficult due to iterative nature of the method. The weights $w_{ij}^{(k-1)}$ from the step $k - 1$ depend from the same input data, so empirical process theory for the sums $\sum_j w_{ij}^{(k-1)}$ is not applicable.
- Many attempts to **represent** each step of the method as gradient decent for some **optimization problem** – failed so far.
- Similarly, it is unclear whether the procedure can be viewed as a **EM algorithm or alternating projections**;
- A rigorous theoretical justification of the method is still called for;
- The **choice of the only tuning parameter λ** is important and matters in complicated examples, the default choice is suboptimal.
- **Semisupervised learning** (combination of labelled and unlabelled data)
- **High dimensional** problems, combination with **dimension reduction**;

-  Ester, M., Kriegel, H.-P., Sander, J., and Xu, X. (1996).
A density-based algorithm for discovering clusters in large spatial databases with noise.
In Kdd, volume 96, pages 226–231.
-  Frey, B. J. and Dueck, D. (2007).
Clustering by passing messages between data points.
science, 315(5814):972–976.
-  MacQueen, J. et al. (1967).
Some methods for classification and analysis of multivariate observations.
In Proceedings of the fifth Berkeley symposium on mathematical statistics and probability, volume 1, pages 281–297. Oakland, CA, USA.



Ng, A. Y., Jordan, M. I., Weiss, Y., et al. (2002).

On spectral clustering: Analysis and an algorithm.

Advances in neural information processing systems, 2:849–856.



Polzehl, J. and Spokoiny, V. (2006).

Propagation-separation approach for local likelihood estimation.

Probability Theory and Related Fields, 135(3):335–362.



Rand, W. M. (1971).

Objective criteria for the evaluation of clustering methods.

Journal of the American Statistical association, 66(336):846–850.