

nDPI - Quick Start Guide Open and Extensible LGPLv3 Deep Packet Inspection Library

Version 1.8 October 2016

© 2011-16

nDPI web	http://www.ntop.org/products/ndpi/
ntop site	www.ntop.org
nDPI License	LGPLv3

Table of Contents

1. Intro	oduction 4	
1.1	Download Source 4	
2. nDF	Pl Library 5	
2.1	Compiling nDPI Source Code 5	
2.2	Compiling the demo pcapReader Source Code 5	
2.3	pcapReader Command Line Options 5	
2.4	Protocol File 6	
3. Examples 8		
3.1	Live Capture Mode 8	
3.2	pcap Capture Mode 8	
3.3	Protocol File 9	
4. API	nDPI 10	
5. Dev	reloping nDPI custom protocol 13	
5.1	Introduction 13	
5.2	Creating new protocol 13	
5.3	Add your protocol to nDPI 15	

1. Introduction

nDPI is a DPI library based on OpenDPI and currently maintained by ntop.

In order to provide you a cross-platform DPI experience, we also support Windows, in addition to Unix/Linux. Furthermore, we have modified nDPI to make it more suitable for traffic monitoring applications. We have achieved this by disabling specific features that are unnecessary for network traffic monitoring, thereby speeding up the DPI engine.

nDPI allows application-layer detection of protocols, regardless of the port being used. This means that it is possible to both detect known protocols on non-standard ports (e.g. detect HTTP on ports other than 80), and also the opposite (e.g. detect Skype traffic on port 80). This is because nowadays the concept of port = application no longer holds.

Over the past few months we have added several features including:

- Enhancement of the demo <u>ndpiReader</u> application both in terms of speed/features and encapsulations supported (for instance you can now analyse GTP tunnelled traffic).
- Ability to compile nDPI inside the Linux kernel so that you can use it for developing efficient kernel-based modules.
- Various speed enhancements so that nDPI is now faster than its predecessor.
- Added many protocols (to date we support ~200 protocols) ranging from "business" protocols such as SAP and Citrix, as well as "desktop" protocols such as Dropbox and Spotify.
- Ability to define port (and port range)-based protocol detection, so that you can complement protocol detection with classic port-based detection.
- In order to let nDPI support encrypted connections, we have added a decoder for SSL (both client and server) certificates, thus we can figure out the protocol using the encryption certificate. This allows us to identify protocols such as Citrix Online and Apple iCloud that otherwise would be undetected.
- Ability to support sub-protocols using string-based matching

1.1 Download Source

nDPI is automatically downloaded when you build ntop and nProbe. However nothing prevents you from using it as a standalone DPI library. The source code can be downloaded from https://github.com/ntop/nDPI.

2. nDPI Library

2.1 Compiling nDPI Source Code

Start using nDPI Library is very simple. In order to compile this library you must meet certain prerequisites such as:

```
GNU autotools/libtool gawk gcc
```

To do this you need to install them using the following commands:

```
Fedora

yum groupinstall Development tools

yum install automake libpcap-devel gcc-c++ libtool

Debian

apt-get install build-essential libpcap-dev

Mac OSX

port install XXX (Please install macports)
```

Once done that, you can compile the nDPI source code as follows:

```
cd <nDPI source code directory>
./autogen.sh
./configure
make
```

2.2 Compiling the demo ndpiReader Source Code

Starting using ndpiReader demo is also simple. In order to compile this you must use the following command:

```
\begin{tabular}{ll} $\operatorname{cd} < \operatorname{nDPI} & \operatorname{source} & \operatorname{code} & \operatorname{directory} > / \operatorname{example} \\ & \operatorname{make} & \end{tabular}
```

2.3 ndpiReader Command Line Options

The demo ndpiReader application can be used both in terms of speed/features analysis and encapsulations support. In particular, it is possible to specify a lot of command line options.

The available options and a minimal explanation of each option are listed below:

```
ndpiReader -i <file|device> [-f <filter>][-s <duration>]
          [-p <protos>][-l <loops> [-q][-d][-h][-t][-v <level>]
          [-n <threads>] [-w <file>] [-j <file>]
Usage:
 -i <file.pcap|device>
                           | Specify a pcap file/playlist to read packets from or a
device for live capture (comma-separated list)
 -f <BPF filter> | Specify a BPF filter for filtering selected traffic
  -s <duration>
                            | Maximum capture duration in seconds (live traffic
capture only)
                           | Specify a protocol file (eg. protos.txt)
 -p <file>.protos
                    | Number of detection loops (test only)
| Number of threads. Default: number of interfaces in -i.
 -1 <num loops>
 -n <num threads>
Ignored with pcap files.
 -j <file.json>
                           | Specify a file to write the content of packets in .json
format
                            | Disable protocol guess and use only DPI
```

-i <file.pcapldevice>

This specifies a pcap file to read packets from or a device for live capture. Only one of these two can be specified.

-f <BPF filter>

It specifies a BPF filter for filtering selected traffic. It allows nDPI to take only those packets that match the filter (if specified).

-s <duration>

It defines the capture duration in seconds, only for live traffic capture.

-p <file>.protos

It specifies a protocol file (e.g. protos.txt) to expand the support of sub-protocols and port-based protocol detection. Be careful, the protocol defined to protos file overwrites the existing protocol.

-l <num loops>

Number of detection loops (test only).

-d

This flag disables the nDPI protocol guess and uses only DPI.

-†

It dissects GTP tunnels

-h

It prints the ndpiReader help.

-v < 112 >

Using this flag, ndpiReader generates verbose output that can be used to tune its performance. Number one is the lowest level that displays the packets with 'unknown protocol', number two is more verbose.

2.4 Protocol File

nDPI has the ability to support sub-protocols using string-based matching. This is because many new sub-protocols such as Apple iCloud/iMessage, WhatsApp and many others use HTTP(S) that can be detected by decoding the SSL certificate host or the HTTP "Host:". Thus we have decided to embed in nDPI an efficient string-matching library based on the popular Aho-Corasick algorithm for matching hundred of thousand sub-strings efficiently (i.e. fast enough to sustain 10 Gbit traffic on commodity hardware).

You can specify sub-protocols at runtime using a protocol file with the following format:

```
# Subprotocols
# Format:
# host:"<value>",host:"<value>",.....@<subproto>
host:"googlesyndacation.com"@Google
host:"venere.com"@Veneer
```

in addition you can specify a port-based protocol detection using the following format:

```
# Format:
# <tcp|udp>:,<tcp|udp>:,....@
tcp:81,tcp:8181@HTTP
udp:5061-5062@SIP
tcp:860,udp:860,tcp:3260,udp:3260@iSCSI
tcp:3000@ntop
```

You can test your custom configuration using the ndpiReader (use -p option) application or enhance your application using the ndpi_load_protocols_file() nDPI API call.

3. Examples

In this section we show some ndpiReader use cases.

3.1 Live Capture Mode

The following example shows the ndpiReader live capture mode by using the parameter -i to specify the device and the parameter -s to specify the live capture duration.

```
$ ./ndpiReader -i eth0 -s 20
* NOTE: This is demo app to show *some* nDPI features.
* In this demo we have implemented only some basic features
^{\star} just to show you what you can do with the library. Feel
* free to extend it and send us the patches for inclusion
Using nDPI nDPI ($Revision: #### $)
Capturing live traffic from device eth0...
Capturing traffic up to 20 seconds
               2390 of 2391 packets total
1775743
pcap file contains
     IP packets: 2390
     IP bytes:
     Unique flows: 78
     nDPI throughout: 122.30 pps / 709.92 Kb/sec
     Guessed flow protocols: 0
```

3.2 pcap Capture Mode

The most simple way to create a pcap file is to use tcpdump command as in the following example:

```
ntop$ tcpdump -ni eth0 -s0 -w /var/tmp/capture.pcap -v
tcpdump: listening on en1, link-type EN10MB (Ethernet), capture size 65535 bytes
Got 0
Got 64
Got 75
Got 76
^C122 packets captured
122 packets received by filter
0 packets dropped by kernel
```

Once the pcap file has been created you will be able to launch the demo ndpiReader with the parameter -i:

```
* NOTE: This is demo app to show *some* nDPI features.
* In this demo we have implemented only some basic features
* just to show you what you can do with the library. Feel
* free to extend it and send us the patches for inclusion
```

\$./ndpiReader -i /var/tmp/capture.pcap

3.3 Protocol File

In order to clarify the features of the protocol file we are now going to explain how you can identify the flow of ntop.org.

For instance it is possible to do it by editing protos.txt.

```
ntop$ echo 'host:"ntop.org"@nTop'> protos.txt
```

Once the protocol file has been modified you will be able to launch the demo ndpiReader with the parameter -p:

```
$ ./ndpiReader -i en1 -s 30 -p protos.txt
* NOTE: This is demo app to show *some* nDPI features.
* In this demo we have implemented only some basic features
^{\star} just to show you what you can do with the library. Feel
* free to extend it and send us the patches for inclusion
Using nDPI nDPI ($Revision: #### $)
Capturing live traffic from device en1...
Capturing traffic up to 30 seconds
WARNING: only IPv4/IPv6 packets are supported in this demo (nDPI supports both IPv4
and IPv6), all other packets will be discarded
pcap file contains
     IP packets: 4755
                         of 4757 packets total
     IP bytes: 1766370
     Unique flows: 245
     Guessed flow protocols: 16
Detected protocols:
    Unknown
```

4. API nDPI

In this section the nDPI API is highlighted.

The demo ndpiReader will be now taken has a basic example to show how to initialize the library. It is required to have a compiled library and a properly configured Makefile (i.e the demo Makefile).

To start to using the API of nDPI within your application - in addition to your includes - you must also add the following include file:

```
#include "ndpi main.h"
```

The library can be initialized as follows:

1. Declare the protocol bitmask and initialise the detection module

This function will allow you to initialise the detection module. The fields have the following meanings:

u_int32_t ticks_per_second;

The timestamp resolution per second (like 1000 for millisecond resolution).

- void* (*__ndpi_malloc)(unsigned long size);
 Function pointer to a memory allocator.
- •void* (* ndpi free)(void* prt);

Function pointer to a debug output function, use NULL in productive environments.

2. Enable all protocols (note that you can enable a subset of the protocols if you) via the appropriate macro and set them within the detection module.

```
// enable all protocols
NDPI_BITMASK_SET_ALL(all);
ndpi set protocol detection bitmask2(ndpi struct, &all);
```

This function will allow you to set the protocol bitmask already defined within the detection module.

3. In order to load an existing protocol file you must use the following function:

```
dpi load protocols file(ndpi struct, protoFilePath);
```

4. Once captured the flows from your pcap file or ingress device, they can be analyzed by using the following function:

```
protocol = (const u_int32_t)ndpi_detection_process_packet(
```

```
ndpi_struct,
ndpi_flow,iph ? (uint8_t *)iph : (uint8_t *)if,
ipsize,
time,
src,
dst);
```

The fields have the following meanings:

- struct ndpi_detection_module_struct *ndpi_struct; The detection module.
- struct ndpi_flow_struct *flow;
 Flow void pointer to the connection state machine.
- const unsigned char *packet;
 The packet as unsigned char pointer with the length of packetlen. The pointer must point to the Layer 3 (IP header).
- const unsigned short packetlen;
 Packetlen the length of the packet.
- const u_int32_t current_tickt;The current timestamp for the packet.
- struct ndpi_id_struct *src;
 Void pointer to the source subscriber state machine.
- struct ndpi_id_struct *dst;
 Void pointer to the destination subscriber state machine.
- 5. Once the flows have been analysed, it is necessary to destroy the detection module via the use of the following function:

```
ndpi_exit_detection_module(ndpi_struct, free_wrapper);
```

The fields have the following meanings:

- struct ndpi_detection_module_struct* ndpi_struct; The detection module to be cleared.
- void (*ndpi_free) (void *ptr);
 Function pointer to a memory free function.

For further information we suggest to read the files

nDPI/example/ndpiReader.c, nDPI/src/include/ndpi_structs.h, nDPI/src/include/ndpi_public_functions.h nDPI/src/ndpi_main.c.

The protocol dissector files are contained in the nDPI/src/protocols directory.

5. Developing nDPI custom protocol

In this section we show the way to include your protocol inside nDPI.

5.1 Introduction

Each nDPI protocol is implemented as an entry function to be used at runtime by nDPI. The nDPI comes with several protocols that can be used as example for this activity. Below, we list the main concepts you need to know if you plan to develop an nDPI protocol.

5.2 Creating new protocol

Each protocol has to have a corresponding #define inside the following include file

```
<nDPI source code directory>/src/include/ndpi_protocols_osdpi.h
```

as follow

```
#define NDPI PROTOCOL MY PROTOCOL 171
```

where NDPI_PROTOCOL_MY_PROTOCOL is the protocol "name" and 171 is the protocol ID that must be unique.

Once the protocol has been defined, you must create a new protocol source file like

```
<nDPI source code directory>/src/lib/protocols/my protocol.c
```

with the following content

```
#include "ndpi_utils.h"
#ifdef NDPI_PROTOCOL_MY_PROTOCOLS
.....
#endif
```

where it will be necessary to define an entry function as a follow

```
void ndpi_search_my_protocol(
        struct ndpi_detection_module_struct *ndpi_struct,
        struct ndpi_flow_struct *flow)
{
    struct ndpi_packet_struct *packet = &flow->packet;

    NDPI_LOG(NDPI_PROTOCOL_MY_PROTOCOL, ndpi_struct, NDPI_LOG_DEBUG, "my protocol detection...\n");

/* skip marked packets by checking if the detection protocol stack */
```

```
if (packet->detected_protocol_stack[0] != NDPI_PROTOCOL_MY_PROTOCOL) {
    ndpi_check_my_protocol(ndpi_struct, flow);
}
```

and a detection core function to process a packet of a flow with the following content

```
static void ndpi_check_my_protocol(
struct ndpi detection module struct *ndpi struct,
struct ndpi flow struct *flow)
       struct ndpi_packet_struct *packet = &flow->packet;
      u_int32_t payload_len = packet->payload_packet_len;
       . . . . .
       . . . . .
      if("Found Protocol") {
             NDPI LOG(NDPI PROTOCOL MY PROTOCOL, ndpi struct,
      NDPI LOG DEBUG, "Found
                                 my protocol.\n");
             ndpi_int_my_protocol_add_connection(ndpi_struct, flow);
             return;
       }
       /*Exclude Protocol*/
      NDPI LOG(NDPI PROTOCOL MY PROTOCOL, ndpi struct, NDPI LOG DEBUG,
                "exclude my protocol.\n");
      NDPI ADD PROTOCOL TO_BITMASK(
             flow->excluded protocol bitmask,
             NDPI PROTOCOL MY PROTOCOL);
       }
}
```

and a specific function to report the correct identification of the protocol as follow

5.3 Add your protocol to nDPI

Once the protocol has been created, you must declare your entry function in the following include file

```
<nDPI source code directory>/src/include/ndpi_protocols.h
```

with the following content

Each protocol must be associated with a NDPI_SELECTION_BITMASK. The full list of NDPI_SELECTION_BITMASK is contained in the file

```
<nDPI source code directory>/src/include/ndpi define.h
```

After choosing the selection bitmask for your protocol, you must inform nDPI of the new protocol by editing the file

```
<nDPI source code directory>/src/lib/ndpi main.c
```

it is necessary to add your protocol to the the function as follow

```
void ndpi_set_protocol_detection_bitmask2(
               struct ndpi detection module struct *ndpi struct,
               const NDPI PROTOCOL BITMASK * dbm)
. . . . .
. . . . .
#ifdef NDPI PROTOCOL MY PROTOCOL
  ndpi_set_bitmask_protocol_detection(ndpi_struct, detection_bitmask, a,
                                     NDPI PROTOCOL MY PROTOCOL,
                                     ndpi_search_my_protocol,
NDPI_SELECTION_BITMASK_MY_PROTOCOL,
SAVE_DETECTION_BITMASK_AS_UNKNOW,
                                     ADD TO DETECTION BITMASK);
  /* Update callback_buffer index */
  a++;
#endif
. . . . .
ndpi struct->callback buffer size = a;
  NDPI LOG(NDPI PROTOCOL UNKNOWN, ndpi struct, NDPI LOG DEBUG,
           "callback_buffer_size is %u\n", ndpi_struct-
>callback buffer size);
```