Switch>en
Switch#conf t
Enter configuration commands, one per line. End with CNTL/Z.
Switch(config)#vlan 2
Switch(config-vlan)#name programmer
Switch(config-vlan)#exit
Switch(config)#vlan 3
Switch(config-vlan)#name buhg
Switch(config-vlan)#exit
Switch(config-vlan)#exit
Switch(config)#show vlan

Switch#show vlan

VLAN	I Name				Stat	tus Po	Ports			
1	default				act:	Fa Fa Fa Fa	Fa0/1, Fa0/2, Fa0/3, Fa0/4 Fa0/5, Fa0/6, Fa0/7, Fa0/8 Fa0/9, Fa0/10, Fa0/11, Fa0/12 Fa0/13, Fa0/14, Fa0/15, Fa0/16 Fa0/17, Fa0/18, Fa0/19, Fa0/20 Fa0/21, Fa0/22, Fa0/23, Fa0/24 Gig0/1, Gig0/2			
3 1002 1003 1004	programmer buhg fddi-default token-ring-default fddinet-default trnet-default					active active active active active active active				
VLAN	Туре	SAID	MTU	Parent	RingNo	BridgeNo	Stp	BrdgMode	Transl	Trans2
2	enet	100001 100002 100003	1500 1500 1500	-	- - -	- - -	- - -	-	0 0 0	0

% Invalid input detected at '^' marker.

Switch(config-if)#
Switch(config-if)#switchport mode access
Switch(config-if)#switchport access vlan 2
Switch(config-if)#exit
Switch(config)#fa0/2

% Invalid input detected at '^' marker.

Switch(config) #int fa0/2 Switch(config-if) #switchport mode accesss

% Invalid input detected at '^' marker.

Switch(config-if)#switchport mode access Switch(config-if)#switchport access vlan 2 Switch(config-if)#exit Switch(config)#show vlan

% Invalid input detected at '^' marker.

