


Схема устройств



Switch

Switch0

Physical Config CLI Attributes

IOS Command Line Interface

```
Hardware Board Revision Number : 0x01

Switch Ports Model          SW Version        SW Image
-----
*   1 26   WS-C2960-24TT-L   15.0(2)SE4       C2960-LANBASEK9-M

Cisco IOS Software, C2960 Software (C2960-LANBASEK9-M), Version 15.0(2)SE4, RELEASE SOFTWARE (fc1)
Technical Support: http://www.cisco.com/techsupport
Copyright (c) 1986-2013 by Cisco Systems, Inc.
Compiled Wed 26-Jun-13 02:49 by mnguyen

Press RETURN to get started!

%LINK-5-CHANGED: Interface FastEthernet0/1, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/1, changed state to up

Switch>en
Switch#conf t
Enter configuration commands, one per line. End with CNTL/Z.
Switch(config)#int fa0/1
Switch(config-if)#int vlan 1
Switch(config-if)#no sh

Switch(config-if)#
%LINK-5-CHANGED: Interface Vlan1, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface Vlan1, changed state to up

Switch(config-if)#ip address 192.168.0.2 255.255.255.0
Switch(config-if)#exit
Switch(config)#
```

Copy Paste

☐ Top

Консоль PC0

PC0

Physical

Config

Desktop

Programming

Attributes

Command Prompt

Password:

% Password: timeout expired!

[Connection to 192.168.0.2 closed by foreign host]

C:\>show vlan

Invalid Command.

C:\>telnet 192.168.0.2

Trying 192.168.0.2 ...Open

User Access Verification

Password:

Password:

Switch>show vlan

VLAN Name	Status	Ports
1 default	active	Fa0/1, Fa0/2, Fa0/3, Fa0/4 Fa0/5, Fa0/6, Fa0/7, Fa0/8 Fa0/9, Fa0/10, Fa0/11, Fa0/12 Fa0/13, Fa0/14, Fa0/15, Fa0/16 Fa0/17, Fa0/18, Fa0/19, Fa0/20 Fa0/21, Fa0/22, Fa0/23, Fa0/24 Gig0/1, Gig0/2
1002 fddi-default	active	
1003 token-ring-default	active	
1004 fddinet-default	active	
1005 trnet-default	active	

VLAN Type	SAID	MTU	Parent	RingNo	BridgeNo	Stp	BrdgMode	Trans1	Trans2
1 enet	100001	1500	-	-	-	-	-	0	0
1002 fddi	101002	1500	-	-	-	-	-	0	0
1003 tr	101003	1500	-	-	-	-	-	0	0
1004 fdnet	101004	1500	-	-	-	ieee	-	0	0
1005 trnet	101005	1500	-	-	-	ibm	-	0	0

Switch>en

Password:

Switch#conf t

Enter configuration commands, one per line. End with CNTL/Z.

Switch(config)#

☐ Top