

VE482 — Introduction to Operating Systems

Project 1 (Compile guide)

Author: [Yihao Liu](#)

Goals of the guide

- Install and use LLVM / Clang
- Use GNU make / CMake
- Submit on JOJ

1 Introduction

You're going to know how to build your project compatible to JOJ and submit it in this guide.

We are using `llvm/clang` to compile and test your program on JOJ, and we provide two build tools: `GNU make` and `CMake`, you can choose either of them in this project.

2 LLVM / Clang

2.1 Introduction

`clang` is now widely used as a substitute of `gcc`, it has GCC compatibility, fast compiles and low memory use, and expressive diagnostics.

So it's a good choice to install and use `clang` to compile and run your projects locally. In addition, Minix 3 only supports `clang` in default, instead of `gcc`.

The LLVM Project is a collection of modular and reusable compiler and toolchain technologies. Despite its name, LLVM has little to do with traditional virtual machines. The name "LLVM" itself is not an acronym; it is the full name of the project.

Find more information on <https://llvm.org/>.

The Clang project provides a language front-end and tooling infrastructure for languages in the C language family (C, C++, Objective C/C++, OpenCL, CUDA, and RenderScript) for the LLVM project.

Find more information on <https://clang.llvm.org/>.

2.2 Installation

On Windows, you can install and use `clang` for normal c projects, but this project needs some POSIX standard supports, while Windows doesn't have a full implementation of the standard, so you're recommended to switching to Linux.

On most Linux distributions, `clang` can be found in the package manager. For example, for Debian (Ubuntu / Linux Mint), you can install it with

```
1 $ sudo apt install clang
```

On Mac OS X, `clang` is the default compiler installed. The `gcc` and `g++` commands are only alias of it. On Minix 3, `clang` is also the default compiler, but you need to install it yourselves.

```
1 $ pkgin install binutils
2 $ pkgin install clang
```

2.3 Sanitizers

clang provides some sanitizers to detect memory leaks, undefined behaviors and etc.

2.3.1 AddressSanitizer

AddressSanitizer is a fast memory error detector. It consists of a compiler instrumentation module and a run-time library. The tool can detect the following types of bugs:

- Out-of-bounds accesses to heap, stack and globals
- Use-after-free
- Use-after-return
- Use-after-scope
- Double-free, invalid free
- Memory leaks

Find more information on <https://clang.llvm.org/docs/AddressSanitizer.html>.

2.3.2 UndefinedBehaviorSanitizer

UndefinedBehaviorSanitizer (UBSan) is a fast undefined behavior detector. UBSan modifies the program at compile-time to catch various kinds of undefined behavior during program execution, for example:

- Using misaligned or null pointer
- Signed integer overflow
- Conversion to, from, or between floating-point types which would overflow the destination

Find more information on <https://clang.llvm.org/docs/UndefinedBehaviorSanitizer.html>.

3 Build tools

3.1 GNU Make

Here we have a sample Makefile for you. Fill in MUMSH_SRC and then run make to build your project.

```
1 CC = clang
2 CFLAGS = -std=gnull -O2 -Wall -Wextra -Werror -pedantic -Wno-unused-result
3 MUMSH_SRC =
4 MUMSH = mumsh
5 MUMSHMC_FLAGS = -fsanitize=address -fno-omit-frame-pointer -fsanitize=undefined
   ↪ -fsanitize=integer
6 MUMSHMC = mumsh_memory_check
7 .PHONY: clean
8
9 all: $(MUMSH) $(MUMSHMC)
10     @echo mumsh successfully constructed
```

```

11
12 $(MUMSH) : $(MUMSH_SRC)
13     $(CC) $(CFLAGS) -o $(MUMSH) $(MUMSH_SRC)
14
15 $(MUMSHMC) : $(MUMSH_SRC)
16     $(CC) $(CFLAGS) $(MUMSHMC_FLAGS) -o $(MUMSHMC) $(MUMSH_SRC)
17
18 .c.o:
19     $(CC) $(CFLAGS) -c $< -o $@
20
21 clean:
22     $(RM) *.o *.a *~ $(MUMSH) $(MUMSHMC)

```

3.2 CMake

Here we have a sample `CMakeLists.txt` for you. Add files in `SOURCE_FILES` and make sure you have `cmake` installed on your system (provided on Linux / Mac OS X / Minix 3 by package manager).

```

1  cmake_minimum_required(VERSION 2.7)
2
3  set(CMAKE_C_STANDARD 11)
4  set(SOURCE_FILES )
5
6  add_executable(mumsh ${SOURCE_FILES})
7  add_executable(mumsh_memory_check ${SOURCE_FILES})
8
9  target_compile_options(mumsh_memory_check PUBLIC -fsanitize=address,undefined,integer
   ↪ -fno-omit-frame-pointer)
10 target_link_libraries(mumsh_memory_check -fsanitize=address,undefined,integer)

```

Then run the following commands to build your project. If you are using CLion, it will be automatically configured with `CMakeLists.txt`.

```

1 $ mkdir cmake-build-debug && cd cmake-build-debug
2 $ cmake -DCMAKE_C_COMPILER=clang .
3 $ make

```

4 Submission on JOJ

You should archive everything in a tarball (*.tar) and submit on JOJ. Remember to select your build tool first, and your `Makefile` and `CMakeLists.txt` must be in the first level directory.