

VE482 — Introduction to Operating Systems

Project 1 (Specifications)

Author: [Yihao Liu](#)

Goals of the guide

- Clarify the descriptions in the project
- Show some test cases

1 Format

1.1 Input

We will test your shell with a carefully coded [driver](#), so the input format in the test cases will be taken as the driver's `stdin`.

There are three kinds of commands in the input:

- `WRITELN <line>`: Write `line` to your shell ended with a `\n`.
- `CTRL <C|D>`: Send `SIGINT` with `CTRL C` or `EOF` with `CTRL D`.
- `WAIT <T>`: Wait for `T` ms.

1.2 Output

All of output should be flushed if it wasn't flushed automatically by `\n`. If you don't do so, the order of the output of different processes can be arbitrary, so you will get wrong answer.

The newline character (`\n`), tab character `\t` and spaces will be considered as the same in the output.

We will redirect your `stdout` and `stderr` to the same file in the driver, so please do not print debug information to `stderr`. The reason why we are doing it is that `s` shell should print prompts and error messages to `stderr`, though our project doesn't have this requirement. Some students may follow this rule but some won't, so we have to consider them together.

1.3 Examples

The examples will show input in the left and output in the right. Most of them are from milestone 1 and 2, and the real test cases before. We open these because we are testing your shell functionalities instead of sticking to your carefulness on I/O formats.

2 Tasks

2.1 Write a working read/parse/execute loop and an exit command; [5]

The loop time should be reasonable (`<10ms`), we will test on your overall preference in this part.

Hint: Don't forget to print `exit` when exiting your shell.

Example (Milestone 1 Case 1)

```
1 WRITELN exit
```

```
1 mumsh $ exit
```

2.2 Handle single commands without arguments; [5]

Hint: We only have three files in the working directory, they are driver, mumsh, mumsh_mmemory_check.

Example (Milestone 1 Case 2)

```
1 WRITELN ls
2 WRITELN exit
```

```
1 mumsh $ driver
2 mumsh
3 mumsh_memory_check
4 mumsh $ exit
```

2.3 Support commands with arguments; [5]

We've seen someone write programs like cat, ls himself, that is totally wrong in a shell. So we have these examples with package managers now.

Example (Milestone 1 Case 5)

```
1 WRITELN ls -a
2 WRITELN exit
```

```
1 mumsh $ .
2 ..
3 driver
4 mumsh
5 mumsh_memory_check
6 mumsh $ exit
```

2.4 File I/O redirection: [5+5+5+2]

This task is based on Task 2 and 3.

Only one output redirection and one input redirection is allowed in a command. The test cases will strictly follow this rule.

2.4.1 Output redirection by overwriting a file [5]

Example (Milestone 1 Case 7)

1	WRITELN	echo	321	>	1.txt	1	mumsh	\$	mumsh	\$	mumsh	\$	123
2	WRITELN	echo	123	>	2.txt	2	mumsh	\$	321				
3	WRITELN	cat	2.txt			3	mumsh	\$	1.txt				
4	WRITELN	cat	1.txt			4	2.txt						
5	WRITELN	ls				5	driver						
6	WRITELN	exit				6	mumsh						
						7	mumsh_memory_check						
						8	mumsh	\$	exit				

2.4.2 Output redirection by appending to a file; [5]

Example (Milestone 1 Case 9)

1	WRITELN	echo	321	>>	1.txt	1	mumsh	\$	mumsh	\$	321		
2	WRITELN	cat	1.txt			2	mumsh	\$	1.txt				
3	WRITELN	ls				3	driver						
4	WRITELN	exit				4	mumsh						
						5	mumsh_memory_check						
						6	mumsh	\$	exit				

2.4.3 Input redirection; [5]

Example (Milestone 1 Case 11)

1	WRITELN	echo	123	>	1.txt	1	mumsh	\$	mumsh	\$	123		
2	WRITELN	cat	<	1.txt		2	mumsh	\$	1.txt				
3	WRITELN	ls				3	driver						
4	WRITELN	exit				4	mumsh						
						5	mumsh_memory_check						
						6	mumsh	\$	exit				

2.5 Support for bash style redirection syntax; [8]

The bash style redirection syntax is very complex, we only require you to implement part of it. The following example actually shows all of the requirements:

- space between redirection symbols and arguments can be omitted.
- the redirection symbol can take place everywhere in the command.

Example (Milestone 1 Case 18)

1	WRITELN	echo 123 > 1.txt	1	mumsh \$ mumsh \$ mumsh \$ mumsh \$ mumsh
2	WRITELN	echo 222 > 2.txt		↪ \$ 123
3	WRITELN	echo 321 > 4.txt	2	mumsh \$ 222
4	WRITELN	<1.txt>3.txt cat 2.txt 4.txt	3	mumsh \$ 222
5	WRITELN	cat 1.txt	4	321
6	WRITELN	cat 2.txt	5	mumsh \$ 321
7	WRITELN	cat 3.txt	6	mumsh \$ 1.txt
8	WRITELN	cat 4.txt	7	2.txt
9	WRITELN	ls	8	3.txt
10	WRITELN	exit	9	4.txt
			10	driver
			11	mumsh
			12	mumsh_memory_check
			13	mumsh \$ exit

2.6 Pipes: [5+5+5+10]

2.6.1 Basic pipe support; [5]

Example (Milestone 2 Case 1)

1	WRITELN	ls -a grep mum	1	mumsh \$ mumsh
2	WRITELN	exit	2	mumsh_memory_check
			3	mumsh \$ exit

2.6.2 Run all 'stages' of piped process in parallel; [5]

We simply limit your total runtime in 1s in the test.

Example (Milestone 2 Case 3)

1	WRITELN	sleep 0.6 sleep 0.6	1	mumsh \$ mumsh \$ success
2	WRITELN	echo success	2	mumsh \$ exit
3	WRITELN	exit		

A tricky test of executing the shell itself.

Example (Milestone 2 Case 4)

1	WRITELN	echo exit ./mumsh	1	mumsh \$ mumsh \$ exit
2	WRITELN	exit	2	mumsh \$ exit

2.6.3 Extend 6.2 to support requirements 4. and 5. ; [5]

Input redirection can only be found in the first command, and output redirection can only be found in the last command, and each of them can occur only once. The test cases will strictly follow this rule.

Example (Milestone 2 Case 5)

1	WRITELN	echo	123	>	1.txt	1	mumsh	\$	mumsh	\$	mumsh	\$	mumsh	\$	123
2	WRITELN	echo	321	>	2.txt	2	mumsh	\$	321						
3	WRITELN	cat	<	1.txt		cat	>>	2.txt	3	123					
4	WRITELN	cat	1.txt			4	mumsh	\$	1.txt						
5	WRITELN	cat	2.txt			5	2.txt								
6	WRITELN	ls				6	driver								
7	WRITELN	exit				7	mumsh								
						8	mumsh_memory_check								
						9	mumsh	\$	exit						

2.6.4 Extend 6.3 to support arbitrarily deep “cascade pipes” ; [10]

Do you like the cats in the example? (Miao -,-)

Example (Milestone 2 Case 8)

1	WRITELN	echo	123	>	1.txt	1	mumsh	\$	mumsh	\$	mumsh	\$	mumsh	\$	123
2	WRITELN	echo	321	>	2.txt	2	mumsh	\$	321						
3	WRITELN	cat	<	1.txt		cat		cat		cat		3	123		
			↔			cat		cat		cat		cat		cat	
			↔		cat		cat		cat		cat		cat		cat
			↔		>>	2.txt						4	mumsh	\$	1.txt
4	WRITELN	cat	1.txt			5	2.txt					6	driver		
5	WRITELN	cat	2.txt			7	mumsh					8	mumsh_memory_check		
6	WRITELN	ls				9	mumsh	\$	exit						
7	WRITELN	exit													

2.7 Support CTRL-D (similar to bash, when there is no/an unfinished command); [5]

If there is an unfinished command, nothing should happen.

If the command line is empty, exit the shell and print exit.

2.8 Internal commands: [5+5+5]

2.8.1 Implement pwd as a built-in command; [5]

Do not use the builtin pwd command.

2.8.2 Allow changing working directory using cd; [5]

You should consider these:

- Execute `pwd` , then execute `cd ..` followed by `cd .` and another `pwd`
- Execute `cd /etc/../../etc/../../etc`
- Execute `cd` alone.
- Execute `cd` with more than 1 argument

2.8.3 Allow `pwd` to be piped or redirected as specified in requirement 4.; [5]

Example (Milestone 2 Case 13)

1	WRITELN <code>pwd</code> > <code>1.txt</code>	1	mumsh \$ mumsh \$ /out/package
2	WRITELN <code>cat 1.txt</code>	2	mumsh \$ <code>1.txt</code>
3	WRITELN <code>ls</code>	3	driver
4	WRITELN <code>exit</code>	4	mumsh
		5	mumsh_memory_check
		6	mumsh \$ <code>exit</code>

2.9 Support CTRL-C: [5+3+2+10]

Your shell is likely to get TLE (Time Limit Exceeded) if CTRL-C is not handled correctly.

You should NOT use `kill(0, signal)`, it may destroy the judger. You will be sent to the honor council if you intentionally use it.

2.9.1 Properly handle CTRL-C in the case of requirement 4. [5]

Example (Milestone 2 Case 15)

1	WRITELN <code>sleep 10</code>	1	mumsh \$
2	CTRL C	2	mumsh \$ success
3	WRITELN <code>echo success</code>	3	mumsh \$
4	CTRL C	4	mumsh \$ <code>exit</code>
5	WRITELN <code>exit</code>		

2.9.2 Extend 9.1 to support subtasks 6.1 to 6.3; [3]

Example (Milestone 2 Case 16)

1	WRITELN <code>sleep 10 echo 123</code>	1	mumsh \$ <code>123</code>
2	CTRL C	2	
3	WRITELN <code>echo success</code>	3	mumsh \$ success
4	WRITELN <code>exit</code>	4	mumsh \$ <code>exit</code>

2.9.3 Extend 9.2 to support requirement 7., especially on an incomplete input; [2]

Example (Milestone 2 Case 17)

1	CTRL C	1	mumsh \$
2	CTRL C	2	mumsh \$
		3	mumsh \$ exit

2.9.4 Extend 9.3 to support requirement 6.; [10]

Example (Milestone 2 Case 18)

1	WRITELN sleep 10 sleep 10 sleep 10		
	↪ sleep 10 sleep 10 sleep 10	1	mumsh \$ 123
	↪ sleep 10 sleep 10 sleep 10	2	
	↪ echo 123	3	mumsh \$
2	CTRL C	4	mumsh \$ success
3	CTRL C	5	mumsh \$
4	WRITELN echo success	6	mumsh \$ exit
5	CTRL C		
6	WRITELN exit		

2.10 Support quotes: [5+2+3+5]

2.10.1 Handle single and double quotes; [5]

Hint: the program name can also be quoted.

Example (Final Pretest Case 2)

1	WRITELN "echo" 'abc def' "xm" "fxh"	1	mumsh \$ abc def xmfxh
2	WRITELN exit	2	mumsh \$ exit

2.10.2 Extend 10.1 to support requirement 4. and subtasks 6.1 to 6.3; [2]

Example (Final Pretest Case 3)

1	WRITELN echo 123 > 1.txt	1	mumsh \$ mumsh \$ mumsh \$ 123
2	WRITELN "echo" "<1.'txt'" < 1.txt >	2	mumsh \$ <1.'txt'
	↪ "2.""txt"	3	mumsh \$ 1.txt
3	WRITELN cat 1.txt	4	2.txt
4	WRITELN cat 2.txt	5	driver
5	WRITELN ls	6	mumsh
6	exit	7	mumsh_memory_check
		8	mumsh \$ exit

Example (Final Pretest Case 4)

```
1 WRITELN "echo" "123" "|" | cat > 1.txt 2 mumsh $ 1.txt
2 WRITELN cat 1.txt 3 driver
3 WRITELN ls 4 mumsh
4 exit 5 mumsh_memory_check
6 mumsh $ exit
```

2.10.3 Extend 10.2 in the case of incomplete quotes; [3]

This part is similar to some functions in task 11, consider them together.

You should output "> " before after user hitting enter.

Example (Final Pretest Case 6)

```
1 WRITELN echo 123 > 1.txt 1 mumsh $ mumsh $ > mumsh $ 123
2 WRITELN echo "<1.'txt'" 2 mumsh $ <1.'txt'
3 3
4 WRITELN cat 1.txt 4 mumsh $ 1.txt
5 WRITELN cat 2.'"txt'" 5 2.'txt'
6 WRITELN ls 6 driver
7 WRITELN exit 7 mumsh
8 mumsh_memory_check
9 mumsh $ exit
```

2.10.4 Extend 10.3 to support requirements 4. and 6., together with subtask 9.3; [5]

Usually you do not need to modify many things for this task if you design your shell well. It is not tested in the final pretest, but will be tested in the final shell.

2.11 Wait for the command to be completed when encountering >, <, or |: [3+2]

You should output "> " before after user hitting enter.

2.11.1 Support requirements 3. and 4. together with subtasks 6.1 to 6.3; [3]

Hint: "»" don't need to be supported.

Example (Final Pretest Case 7)

```
1 WRITELN echo 123 >  
2 WRITELN 1.txt  
3 WRITELN cat 1.txt  
4 WRITELN ls  
5 WRITELN exit
```

```
1 mumsh $ > mumsh $ 123  
2 mumsh $ 1.txt  
3 driver  
4 mumsh  
5 mumsh_memory_check  
6 mumsh $ exit
```

Example (Final Pretest Case 9)

```
1 WRITELN echo 321 > 1.txt  
2 WRITELN cat <  
3 WRITELN 1.txt  
4 WRITELN ls  
5 WRITELN exit
```

```
1 mumsh $ mumsh $ > 321  
2 mumsh $ 1.txt  
3 driver  
4 mumsh  
5 mumsh_memory_check  
6 mumsh $ exit
```

Example (Final Pretest Case 11)

```
1 WRITELN echo 321 |  
2 WRITELN cat  
3 WRITELN exit
```

```
1 mumsh $ > 321  
2 mumsh $ exit
```

2.11.2 Extend 11.1 to support requirement 10.; [2]

Hint: Actually 10.3 already has this functionality, so only need to extend to 10.1, 10.2, 10.4

Example (Final Pretest Case 13)

```
1 WRITELN echo 123 > 1.txt  
2 WRITELN "echo" "<  
3 WRITELN 1.'txt'" <  
4 WRITELN 1.txt >  
5 WRITELN "2." "txt"  
6 WRITELN cat 1.txt  
7 WRITELN cat 2.txt  
8 WRITELN ls  
9 exit
```

```
1 mumsh $ mumsh $ > > > mumsh $ 123  
2 mumsh $ <  
3 1.'txt'  
4 mumsh $ 1.txt  
5 2.txt  
6 driver  
7 mumsh  
8 mumsh_memory_check  
9 mumsh $ exit
```

2.12 Handle errors for all supported features. [10]

There are eight kinds of errors to be handled. In test cases of other tasks, none of these errors will be included. You will always get a correct command then. At most one error occurs in a command, so you do not need to consider about the order of errors.

The output format of your errors should strictly follow the format listed below. It is very similar to the bash style error output format.

1. Non-existing program

- input: `non-exist abc def`
- input: `echo abc | non-exist`
- output: `non-exist: command not found`

2. Non-existing file in input redirection

- input: `cat < non-existing.txt`
- output: `non-existing.txt: No such file or directory`

3. Failed to open file in output redirection

- input: `echo abc > /dev/permission_denied`
- output: `/dev/permission_denied: Permission denied`

4. Duplicated input redirection

- input: `echo abc < 1.txt < 2.txt`
- input: `echo abc | grep abc < 1.txt`
- output: `error: duplicated input redirection`

5. Duplicated output redirection

- input: `echo abc > 1.txt > 2.txt`
- input: `echo abc > 1.txt >> 2.txt`
- input: `echo abc > 1.txt | grep abc`
- output: `error: duplicated output redirection`

6. Syntax Error

- input: `echo abc > > > >`
- output: `syntax error near unexpected token `>'`
- input: `echo abc > < 1.txt`
- output: `syntax error near unexpected token `<'`
- input: `echo abc > | grep abc`
- output: `syntax error near unexpected token `|'`

7. Missing program

- input: `> abc | | grep 123`
- output: `error: missing program`

8. cd to non-existing directory

- input: `cd non-existing`
- output: `non-existing: No such file or directory`

2.13 A command ending with an & should be run in background. [10+5]

2.13.1 For any background job, the shell should print out the command line, prepended with the job ID [10]

Hints:

- Do not print the process ID.
- Do not print complete information and "mumsh \$" after the job is finished (like 'bash' or 'zsh').
- The job ID starts from 1.

Example (Final Pretest Case 23)

1	WRITELN /bin/ls &	1	mumsh \$ [1] /bin/ls &
2	WRITELN sleep 0.2	2	mumsh \$ driver
3	WRITELN /bin/ls cat &	3	mumsh
4	WRITELN sleep 0.2	4	mumsh_memory_check
5	WRITELN exit	5	mumsh \$ [2] /bin/ls cat &
		6	mumsh \$ driver
		7	mumsh
		8	mumsh_memory_check
		9	mumsh \$ exit

2.13.2 Implement the command jobs which prints a list of background tasks together with their running states [5]

Hint: Print all of done and running background processes in this shell.

Example (Final Pretest Case 24)

1	WRITELN /bin/ls &	1	mumsh \$ [1] /bin/ls &
2	WRITELN sleep 0.2	2	mumsh \$ driver
3	WRITELN sleep 0.2 &	3	mumsh
4	WRITELN jobs	4	mumsh_memory_check
5	WRITELN sleep 0.4	5	mumsh \$ [2] sleep 0.2 &
6	WRITELN exit	6	mumsh \$ [1] done /bin/ls &
		7	[2] running sleep 0.2 &
		8	mumsh \$ mumsh \$ exit