

# Lab: Syntax, Functions and Statements

Problems for in-class lab for the ["JavaScript Essentials" course @ SoftUni](#). Submit your solutions in the SoftUni judge system at <https://judge.softuni.bg/Contests/1421/Lab-JavaScript-Syntax-and-Operators>.

## 1. String Length

Write a JS function that takes **three string arguments** as an input.

Calculate the **sum** of the **length** of the **strings** and the **average length** of the strings **rounded down** to the nearest integer.

The **input** comes as **three string arguments** passed to your function.

The **output** should be printed on the console on two lines.

### Examples

Input	Output
'chocolate', 'ice cream', 'cake'	22 7

Input	Output
'pasta', '5', '22.3'	10 3

### Hints

- Write a function that receives three string arguments.
- Declare two variables named **sumLength** and **averageLength** that will keep the mathematical results.
- Calculate the length of the strings using the **length property**.

```
function solve(arr1, arr2, arr3) {  
    let sumLength;  
    let averageLength;  
  
    let firstArgumentLength = arr1.length;  
    let secondArgumentLength = arr2.length;  
    let thirdArgumentLength = arr3.length;
```

- Calculate the sum of the three lengths.

```
sumLength = firstArgumentLength + secondArgumentLength + thirdArgumentLength;
```

- Calculate the **average length** of the strings **rounded down** to the nearest integer. Use the `Math.floor()` function.

```
averageLength = Math.floor(sumLength / 3);
```

- Print the results on the console.

```
console.log(sumLength);
console.log(averageLength);
```

## 2. Math Operations

Write a JS function that takes **two numbers** and a **string** as an input.

The string may be one of the following: '+', '-', '\*', '/', '%', '\*\*'.

Print on the console the result of the mathematical **operation** between **both numbers** and the **operator** you receive as a string.

The **input** comes as **two numbers** and a **string argument** passed to your function.

The **output** should be printed on the console.

### Examples

Input	Output
5, 6, '+'	11

Input	Output
3, 5.5, '*'	16.5

### Hints

- Write a function which receives **three** arguments:

```
function solve(num1, num2, operator) {
}
solve(5, 6, '+');
```

- Declare a variable named **result** that will keep your mathematical result.
- Write down **switch** command that will take the string from your input and depending on it, perform the mathematical logic between the two numbers.

```
function solve(num1, num2, operator) {

    let result;
    switch (operator){
        case '+': result = num1+num2; break;
        case '-': result = num1-num2; break;
        case '/': result = num1/num2; break;
        case '*': result = num1*num2; break;
        case '%': result = num1%num2; break;
        case '**': result = num1**num2; break;
    }

    console.log(result);
}
```

- Print the result on the console.

```
console.log(result);
```

### 3. Sum of Numbers N...M

Write a JS function that takes two numbers **n** and **m** as an input and **prints the sum** of all numbers from **n** to **m**.

The **input** comes as **two string elements** that need to be **parsed** as numbers.

The **output** should **return the sum**.

#### Examples

Input	Output
'1', '5'	15

Input	Output
'-8', '20'	174

#### Hints

- Write a function that receives two string arguments and parse them as numbers. Use **Number(string)** function or just put the '+' sign before the string.

```
function solve(n, m) {
    let num1 = Number(n);
    let num2 = Number(m);
}
```

```
function solve(n, m) {
    let num1 = +n;
    let num2 = +m;
}
```

- Declare a variable named **result** that will keep the mathematical results.
- Write a **for** loop from **num1** to **num2** and for every turn of the cycle, until it's completed, add the current value.

```
for (let i = num1; i <= num2; i++) {
    result += i;
}
```

- Finally, return the result.

```
return result;
```

## 4. Largest Number

Write a function that takes **three number arguments** as an input and find the **largest** of them. Print the following text on the console: 'The largest number is {number}.'

The **input** comes as **three number arguments** passed to your function.

The **output** should be printed to the console.

### Example

Input	Output
5, -3, 16	The largest number is 16.
Input	Output
-3, -5, -22.5	The largest number is -3.

### Hints

- Write a function that receives three number arguments.
- Declare a variable named **result** that will keep the result.

```
function solve(num1, num2, num3) {
    let result;
}
```

- Make several checks to find out the largest of the three numbers. Start with num1.

```
if (num1 > num2 && num1 > num3) {
    result = num1;
}
```

- Do the same for the others.

```

else if (num2 > num1 && num2 > num3) {
    result = num2;
}
else if (num3 > num1 && num3 > num2) {
    result = num3;
}

```

- Print the result on the console.

```
console.log(`The largest number is ${result}.`)
```

## 5. Circle Area

Write a function that takes a **single argument** as an input.

**Check the type** of the input argument. If it is a **number**, assume it is the radius of a circle and **calculate the circle area**. Print the **area rounded to two decimal places**.

If the argument type is **NOT** a number, print the following text on the console:

'We cannot calculate the circle area, because we receive a {type of argument}.'

The **input** comes as a **single argument** passed to your function.

The **output** should be printed on the console.

### Example

Input	Output
5	78.54

Input	Output
'name'	We can not calculate the circle area, because we receive a string.

### Hints

- Write a function that receives a single argument.
- Declare a variable named **result** that will keep your result.

```

function solve(input) {
    let result;
}
solve(5);
solve('name');

```

- Check the type of the input argument with the **typeof()** function.

```
let inputType = typeof(input);
```

- If the type is equal to **'number'**, calculate the circle area and print it on the console rounded to two decimal places. To do this, use the method **toFixed()**.

The **Math.pow()** function returns the base to the exponent power, that is, base exponent. You can find more information about the area [here](#):

```
if (inputType === 'number') {
    result = Math.pow(input, 2) * Math.PI;
    console.log(result.toFixed(2));
}
```

- If the type is **NOT** a **'number'**, print the following text on the console:

```
else {
    console.log(`We can not calculate the circle area,
    because we receive a ${inputType}.`);
}
```

## 6. Square of Stars

Write a function that **prints a rectangle** made of **stars** with variable **size**, depending on an input parameter. If there is **no parameter** specified, the rectangle should **always** be of **size 5**. Look at the examples to get an idea.

The **input** comes as a single **number** argument.

The **output** is a series of lines printed on the console, forming a rectangle of variable size.

### Examples

Input	Output	Input	Output	Input	Output	Input	Output
1	*	2	** **	5	***** ***** ***** ***** *****		***** ***** ***** ***** *****

## 7. Day of Week

Write a function that prints a number between 1 and 7 when a **day of the week** is passed to it as a string and an **error message** if the string is **not recognized**.

The **input** comes as a single string argument.

The **output** should be returned as a result.

## Examples

Input	Output
Monday	1

Input	Output
Friday	5

Input	Output
Invalid	error

## 8. Functional Calculator

Write a program that receives **two numbers** and an **operator** and performs a calculation between the variables, using the operator. Store the different functions in variables and pass them to your calculator.

The **input** comes as three arguments - two numbers, and a string, representing the operator.

The **output** should be printed on the console.

## Examples

Input	Output
2, 4, '+'	6

Input	Output
3, 3, '/'	1

Input	Output
18, -1, '*'	-18

## 9. Aggregate Elements

Write a program that performs different operations on an array of elements. Implement the following operations:

- **Sum( $a_i$ )** - calculates the sum all elements from the input array
- **Sum( $1/a_i$ )** - calculates the sum of the inverse values ( $1/a_i$ ) of all elements from the array
- **Concat( $a_i$ )** - concatenates the string representations of all elements from the array

The **input** comes as an array of number elements.

The **output** should be printed on the console on a new line for each of the operations.

## Examples

Input	Output
[1, 2, 3]	6 1.8333 123

Input	Output
[2, 4, 8, 16]	30 0.9375 24816

## 10. \*Words Uppercase

Write a program that **extracts all words** from a passed in string and converts them to **upper case**. The extracted words in upper case must be printed on a single line separated by ", ".

The **input** comes as a single string argument - the text to extract and convert words from.

The **output** should be a single line containing the converted string.

## Examples

Input	Output	Input	Output
'Hi, how are you?'	HI, HOW, ARE, YOU	'hello'	HELLO

## Hints

- You may need to use a [Regular Expression](#) or alternatively check for all delimiters that can be found in a sentence (ex. ",", " ", "!", "?" and so on).