

Exercise: String and Text Processing

Problems for exercise for the ["PHP Fundamentals" course @ SoftUni](#).

You can check your solutions in [Judge](#).

1. Valid Usernames

Write a program that reads user names on a single line (joined by ", ") and prints all valid usernames.

A valid username is:

- Has **length** between 3 and 16 characters
- **Contains** only letters, numbers, hyphens and underscores
- Has **no redundant symbols** before, after or in between

Examples

Input	Output
sh, too_long_username, !lleg@l ch@rs, jeffbutt	jeffbutt
Jeff, john45, ab, cd, peter-ivanov, @smith	Jeff john45 peter-ivanov

2. Character Multiplier

Create a **method** that takes two strings as arguments and returns the sum of their character codes multiplied (multiply `str1[0]` with `str2[0]` and add to the total sum). Then continue with the next two characters. If one of the strings is longer than the other, **add the remaining character codes to the total sum without multiplication**.

Examples

Input	Output
Gosho Pescho	53253
123 522	7647
a aaaa	9700

3. Extract File

Write a program that reads the path to a file and subtracts the file name and its extension.

Examples

Input	Output
C:\Internal\training-internal\Template.pptx	File name: Template File extension: pptx
C:\Projects\Data-Structures\LinkedList.cs	File name: LinkedList

4. Caesar Cipher

Write a program that returns an encrypted version of the same text. Encrypt the text by shifting each character with three positions forward. For example A would be replaced by D, B would become E, and so on. Print the encrypted text.

Examples

Input	Output
Programming is cool!	Surjudpplqj#lv#frro\$
One year has 365 days.	Rqh# hdu#kdv#698#gd v1

5. Multiply Big Number

You are given two lines – the first one can be a really big number (0 to 10^{50}). The second one will be a single digit number (0 to 9). You must display the product of these numbers.

Note: do not use the function `bcmul()`.

Examples

Input	Output	Input	Output	Input	Output
23	46	9999	89991	923847238931983192462832102	3695388955727932769851328408
2		9		4	

6. Replace Repeating Chars

Write a program that reads a string from the console and replaces any sequence of the same letters with a single corresponding letter.

Examples

Input	Output
aaaaabbbbcbdddeeeedssaa	abcdedsa
qqqwerqweccwd	qwerqwecwd

7. String Explosion

Explosions are marked with '>'. Immediately after the mark, there will be an **integer**, which signifies the **strength** of the explosion.

You should **remove x characters** (where x is the **strength** of the explosion), **starting after** the punch **character** ('>').

If you find **another** explosion mark ('>') while you're deleting characters, you should **add** the **strength** to your **previous explosion**.

When all characters are processed, **print** the string **without** the **deleted characters**.

You should **not** delete the **explosion** character – '>', but you should **delete** the **integers**, which represent the **strength**.

Input

You will receive **single line** with the string.

Output

Print what is left from the string after explosions.

Constraints

- You will **always** receive a **strength** for the punches
- The path will consist only of letters from the **Latin alphabet**, **integers** and the char '>'
- The strength of the punches will be in the interval **[0...9]**

Examples

Input	Output	Comments
abv>1>1>2>2asdasd	abv>>>>dasd	<p>1st explosion is at index 3 and it is with strength of 1. We delete only the digit after the explosion character. The string will look like this: abv>1>2>2asdasd</p> <p>2nd explosion is with strength one and the string transforms to this: abv>>2>2asdasd</p> <p>3rd explosion is now with strength of 2. We delete the digit and we find another explosion. At this point the string looks like this: abv>>>2asdasd.</p> <p>4th explosion is with strength 2. We have 1 strength left from the previous explosion, we add the strength of the current explosion to what is left and that adds up to a total strength of 3. We delete the next three characters and we receive the string abv>>>>dasd</p> <p>We do not have any more explosions and we print the result: abv>>>>dasd</p>
pesho>2sis>1a>2akarate>4hexmaster	pesho>is>a>karate>master	

8. *Letters Change Numbers

Nakov likes Math. But he also likes the English alphabet a lot. He invented a game with numbers and letters from the **English** alphabet. The game was simple. You get a string consisting of a **number between two letters**. Depending on whether the letter was in front of the number or after it you would perform different mathematical operations on the number to achieve the result.

First you start with the letter **before** the number.

- If it's **uppercase** you **divide** the number by the letter's **position** in the alphabet.
- If it's **lowercase** you **multiply** the number with the letter's **position** in the alphabet.

Then you move to the **letter after** the number.

- If it's **uppercase** you **subtract** its position from the resulted number.

- If it's **lowercase** you **add** its position to the resulted number.

But the game became too easy for Nakov really quick. He decided to complicate it a bit by doing the same but with **multiple** strings keeping track of only the **total sum** of all results. Once he started to solve this with more strings and bigger numbers it became quite hard to do it only in his mind. So he kindly asks you to write a program that **calculates the sum of all numbers after the operations on each number have been done**.

For example, you are given the sequence "**A12b s17G**":

We have two strings – "**A12b**" and "**s17G**". We do the operations on each and sum them. We start with the letter before the number on the first string. **A is Uppercase** and its position in the alphabet is **1**. So we divide the number 12 with the position 1 (**12/1 = 12**). Then we move to the letter after the number. **b is lowercase** and its position is 2. So we add 2 to the resulted number (**12+2=14**). Similarly for the second string **s is lowercase** and its position is 19 so we multiply it with the number (**17*19 = 323**). Then we have Uppercase G with position 7, so we subtract it from the resulted number (**323 – 7 = 316**). Finally, we sum the 2 results and we get **14 + 316=330**.

Input

The input comes from the console as a **single line, holding the sequence of strings**. Strings are separated by **one or more white spaces**.

The input data will always be valid and in the format described. There is no need to check it explicitly.

Output

Print at the console a single number: the **total sum of all processed numbers** rounded up to **two digits** after the decimal separator.

Constraints

- The **count** of the strings will be in the range [**1 ... 10**].
- The numbers between the letters will be integers in range [**1 ... 2 147 483 647**].
- Time limit: 0.3 sec. Memory limit: 16 MB.

Examples

Input	Output	Comment
A12b s17G	330.00	12/1=12, 12+2=14, 17*19=323, 323-7=316, 14+316=330
P34562Z q2576f H456z	46015.13	
a1A	0.00	

9. *Rage Quit

Every gamer knows what rage-quitting means. It's basically when you're just not good enough and you blame everybody else for losing a game. You press the CAPS LOCK key on the keyboard and flood the chat with gibberish to show your frustration.

Chochko is a gamer, and a bad one at that. He asks for your help; he wants to be the most annoying kid in his team, so when he rage-quits he wants something truly spectacular. He'll give you **a series of strings followed by non-negative numbers**, e.g. "a3"; you need to print on the console **each string repeated N times; convert the letters to uppercase beforehand**. In the example, you need to write back "AAA".

On the output, print first a statistic of the **number of unique symbols** used (the casing of letters is irrelevant, meaning that 'a' and 'A' are the same); the format should be "**Unique symbols used {0}**". Then, **print the rage message** itself.

The **strings and numbers will not be separated by anything**. The input will always start with a string and for each string there will be a corresponding number. The entire input will be given on a **single line**; Chochko is too lazy to make your job easier.

Input

- The input data should be read from the console.
- It consists of a single line holding a series of **string-number sequences**.
- The input data will always be valid and in the format described. There is no need to check it explicitly.

Output

- The output should be printed on the console. It should consist of **exactly two lines**.
- On the first line, print the **number of unique symbols used** in the message.
- On the second line, print the **resulting rage message** itself.

Constraints

- The count of **string-number pairs** will be in the range [1 ... 20 000].
- Each string will contain any character **except digits**. The **length** of each string will be in the range [1 ... 20].
- The **repeat count** for each string will be an integer in the range [0 ... 20].
- Allowed working time for your program: 0.3 seconds. Allowed memory: 64 MB.

Examples

Input	Output	Comments
a3	Unique symbols used: 1 AAA	We have just one string-number pair. The symbol is 'a', convert it to uppercase and repeat 3 times: AAA. Only one symbol is used ('A').
aSd2&5s@1	Unique symbols used: 5 ASDASD&&&&&S@	"aSd" is converted to "ASD" and repeated twice; "&" is repeated 5 times; "s@" is converted to "S@" and repeated once. 5 symbols are used: 'A', 'S', 'D', '&' and '@'.