

# Close relationships: assortativity & reciprocity

NETWORK ANALYSIS IN R




**James Curley**


Associate Professor, University of Texas  
at Austin

# Assortativity

The preferential attachment of vertices to other vertices that are similar in numerical or categorical attributes.



# Assortativity




```
assortativity(g, values)
```

```
0.45
```

```
assortativity.degree(  
  g,  
  directed = FALSE  
)
```

```
-0.31
```

# Reciprocity



```
reciprocity(g)
```

```
0.6
```

**Let's practice!**  
NETWORK ANALYSIS IN R

# Community detection


NETWORK ANALYSIS IN R




**James Curley**

Associate Professor, University of Texas  
at Austin

# Community detection in networks



# Fast-greedy detection



```
fastgreedy.community(g)
```

```
IGRAPH clustering fast greedy,  
groups: 3, mod: 0.5
```

+ groups:

\$`1`

```
[1] "A" "B" "C" "D" "E" "F"
```

\$`2`


```
[1] "J" "G" "H" "I" "K" "L"
```

\$`3`

```
[1] "M" "N" "O" "P"
```



# Edge-betweenness detection



```
edge.betweenness.community(g)
```

```
IGRAPH clustering edge betweenness,  
groups: 3, mod: 0.5
```

```
+ groups:
```

```
$`1`
```

```
[1] "A" "B" "C" "D" "E" "F"
```

```
$`2`
```

```
[1] "J" "G" "H" "I" "K" "L"
```

```
$`3`
```

```
[1] "M" "N" "O" "P"
```

```
x <- fastgreedy.community(g)
length(x)
```

```
[1] 3
```


```
sizes(x)
```

```
Community sizes
1 2 3
6 6 4
```

```
membership(x)
```

```
A B C D E F J G H I K L M N O P
1 1 1 1 1 1 2 2 2 2 2 2 3 3 3 3
```

```
plot(x, g)
```



**Let's practice!**  
NETWORK ANALYSIS IN R

# Interactive network visualizations

NETWORK ANALYSIS IN R




**James Curley**

Associate Professor, University of Texas  
at Austin

# R network visualization packages



- igraph
- statnet
- ggnet
- ggnetwork
- ggraph
- visNetwork
- networkD3
- sigma
- rgexf (igraph to Gephi)
- **threejs**

# threejs



# Creating a threejs visualization

```
library(threejs)  
graphjs(g)
```




# Adding attributes

```
g <- set_vertex_attr(  
  g,  
  "label",  
  value = V(g)$name  
)
```

```
g <- set_vertex_attr(  
  g,  
  "color",  
  value = "mistyrose"  
)
```

```
graphjs(g, vertex.size = 1)
```






# Coloring communities

```
x = edge.betweenness.community(g)
i <- membership(x)

g <- set_vertex_attr(
  g,
  "color",
  value = c(
    "yellow", "blue", "red"
  )[i]
)

graphjs(g)
```



**Let's practice!**  
NETWORK ANALYSIS IN R