
SHIFT-LOCK SYSTEM id051800140300

# **Purpose, Function**


• The shift-lock system operates when the ignition is switched to ON and the brake pedal is not depressed, and inhibits the selector lever from being shifted from the P position to other positions.

If the shift-lock cannot be released by the normal operation, it can be released manually by inserting a flathead screwdriver into the shift-lock release hole (emergency manual shift-lock release system).

## Construction Wiring diagram



#### Structural view



# Operation


# **Shift-lock Release Conditions**

- The shift-lock is released when all of the following conditions are met (except emergency manual shift-lock release system is operated).
  - Selector lever is in P position
  - Ignition is switched to ON
  - Brake pedal is depressed (brake light switch is on)


# Shift-lock operation conditions (shift-lock release conditions not satisfied)

- When the shift-lock release conditions are not met, the shift-lock operates.
- Because there is no energization to the shift-lock solenoid at this time, the shift-lock solenoid is not energized.
- As a result, the lock slider is positioned where it restricts the selector lever movement and the selector lever cannot be moved to any position other than P.

#### L.H.D.



### R.H.D.




ac5wzn00000928

# Shift-lock release (Shift-lock release conditions are satisfied)


- When the shift-lock release conditions are met, the shift-lock does not operate.
- At this time, the shift-lock solenoid is energized because there is energization to the shift-lock solenoid.
- As a result, the selector lever can be moved to any position other than P by moving the lock slider to a position where it does not restrict the selector lever movement.

# L.H.D.




ac5uun00000579

### R.H.D.



- Emergency manual shift-lock release system operation
  The emergency manual shift-lock release system can be released manually even if the shift-lock release conditions are not met.
- The lock slider restriction can be cancelled forcibly by pressing the shift-lock override button using a flathead screwdriver.
- As a result, the selector lever can be moved to any position other than P.

# L.H.D.



# R.H.D.

