DTC P0736:00 [GW6A-EL, GW6AX-EL]

id050230823200

DTC P0736:00	Gear reverse incorrect ratio			
DETECTION CONDITION	 Speed ratio is 0.75 to 1.2 for 2,000 ms while vehicle is stopped in R position. Diagnostic support note The check engine light does not illuminate. The automatic transaxle warning light illuminates if the TCM detects the above malfunction condition in two consecutive drive cycles or in one drive cycle while the DTC for the same malfunction has been stored in the TCM. PENDING CODE is available. FREEZE FRAME DATA is not available. DTC is stored in the TCM memory. 			
FAIL-SAFE FUNCTION	·· Inhibits neutral idle control			
POSSIBLE CAUSE	T T I • Shift solenoid malfunction			
SYSTEM WIRING DIAGRAM	Not applicable			

Diagnostic procedure

Diagnostic procedure				
STEP	INSPECTION		ACTION	
1	VERIFY DTC OUTPUT STATUS	Yes	Go to the applicable DTC inspection.	
	Are any the following DTCs displayed?		(See ON-BOARD DIAGNOSTIC SYSTEM DTC TABLE	
	— P0738:00, P0746:00, P0751:00, P0752:00,		[GW6A-EL, GW6AX-EL].)	
	P0756:00, P0757:00, P0761:00, P0762:00,	No	Go to the next step.	
	P0766:00, P0767:00, P0771:00, P0772:00,			
	P079A:00, P0842:00, P0843:00, P0847:00,			
	P0848:00, P0872:00, P0873:00, P0877:00,			
	P0878:00, P1784:00			
2	INSPECT ATF LEVEL	Yes	Adjust the ATF level to the specification, then go to the next	
	Inspect the ATF level.		step.	
	(See AUTOMATIC TRANSAXLE FLUID (ATF)		(See AUTOMATIC TRANSAXLE FLUID (ATF)	
	INSPECTION [GW6A-EL, GW6AX-EL].)		REPLACEMENT [GW6A-EL, GW6AX-EL].)	
	Is there any malfunction?	No	Go to the next step.	
3	PERFORM ON-BOARD DIAGNOSTIC TEST TO	Yes	Go to the applicable DTC inspection.	
	SPECIFY MALFUNCTIONING PART		(See ON-BOARD DIAGNOSTIC SYSTEM DTC TABLE	
			[GW6A-EL, GW6AX-EL].)	
	Note	No	ATF amount in Step 2 is correct:	
	If only DTCs in which the malfunctioning part		Replace the automatic transaxle.	
	is not confirmed are displayed as in the		(See AUTOMATIC TRANSAXLE REMOVAL/	
	following DTCs, all of the diagnosis may not		INSTALLATION [GW6A-EL].)	
	have been completed. In such cases, the		(See AUTOMATIC TRANSAXLE REMOVAL/	
	malfunction cause can be determined by		INSTALLATION [GW6AX-EL].)	
	performing the on-board diagnostic test.		ATF amount adjusted in Step 2:	
	Derform the on heard diagnostic test		Drive the vehicle to check it, and if there is no problem then	
	• Perform the on-board diagnostic test.		the DTC troubleshooting is complete.	
	(See ON-BOARD DIAGNOSTIC TEST MODE			
	[GW6A-EL, GW6AX-EL].)			
	Are any DTCs present?			