
DTC P2149:00	Fuel injector No.2 and No.3 circuit abnormal operation
	 When the following condition is met, the PCM detects the control current at fuel injectors No.2 and No.3 as less than the specified value 6 times: MONITORING CONDITIONS
	Battery voltage: more than 8 V
DETECTION	Diagnostic support note
CONDITION	This is an intermittent monitor (fuel system).
	• The check engine light illuminates if the PCM detects the above malfunction condition during the first drive
	cycle.
	• FREEZE FRAME DATA (Mode 2)/Snapshot data is available.
	DTC is stored in the PCM memory.
	PCM restricts engine torque.
FAIL-SAFE	• Inhibits the EGR control.
FUNCTION	Inhibits the diesel particulate filter regeneration control.
1 Gitto Hoit	Inhibits engine-stop by operating the i-stop function.
	PCM restricts engine-transaxle integration control.
	Fuel injector No.2 connector or terminals malfunction
	Fuel injector No.3 connector or terminals malfunction
	PCM connector or terminals malfunction
POSSIBLE	Open circuit in wiring harness between the following terminals:
CAUSE	Fuel injector No.2 terminal A—PCM terminal 1CW
	— Fuel injector No.3 terminal A—PCM terminal 1DA
	• Fuel injector No.2 malfunction
	• Fuel injector No.3 malfunction
	PCM malfunction



Diagnostic Procedure

Diagnic	Diagnostic Procedure					
STEP	INSPECTION		ACTION			
1	VERIFY FREEZE FRAME DATA (MODE 2)/	Yes	Go to the next step.			
	SNAPSHOT DATA HAS BEEN RECORDED	No	Record the FREEZE FRAME DATA (Mode 2)/snapshot data			
	Has the FREEZE FRAME DATA (Mode 2)/		on the repair order, then go to the next step.			
	snapshot data been recorded?					
2	VERIFY RELATED SERVICE INFORMATION	Yes	Perform repair or diagnosis according to the available			
	AVAILABILITY		Service Information.			
	Verify related Service Information availability.		If the vehicle is not repaired, go to the next step.			
	Is any related Service Information available?	No	Go to the next step.			
3	INSPECT FUEL INJECTOR NO.2 CONNECTOR	Yes	Repair or replace the connector and/or terminals, then go to			
	CONDITION		Step 9.			
	Switch the ignition off.	No	Go to the next step.			
	Disconnect the fuel injector No.2 connector.					
	Inspect for poor connection (such as damaged/					
	pulled-out pins, corrosion).					
	Is there any malfunction?					

STEP	INSPECTION		ACTION
4	INSPECT FUEL INJECTOR NO.3 CONNECTOR	Yes	Repair or replace the connector and/or terminals, then go to
	CONDITION		Step 9.
	Disconnect the fuel injector No.3 connector.	No	Go to the next step.
	Inspect for poor connection (such as damaged/		
	pulled-out pins, corrosion).		
	• Is there any malfunction?		
5	INSPECT PCM CONNECTOR CONDITION	Yes	Repair or replace the connector and/or terminals, then go to
	Disconnect the PCM connector.		Step 9.
	 Inspect for poor connection (such as damaged/ 	No	Go to the next step.
	pulled-out pins, corrosion).		r i i i i i i i i i i i i i i i i i i i
	Is there any malfunction?		
6	INSPECT FUEL INJECTOR CIRCUIT FOR OPEN	Yes	Go to the next step.
	CIRCUIT	No	Repair or replace the wiring harness for a possible open
	Verify that the fuel injector No.2 and fuel injector		circuit, then go to Step 9.
	No.3 and PCM connectors are disconnected.		
	Inspect for continuity between the following		
	terminals (wiring harness-side):		
	 Fuel injector No.2 terminal A—PCM terminal 		
	1CW		
	 Fuel injector No.3 terminal A—PCM terminal 		
	1DA		
	Is there continuity?		
7	INSPECT FUEL INJECTOR NO.2	Yes	Replace the fuel injector No.2, then go to Step 9.
	Inspect the fuel injector No.2.		(See FUEL INJECTOR REMOVAL/INSTALLATION
	(See FUEL INJECTOR INSPECTION		[SKYACTIV-D 2.2].)
	[SKYACTIV-D 2.2].)	No	Go to the next step.
	Is there any malfunction?		
8	INSPECT FUEL INJECTOR NO.3	Yes	Replace the fuel injector No.3, then go to the next step.
	Inspect the fuel injector No.3.		(See FUEL INJECTOR REMOVAL/INSTALLATION
	(See FUEL INJECTOR INSPECTION		[SKYACTIV-D 2.2].)
	[SKYACTIV-D 2.2].)	No	Go to the next step.
	Is there any malfunction?		
9	VERIFY DTC TROUBLESHOOTING	Yes	Repeat the inspection from Step 1.
	COMPLETED		• If the malfunction recurs, replace the PCM.
	Always reconnect all disconnected connectors.		(See PCM REMOVAL/INSTALLATION [SKYACTIV-D
	Clear the DTC from the PCM memory using the		2.2].)
	M-MDS.	N. 1	Go to the next step.
	(See AFTER REPAIR PROCEDURE	No	Go to the next step.
	[SKYACTIV-D 2.2].)		
	Perform the KOER self test. (See KOEO/KOER SELE TEST (SKYACTIV D.) (SEE KOEC SELE TEST (SKYACTIV D.) (SEE KOEC SELE TE		
	(See KOEO/KOER SELF TEST [SKYACTIV-D		
	2.2].) • Is the same DTC present?		
10	VERIFY AFTER REPAIR PROCEDURE	Voc	Go to the applicable DTC inspection.
10		Yes	· ·
	Perform the "AFTER REPAIR PROCEDURE". (See AFTER REPAIR PROCEDURE)	NI-	(See DTC TABLE [SKYACTIV-D 2.2].)
	(See AFTER REPAIR PROCEDURE [SKYACTIV-D 2.2].)	No	DTC troubleshooting completed.
	• Are any DTCs present?		
	TAILE AIR DIOS PIESEIR!		