DTC U2300:00	Global central configuration error				
Any of following conditions occurs: No configuration of instrument cluster The configuration signal with the estimated CAN ID is not sent from the instrument cluster. The configuration signal value sent via CAN from the instrument cluster is unknown or invalid. The configuration signal value sent via CAN from the instrument cluster is a value other than the estimated value. The configuration signal value sent via CAN from the instrument cluster does not match the PCM value. Diagnostic support note This is a continuous monitor (other). The check engine light does not illuminate. FREEZE FRAME DATA (Mode 2)/Snapshot data is not available. The DTC is stored in the PCM memory.					
FAIL-SAFE FUNCTION	Operates by the previously learned configuration value.				
CAN drive error (instrument cluster or PCM) Configuration data for the instrument cluster is incorrectly set CAN communication line between instrument cluster and PCM malfunction PCM connector or terminals malfunction Instrument cluster connector or terminals malfunction Instrument cluster loose Instrument cluster malfunction Error in non-volatile memory in PCM					
	• PCM malfunction PCM				
INSTRUMENT CLUSTER (5) (4) (2AK) (5) (4) (2AL)					
INSTRUMENT CLUSTER WIRING HARNESS-SIDE CONNECTOR					
W U S Q O M K I G E C A X V T R P N L J H F D B					
PCM WIRING HARNESS-SIDE CONNECTOR					
2BE 2AZ 2AU 2AP 2AK 2BF 2BA 2AV 2AQ 2AL 2BG 2BB 2AW 2AR 2AM 2BH 2BC 2AX 2AS 2AN 2BD 2AY 2AT 2AO 2AE 2AA 2W 2S 2O 2K 2G 2C 2AF 2AB 2X 2T 2P 2L 2H 2D					

Diagnostic Procedure

	Diagnostic Procedure					
STEP	INSPECTION		ACTION			
1	VERIFY RELATED SERVICE INFORMATION	Yes	Perform repair or diagnosis according to the available			
	AVAILABILITY		Service Information.			
	Verify related Service Information availability.		If the vehicle is not repaired, go to the next step.			
	Is any related Service Information available?	No	Go to the next step.			
2	VERIFY DTC FOR MODULE COMMUNICATION	Yes	Go to the applicable DTC inspection.			
	Switch the ignition to off, then to ON (engine off).		(See DTC U0073:00, U0101:00, U0121:00, U0131:00,			
	Perform the DTC Reading Procedure.		U0140:00, U0151:00, U0155:00, U0214:00, U0235:00			
	(See ON-BOARD DIAGNOSTIC TEST		[SKYACTIV-G 2.0].)			
	[SKYACTIV-G 2.0].)	No	Go to the next step.			
	Is the DTC U0155:00 also present?		·			
3	CONFIRM INSTRUMENT CLUSTER DTC	Yes	Go to the applicable DTC inspection.			
	Perform the instrument cluster DTC inspection		(See DTC TABLE [INSTRUMENT CLUSTER].)			
	using the M-MDS.	No	Go to the next step.			
	(See DTC INSPECTION [INSTRUMENT		'			
	CLUSTER].)					
	Are any DTCs present?					
4	INSPECT PCM CONNECTOR CONDITION	Yes	Repair or replace the connector and/or terminals, then go to			
	Switch the ignition to off.		Step 8.			
	Disconnect the PCM connector.	No	Go to the next step.			
	Inspect for poor connection (such as damaged/		,			
	pulled-out pins, corrosion).					
	Is there any malfunction?					
5	INSPECT INSTRUMENT CLUSTER	Yes	Repair or replace the connector and/or terminals, then go to			
	CONNECTOR CONDITION		Step 8.			
	Disconnect the instrument cluster connector.	No	Go to the next step.			
	• Inspect for poor connection (such as damaged/					
	pulled-out pins, corrosion).					
	Is there any malfunction?					
6	INSPECT INSTALLATION OF INSTRUMENT	Yes	Go to the next step.			
	CLUSTER	No	Retighten the instrument cluster, then go to Step 8.			
	Inspect installation of instrument cluster.		(See INSTRUMENT CLUSTER REMOVAL/			
	Is the instrument cluster installed securely?		INSTALLATION.)			
7	INSPECT INSTRUMENT CLUSTER	Yes	Replace the instrument cluster, then go to the next step.			
	Inspect the instrument cluster.		(See INSTRUMENT CLUSTER REMOVAL/			
	(See INSTRUMENT CLUSTER INSPECTION.)		INSTALLATION.)			
	Is there any malfunction?	No	Go to the next step.			
8	VERIFY DTC TROUBLESHOOTING	Yes	Repeat the inspection from Step 1.			
	COMPLETED		If the malfunction recurs, replace the PCM.			
	Make sure to reconnect all disconnected		(See PCM REMOVAL/INSTALLATION [SKYACTIV-G			
	connectors.		2.0].)			
	Clear the DTC from the PCM memory using the		Go to the next step.			
	M-MDS.	No	Go to the next step.			
	(See AFTER REPAIR PROCEDURE		·			
	SKYACTIV-G 2.0].)					
	• Switch the ignition ON (engine off or on) and wait					
	for 15 s or more.					
	• Wait until the main relay is off (approx. 1 min).					
	Perform the KOER self test.					
	(See KOEO/KOER SELF TEST [SKYACTIV-G					
	2.0].)					
	Is the same DTC present?					
9	VERIFY AFTER REPAIR PROCEDURE	Yes	Go to the applicable DTC inspection.			
	Perform the "AFTER REPAIR PROCEDURE".		(See DTC TABLE [SKYACTIV-G 2.0].)			
	(See AFTER REPAIR PROCEDURE	No	DTC troubleshooting completed.			
	(SKYACTIV-G 2.0].)					
	Are any DTCs present?					
	<i>y</i> 1		Į.			