SUPPLIER IDENTIFICATION PROCEDURE [AUDIO]

id0902f6803800


Note

• The unit supplier can vary. When asking the supplier (service center) for repair or replacement, identify the supplier and fill in the Audio Repair Order Form using the following procedures.


Verification procedure using label or inscribed lettering

- 1. Disconnect the negative battery cable. (See NEGATIVE BATTERY CABLE DISCONNECTION/CONNECTION [SKYACTIV-G 2.0, SKYACTIV-G 2.5].) (See NEGATIVE BATTERY CABLE DISCONNECTION/CONNECTION [SKYACTIV-G 2.0, SKYACTIV-G 2.5 (WITHOUT i-stop)].) (See NEGATIVE BATTERY CABLE DISCONNECTION/CONNECTION [SKYACTIV-D 2.2].)
- 2. Remove the decoration panel. (See DECORATION PANEL REMOVAL/INSTALLATION.)
- 3. Remove the audio unit. (See AUDIO UNIT REMOVAL/INSTALLATION.)
- 4. Verify the supplier name by referring to the label attached to the unit.

Audio unit (with color LCD)



Audio unit (without color LCD)




Verification procedure using on-board diagnostic assist function

- 1. Switch the ignition to ACC or ON (engine off).
- 2. Verify that the audio is turned on. If the audio is turned off, press the POWER/VOLUME switch to turn it on.
- 3. Press the POWER/VOLUME switch and SEEK switch (up) simultaneously to launch the diagnostic assist function.


With POWER/VOLUME switch on left side

Audio unit (with color LCD)




ac5wzw00003318

With POWER/VOLUME switch on right side







6. Select "ENTER switch".





Supplier code	Supplier name
M-01	SANYO Automedia
M-02	Panasonic
M-03	Clarion
M-04	Pioneer
M-05	VISTEON


- 8. Press the POWER/VOLUME switch and return to the diagnostic assist screen.
- 9. Press the POWER/VOLUME switch and end the diagnostic assist function.












Audio unit (without color LCD)


- 1. Switch the ignition to ACC or ON (engine off).
- 2. Verify that the audio is turned on. If the audio is turned off, press the POWER/VOLUME switch to turn it on.
- 3. Press PRESET switch 5 for 3 s or more while simultaneously pressing the POWER/VOLUME switch to launch the supplier verification mode.

With POWER/VOLUME switch on left side



ac5jjw00001770

With POWER/VOLUME switch on right side



4. Identify the supplier code by referring to the audio display.

Supplier code	Supplier name
M-01	SANYO Automedia
M-02	Panasonic
M-03	Clarion
M-04	Pioneer
M-05	VISTEON

5. Switch the ignition off (LOCK) to complete the manufacturer code verification mode.

