

CONTROL SYSTEM PERSONALIZATION FEATURES SETTING PROCEDURE

id094000439800

1. Connect the M-MDS to DLC-2.
2. After the vehicle is identified, select the following items from the initial screen of the M-MDS.
 - Select the "Module Programming".
 - Select "Programmable Parameters".
 - Select menu in the R_BCM.
3. Select an item name, and then select option.

Security And Locks

Power door lock system

M-MDS display	Function	Initial setting	Setting contents	Control unit
Auto Door Lock Mode.	Auto door lock function can be changed.	Lock: Driving, Unlock: IGN Off.	Not Adopted./OFF/ Lock When Driving./ Lock: Driving, Unlock: IGN Off./Lock When Shifting Out Of P./ Lock: Shift From P, Unlock: In P.	Rear body control module (RBCM)

Lighting Systems

Turn light system

M-MDS display	Function	Initial setting	Setting content	Control unit
3-Flash Turn Signal.	The turn light system can be switched between operable and inoperable.	OFF	Not Adopted./OFF/ON	Rear body control module (RBCM)

Auto light system

M-MDS display	Function	Initial setting	Setting content	Control unit
Auto-headlight On.	Auto light sensor sensitivity can be changed.	Medium	Not Adopted./Dark/ Medium Dark/Medium/ Medium Light/Light	Rear body control module (RBCM)

Note

- If the mode is set to "Light" and "Medium Light", the illumination level for illuminating the TNS and headlight increases. Therefore, the TNS and headlights illuminate when the ambient light is brighter than when the level is set to "Medium". In addition, if the mode is set to "Medium Dark" and "Dark", the illumination level for illuminating the TNS and headlights decreases. Therefore, the TNS and headlights illuminate when the ambient light is lower than when the level is set to "Medium".

Room Light Control System

M-MDS display	Function	Initial setting	Setting content	Control unit
Interior Light Timeout-Door Open.	The front/rear map light illumination time after any door is open can be changed.	30 minutes.	Not Adopted./30 minutes./60 minutes./ 10 minutes.	Rear body control module (RBCM)
Interior Light Timeout-Door Closed.	The front/rear map light illumination time after any door is closed can be changed.	15 seconds.	Not Adopted./15 seconds./7.5 seconds./30 seconds./ 60 seconds.	Rear body control module (RBCM)

Wiper/washer System

Auto wiper system

M-MDS display	Function	Initial setting	Setting content	Control unit
Rain Sensing Wipers.	Auto wiper system can be set to operable or inoperable.	Lock: Driving, Unlock: IGN Off.	Not Adopted./Off (Intermittent)/On (Rein Sensing)	Rear body control module (RBCM)