DTC P0089:00 [SKYACTIV-G 2.0]

id0102h1008900

DTC P0089:00	Spill valve control solenoid valve control circuit range/performance problem				
DETECTION CONDITION	 The average fuel pressure on the high pressure side, measured by the fuel pressure sensor while the camshaft is rotating at the specified speed, exceeds the specified value. Diagnostic support note This is a continuous monitor (CCM). The check engine light illuminates if the PCM detects the above malfunction condition during the first drive cycle. FREEZE FRAME DATA (Mode 2)/Snapshot data is available. The DTC is stored in the PCM memory. 				
FAIL-SAFE FUNCTION	· · I imits the intake air amount				
POSSIBLE CAUSE	High pressure fuel pump connector or terminals malfunction PCM connector or terminals malfunction Fuel pressure sensor malfunction High pressure fuel pump malfunction Spill valve control solenoid valve (built-into high pressure fuel pump) malfunction				

Diagnostic Procedure

STEP	INSPECTION		ACTION
1	VERIFY FREEZE FRAME DATA (MODE 2)/	Yes	Go to the next step.
	SNAPSHOT DATA HAS BEEN RECORDED	No	Record the FREEZE FRAME DATA (Mode 2)/snapshot data
	Has the FREEZE FRAME DATA (Mode 2)/		on the repair order, then go to the next step.
	snapshot data been recorded?		
2	VERIFY RELATED SERVICE INFORMATION	Yes	Perform repair or diagnosis according to the available
	AVAILABILITY		Service Information.
	Verify related Service Information availability.		If the vehicle is not repaired, go to the next step.
	 Is any related Service Information available? 	No	Go to the next step.
3	INSPECT HIGH PRESSURE FUEL PUMP	Yes	Replace the following parts because the part for the high
	CONNECTOR CONDITION		pressure fuel is damaged.
	Switch the ignition to off.		High pressure fuel pump
	Disconnect the high pressure fuel pump		(See HIGH PRESSURE FUEL PUMP REMOVAL/
	connector.		INSTALLATION [SKYACTIV-G 2.0].)
	Inspect for poor connection (such as damaged/		High pressure fuel pipe
	pulled-out pins, corrosion).		Fuel injector No.1
	Is there any malfunction?		(See FUEL INJECTOR REMOVAL/INSTALLATION
			[SKYACTIV-G 2.0].)
			Fuel injector No.2
			• Fuel injector No.3
			• Fuel injector No.4
			Fuel distributor
			Go to Step 9.
		No	Go to the next step.

STEP	INSPECTION		ACTION
4	INSPECT PCM CONNECTOR CONDITION • Disconnect the PCM connector. • Inspect for poor connection (such as damaged/pulled-out pins, corrosion). • Is there any malfunction?	Yes	Replace the following parts because the part for the high pressure fuel is damaged. • PCM connector and/or terminals • High pressure fuel pump (See HIGH PRESSURE FUEL PUMP REMOVAL/INSTALLATION [SKYACTIV-G 2.0].) • High pressure fuel pipe • Fuel injector No.1 (See FUEL INJECTOR REMOVAL/INSTALLATION [SKYACTIV-G 2.0].) • Fuel injector No.2 • Fuel injector No.3 • Fuel injector No.4 • Fuel distributor Go to Step 9. Go to the next step.
5	 INSPECT FUEL PRESSURE SENSOR Reconnect all disconnected connectors. Inspect the fuel pressure sensor. (See FUEL PRESSURE SENSOR INSPECTION [SKYACTIV-G 2.0].) Is there any malfunction? 	Yes	Replace the fuel distributor, then go to Step 9. (See FUEL INJECTOR REMOVAL/INSTALLATION [SKYACTIV-G 2.0].) Go to the next step.
6	INSPECT HIGH PRESSURE FUEL PUMP Inspect the high pressure fuel pump. (See HIGH PRESSURE FUEL PUMP INSPECTION [SKYACTIV-G 2.0].) Is there any malfunction?	Yes	Replace the following parts because the part for the high pressure fuel is damaged. • High pressure fuel pump (See HIGH PRESSURE FUEL PUMP REMOVAL/INSTALLATION [SKYACTIV-G 2.0].) • High pressure fuel pipe • Fuel injector No.1 (See FUEL INJECTOR REMOVAL/INSTALLATION [SKYACTIV-G 2.0].) • Fuel injector No.2 • Fuel injector No.3 • Fuel injector No.4 • Fuel distributor Go to Step 9. Go to the next step.
7	INSPECT HIGH PRESSURE FUEL PIPE • Inspect the high pressure fuel pipe. (See HIGH PRESSURE FUEL PUMP REMOVAL/ INSTALLATION [SKYACTIV-G 2.0].) • Is there clogging or damage in the high pressure fuel pipe?	Yes	Replace the following parts because the part for the high pressure fuel is damaged. • High pressure fuel pump (See HIGH PRESSURE FUEL PUMP REMOVAL/ INSTALLATION [SKYACTIV-G 2.0].) • High pressure fuel pipe • Fuel injector No.1 (See FUEL INJECTOR REMOVAL/INSTALLATION [SKYACTIV-G 2.0].) • Fuel injector No.2 • Fuel injector No.3 • Fuel injector No.4 • Fuel distributor Go to Step 9. Go to the next step.

STEP	INSPECTION		ACTION
8	INSPECT FUEL INJECTOR Inspect the fuel injector. (See FUEL INJECTOR INSPECTION [SKYACTIV-G 2.0].) Is there any malfunction?	Yes	111111
9	VERIFY DTC TROUBLESHOOTING COMPLETED • Make sure to reconnect all disconnected connectors. • Clear the DTC from the PCM memory using the M-MDS. (See AFTER REPAIR PROCEDURE [SKYACTIV-G 2.0].) • Perform the KOER self test. (See KOEO/KOER SELF TEST [SKYACTIV-G 2.0].) • Is the same DTC present?	Yes	Repeat the inspection from Step 1. If the malfunction recurs, replace the PCM. (See PCM REMOVAL/INSTALLATION [SKYACTIV-G 2.0].) Go to the next step. Go to the next step.
10	• Perform the "AFTER REPAIR PROCEDURE". (See AFTER REPAIR PROCEDURE [SKYACTIV-G 2.0].) • Are any DTCs present?	Yes	Go to the applicable DTC inspection. (See DTC TABLE [SKYACTIV-G 2.0].) DTC troubleshooting completed.